

NUCLEAR ENERGY BUSINESS GROUP • GENERAL ELECTRIC COMPANY
SAN JOSE, CALIFORNIA 95125

GENERAL ELECTRIC

APPLICABLE TO:	
PUBLICATION NO.	<u>NEDO-24146/24146A</u>
T. I. E. NO.	<u>79NED273</u>
TITLE	<u>LOCA ANALYSIS REPORT FOR</u>
	<u>DRESDEN UNITS 2, 3 AND QUAD</u>
	<u>CITIES 1, 2 NUCLEAR POWER STATIONS</u>
ISSUE DATE	<u>April 1979</u>

ERRATA And ADDENDA SHEET

NO.	<u>4</u>
DATE	<u>June 1980</u>
<i>NOTE: Correct all copies of the applicable publication as specified below.</i>	

ITEM	REFERENCES (SECTION, PAGE PARAGRAPH, LINE)	INSTRUCTIONS (CORRECTIONS AND ADDITIONS)
1.	Page 4-7	Replace with new page 4-7.
2.	Page 4-8	Replace with new page 4-8.

8102030 532

Table 4A

MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

PLANT: Dresden - 3FUEL TYPE: 7D212 - NO GAD

<u>Average Planar Exposure (MWd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
5,000	14.8	2192	0.036
12,500	14.7	2198	0.061
22,500	14.2	2189	0.082
30,000	12.5	1994	0.038
32,000	12.1	1966	0.041

Table 4B

MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

PLANT: Dresden 2/Quad Cities 1,2FUEL TYPE: 7D212L

<u>Average Planar Exposure (MWd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
200	14.0	2198	0.042
1,000	14.1	2195	0.040
5,000	14.7	2198	0.037
10,000	14.7	2197	0.036
15,000	14.4	2198	0.081
25,000	13.2	2063	0.023
30,000	12.1	1938	0.015
32,000	11.6	1896	0.025

Table 4C

MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

PLANT: Dresden 2,3/Quad Cities 1FUEL TYPE: 7D230

<u>Average Planar Exposure (MWd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
200	14.3	2198	0.034
1,000	14.5	2197	0.034
5,000	14.7	2198	0.032
10,000	14.5	2198	0.032
15,000	14.0	2198	0.074
20,000	13.7	2197	0.073
25,000	13.6	2198	0.070
30,000	13.2	2127	0.056
35,000	12.1	2043	0.043
40,000	11.0	1873	0.022

Table 4D

MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

PLANT: Quad Cities 1FUEL TYPE: EEIC - PU

<u>Average Planar Exposure (MWd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
200	14.1	2198	0.042
1,000	14.3	2194	0.040
5,000	14.6	2197	0.039
10,000	14.2	2198	0.088
15,000	13.5	2198	0.112
20,000	13.3	2195	0.114
25,000	13.2	2195	0.116
30,000	12.6	2200	0.117
35,000	12.1	2198	0.117
40,000	11.9	2196	0.116
45,000	9.4	1747	0.018
50,000	8.2	1557	0.003