

Facility: Point Beach		Date of Exam: May 8 - 19, 2017 Operating Test No.: 2017															
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)		
		1			2			4			CREW POSITION						
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
												R	I	U			
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/> SRO-I 1 <input checked="" type="checkbox"/>	RX	4						2								2	1
	NOR					1, 2							2	1	1	1	
	I/C	1, 2, 5				3, 4, 8		3, 5, 7					9	4	4	2	
	MAJ	6				6		6					3	2	2	1	
	TS	1, 3											2	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/> SRO-I 2 <input checked="" type="checkbox"/>	RX		4		2								2	1	1	0	
	NOR				1				1, 2				3	1	1	1	
	I/C		5		3, 4, 5				4, 8				6	4	4	2	
	MAJ		6		6				6				3	2	2	1	
	TS				3, 4								2	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/> SRO-I 3 <input checked="" type="checkbox"/>	RX				2		2						2	1	1	0	
	NOR			4			1						2	1	1	1	
	I/C			1, 2, 7, 8		5, 7		3, 4, 5					9	4	4	2	
	MAJ			6		6		6					3	2	2	1	
	TS							3, 4, 5					3	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR													1	1	1	
	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls" (ATC) and "balance-of-plant" (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a one-for-one basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.
- For licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.

Facility: Point Beach		Date of Exam: May 8 - 19, 2017											Operating Test No.: 2017				
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)		
		1			3			4			CREW POSITION						
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P		R	I	U
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input checked="" type="checkbox"/> SRO-I 4	RX	4						2					2	1	1	0	
	NOR					3							1	1	1	1	
	I/C	1, 2, 5				1, 2, 4		3, 5, 7					9	4	4	2	
	MAJ	6				5		6					3	2	2	1	
	TS	1, 3											2	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input checked="" type="checkbox"/> SRO-I 5	RX		4		3								2	1	1	0	
	NOR								1, 2				2	1	1	1	
	I/C		5		1, 2, 4				4, 8				6	4	4	2	
	MAJ		6		5				6				3	2	2	1	
	TS				1, 3, 4								3	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input checked="" type="checkbox"/> SRO-I 6	RX				3		2						2	1	1	0	
	NOR			4			1						2	1	1	1	
	I/C			1, 2, 7, 8		6, 7, 8		3, 4, 5					10	4	4	2	
	MAJ			6		5		6					3	2	2	1	
	TS							3, 4, 5					3	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR													1	1	1	
	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls" (ATC) and "balance-of-plant" (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a one-for-one basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.
- For licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.

Facility: Point Beach		Date of Exam: May 8 - 19, 2017 Operating Test No.: 2017															
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M(*)		
		1			3			4			CREW POSITION						
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
												R	I	U			
RO <input type="checkbox"/>	RX	4			3		2									3	1
SRO-I <input checked="" type="checkbox"/>	NOR						1						1	1	1	1	
SRO-U <input type="checkbox"/>	I/C	1, 2, 5			6, 7, 8		3, 4, 5						9	4	4	2	
SRO-I 7	MAJ	6			5		6						3	2	2	1	
	TS	1, 3					3, 4, 5						5	0	2	2	
RO <input type="checkbox"/>	RX		4		3								2	1	1	0	
SRO-I <input checked="" type="checkbox"/>	NOR								1, 2				2	1	1	1	
SRO-U <input type="checkbox"/>	I/C		5		1, 2, 4				4, 8				6	4	4	2	
SRO-I 8	MAJ		6		5				6				3	2	2	1	
	TS				1, 3, 4								3	0	2	2	
RO <input checked="" type="checkbox"/>	RX						2						1	1	1	0	
SRO-I <input type="checkbox"/>	NOR			4		3							2	1	1	1	
SRO-U <input type="checkbox"/>	I/C		1, 2, 7, 8			1, 2, 4	3, 5, 7						10	4	4	2	
RO 1	MAJ		6			5	6						3	2	2	1	
	TS												0	0	2	2	
RO <input type="checkbox"/>	RX													1	1	0	
SRO-I <input type="checkbox"/>	NOR													1	1	1	
SRO-U <input type="checkbox"/>	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls" (ATC) and "balance-of-plant" (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a one-for-one basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.
- For licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.

Facility: Point Beach		Date of Exam: May 8 - 19, 2017											Operating Test No.: 2017					
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)			
		2			3													
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P					
RO <input type="checkbox"/>	RX	2													1	1	1	0
SRO-I <input type="checkbox"/>	NOR	1				3									2	1	1	1
SRO-U <input type="checkbox"/>	I/C	3, 4, 5				1, 2, 4									6	4	4	2
<input checked="" type="checkbox"/>	MAJ	6				5									2	2	2	1
SRO-U 1	TS	3, 4													2	0	2	2
RO <input type="checkbox"/>	RX				3										1	1	1	0
SRO-I <input type="checkbox"/>	NOR		2												1	1	1	1
<input checked="" type="checkbox"/>	I/C		5, 7		1, 2, 4										5	4	4	2
SRO-U <input type="checkbox"/>	MAJ		6		5										2	2	2	1
SRO-I 9	TS				1, 3, 4										3	0	2	2
RO <input checked="" type="checkbox"/>	RX			2		3									2	1	1	0
SRO-I <input type="checkbox"/>	NOR			1											1	1	1	1
SRO-U <input type="checkbox"/>	I/C			3, 4, 8		6, 7, 8									6	4	4	2
RO 2	MAJ			6		5									2	2	2	1
	TS														0	0	2	2
RO <input type="checkbox"/>	RX															1	1	0
SRO-I <input type="checkbox"/>	NOR															1	1	1
SRO-U <input type="checkbox"/>	I/C															4	4	2
	MAJ															2	2	1
	TS															0	2	2

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls" (ATC) and "balance-of-plant" (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a one-for-one basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.
- For licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.

Facility: Point Beach		Date of Exam: May 8 - 19, 2017 Operating Test No.: 2017																
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)			
		2			4													
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P					
<input type="checkbox"/> RO	RX	2													1	1	1	0
<input type="checkbox"/> SRO-I	NOR	1													1	1	1	1
<input type="checkbox"/> SRO-U	I/C	3, 4, 5													3	4	4	2
<input checked="" type="checkbox"/> SRO-U 2	MAJ	6													1	2	2	1
	TS	3, 4													2	0	2	2
<input type="checkbox"/> RO	RX			2											1	1	1	0
<input type="checkbox"/> SRO-I	NOR			1											1	1	1	1
<input type="checkbox"/> SRO-U	I/C			3, 4, 5											3	4	4	2
<input checked="" type="checkbox"/> SRO-U 3	MAJ			6											1	2	2	1
	TS			3, 4, 5											3	0	2	2
<input checked="" type="checkbox"/> RO	RX	2													1	1	1	0
<input type="checkbox"/> SRO-I	NOR					1, 2									2	1	1	1
<input type="checkbox"/> SRO-U	I/C		5, 7			4, 8									4	4	4	2
<input type="checkbox"/> RO 3	MAJ		6			6									2	2	2	1
	TS														0	0	2	2
<input checked="" type="checkbox"/> RO	RX				2										1	1	1	0
<input type="checkbox"/> SRO-I	NOR		1, 2												2	1	1	1
<input type="checkbox"/> SRO-U	I/C		3, 4, 8		3, 5, 7										6	4	4	2
<input type="checkbox"/> RO 4	MAJ		6		6										2	2	2	1
	TS														0	0	2	2
Instructions:																		
1. Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls" (ATC) and "balance-of-plant" (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I <i>additionally</i> serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.																		
2. Reactivity manipulations may be conducted under normal or <i>controlled</i> abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a one-for-one basis.																		
3. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.																		
4. For licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.																		