my the	REGUL	ATOR	INFORMA	TION	DISTRIBUTI	ON ST	EM (RID	S)	
AUTH'N WILLIAM	S,J.W. Flo NAME RE	THOR rida CIPIE	AFFILIAT Power & NT AFFIL	ION Light IATIO	Co.	OTARIZE wer & L	D: NO ight Co	•	DOCKET # 05000389
	: Advises tha condensate SSER 2 (NUR satisfies N	stora EG=084 RC al	ge tank 43),Reac lowable	vent: tor a ducti	hood housi uxiliary p lity facto	ng modi 1dg sli r.	fied,pei ding do		
DISTRIB TITLE:	UTION CODE: A OR [,] Submittal:	001D Genei	COPIES ral Dist	RECEI ribut	yED:LTR _(ion	ENCL	SIZE	:	₹. ¢ 9 ond app for brit par
NOTES: O	L:04/06/83								05000389
	RECIPIENT ID CODE7NAM NRR ORB3 BC		COPIES LTTR EN 7	ĊL 1	RECIPIE ID CODE/		COPI LTTR		
INTERNAL:	ACRS ELD/HDS2 NRR/DL ^x DIR N RR/DSI/ METB REG FILE	09 04	6 1 1 1	6	ADM/LFMB NRR/DE/MT NRR/DL/OR NRR/DSI/R RGN2	AB	1 1 1 1	0	
EXTERNAL:	LPDR NSIC	03⊧ 05⊧	1 1		NRC PDR NTIS	. 20	1 - 1	ł	

1

Ð

23

TOTAL NUMBER OF COPIES REQUIRED: LTTR 26 ENCL -

я	•	r ,,	и	÷	

х х + 2 , + 2 , + 3 • 1 Å й • ль Va

. н .

∯ ≂00-007 4 i t ⁶⁴ 7.3 <u>∈</u> ⁹ i 1 ¶ 2,3 ±3

at 1999 a							а Хол Х., .
	t)) Тя"	1) T	,		и) X , 1 , 1 , 1 , 1 , 1 , 1 , 1 , 1 , 1 , 1
	8	ł	¥ * ~			٠	к п; 5 В , К , , X , ; , X , ; , X , ;
		K	3. 🔨 ¹				\$
		•	· • •	Þ			, k ,
	K	R.	s selling se	12)(o∦ E S S S S
	Ļ	t		1	<i>5</i> ,	(·))

· « اد پې ۲ , I त्री ग 1.4. s.

).	вох	14000,	JUNO	BEACH,	FL 33408
----	-----	--------	------	--------	----------



FLORIDA POWER & LIGHT COMPANY

November 29, 1984 L-84-343

Office of Nuclear Reactor Regulation Attention: Mr. James R. Miller, Chief Operating Reactors Branch #3 Division of Licensing U.S. Nuclear Regulatory Commission Washington, D.C. 20555

Dear Mr. Miller:

Re: St. Lucie Unit No. 2 Docket No. 50–389 Tornado Missile Protection

The St. Lucie Unit 2 Safety Evaluation Report (NUREG-0843) Supplement No. 2, Section 3.5.3 identified three structures requiring strengthening because the design ductility ratio was greater than that allowed by the NRC staff. Two of these structures, the Intake Structure Pump enclosure fan housing and the Condensate Storage Tank vent hood housing, were modified as required. The third structure, the Reactor Auxiliary Building sliding door, was not modified because the certified material test report for the structural member in question specified an actual yield stress of 59 ksi, rather than the 50 ksi assumed in the original design. Therefore, the unmodified structure satisfies the NRC staff's allowable ductility factor, and no modification was necessary.

Very truly yours,

(Derody J. W. Williams. Jr.

Group Vice President Nuclear Energy

JWW/RJS/kgn