REGUL MORY INFORMATION DISTRIBUTINE SYSTEM (RIDS).

ACCESSION NBR:8010030375 DOC.DATE: 80/09/26 NOTARIZED: NO DOCKET # FACIL:50-244 Robert Emmet Ginna Nuclear Plant, Unit 1, Rochester G 05000244 AUTH.NAME AUTHOR AFFILIATION WHITE,L.D. Rochester Gas & Electric Corp. RECIP.NAME RECIPIENT AFFILIATION NOVAK,T.M. Assistant Director for Operating Reactors

SUBJECT: Responds to NRC 800815 |tr re exposure of fuel: assemblies & control rods during transfer while in refueling mode, Revised Tech Specs will be revised to include min level requirement.

DISTRIBUTION CODE: A001S COPIES RECEIVED:LTR _/ ENCL! O SIZE: // TITLE: General: Distribution for after Issuance of Operating Lic

1

NOTES:1 copy:SEP Sect. Ldr.

ACTION:	RECIPIENT ID CODE/NAME CRUTCHFIELD 04	COPIES LITTR ENCL 13 13	RECIPIENT ID CODE/NAME	COPIES LTTR ENCL
INTERNAL:	D/DIR,HUM FAC08 NRC PDR 02 OR ASSESS BR 10	1 1 1 0	I&E 06 OELD 11 REGELLE 01	2 2 1 0 1.
EXTERNAL':	ACRS 09 NSIC 05	16 16 1 1	LPDR 03	1

Uêt-6 1980

05000244

C ENCL 34

TOTAL NUMBER OF COPIES REQUIRED: LITR

n e de la companya de

A Constant of the second of th

and and a second a s In the second a second

Michille Cha

و ۲۹ م ∿گور کا کا س

н Г. е

The second se

• ,* • ·

.

* -

ROCHESTER GAS AND ELECTRIC CORPORATION • 89 EAST AVENUE, ROCHESTER, N.Y. 14649

LEON D. WHITE, JR. VICE PRESIDENT

TELEPHONE AREA CODE 716 546-2700

September 26, 1980

Director of Nuclear Reactor Regulation ATTN: Mr. Thomas M. Novak, Assistant Director for Operating Reactors Division of Licensing U. S. Nuclear Regulatory Commission Washington, D. C. 20555

Crutchfield

Subject: August 15, 1980 NRC Letter to All Westinghouse Pressurized Water Reactor Licensees - Water Level above Reactor Vessel Elange-while-in-Mode 6 R. E. Ginna Nuclear Power Plant, Unit #1 Docket No. 50-244

Dear Mr. Novak:

8010030

This is in response to your letter concerning the possibility of exposure of fuel assemblies and control rods during transfer while the plant is in Mode 6 (Refueling).

It has been normal practice at Ginna during refueling mode to maintain approximately 24.5 feet of water above the reactor vessel flange. Since the manipulator crane lifts the bottom of the fuel assembly no more than one foot above the reactor vessel flange during the transfer, this results in a water height of approximately 10 feet above the top of the fuel assembly and control rods at their highest point during transfer. Thus, our past practice of maintaining the proper refueling water level exceeds the NRC recommendation.

This requirement is not at present part of our Technical Specification. Our Technical Specifications will be revised to include the requirements of maintaining at least 23 feet of water above the reactor vessel flange while in refueling mode and our appropriate refueling procedures will be revised to include this minimum level requirement.

Very truly yours,

Lowhite, Je.

L. D. White, Jr.

н, э

• • • • •

)

•

i