LICENSEE EVENT REPORT

	CONTROL BLOCK:
01	FILISILISI 1 2 0 1 01 - 1 0 10 1 0 1 0 1 0 1 0 1 0 1 0
CONT	REPORT LL 6 0 5 100 1013 1315 7 019 12 1717.19 8 11 011 11 719 9
0 2	While shutdown during a planned plant outage, a QC verification check of
03	the installation of new Safety Injection Tank sample lines showed that four
04	raceway clips had been welded to the containment vessel wall. The clips
0 5	<pre>[were 1/2" x 2" in size and provided support to the 3/8" sample line. The]</pre>
05	clips were installed during the 1979 refueling outage, and their location
07	<pre>unoted after completion of the modification. Containment vessel integrity </pre>
0 13	remained intact. This is the first occurrence of this type. SYSTEM CAUSE CAUSE CAUSE COMP. VALVE
0 9	STOLE SUBCODE
	17 REPORT NUMBER 71 22 23 24 26 27 29 29 30 30 31 32
	ACTION FUTURE CAPECT SHUTGOWN HOURS (22) ATTACHMENT NORDA PRIME COMP. COMPONENT TAKEN ACTION CNPLANT METHOD HOURS (22) SUBMITTED PORMSUB. SUPPLIER MANUFACTURER (A) (B) [Z] (9) [Z] (0) [O]
	33 34 35 35 37 40 41 4 73 35
10	CAUSE DESCRIPTION AND CORRECTIVE ACTIONS (27) The clips were welded to the containment vessel by contractor personnel.
III IIII	•
	The clips were welded to the containment vessel by contractor personnel.
ш ш	The clips were welded to the containment vessel by contractor personnel They were removed from the containment vessel wall by grinding and have
	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have placed been re-installed in a proper location. The wall area in question was placed then non-destructively tested (PT) to verify wall proper location was required.
	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have peen re-installed in a proper location. The wall area in question was heat-treated and then non-destructively tested (PT) to verify wall integrity and to assure that no further action was required. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the personnel of the containment vessel wall by grinding and have provided the
	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have been re-installed in a proper location. The wall area in question was heat-treated and then non-destructively tested (PT) to verify wall integrity and to assure that no further action was required. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have personnel. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were removed from the containment vessel wall by grinding and have production was required. They were remov
	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have peen re-installed in a proper location. The wall area in question was heat-treated and then non-destructively tested (PT) to verify wall pintegrity and to assure that no further action was required. Integrity and to assure th
	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have been re-installed in a proper location. The wall area in question was heat-treated and then non-destructively tested (PT) to verify wall integrity and to assure that no further action was required. integrity and to assure that no further action was required. Contract 12 13 Control C
	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have placed been re-installed in a proper location. The wall area in question was heat-treated and then non-destructively tested (PT) to verify wall integrity and to assure that no further action was required. Integrity and to ass
111 112 113 114 , 14 , 15 , 15 , 15 , 17 , 18	The clips were welded to the containment vessel by contractor personnel. They were removed from the containment vessel wall by grinding and have been re-installed in a proper location. The wall area in question was heat-treated and then non-destructively tested (PT) to verify wall integrity and to assure that no further action was required. Integrity and to assure tha

· Come way

The first section of the section of

.

y

•

.

?