REGULATORY CORMATION DISTRIBUTION STORM (RIDS)

DOCKET #

05000389

ACCESSION NBR:8306210160 DOC.DATE: 83/06/17 NOTARIZED: NO FACIL:50-389 St. Lucie Plant, Unit 2, Florida Power & Light Co. AUTH.NAME AUTHOR AFFILIATION UHRIG.R.E. Florida Power & Light Co. RECIP.NAME RECIPIENT AFFILIATION EISENHUT.D.G. Division of Licensing

SUBJECT: Application to amend License NPF-16 revising Tech Spec requirement for primary & secondary coolants in steam generator to be greater than 100 F when coolant pressure greater than 200 psig.SER encl.

DISTRIBUTION CODE: BOOIS COPIES RECEIVED:LTR _/ ENCL __ SIZE: _____ TITLE: Licensing Submittal: PSAR/FSAR Amdts & Related Correspondence

NOTES:

	RECIPIENT ID CODE/NAME A/D LICENSNG LIC BR #3 LA	Ξ	COPIE LTTR 1 1		RECIPIENT ID CODE/NAME LIC BR #3 BC NERSES,V. 01	COPI LTTR 1 1	
INTERNAL:	ELD/HDS2		1	0	IE FILE	1	1
411 (WINNE +	IE/DEPER/EPB	36	3	3	IE/DEPER/IRB 35	1	1
	IE/DEQA/QAB	21.	Ť.	1	NRR/DE/AEAB	1	0
	NRR/DE/CEB	11	1.	1	NRR/DE/EHEB	1	1
	NRR/DE/EQB	13	2	1 2	NRR/DE/GB 28	2	2
	NRR/DE/MEB	18	1	ī	NRR/DE/MTEB 17	1	1
	NRR/DE/SAB	24	ī	ī	NRR/DE/SGEB 25	1	1
	NRR/DE/SGEB	30	ī	1	NRR/DHFS/HFEB40	1	1
	NRR/DHFS/LQB		ī	ī	NRR/DHFS/PSRB	1	1
	NRR/DL/SSPB		ĩ	Õ	NRR/DSI/AEB 26	1	1
	NRR/DSI/ASB		ĩ	1	NRR/DSI/CPB 10	1	1
	NRR/DSI/CSB	09	1	1	NRR/DSI/ICSB 16	1	1
	NRR/DSI/METB	12	Ĩ	1	NRR/DSI/PSB 19	1	1
	NRR/DSI/RAB	22	1	1	NRR/DSI/RSB 23	1	1
F	REGFILE	04	1	1	RGN2	×3	3
	RM/DDAMI/MIB		1	• 0			
EXTERNAL:	ACRS	41	6	- 6	BNL(AMDTS ONLY)	1	1
	DMB/DSS (AMDT	rs)	1	1	FEMA-REP DIV 39	1	1
	LPDR	03	1	1	NRC PDR 02	1	1
	NSIC	05	1	1	NTIS	1	1

					<u>م</u>		¥ .
(11 T)	11	PHOP.	1 7	X	s ³ , , } ⇔}	

- A REPART OF A R
- - CONTRACTOR AND CLARATER STATES S

STAND CLE BY LARGERARD AND GREENERS KÄRPHEND HER FILTER REVATERARD HERER Provider Frederik Kärpe Predeasting in Science Hander Kärphären in Steven Handelige Andrike Large Hergelene Kärphäre Kärphäre Frederik Frederik Predeasting Rockston ander greener for Ober Film Predeasting Rockston ander greener for Ober Film

A LAR A REPORT A LARGE A LARGE

: → →) →

		第三日第二日第二月第二日 第三月 - 八月 - 八月 - 八月 - 八月 - 八月 - 八月 - 二月 - 二			
нĤ	-	and an it fait	¥	¥ · ···	at the days of the
Å	1	n territan N territan N territan	ħ	ĩ	Sat an All All All A
×	R	Raj K Itk	,*	å	San 1993年1月1日 ● 第二日第三日日
۶,	1	デビー・「第人」(第4年の人一天	×	ĸ	\mathbf{x}_{i} $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$ $\hat{\mathbf{x}}_{i}$
۴.,	1	Alter Al No 🖈 🔊 Solo	ľ	1.	Star 1 B. Mar & Say
ĩ	t i	£ \$P\$ → \$P\$ 1 = #\$ X→	ľ	2	LE CONSIN CON
a)	5	A N I I I I N I KN I HAD	•	.1	e & And A Warden
X	<u>I</u>	NK - + BR N + WN + PA	i	X	in the second
L	1	Radio - Exercise 🗙 🖇 🗛 🖓	R	ł	\$15 1 1 14 17 N \$ 4 N 15 14 6
Į.	\$	One of the North State North	ł	j.	S. S. Contest N B. N. Bland
1	t	CONCRESS OF	₿.	X	58 16 N X 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
1	1	A. Barris Bright will	<i>ل</i> ا	I	Electropy 🔨 🗶 🐥 🖉 👘 👘
1	1	PERCENTER IN 197	1	Å	$d(1 + i\mathbf{N}) = \mathbf{N} + \mathbf{N} = \mathbf{N}$
Ŕ	t	14月 - 46月XX年代 411日	*	1	NE CANED N
Į	t	STA 11 11 11 11 11 11 11 11 11 11 11 11 11	,	×	
1	t	AS CONTRACT OF		1	S FRANK NO NO
¢.	8	3 () **!	X	x	eth film a
			K W	3	HAT NI CONN
1	t	CALLAR REPORT OF LAST	۰ م	4 #	st in a constant of
L	7	rie vIvx id Xi≩⊷ising R	ł	1.	VETA AD ARIN " +
8	t	1 3 1 1 1 1	5	11	e ka 10 fe g
X	t	*2 î i	,	x	e esta a la companya de la comp

•	W

FLORIDA POWER & LIGHT COMPANY June 17, 1983 L-83-349

Office of Nuclear Reactor Regulation Attention: Mr. Darrell G. Eisenhut, Director Division of Licensing U. S. Nuclear Regulatory Commission Washington, D.C. 20555

Dear Mr. Eisenhut:

Re: St. Lucie Unit No. 2 Docket No. 50-389 Proposed License Amendment Steam Generator Pressure/Temperature Limitation and Administrative/Editorial changes

In accordance with 10 CFR 50.90, Florida Power & Light Company submits herewith three signed originals and forty copies of a request to amend Appendix A of Facility Operating License NPF-16.

This amendment is submitted to revise the requirement for both primary and secondary coolants in the steam generator to be greater than 100°F when the pressure in either coolant is greater than 200 psig. This change is necessary to allow heatup of the primary coolant with the Reactor Coolant Pumps. This change is a revision to the like change submitted as part of FPL letter L-83-248 dated April 20, 1983, and therefore, supercedes that part of the April 20th submittal.

This amendment is also submitted to make several administrative/editorial changes. These changes have been identified as a result of continuing review of the Technical Specifications by both NRC and FPL.

The proposed amendment is described below and shown on the accompanying Technical Specification pages.

Page 3/4 4-1

In the footnote, delete "and 3.10.6". There is no Special Test Exception 3.10.6.

Page 3/4 7-10

Change the "5.6" and the "5.35" in Specification 4.7.1.6 b. to "4.2".

Page 3/4 7-12

Revise Specification .3.7.2 to apply only to the secondary coolant in the steam generator. Also, change the "275" in Specifications 3.7.2, 3.7.2 a. and 4.7.2 to "200".

Page 3/4 7-30

05000298

06210160 830617

Change the "3.7.11.4 and 3.7.11.5" in Specification 3.7.11.1 c. to "3.7.11.3 and 3.7.11.4".

Page 2 Office of N⊎clear Reactor Regulation Mr. Darrell G. Eisenhut, Director

Page B 3/4 7-4

Change the "275" to "200" and the "30" to "20" in BASES 3/4.7.2.

Page 6-20

Delete the words "first half year" in the first line of the double - asterisk footnote.

In accordance with 10 CFR 50.91(b)(1), a copy of this proposed license amendment is being forwarded to the State Designee for the State of Florida.

In accordance with 10 CFR 50.91(a)(1), we have determined that this amendment does not involve any significant hazards considerations pursuant to 10 CFR 50.91(c) in that the amendment is administrative in nature and therefore does not:

- 1) involve a significant increase in the probability or consequences of an accident previously evaluated; or
- 2) create the possibility of a new or different kind of accident from any accident previously evaluated; or
- 3) involve a significant reduction in a margin or safety.

The proposed amendment has been reviewed by the St. Lucie Facility Review Group and the Florida Power & Light Company Nuclear Review Board....

In that this amendment is administrative in nature, it has been determined to be a Class II amendment, in accordance with 10 CFR 170.22. A check for \$1,200.00 will follow shortly.

Very truly yours,

Robert E. Uhrig Vice President Advanced Systems & Technology

REU/RJS/cab

Attachments

cc: J. P. O'Reilly, Region II Harold F. Reis, Esquire

> Ulray Clark, Administrator Radiological Health Services Department of Health and Rehabilitative Services 1323 Winewood Boulevard Tallahassee, Florida 32301

SAFETY EVALUATION

Page 3/4 4-1

This change is administrative/editorial, and therefore of no safety concern.

Page 3/4 7-10

This change is administrative/editorial (the actual valve closure time is 4.2 seconds, not 5.6 seconds or 5.35 seconds), and therefore of no safety conern.

Page 3/4 7-12 and B 3/4 7-4

Limiting Condition for Operation 3.7.2 for Technical Specification 3/4.7.2 requires that the temperatures of both primary and secondary coolants in the steam generators shall be greater than 100°F when the pressure of either coolant in the steam generator is greater than 275 psig. Our NSSS vendor has indicated that the 275 psig limit is incorrect and should be 200 psig. Furthermore, our startup procedures call for initial heating of the primary coolant to be performed utilizing pump heat from the reactor coolant pumps (RCP). However, the pump curve received from the vendor indicates that operation of the RCPs within these primary coolant system pressure limits will cause reduction in life of the RCP seals. Since the temperature of the secondary coolant in the steam generator is at ambient, about 80 to 90°F, this Technical Specification would preclude the use of RCPs to heat up the primary coolant without reducing seal life.

The bases for this Technical Specification is that by placing limits on the pressure and temperature of both the primary and secondary coolants, the pressure induced stresses in the steam generators do not exceed the maximum allowable fracture toughness stress limits. The current limits are based on a steam generator RT_{NDT} of 20°F.

However, Technical Specification 3/4.4.9 also contains pressure and temperature limitations for the reactor coolant system (RCS). The bases for these limits is the same as that for Technical Specification 3/4.7.2, i.e., to ensure that the maximum pressure induced stresses do not exceed the maximum allowable fracture toughness stress limits for the RCS pressure retaining components. Bases 3/4.4.9 states that these curves were developed assuming the maximum RTNDT for all RCS pressure-retaining materials, with the exception of the reactor pressure vessel, of 50°F.

Therefore, the pressure/temperature curves for Technical Specification 3/4.4.9 are appropriate for use for the primary coolant in the steam generator as well, since they are based on a more conservative basis (higher RT_{NDT}) than those in Technical Specification 3/4.7.2.

The pressure temperature limits in Technical Specification 3/4.7.2 are clearly more conservative and restrictive than required. Due to the potential problems of the RCP seals being operated at the low pressure currently required, the existing limits of 3/4.7.2 may cause the system to be operated in a condition less safe than desired.

Based on the above, it is our determination that removal of the pressure temperature limits for the primary coolant from Technical Specification 3/4.7.2 does not pose a risk to health and safety of the public. This is due to the fact that the secondary pressure boundary remains protected by this Technical Specification and that the primary pressure boundary is protected by Technical Specification 3/4.4.9. Our NSSS vendor concurs with this conclusion.

SAFETY EVALUATION (continued)

Page 3/4 7-30

Ths change is administrative/editorial, and therefore of no safety concern.

<u>Page 6-20</u>

This change is administrative/editorial, and therefore of no safety concern.

11 + 1