REGULATORY NFORMATION DISTRIBUTION STEEM (RIDS)								
STN-50-530 Palo Ve AUTH.NAME AUTHOR HAYNES,J.G. Arizona	rde Nuclear S rde Nuclear S rde Nuclear S AFFILIATION	Station, Unit 1, Ar Station, Unit 2, Ar Station, Unit 3, Ar The Project (formerly	izona Publi izona Publi izona Publi	05000528 05000529 05000530				
		ranch (Document Com	ntrol Desk)					
SUBJECT: Documents 870323 discussion re making both control element assembly calculators (CEACs) inoperable while performing certain surveillance tests,per Tech Spec 3.3.1,Action 6. Inoperabilaity of CEACs & entry into Action 6.desirable.								
DISTRIBUTION CODE: A001D COPIES RECEIVED:LTR / ENCL O SIZE: 2 TITLE: OR Submittal: General Distribution								
NOTES:Standardized plant Standardized plant Standardized plant	.M. Davis, NRR:	1Cy.		05000528 05000529 05000530				
RECIPIENT ID CODE/NAME PD5 LA LICITRA,E	COPIES LTTR ENCL 1 0 1	RECIPIENT ID CODE/NAME PD5 PD DAVIS,M	COPIES LTTR ENCL 5 \$ 1 1					
INTERNAL: ACRS NRR/DEST/ADE NRR/DLPQ/HFB NRR/PMAS/ILRB REG FILE 01	6 ' 6 1 1 1 1	ADM/LFMB NRR/DEST/ADS NRR/DDEA/TSB OGC/HDS1	1 0 1 1 1 1 1 D					
EXTERNAL: EG&G BRUSKE, S	1	LPDR		•				

1

3

NOTES:

27 ENCL TOTAL NUMBER OF COPIES REQUIRED: LTTR

## 

n an File

	1	1 4 A & A & A & A & A & A & A & A & A & A	Constant Republic	1	4 N 8 1
	UN 35	£	in the first of the Kerker	жан кил	** ( * j · · · · · · · · · · · · · · · · · ·
24. SOSC	Plate Provide States	્રે ર્વસ્ક્ર		\$ 4, - K, <sup>6</sup>	જ ઉપત્ની ચાલું છે.
1.350020340	for the second second	E . M	్రమహాలుతూ కాటుగ్రాశ్ కి. కి.		f
			1 N 1 N 1 N 1 N 1	} <b>*</b> -	15 M
	- 12 C L 5 F H	* <b>•</b> •	-1, ¶ <sup>2</sup> α − μ <sub>1</sub> (2) <sup>20</sup> − <sup>2</sup> (k) ( <sup>4</sup> → C <sup>-1</sup> ) (3)	, <b>S</b> , 11	а <sup>8</sup> т и
			THE ALL THE CONTRACTOR	1 × 14	1 in 10 .
	a total topa is	2 m m 1	1 <b>1</b> 2 1 480 - 930	1 اور مو	

ార్ వాసువేసు నీరుకు కర్షి లోపుర్రశ్ సినారాండా గాపుపారాడు? ఇద్ద స్పూర్ సంఎం కెంట్ సిని కాటా లోపెంటినిప్పాడు. కర్షి ఓటేంట్ ఎం కాపినిప్పు ప్రేక్ నాటా కర్షెటు పర్షిటు ఎం 13రెస్ వేస్ స్పోపు పు పు ప్రేక్షి కోప్పుడు. కర్షిటు ఓక్ స్పోటు ఎండ్ స్టాలు కోట్ ఎంటుగు ఓరాలు కా భాధారి స్పోటింగు పూరాలు పూరాలు.

I.

2 ( ) 1 · · · · · ·

', 1 4		· 使一下了了你,我们不可能。 王王子,一下韩妻,下了我不能说。	يە يە مەربى 10 مەربى		The second s
17	4	tan Bar Astoria	89 1997 1997 1997	¥ 8.	ν το β <sup>ανο</sup> τ . <b>≫<sup>3</sup> χ</b> <sup>το</sup> μ
4 1	*	ેસ્ટ વ્યવસાય 11 વિશ્વ કે વિશ્વ કે વ્યવસાય ઉલ્લાહ કે વિશ્વ કે વિશ્વ કે સંદર્ભ કરે વિશ્વ કે	4 × 4	۰,	
۱ بو	ţ	<sup>२</sup> ्व,_ इ.स. १	•	2 1	e e la station de la station d

2 e 34



Arizona Nuclear Power Project P.O. BOX 52034 • PHOENIX, ARIZONA 85072-2034

> March 30, 1987 161-00118-JGH/RAB

U. S. Nuclear Regulatory Commission Attention: Document Control Desk Washington, D. C. 20555 Subject: Palo Verde Nuclear Generating Station (PVNGS) Units 1, 2 and 3 Docket No: STN 50-528 (License No. NPF-41) STN 50-529 (License No. NPF-51) STN 50-530 (License No. NPF-65) Compliance With Technical Specification 3.3.1, Table 3.3-1, I.C.1 (CEACs), Action 6 for PVNGS Units 1, 2 and 3 File: 87-001-211

This is to document discussions on March 23, 1987 between Mr. G. W. Knighton, members of the NRC staff and PVNGS staff members in which the subject of making inoperable both CEAC's while performing certain surveillance tests was discussed.

When performing procedures 77ST-9SB11 and 77ST-9SB12, CEAC 1 and 2 Functional Checks, it is necessary to inop that CEAC for which the ST is being performed. During this time, if the other CEAC should auto-restart, or get a calculational error as has been the case in the past, the plant will trip (the same case exists if one CEAC must be taken out for maintenance). This test usually takes approximately 2 hours per CEAC to perform and is performed on a monthly basis. Beginning with the second fuel cycle for each unit, a software modification is planned which will eliminate this trip. This change has already been reviewed and approved by the NRC for other CPC plants.

If we experience a rod mis-alignment, slip or drop a rod as has happened in the past when performing Procedures 41ST-1SF01, 42ST-2SF01, 43ST-3SF01, CEA Operability Checks, a plant trip can occur. This test typically takes about 1.5 hours to perform and is performed on a monthly basis.

As we indicated, ACTION 6 provides the plant with an equivalent if not more conservative degree of protection, including reducing power and changing addressable constants (RSPT/CEAC INOP and BERR1). Operation per ACTION 6 has been fully analyzed by Combustion Engineering. There is no limit on the amount of time that the plant may be operated in ACTION 6.b or 6.c (both CEACs inop). Operation under ACTION 6 is effectively the normal operational mode of CE's plants with an analog protection system.

8704130191

PDR

ADOCK

u P • · тн **ө** 

1 v

. 3 

Ŧ

.

• • •

U. S. Nuclear Regulatory Commission Attention: Document Control Desk Page 2

Because of this, it is desirable and prudent to inop both CEAC's while performing the above evolutions and enter ACTION 6. This has the overall effect of reducing challenges to the Plant Protection System, and at the same time provide an equivalent or more conservative degree of protection for the plant.

After consultation with members of the NRC staff, Mr. Knighton concurred with our action to proceed with these tests scheduled on Unit 1 and requested we document our discussion via a letter to you.

Please contact R. Bernier of my staff immediately with any concerns.

Very truly yours,

V6. Daynes

J. G. Haynes Vice President Nuclear Production

JGH/RAB/d1m

- cc: O. M. De Michele
  - E. E. Van Brunt, Jr.
  - E. A. Licitra
  - G. W. Knighton
  - J. B. Martin
  - R. P. Zimmerman
  - A. C. Gehr

## • • •

¥ L

e a ser e ser e

ŗ

. **.** 

с г Ф