| | | | | 50-335 |
|-------------|-----------------|----------------------------|---------------------------|----------------------------|
| | S1 | F. LUCIE PI | LANT | Procedure No. |
| | C C | HEMISTRY OPER PROCEDURE | Current Revisión I 0 | |
| | PL | SAFETY RELATE | D | Effective Date 07/06/99 |
| ESTA | BLISHING | REMOTE LA | | |
| Responsible | Department: CHE | MISTRY | | |
| REVISION | SUMMARY: | | | N Res DA I |
| | | | CONTROL | PSL PSL E PRODUCTION |
| Davisian | FRG Review Date | Approved By R.G. West | Approval Date 05/27/99 | SOPS DATE |
| | 05/27/99 | Plant General Manager | Λ | DOCT PROCED |

9907300157 990726 PDR ADDCK 05000335 F PDR

I 1

ι, **.•**⊧ }

١.



ų

e A

÷ •

1 -

•

| · | | | |
|------|----------------|---|---------|
| REVI | SION NO .: | PRECEDURE TITLE: | PAGE: |
| | 0 | ESTABLISHING REMOTE LABORATORY | 2 of 12 |
| PROC | | FOR ANALYSES OF ACCIDENT SAMPLES | |
| | COP-06.11 | ST. LUCIE PLANT | |
| | | TABLE OF CONTENTS | |
| | SECTION | | PAGE |
| 1.0 | PURPOSE | | |
| 2.0 | REFERENCE | ES | 3 |
| 3.0 | PREREQUIS | ITES | 4 |
| 4.0 | PRECAUTIO | NS / LIMITATIONS | 4 |
| 5.0 | RECORDS F | EQUIRED | 4 |
| 6.0 | INSTRUCTIC | DNS | 5 |
| | 6.1 The OS | C Chemistry Supervisor shall establish the operation of | - |
| | 62 Set Up F | Laboratories | ·····.5 |
| | 6.3 Set Up (| Gamma Pulse Height Analyzer(pha) System | |
| | 6.4 Set Up 7 | Tritium Analysis System Date/Time Initials | 9 |
| | 6.5 Set Up A | Alpha Analysis System Date/Time Initials | |
| | 6.6 Set Up S | Sample Prescreening Process in Remote Lab | |
| | | | |
| | FIGURES | • | |
| | | | |
| [FIG | UKE 1 | | |

ä

.• } 1 · · ·

,

,

å

• .

4.

.

d a ſ

| | 10 | | | | | |
|----------------------------------|--|---|--------------------------------------|--|--|--|
| REVISION | NO.: | | PAGE: | | | |
| 0 PROCEDURE NO.: COP-06.11 | | ESTABLISHING REMOTE LABORATORY | 3 of 12 | | | |
| | | ST LUCIE PLANT | | | | |
| | | | | | | |
| 1.0 F | PURPOSE | | | | | |
| 1.1 - (| This procedu Chemistry Su by the Techni | re provides instruction for the Operational Support Ce pervisor to establish remote laboratories at the locatic ical Support Center (TSC) Chemistry Supervisor. | nter (OSC) on(s) specified | | | |
| 1.2 | To identify the minimum analyses equipment required for initial Accident Conditions. | | | | | |
| 2 . 0 F | REFERENCE | ES | | | | |
| | One or more | <u>NOTE</u> of the following symbols may be used in this procedur | e: | | | |
| , , | § Indicates Condition and shal General | s a Regulatory commitment made by Technical Specif n of License, Audit, LER, Bulletin, Operating Experien II NOT be revised without Facility Review Group review Manager approval. | ications, ce, etc. w and Plant | | | |
| | Indicates practice without c | s a management directive, vendor recommendation, p or other non-regulatory commitment that should NOT consultation with the plant staff. | lant be revised | | | |
| L | Ψ Indicates | s a step that requires a sign off on an attachment. | | | | |
| 2 .1 F | Plant Procedu | ures | | | | |
| • | EPIP-0 | 05, Activation and Operation of the Operational Suppo | rt Center | | | |
| • | ADM-1 | 7.09, Invoking 10 CFR 50.54 (X) | | | | |
| • | COP-0 | 6.06, Guidelines for Collecting Post Accident Samples | 6 | | | |
| • | COP-0 | 7.10, Determination of Boron Manual Titration | | | | |
| • | COP-0 | 7-15, Determination of Boron Using the Mettler Titrato | or | | | |
| • | COP-6 | 5.01, Ortec Multichannel Analyzers | | | | |
| • | COP-0 LS6500 | 1.04, Determination of Gross Beta Gamma and Tritiur 0 Liquid Scintillation Counter | n with | | | |
| ٠ | C-46, E | Determination of Gross Alpha Radioactivity | | | | |
| | 1 | | | | | |
| | • | | | | | |
| | | | | | | |
| | | | | | | |

\$!

.+

6

٠

1

| REVIS | ION NO.: | | PAGE: | | | |
|----------------------------------|--|---|--|--|--|--|
| 0 PROCEDURE NO.: COP-06.11 | | ESTABLISHING REMOTE LABORATORY FOR ANALYSES OF ACCIDENT SAMPLES ST. LUCIE PLANT | 4 of 12 | | | |
| 3.0 | PREREQUIS | ITES | ************************************** | | | |
| 3.1 | Power from 1 | 10 volt AC outlets available. | | | | |
| 4.0 | PRECAUTIO | NS / LIMITATIONS | | | | |
| 4.1 | Standard Health Physics precautions shall be observed while handling all Accident samples. | | | | | |
| 4.2 | ADM-17.09, Invoking 10 CFR 50.54(X), addresses the suspension of some Technical Specifications Surveillances when the Reactor Coolant System (RCS) is declared Out of Service. ADM-17.09 should be reviewed if the RCS is declared out of service as a result of accident conditions. | | | | | |
| 4.3 | P-10 Gas is F | LAMMABLE and under high pressure in the bottle. | | | | |
| 5.0 | RECORDS R | EQUIRED | | | | |
| 5.1 | As per routine requirements of the applicable procedures regulating the systems and sampling, etc., as per Chemistry LIMs data base computer, records for | | | | | |

5.

Accident Sample Inventory and Tracking as per Results Templates P1_PAS_INV for Unit 1, and P2_PAS_INV for Unit 2, or shall be maintained in the plant files in accordance with QI-17-PSL-1, Quality Assurance Records.

| REVISIO | :.ON NC: | | | | PAGE: |
|---------|----------------|--|--|----------|-------------|
| PROCE | DURE NC |).: 3.11 | FOR ANALYSES OF ACCIDENT SAMPL ST. LUCIE PLANT | łY ES | 5 of 12 |
| 6.0 | INST | RUCTIC | DNS | Date/Ti | me Initials |
| 6.1 | The C of Re | DSC Cho mote La | emistry Supervisor shall establish the operation aboratories as follows: | l | |
| | 1. | The OS Chemi Remot and se | SC Chemistry Supervisor shall contact the TSC stry Supervisor to assess the location of the te Lab(s) based on the affected Reactor Unit afe location to locate the lab(s). | 7 | , |
| | | Check | the appropriate choices: | | |
| | | Accide | ent affected Reactor is Unit 1 | | |
| | | | OR Unit 2 | | |
| | | Boron | analysis Remote Lab is: | | |
| | | | Unit 1 Hot Lab | | |
| | | | Unit 2 Hot Lab | | • |
| | | | Unit 1 Cold Lab | | |
| | | | Other Location: | / | |
| | | pha an | alysis Remote Lab is: | | |
| | | | Unit 1 Hot Lab | | |
| | | 3 | Unit 2 Hot Lab | | |
| | | | Unit 1 Cold Lab | | |
| | | \$ | Other Location: | / | |
| | 2. | As soo shall as analys Remot stand(s | in as possible, the OSC Chemistry Supervisor ssess and/or direct that the following minimum es equipment is set up in the designated ie Lab(s), and ENTER the location of the test s). | | |
| | | One Bo OPER | oron Analysis Stand per Step 6.2 is ABLE at location: | / | |
| | | One pł OPER, | na multi-channel analyzer per Step 6.3 is ABLE at location: | / | |

*,

,

• .

•

• • • • • × .

• •

•

.

,

۴.

`

| DEVISION | | | r | | 1940E |
|-------------------|---|---|--|----------------------------|--------------------|
| | 0 RE NO.: P-06.11 | ESTABLISHI FOR ANALYS S | NG REMOTE LABOR ES OF ACCIDENT S T. LUCIE PLANT | RATORY SAMPLES | 6 of 12 |
| 5.1 T oj (c | he OSC Che peration of 1 continued) | emistry Supervisor s the Remote Laborat | shall establish the tories as follows: | <u>Date/Ti</u> | <u>me</u> Initials |
| 3. | As acc. the OS direct t up in th | ident time and man C Chemistry Super hat the following eq ne designated Remo | power conditions per visor shall assess an juipment / processes ote Lab(s). | mit, d/or are set | |
| | One Tr OPER/ | itium Analysis Syste ABLE at location: | em per Step 6.4 is | / | |
| | One Al OPER/ | pha Analysis System ABLE at location: | m per Step 6.5 is | / | |
| | A seco the Re Countin | nd pha Detector an mote Lab per Step (ng Room cannot be | d 92X spectrum mas 6.3 if the Chemistry used as a Remote L | ter in .ab/ | |
| | One Sa | ample Prescreening | J Process per Step 6. | 6/_ | <u> </u> |
| , | Implem Docum Step 5. | nent Accident Samp lentation Process fo .1 | le Inventory and Res or records required pe | sults er [:] / | , |
| | ÷ | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | • | | | | |
| | | | | | |
| | | | | | |

29,

<u>بر</u>

END OF SECTION 6.1

b:

.

• • • · · ·

.

T ar **X** a

| REVISI | ION NO.: | | PROCEDURE TITLE: | | PAGE: | |
|----------------------------------|----------|---|---|--------|-------|-----------------|
| 0 PROCEDURE NO.: COP-06.11 | | | ESTABLISHING REMOTE LABORATORY FOR ANALYSES OF ACCIDENT SAMPLES ST. LUCIE PLANT | | | 7 of 12 |
| 6.2 | Set L | Jp Boron | Analysis Stand(s) | Date/1 | ime | <u>Initials</u> |
| | 1. | ENSU of Bord choice Boron Lab loo | RE that a copy of COP-07.15, Determination on Using the Mettler Titrator, <u>or</u> as a second , a copy of COP-07.10, Determination of Manual Titration, is available for the Remote cation. | / | | |
| | 2. | ENSU reager applica | RE test stand equipment, standard and Its are available in the Remote Lab per the able procedure above. | /_ | | |
| | 3. | ENSU perforr | RE a QC Boron Calibration Check is ned on the instrument test stand prior to use. | / | | |
| | | | | | | |
| | | | 、 | | | |
| | | | | | | |
| | | | | | | |

4.

END OF SECTION 6.2

| REVISION NO .: | | | PAGE: |
|--------------------------------------|--|------------------|---------------------|
| 0 PROCEDURE NO.: COP-06.1 | ESTABLISHING REMOTE LABORATOR FOR ANALYSES OF ACCIDENT SAMPLI 1 ST. LUCIE PLANT | PRY 8 of PLES | |
| 6.3 Set Up | Gamma Pulse Height Analyzer(pha) System | Date/T | <u>ime Initials</u> |
| 1. E F | ENSURE that a pha system is available in the Remote Lab(s) consisting of: | | |
| F | PC Computer "HOBBES", one 92X Spectrum Master, and Detector #1 and/or Detector #2. | | |
| | OR | | |
| F | C Computer "CALVIN", one 92X Spectrum Master, and Detector #3. | / | <u></u> |
| 2. E N L | ENSURE that a copy of COP-65.01, Ortec Aultichannel Analyzers, is available in the Remote ab for the pha system(s). | / | |
| 3. <u> </u> C V F t t | the pha system(s) were moved from the Unit 1 Chemistry Counting Room <u>or</u> the Power to them vas interrupted, <u>Then</u> VERIFY that the High Voltage Power Supply to the Detector(s) has been restored to the values displayed on the front panel of each Detector's 92X interface box. | / | <u>,</u> |
| 4. E a t | NSURE that a Quality Control Check Source is vailable <u>and</u> that an Activity Check is performed on the Detector(s) that are present, prior to use. | / | <u> </u> |
| | | | , |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | : |
| | | | ¥ |
| , | | | |
| | END OF SECTION 6.3 | | |

'n

\$

3

1 r r r

. , 14

· · · .

, ,

.

u ' { \

¥ . ,

.

| REVIS | ION NO.: | | | | 10.01 | |
|-----------|----------|--|---|---|---------|----------|
| | | | CEDURE IIILE. | | PAGE | 2: |
| 0 | | | ESTABLISHING REMOTE | E LABORATORY | | 9 of 12 |
| PROCE | EDURE NC |).: | FOR ANALYSES OF ACC | IDENT SAMPLES | | 50112 |
| COP-06.11 | | | ST. LUCIE PL | ANT | | |
| 6.4 | Set U | lp Tritiun | n Analysis System | Da | te/Time | Initials |
| | 1. | ENSU availat | RE that a Beckman LS 6500 Sci le in a Remote Lab. | ntillator is | _/ | |
| | 2. | ENSU of Gros Liquid Remot | RE that a copy of COP-01.04, Des Beta Gamma and Tritium with Scintillation Counter is available Eab. | etermination n LS6500 in the | _/ | |
| | 3. | ENSUI availat the Us prior to | RE that Quality Control Check S le and that an Activity Check is er Program(s) for Tritium and/or use. | ource(s) are performed on 1 ml. Gross | _/ | |
| | | • • • • | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | r | | |
| | | | | ł | | |
| | | | | ł | | |
| | | | | T | | |
| | | | | t | | |
| | | | | | | |
| | | | | | | |

. *

40

 \cap

• . .

10 1 1

.

ۇ د

,

** *

·

· · · ,

| REVIS | | | PROCEDURE TITLE: | | PAG | Ξ: |
|-----------------------------|-------|---|--|--|---------|-------------|
| PROCEDURE NO.: COP-06.11 | | o.: 6.11 | ESTABLISHING REMOTE LABORATOF FOR ANALYSES OF ACCIDENT SAMPL ST. LUCIE PLANT | | | 10 of 1 |
| 6.5 | Set l | Jp Alpha | Analysis System | Da | te/Time | Initia |
| | 1. | ENSU assem | RE that one Alpha Counter and counter and counter and counter by is available in a Remote Lab. | ounting | | |
| | 2. | ENSU Gross Lab. | RE that a copy of C-46, Determina Alpha Radioactivity is available in | ation of the Remote | _/ | . <u></u> . |
| | | | | | | |
| | L | | P-10 gas is FLAMMA | <u>3LE.</u> | | |
| | 3. | ENSUI supply | RE that a P-10 gas bottle is availa the instrument at the Remote Lab | ble to location. | _/ | |
| | 4. | <u>If</u> a P-1 up in a Countin instrum for gas | 0 bottle and temporary tubing hav Remote Lab (other than the Cher ng Room), <u>Then</u> the bottle connec lent tubing connections should be leaks. | ve to be set mistry Unit 1 stions and checked | _/ | |
| | 5. | ENSUI availab prior to | RE that a Quality Control Check S le and that an Activity Check is po use. | ource is erformed | | |
| | | | | | | |
| | • | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | END OF SECTION | 6.5 | ı | |
| | | | | | | |

ĵ^

,• <u>,</u> t

• • • •

a 1 ¹⁰ e , (

, 4

N. . ,

.

x

• . •

| REVISIC | N NO.: | | CEDURE TITLE: | | PAGE: | |
|-----------------------------|--------|---|--|--------|-------------|-----------------|
| PROCEDURE NO.: COP-06.11 | |).: 5.11 | ESTABLISHING REMOTE LABORATOR FOR ANALYSES OF ACCIDENT SAMPLI ST. LUCIE PLANT | | 1 | 1 of 12 |
| 5.6 Set Up Sa | | lp Samp | le Prescreening Process in Remote Lab | Date/1 | <u>'ime</u> | <u>Initials</u> |
| | 1. | OBTAI Meter f survey window | N a Health Physics General Area Survey for the Remote Lab. <u>If</u> available, <u>Then</u> the meter should have OPEN and CLOSED v capability. | / | | - |
| | 2. | VERIF affixed | Y that the Survey Meter is calibrated per the calibration sticker. | / | | |
| | 3. | CHECI satisfa | K the Survey Meter's Battery Check is ctory. | / | | |
| | 4. | The Su contac countir | rvey Meter should be used to measure t readings on accident samples prior to ig. | / | | |
| | 5. | For lon filled of sample countir | g-term accident recovery, Figure 1 should be ut to provide guidance for the maximum e radiation reading(s) that can be tolerated for ng without sample pretreatment (dilution). | / | | |
| | | | . · | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | END OF SECTION 6.6 | ų | | |

54

۰ ڏر

•

.

REVISION NO.:

١Ť

CEDURE TITLE:

PAGE:

PROCEDURE NO .:

COP-06.11

0

FOR ANALYSES OF ACCIDENT SAMPLES ST. LUCIE PLANT

ESTABLISHING REMOTE LABORATORY

12 of 12

FIGURE 1

MAXIMUM ALLOWABLE RADIATION READING ON SAMPLE FOR AVOIDING EXCESSIVE ANALYSIS DEAD TIME

(Page 1 of 1)

| For GAMMA Analysis Without Pre-Dilution | | | | | | | |
|---|-----------------------------------|---|---------------------------------|--|--|--|--|
| Sample TYPE and Container | Analysis System | HP Survey Meter Maximum Allowable Contact Reading | Specify Engineering Units | | | | |
| Gas in ~30 cc glass sphere | pha on Shelf #1 | | | | | | |
| Gas in 1250 cc mari beaker | pha on Face | | | | | | |
| Liquid in 16 ml vial geometry | pha on Shelf #1 | | | | | | |
| Liquid in 4000 ml mari beaker | 、 pha on Face | | | | | | |
| lodine in TEDA II cartridge | pha on Shelf #1 (flip counted) | | | | | | |
| Particulate Filter in Whirlpak on Shelf # 0 (zero) on Detector 1 (or 2) | pha on Shelf #0 (zero) | | | | | | |
| Particulate Filter in Whirlpak on Shelf #1 on Detector 3 | pha on Shelf #1 | | | | | | |
| Evaporated Liquid in planchet | pha on appropriate shelf | , | | | | | |

| For Alpha and Tritium Analysis Without Pre-Dilution | | | | | | | | |
|---|--------------------------|--|---------------------------------|--|--|--|--|--|
| Sample TYPE and Container | Analysis System | HP Survey Meter Maximum Allowable Contact Reading: Specify Open Window (OW) or Closed Window (CW) | Specify Engineering Units | | | | | |
| Tritium in Liquid Sample | Beckman LS6500 | | | | | | | |
| Tritium in Gas Sparger Sample | Beckman LS6500 | | | | | | | |
| Alpha in Evaporated Liquid Sample In Planchet | Alpha Counting System | | | | | | | |
| Alpha Filter Sample in Planchet | Alpha Counting System | | | | | | | |

.

· • .

, ·

· · ·

л . . , A

1/12/2000

Distri53.txt Distribution Sheet

Priority: Normal

From: Andy Hoy

| Action Recipients: K Jabbour | Copies: 1 | Paper Copy |
|--|------------------|--|
| Internal Recipients: RGN2.FILE 01 NRR/DSSA/SRXB FILE CENTER ACRS | 1 1 1 1 | , Paper Copy Paper Copy Paper Copy Paper Copy Paper Copy |
| External Recipients: NOAC | . 1 | Paper Copy |
| Total Copies: | · 6 | |

Item: ADAMS Document Library: ML ADAMS^HQNTAD01 ID: 003677141

Subject: St. Lucie Unit 1, Cycle 16 Startup Physics Testing Report

Body: ADAMS DISTRIBUTION NOTIFICATION.

Electronic Recipients can RIGHT CLICK and OPEN the first Attachment to View the Document in ADAMS. The Document may also be viewed by searching f or Accession Number ML003677141.

IE26 - Startup Report/Refueling Report (per Tech Specs)

Docket: 05000335

Page 1

• • • • •

. . .

۶ η



Florida Power & Light Company, 6351 S. Öcean Drive, Jensen Beach, FL 34957

January 12, 2000

L-2000-008 10 CFR 50,36

U. S. Nuclear Regulatory Commission Attn: Document Control Desk Washington, DC 20555

Re: St. Lucie Unit 1 Docket 50-335 Cycle 16 Startup Physics Testing Report

Pursuant to St. Lucie Unit 1 Technical Specification 6.9.1.1, the enclosed summary report of plant startup and power escalation testing for Cycle 16 is hereby submitted.

Should you have any questions, please contact us.

Very truly yours,

J. A. Stall Vice President St. Lucie Plant

JAS/spt

Enclosure: St. Lucie Unit 1, Cycle 16 Reactor Startup Physics Testing Report

cc: Regional Administrator, USNRC, Region II Senior Resident Inspector, USNRC, St. Lucie Plant

0036774)

TEXO

an FPL Group company

и В С , ***** • · .

• • • •

-• .

.

•

ST. LUCIE UNIT 1 CYCLE 16



STARTUP PHYSICS TESTING REPORT

(D/RE/930584-R0)

, , ,

.

· · ·

St. Lucie Unit 1, Cycle 16 Startup Physics Testing Report Author 99 Date 30 Walter D. Mead, Jr. Reactor Engineering, St. Lucie Plant 31/59 Date 12 Reviewed Lourdes M. Porro Reactor Engineering, St. Lucie Plant SEE FOLLOWING PAGE. Reviewed_ Date K. Nordmeyer for C. O'Farrill Nuclear Fuel, ENG Approved_ Ø Date 00 C. Ashton Pell Reactor Engineering Supervisor, St. Lucie Plant

• . . • • .

· · · · · • • .

•

-.

. .



· · x

• , _____

ł

Table of Contents

| Title | Page |
|-------------------------------------|--|
| Introduction | 3 |
| Cycle 16 Fuel Inspection and Repair | 4 |
| Cycle 16 Fuel Design | 5 |
| CEA Drop Time Testing | 6 |
| Approach to Criticality | 7 |
| Zero Power Physics Testing | 8 |
| Power Ascension Program | 9 |
| Summary | 10 |
| References | · 11 |
| | Title Introduction Cycle 16 Fuel Inspection and Repair Cycle 16 Fuel Design CEA Drop Time Testing Approach to Criticality Zero Power Physics Testing Power Ascension Program Summary References |

List of Figures

| Page |
|----------|
| 12 |
| . 13 |
| 14 |
| 15 |
| 16 |
| . 17 |
| . , 18 . |
| |

List of Tables

| Table | Title | Page |
|-------|------------------------------|------|
| | ۳ | |
| 1 | Cycle 16 Reload Sub-Batch ID | 19 |
| 2 | Approach to Criticality | 20 |
| 3 | CEA Group Worth Summary | , 21 |

I. Introduction

The purpose of this report is to provide a description of the fuel design and core load, and to . summarize the startup testing performed at St. Lucie Unit 1 following the cycle 16 refueling outage. The Startup testing verifies key core and plant parameters are as predicted. The major parts of this testing program include:

- 1) Initial criticality following refueling,
- 2) Zero power physics testing, and
- 3) Power ascension testing

During cycle 15 operation, an increase in iodine chemistry trending indicated the failure of one or more fuel pins. Fuel sipping and ultrasonic inspections were performed during the cycle 16 refueling outage. This testing confirmed the presence of failed rods in fuel assemblies residing in very low power locations in the cycle 15 core. Of these failures, 7 of 8 assemblies with failed fuel rods were scheduled for discharge to the spent fuel pool. The remaining assembly with a failed fuel rod was repaired for re-use in the cycle 16 loading pattern. The root cause of the failures was determined by the fuel vendor to be grid-to-rod fretting.

This Cycle 16 Startup Report is being submitted in accordance with Technical Specification 6.9.1.1 as the result of the use of:

- 1) a repaired and reconstituted, twice-burned fuel assembly that experienced a fuel pin breach near the end of cycle 15 operation and,
- 2) an assembly substituted for a fuel bundle that suffered grid strap damage in the spent fuel pool during fuel handling operations.

The test data collected during startup and summarized in this report indicates there were no observable changes in neutronic or thermal-hydraulic parameters and thus there was no significant impact to the performance of the unit. The test data satisfied all acceptance criteria and demonstrated general conformance to predicted performance.

۰ . ۰

. . . .

.

II. Cycle 16 Fuel Inspection and Repair

During the refueling outage, core-wide sipping of fuel used in cycle 15 was performed via a wet sipping system installed in the refueling machine mast. In this inspection campaign, eight fuel assemblies were identified with possible fuel failures; one twice-burned assembly (T-01) scheduled for reinsertion and seven thrice-burned assemblies scheduled to be discharged (S-30, S-32, S-34, S36, S-44, S-45, and S-48). The seven S-batch assemblies were all on the core periphery in low power locations during cycle 15 operation.

Ultrasonic inspections of these assemblies pinpointed fuel pins having the greatest probability of failure. These assemblies were reconstituted and the fuel pins subjected to further testing. Inspection of suspect rods using eddy-current and visual techniques resulted in identifying one failed rod out of four inspected in assembly T-01, four failed rods and two rods indicating wear out of nine rods inspected in assembly S-45, and one failed rod out of four inspected in assembly S-36.

Assembly T-01 was found to have one (1) leaking fuel pin in location E-2. The failed UO_2 pin has been reconstituted with a stainless steel filler rod, as shown in Figure 1. The final as-built configuration of assembly T-01 is bounded by the calculations performed in Reference 1 and satisfies all of the requirements in the guidelines provided by the Nuclear Fuels department. The fuel vendor, Seimen's Power Corporation (SPC), has stated in Reference 2 that it is acceptable to return assembly T-01 to the reactor for continued service in Cycle 16. The S-batch assemblies were discharged to the spent fuel pool for storage.

The results of SPC's evaluation support the conclusion that the failures observed do not represent a reactor safety or a fuel operability concern. This conclusion is further strengthened by the knowledge that the rods at greatest risk for grid-to-rod fretting are high exposure, low power rods operating at the reactor core's edge and that the RCS activity of cycle 15 and prior cycles has remained at levels well below Technical Specification limits.

In addition to the repairs made to T-01, a second assembly, S-76, was replaced with fuel bundle S-50 subsequent to the original core design loading pattern. S-76 resided in the spent fuel pool during cycle 15 operation and was inspected prior to use in cycle 16. The inspection revealed damage to a spacer grid strap necessitating replacement of the assembly. The assembly S-50 is equivalent to the assembly S-76 in terms of physical dimension and neutronic characteristics. The impact on the core design parameters and the operational data was determined to be insignificant. All the reload analyses continued to remain applicable for the revised core loading pattern (Reference 12)

4

)

•

, ,

III. <u>Cycle 16 Fuel Design</u>

The cycle 16 reload consists entirely of fuel manufactured by Siemens Power Corporation (SPC). The 217 assemblies of the cycle 16 core are comprised of fuel from four batches. Of these, 76 are fresh assemblies (Batch X), 76 are once-burned batch T and Batch U assemblies, and 65 are twice-burned assemblies from batches T and S. Table 1 provides enrichment information for the cycle 16 reload sub-batches. The design supports a cycle length between 12,480 EFPH and 12,858 EFPH based on a cycle 15 exposure of 13,600 to 14,370 EFPH.

This is the tenth cycle of operation utilizing gadolinium in the form of Gd_2O_3 , as a burnable neutron absorber. Batch X assemblies consist of enriched UO_2 fuel rods and UO_2 - Gd_2O_3 bearing rods (gadolinia burnable absorber fuel rods). UO_2 fuel rods have a central zone enrichment of 4.15 and 4.45 w/o U_{235} , whereas the UO_2 - Gd_2O_3 rods have a central zone of 4 to 8 w/o Gd_2O_3 dispersed in a 2.6 to 3.5 w/o U_{235} carrier. The total batch burnable absorber requirement for fresh fuel is 992 Gd_2O_3 rods. The mechanical design of Batch X fuel is essentially the same as that of Batches U & T (Cycle 15), Batch T (Cycle 14) and Batch S (Cycle 13) reload fuel. However the length of the axial blankets (UO_2) rods and cutback regions (Gadolinia rods) have changed for Batch X. Also the fuel assembly design for Batch X fuel utilizes radial enrichment zoning.

The entire cycle 16 fuel load, batches S, T, U and X, consist of the debris resistant fuel assembly design first implemented in cycle 11. This design has long fuel rod lower end caps which provides protection against debris-induced-fretting in the lower end-fitting region.

The cycle 16 core map is represented in Figure 2. The assembly serial numbers and control element assembly (CEA) serial numbers are given for each core location. A low-leakage fuel management scheme similar to that of Cycle 15 is utilized in the Cycle 16 core design. There are no vessel fluence reduction assemblies (VFRA) in the Cycle 16 core, similar to Cycle 15 core design. The Cycle 16 core loading pattern is 90 degrees rotationally symmetric.

۰ ۰ ۳ ,

IV. <u>CEA Drop Time Testing</u>

Following the core reload and prior to the approach to criticality, CEA drop time testing was performed. The purpose of this test is to demonstrate that the reactivity insertion as a function of time is bounded by the CEA scram worth curve assumed in the FSAR analysis.

The objective of this test is to measure the time of insertion from the fully withdrawn position (upper electrical limit) to the 90% inserted position under hot, full flow conditions. The average CEA drop time was found to be 2.28 seconds with maximum and minimum times of 2.52 seconds and 2.18 seconds, respectively. All drop times were within the 3.1 second requirement of Technical Specification 3.1.3.4 and the reload PC/M 99-016 requirements (References 10 & 13).

б

V. Approach to Criticality

The approach to criticality involved diluting from a non-critical boron concentration of 1592 PPM to a predicted critical boron concentration of 1383 PPM. Inverse count rate ratio (ICRR) plots were maintained during the period of dilution using wide range Nuclear Instrument Channels B and D. Refer to Figures 3 and 4 for ICRR information. Table 2 summarizes the dilution rates and times, as well as beginning and ending boron concentrations.

Initial criticality for St. Lucie Unit 1, Cycle 16, was achieved on October 16, 1999 at 1000 with CEA group 7 at 60 inches withdrawn and all other CEAs at the all-rods-out (ARO) position. The actual critical concentration was measured to be 1393 PPM.

*

• · · · · · ,

۰ ۰ ۰ · , •

•

• • .

VI. Zero Power Physics Testing

To ensure that the operating characteristics of the cycle 16 core were consistent with the design predictions, the following tests were performed:

- 1) Reactivity Computer Checkout;
- 2) Dual CEDM Symmetry Test;
- 3) All Rods Out Critical Boron Concentration;
- 4) Isothermal Temperature Coefficient Measurement; and
- 5) CEA Group Rod Worth Measurements.

Proper operation of the reactivity computer was verified through the performance of two tests. In the first, reactor power was elevated sufficiently high to ensure maximum sensitivity of the reactivity measuring system and at the same time preserve adequate margin to the point of adding heat. The second test ascertains the response to a known value of positive or negative reactivity by measuring the values of positive or negative reactor periods that result. The results of the reactivity computer checkout were compared to the appropriate predictions supplied in the reload PC/M 99-016. Satisfactory agreement was obtained.

Verification of proper CEA latching is confirmed through the use of a CEA symmetry test for those groups which contain dual CEAs (shutdown banks A&B). The prescribed acceptance criteria is that the reactivity measured for each dual CEA shall be within ± 15.0 pcm of the average reactivity measured all dual CEAs within the entire group. The acceptance criterion was satisfied and it was concluded there were no unlatched CEAs in either shutdown group.

The measurement of the all-rods-out (ARO) critical boron concentration was performed. The measured value was 1434 PPM which compared favorably with the design value of 1426 PPM (Reference 7). This was within the acceptance limits of \pm 50 PPM.

The measurement of the isothermal temperature coefficient was performed and the resulting moderator temperature coefficient (MTC) was derived. The MTC was determined to be 1.15 pcm/°F which fell well within the acceptance criteria of ± 2.0 pcm/°F of the design MTC of 0.99 pcm/°F (corrected). This satisfies the Unit 1 Technical Specification which states that the MTC shall be less positive than 7.0 pcm/°F when reactor power is less than 70% power.

Rod worth measurements were performed using the rod swap methodology. This method involves exchanging a reference group, which is measured by the boration dilution technique, with each of the remaining test groups. A comparison of the measured and design CEA 'reactivity worths is provided in Table 3. The following acceptance criteria applies to the measurements made:

1) The measured value of each test group, or supergroup measured, is within $\pm 15\%$ or ± 100 pcm of its corresponding design CEA worths, whichever is greater and,

2) The worth of the reference group and the total worth for all the CEA groups measured is within $\pm 10\%$ of the total design worth.

All acceptance criteria were met.

VII. Power Ascension Program

During power ascension, the fixed incore detector system is utilized to verify that the core is loaded properly and there are no abnormalities occurring in various core parameters (core peaking factors, linear heat rate, and tilt) for power plateaus at 30%, 45%, and 98% rated thermal power.

A summary of the flux maps at the 30%, 45% and 98% power plateaus is provided in Figures 5, 6 & 7. These flux maps are used for comparing the measured power distribution with the predicted power distribution. For the purposes of the power ascension, the acceptance criteria requires the root mean square (RMS) value of the power deviation be less than or equal to 5%. In addition, for the 30% and 98% plateaus, the individual assembly powers should be within 10% of the predicted power (both) and the relative power density (RPD) should be within 0.1 RPD units of predicted for the 30% power case. These criteria were satisfied.

When the unit reached full power, a calorimetric was performed in accordance with reference 8 for the purpose of calculating the RCS flow rate. The RCS flow rate was determined to have increased from 407,206 gpm (measured in cycle 15) to 409,240 gpm in cycle 16 (reference 8). This measured flow was well in excess of the Technical Specification minimum of 365,000 gpm and well within the flow measurement uncertainty.

Within seven effective full power days of attaining the equilibrium value of 100% power, a hot full power (HFP) MTC test was performed by maintaining power constant and varying temperature. The center CEA (7-1) was operated to permit compensation of the resulting reactivity changes. The HFP MTC was measured to be -6.21 pcm/°F. This satisfied the acceptance criteria to verify compliance with Technical Specification 3.1.1.4 to have a measured MTC less positive than +2.0 pcm/°F while thermal power is greater than 70%. The power coefficient was not measured.



VIII. Summary

Compliance with the applicable Unit 1 Technical Specifications was satisfactory and all acceptance criteria were met. The test data supports a conclusion that the repairs made to fuel assembly T-01 and the replacement of assembly S-76 with assembly S-50 had no significant effect on core behavior. The physics and thermal-hydraulic performance test data satisfied all acceptance criteria and demonstrated general conformance to predicted performance.

•

> .

· · · ·

•

•

" " .

.

IX. <u>References</u>

- 1) FPL Calculation PSL-1FJF-99-141, Rev 1, "St. Lucie Unit 1 Cycle 16 Region T Bounding Fuel Pin Reconstitution"
- 2) SPC Letter RIW:99:220, "Acceptability of Repaired Assembly T01 for Use in St. Lucie Unit 1 Cycle 16" September 29, 1999.
- 3) *"Initial Criticality,"* Pre-Operational Procedure 1-3200088
- 4) "Reload Startup Physics Testing," Pre-Operational Procedure 3200091
- 5) "Reactor Engineering Power Ascension Program," Pre-Operational Procedure 3200092
- 6) St. Lucie Unit 1 Technical Specifications.
- 7) St. Lucie Unit 1 Cycle 16 Reload PC/M #99016, CRN 99016-8628, Table 2.3.1
- 8) "RCS Flow Determination By Calorimetric Procedure," St. Lucie Unit 1 Operating Procedure 1-0120051
- St. Lucie Unit 1 Cycle 16 Reload PC/M #99016, Rev. 2, Attachment 1, Page 28 of 30.
- 10) ENG Calculation PSL-1FJF-93-025, Revision 0, "PSL1 CEA Drop Time Criteria for 90% Insertion"
- 11) "At Power Determination of Moderator Temperature Coefficient and Power Coefficient," Operating Procedure 3200051
- 12) St. Lucie Unit 1 Cycle 16 Reload PC/M #99016, Rev. 2, Page 18 of 62.
- 13) "Periodic Rod Drop Time Test and CEA Position Functional Test," Operating Procedure 1-0110054





SST Stainless Steel Filler Rod

• •

.

4

| 1 | | | , | | С | ycle 1 | 6 Coi | re Loa | ding | Patte | rn | | | ľ | N₽ | | | |
|----------|-----|-----|-------------|------|------|----------|-----------|------------|--------|--|-------------|-------|---------|-----------------|------------------|----------------|------------|---|
| | | | | | I. | I | | л і | < 1 | 4 | | | | | 1 | | | |
| Y | X | W | V | T | S | R | Ņ | Ļ | J | Ģ | F | E | D | ç | В | A | | |
| ļ | 1 | | | | | : · [| | 20 7 | | 70 | | | | | ļ | | | |
| . | | i | | : | ! | '' | 55 1. | 59 1. | 50 I | ^{, ,} , , , , , , , , , , , , , , , , , | | | | · · · · · · · · | · | | 21 | |
| i | | i | | T13 | S72 | U64 | X03 | X08 | X10 | T44 | S74 | T27 | | | | | 20 | |
| - | 1 | | Ì | | | | 130 | | 129 | | | | ł | | ! | - | 20 | |
| i | i | i | Т90 | X16 | X26 | X35 | U23 | T23 | U20 | X40 | X28 | X17 | T60 | | | | 19 | |
| i | | T92 | | 114 | TOS | 120 | ¥50 | 307 | Y64 | 106 | 1168 | 121 | ¥22 | T83 | | i | | |
| | : | 102 | 207 | 051 | 117 | 030 | 118 | 047 | 125 | 022 | 133 | 052 | 204 | 103 | | | 18 | |
| | T22 | X02 | U46 | X66 | U13 | X42 | T28 | U45 | T12 | X51 | U17 | X72 | U43 | X20 | T21 | | 4 7 | |
| i | | 105 | | | | 103 | | | | 132 | | | | 102 | | | 17 | |
| | S50 | X29 | U66 | U24 | U21 | U06 | X73 | S13 | X58 | U05 | U26 | U16 | T94 | X30 | S69 | _ | 16 | |
| | | | 79 | | 94 | | | | | | 97 | | 143 | | | i | | |
| : | T43 | X52 | U28 | X34 | U08 | X55 | T07 | X36 | T01 | X46 | U03 | X47 | U15 | X43 | U63 | | 15 | |
| T57 | | 122 | | 99 | | 124 | | 127 | | 113 | | 104 | | 119 | | ^{T63} | 14 | ŧ |
| | X04 | 032 | X76 | 111 | X60 | 104 | 060 | 039 | 058 | 102 | X69 | 124 | X70 | U10 | X13 | | 13 | |
| 134 | 140 | 710 | 101 | 1150 | 800 | YAA | 95 | 600 | 85 | ¥20 | 610 | HEE | 134 | T00 | 141 | | 12 | 2 |
| T30 | A14 | 306 | 042 | 050 | 309 | 123 | 019 | 520 F01 | 031 | 135 | 510 | 055 | 049 | 308 | | T32 -· | 11 | |
| 100 | X12 | U38 | X67 | T14 | X68 | T03 | U59 | U14 | U57 | T08 | X63 | T26 | X65 | U12 | X07 | ** | 10 |) |
| T72 | 126 | | 82 | | | | 115 | | 96 | | | | 137 | | 128 | T92 | 9 | |
| | Ū62 | X41 | U09 | X33 | U02 | X50 | T05 | X38 | T06 | X37 | U04 | X54 | U27 | X53 | T42 | | 8 | |
| | | 91 | | 109 | | 142 | | 112 | | 81 | | 87 | | 88 | | | 1 | |
| | S70 | X31 | T 95 | U30 | U25 | U01 | X57 | S14 | X71 | U07 | U33 | U29 | U67 | X25 | S75 | | 6 | |
| | • | | 80 | | 131 | | | | | | 116 | | 83 | | _ | | U | |
| | T20 | X09 | U53 | X62 | U35 | X49, | T15 | U54 | T17 | ,X56 | U34 | X61 | U41 | X01 | T19 | | 5 | |
| | | 111 | Voo | 1150 | 1105 | F02 | VTE | 1140 | VTA | 110 | 700 | 1144 | VOA | 108 | | | | |
| | | 173 | 203 | 056 | 005 | 018 | X/5 03 | 048 | X/4 | 011 | 193 | 044 | 205 | 189 | | | · 4 | |
| ٠ | 1 | | T67 | X15 | X32 | X48 | U37 | T25 | 1140 | X45 | X27 | X06 | T59 | | | | | |
| | | - | 107 | 100 | | 89 | 00, | 309 | 040 | 90 | <i>//_/</i> | . 98 | 105 | | | | • 3 | |
| | | | | T16 | S73 | T41 | X05 | X19 | X18 | U61 | S71 | T18 | | | | | . 2 | |
| • | | | | | | | 139 | | 138 | L | | | | | | | | |
| | | | | | | Т | 78 T | 36 T | 31 T | 81 | | | | | | | · 1 | |
| | | | | | | | | | ! | | Δ۵ | sembl | v Seri: | al # | - → [x] | xxI | | |
| | | | | | | | | | | | | Inse | t Seria | al # | → [^] # | ## | | |
| | | | | | | | | | | | | | | | تسا | | | |

Figure 2

F .

St. Lucie Unit 1, Cycle 16 Startup Physics Testing Report Figure 3 Inverse Count Ratio Plot - Channel B



St. Lucie Unit 1, Cycle 16 Startup Physics Testing Report Figure 4 Inverse Count Ratio Plot - Channel D

.







Power Distribution - 30% Power

| Measured: Source Power Level Exposure CEA Position | BEACON fe1_091020_ 28.5% 6.1 119 | 2019 *** *** F F F f F F F F F | Design: PCM 99016 F 30.0% 5 122 | ov 2 Attachme | ot 17 | | | | | | - | | | † | | | |
|--|--|---|---|---|---|---|---|---|--|---------------------------------------|--|---|---|---|--|----------------------------------|---------------|
| buron Conc. | 3600 (June 1 | nna llonaetade yn | (1200 ₁₉₄₀ - 1947) | arkhalenna ar seite s I | oli¥uti's' S | R 217 6 | 216 2250 216 2260 0 0.010 -4 | M L 215 1350 0 1343 0 1013 -4 | K J 1350 1343 1013 | H G L260 L265 9.005 | - | | | | | | _21 |
| | | 1 | ľ | 213 0.280 0.292 -0.012 -4.3 | 212 0.400 0.407 -0.007 -1.7 | 211 0.680 0.696 -0.016 | 210 1.120 1.135 -0.015 | 2079 1.220 1.242 -0.022 | 208 1.120 1.134 .0.014 | 207 0.697 -0.017 | 206 0.400 0.407 -0.007 | 205 0.280 0.292 -0.012 | _ | | <u> </u> | | _20 |
| | • | ĭ | 204 0.370 0.410 -0.020 -5.1 | 203 1.020 1.048 -0.028 -2.7 | 202 1.130 1.157 -0.027 -2.4 | 201 1.170 1.186 -0.016 -1.4 | 200 1.078 1.074 -0.004 -0.4 | 199 1.060 1.075 -0.015 | 192 1.070 1.074 -0.004 | 197 1.170 1.186 -0.016 | 196 1.130 1.155 -0.025 | 195 1.020 1.047 -0.027 | 194 0.390 0.403 -0.018 |][| | | _19 |
| - | × | 193 0,390 0,403 -0.018 -1.6 | 192 1.100 1.152 -0.052 -4.7 | 191 1.180 1.299 -0.029 -2.5 | 190 1.140 1.156 -0.016 -1.4 | 189 1.100 1.101 0.001 -0.1 | 188 1.330 1.326 0.004 0.3 | 187 1.240 1.234 0.006 0.5 | 1\$4 1.330 1.328 0.002 0.2 | 185 1.100 1.100 0.000 | 184 1.140 1.152 -0.012 | 183 1.180 1.207 -0.027 | 182 1.110 1.152 -0.042 | 181 0.400 0.410 -0.010 |] | | _11 |
| | 140 0.250 0.292 -0.012 -4.3 | 179 1.010 1.047 -0.037 -3.7 | 178 1.170 1.207 -0.037 -3.2 | 177 1.310 1.339 -0.029 -2.2 | 176 1.100 1.105 -0.005 -0.5 | 175 1.340 1.333 0.007 0.5 | 174 1.170 1.151 0.019 1.6 | 173 1.260 1.234 0.024 1.9 | 172 1.160 1.148 0.012 1.0 | 171 1.340 1.331 0.009 0.7 | 170 1.100 1.099 0.001 | 169 1.330 1.339 -0.009 -0.7 | 148 1.130 1.209 -0.029 | 167 1.020 1.043 -0.028 | 166 0.280 0.292 -0.012 |] | _ 17 |
| | 165 0.390 0.407 -0.017 -1.4 | 164 1.120 1.155 -0.035 -3.1 | 163 1.130 1.152 -0.022 -1.9 | 162 1.090 1.099 -0.009 -0.8 | 161 1.060 1.056 0.004 0.4 | 160 1.120 1.105 0.015 1.3 | 159 1.360 1.328 0.032 2.4 | 158 1.100 1.075 0.025 2.3 | 157 1.360 1.327 0.033 2.4 | 156 1.120 1.104 0.016 1.4 | 155 1.060 1.056 0.004 9.4 | 154 1.100 1.105 -0.005 | 153 1.140 1.156 -0.016 -1.4 | 152 1.130 1.157 -0.027 | 151 9.390 9.407 -0.017 |] | 14 |
| Y 135 0.750 | 150 0.670 0.697 -0.027 -4.0 | 149 1.160 1.186 -0.926 -2.2 | 148 1.090 1.100 -0.010 -0.9 | 147 1,340 1,331 0,009 0,7 | 146 1.120 1.164 0.016 1.4 | 145 1,350 1,315 0,035 2,6 | 144 1.130 1.097 0.033 2.9 | 143 1.330 1.274 0.036 2.7 | 142 1.130 1.100 0.030 2.7 | 141 1.350 1.315 0.035 2.6 | 140 1.130 1.105 0.025 2.2 | 137 1.350 1.333 0.017 > | 138 1.100 1.101 -0.001 | 137 1.170 1.186 -0.016 -1.4 | 136 0.650 0.696 -0.016 | | <u>.</u> 1 |
| 0.245 -0.015 -6.0 118 | 133 1.100 1.134 -0.034 -3.1 | 132 1.060 1.074 -0.014 -1.3 | 131 1,330 1,328 0,002 0,2 | 130 1.170 1.148 0.022 1.9 | 129 1.360 1.327 0.033 2.4 | 128 1.140 1.100 0.040 | 127 1.140 1.122 0.038 | 126 1.030 0.979 0.031 3.0 | 125 1.160 1.122 0.038 | 124 1.130 1.097 0.033 2.9 | 123 1.360 1.328 0.032 2.4 | 122 1.170 1.151 0.019 | 121 1.330 1.326 0.004 | 120 1.060 1.074 -0.014 | 119 1.110 1.135 -0.025 | 0.250 0.260 -0.010 -4.0 | 14 12 |
| 0.350 0.363 -0.013 -3.7 101 | 116 1.210 1.242 -0.032 -2.6 | 115 1.060 1.075 -0.015 -1.4 | 114 1.240 1.234 0.006 | 113 1.260 1.234 0.024 | 112 1.110 1.075 0.035 3.2 | 111 1.340 1.294 0.046 3.4 | 110 1.030 0.979 0.031 1.5 | 109 0.9 0.831 0.019 2.1 | 103 1.030 0.999 0.031 | 107 1.340 1.274 0.046 | 104 1.110 1.075 6.035 | 105 1.260 1.236 0.024 | 104 1.240 1.234 0.006 | 103 1.060 1.075 1.0015 | 102 1.210 1.242 -0.032 | 0.350 0.363 -0.013 -3.7 | 11 11 |
| 0.356 0.363 -0.013 -3.7 84 | 11 1.110 1.135 -0.025 -2.3 | 98 1.060 1.074 -0.014 -1.3 | 97 1.340 1.326 0.014 | 96 1.120 1.151 0.029 2.5 | 95 1.370 1.328 0.042 3.1 | 94 1.140 1.097 8.043 3.8 | 93 1.160 1.122 0.038 | 92 1.030 0.979 0.031 | 91 1.150 1.122 0.028 | 90 1.130 1.100 0.030 | 87 1.360 1.327 0.033 | 11 1.160 1.141 0.012 | \$7 1.330 1.328 0.002 | 86 1.050 1.074 -0.014 | \$5 1.100 1.134 -0.034 | 0.350 0.343 -0.013 -3.7 | 10 |
| 0.250 0.260 -0.010 -4.0 | 82 , 0.630 0.696 -0.016 -2.4 | \$1 1.170 1.186 -0.016 -1.4 | \$0 1.100 1.191 -0.001 -0.1 | 77 1.350 1.333 0.017 1.3 | 78 1.130 1.105 0.025 2.2 | 77 1.360 1.315 8.045 1.3 | 76 1.140 1.100 0.040 | 75 1.340 1.294 0.046 | 74 1.130 1.097 0.033 | 73 1.340 1.315 0.025 | 72 1.120 1.104 0.016 | 71 1,340 1,331 0,009 | 70 1.070 1.100 -0.010 | 69 1.160 1.186 -0.026 | 63 0.630 0.697 -0.017 | 0.250 0.265 -0.015 -6.0 | - - |
| | 67 0.390 0.407 -0.017 -4.4 | 66 1.130 1.157 .: -0.027 -2.4 | 65 1.140 1.156 -0.016 -1.4 | 64 1.110 1.105 0.005 0.5 | 43 1.070 1.054 0.014 1.3 | 62 1.130 1.164 0.026 2.3 | 61 1.370 1.327 " 0.643 3.1 | 60 1.110 1.075 0.035 3.2 | 59 1.360 1.328 0.032 2.4 | 58 1.320 1.105 0.015 | 57 1.060 1.056 0.004 | 56 1.100 1.077 0.001 0.1 | 55 1.140 1.152 -0.012 | 54 1.120 1.155 -0.035 | 53 0.390 0.407 -0.017 | | _6 |
| | 52 0.230 0.292 -0.012 -4_3 | 51 1.010 1.045 -0.038 -3.5 | 50 1.180 1.209 -0.029 -2.5 | 47 1.330 1.339 -0.009 -0.7 | 43 1.110 1.679 0.011 1.0 | 47 1.360 1.331 0.029 2.1 | 46 1.180 1.148 0.032 2.7 | 45 1.270 1.236 0.034 2.7 | 44 1.150 1.151 0.029 2.5 | 43 1.350 1.333 0.017 1.3 | 42 1.110 1.105 0.005 0.5 | 41 1.330 1.339 -0.009 -0.7 | 40 1.180 1.207 -0.027 -2.3 | 37 1.010 1.047 -0.037 -3.7 | 38 0.250 0.292 -0.012 -1.3 | | <u>_£</u> |
| | | 37 0.390 0.419 -6.020 -5.1 | 36 1.110 1.152 -0.042 -3.5 | 35 1.190 1.207 -0.017 -1.4 | 34 1.150 1.152 -0.002 -0.2 | 33 1.120 1.100 0.020 1.8 | 32 1.360 1.328 0.032 2.4 | 31 1.260 1.234 0.026 2.1 | 30 1.350 1.326 0.024 1.8 | 29 1.110 1.101 0.009 0.8 | 23 1.150 1.156 -0.006 -0.5 | 27 1.190 1.209 -0.019 -1.6 | 26 1.110 1.152 -0.042 -3.8 | 25 0.370 0.403 -0.018 -1.6 | | | -4 |
| | | | 24 0.400 6.403 -0.005 -2.0 | 23 1.030 1.047 -0.017 -1.7 | 22 1.150 1.155 -0.005 -0.4 | 21 1.199 1.184 0.004 0.3 | 20 1.070 1.074 0.016 1.5 | 19 1.090 1.075 0.015 1.4 | 18 1.070 1.074 0.016 1.5 | 17 5.190 5.156 0.004 0.3 | 16 1.150 1.157 -0.007 -0.6 | 15 1.020 1.045 | 14 0.400 0.410 -0.010 .2.5 | | <u></u> | | -2 |
| | | | | 13 0.290 0.292 -0.002 -0.7 | 12 0.400 0.407 -0.007 -1.7 | 11 8.700 8.697 8.003 0.4 | 10 1.140 1.134 0.006 | 9 1.250 1.242 0.008 0.6 | 8 1.140 1.135 0.005 0.4 | 7 8,690 0,496 -0.006 * | 6 6.400 6.407 -0.007 -1.7 | \$ 0.230 0.292 -0.012 -1.3 | | | | ····· | -2 |
| RMS Devi | ation: | 2.26% | | | , | 4 0.240 0.265 0 .1.9 | 3 0.349 0.343 -0.0 0.8 | 2 0.369 0.363 -0.0 -0.9 | 1 0.260 0.3 0.0 | »» | | * | | <u> </u> | | | _1 |

Key: Box # Measured Deelgn DeRa % DFL

4 -

. (

· · **4** , ,

•

۰. ۰

• • • • • • •

. .

*

1

.

۲



Power Distribution - 45% Power

F

| Measured: Source Power Level Exposure CEA Position | BEACON te1_001020_ 45.0% 9.0 124 | 1157 | Design: PCM 990181 45.0% 7 124 | Rev 2'Attachere | nt 17 | | | | | | | × | | † | | | |
|--|--|---|--|---|---|---------------------------------------|--|--|---|--|--|---|--|---|---|---|------------------|
| Inoron Conc. | (IEFAB Romina) X | inn an y no internet | ,1220 | T | insum cano i | R 217 | P N 216 0.260 0 0.003 -4 | H L 1 1 1360 6 1366 6 1006 1 | K J 1 214 1360 1367 1007 | H G 1 1 1.260 0.268 0.005 | | E | | | a | | 21 |
| | | | | 213 0.290 0.295 -0.005 -1.7 | 212 6.400 6.410 -0.010 -2.5 | 211 0.690 0.699 -0.009 | 210 1.120 1.133 -0.013 -1.2 | 209 1.230 1.239 -0.009 | 208 1.120 1.133 -0.013 -1.7 | 207 9.690 0.700 -0.010 | 206 0.400 0.410 -0.010 | 205 0.290 0.295 -0.005 |] | | | | _2 |
| | , | Ĩ | 204 0.400 0.413 -4.013 -3.2 | 203 1.020 1.046 -0.026 -2.5 | 202 1.130 1.153 -0.023 -2.0 | 201 1.170 1.183 -0.013 | 2009 1.070 1.073 -0.003 , -0.3 | 199 1.080 1.077 0.003 0.3 | 198 1.070 1.073 -0.003 | 197 1.170 1.183 -0.013 | 196 1.130 1.151 -0.021 | 195 1.020 1.045 -0.025 | 194 0.400 0.411 . -0.011 |] | | | _11 |
| | × | 193 0.400 0.411 -0.011 -2.7 | 192 1.120 1.152 -0.032 -2.9 | 191 1.180 1.204 -0.024 -2.0 | 190 1.140 1.153 -0.013 -1.1 | 189 1.100 1.100 0.006 0.0 | 188 1.330 1.322 0.003 0.6 | 1\$7 1.240 1.232 0.005 0.6 | 186 1.330 1.324 0.006 | 185 1.100 1.098 0.002 0.2 | 184 1.140 1.149 -0.009 | 183 1.180 1.202 -0.022 | 1\$2 1.120 1.152 -0.032 | 181 0.400 0.413 -0.013 |] | | _11 |
| | 180 0.280 0.295 -0.015 -5.4 | 179 1.010 1.045 0.035 -3.5 | 178 1.170 1.202 -0.032 -2.7 | 177 1.310 1.333 -0.023 -1.8 | 176 1.100 1.104 -0.004 -0.4 | 175 1.340 1.330 0.010 0.7 | 174 1.170 1.150 0.020 1.7 | 173 1.250 1.235 0.015 1.2 | 172 1.160 1.147 0.013 1.1 | 171 1.340 1.328 0.012 | 170 1.100 1.091 0.002 0.2 | 169 1.320 1.333 -0.013 | 168 1.180 1.204 -0.024 | 167 1.020 1.046 -0.026 | 166 0.290 0.295 -0.005 |] | 17 |
| | 165 0.390 0.410 -0.020 -5.1 | 164 1.120 1.151 -0.031 -2.8 | 163 1.130 1.149 -0.019 -1.7 | 162 1.090 1.098 -0.008 -0.7 | 161 1.060 1.058 0.002 0.2 | 160 1.120 1.106 0.014 1.3 | 159 1.360 1.326 0.034 2.5 | 158 1.100 1.077 0.023 2.1 | 157 1.350 1.325 0.025 | 156 1.120 1.106 0.014 | 155 1.070 1.058 0.012 | 154 1.100 1.104 -0.004 -0.4 | 153 1.140 1.153 -0.013 | 152 1.130 1.153 -0.023 -2.0 | 151 0.400 0.410 -0.010 -2.5 | | _15 |
| Y 135 6.240 0.248 -0.003 -3.1 | 150 0.630 0.700 -0.020 -2.9 | 149 1.160 1.183 -0.023 -2.0 | 143 1.090 1.098 -0.008 -0.7 | 147 1.330 1.328 0.002 0.2 | 146 1.120 1.106 0.014 1.3 | 145 1,340 1,315 0,025 1,9 | 144 1.130 1.101 0.027 2.6 | 143 1.330 1.297 0.033 2.5 | 142 1.130 1.103 9.027 2.4 | 141 1.350 1.315 0.035 2.6 | 140 1.120 1.106 •.014 | 139 1.340 1.330 0.919 0.7 | 134 1.100 1.100 0.00 | 137 1.176 1.183 -0.013 -1.1 | 136 0,650 0,679 -0.019 -2.5 | | _ <u>15</u>] |
| | 133 1.100 1.133 -0.033 -3.0 | 132 1.060 1.073 -0.013 -1.2 | 131 1.336 1.324 0.006 - | 130 1.160 1.147 0.013 1.1 | 129 1340 1325 0.035 2.6 | 128 1.140 1.103 0.037 3.2 | 127 1.160 1.130 0.030 2.6 | 126 1.040 1.009 0.031 3.0 | 125 1.140 1.130 0.030 2.6 | 124 1.130 1.101 0.029 2.6 | 123 1.360 1.326 0.034 2.5 | 122 1.170 1.150 0.020 1.7 | 121 1.330 1.322 0.008 0.6 | 120 1.060 1.073 -0.013 -1.2 | 117 1.110 1.133 -0.023 -2.1 | 0.240 0.263 -0.003 -1.2 117 | 14 13 |
| 0.350 0.367 -0.017 -1.9 101 | 116 1.210 1.239 -0.029 -2.4 | 115 1.070 1.077 -0.007 -0.7 | 114 1.240 1.232 0.008 0.6 | 113 1.260 1.235 0.025 2.0 | 112 1.110 1.077 0.033 | 111 1.340 1.297 0.043 3.2 | 110 1.040 1.009 0.031 2.2 | 109 0.92 0.897 0.023 2.5 | 103 1.040 1.009 0.031 | 107 1.340 1.297 0.043 | 106 1.100 1.077 0.023 | 105 1.250 1.235 0.015 | 104 1.240 1.232 0.003 | 103 1.070 1.077 -0.007 | 102 1.210 1.239 -0.029 | 0.360 0.366 -0.006 -1.7 100 | 11 |
| 0,350 0,366 -0,036 -4,6 84 | 99 1.110 1.133 -0.023 -2.1 | 98 1.060 1.073 -0.013 -1.2 | 97 1.330 1.322 0.008 | 96 1.179 1.150 0.020 1.7 | 95 1.360 1.326 0.034 2.5 | 94 1.140 1.101 0.039 3.4 | 93 1.170 1.130 0.040 3.4 | 92 1.040 1.009 0.031 | 91 1.160 1.130 0.030 2.6 | 90 1.130 1.103 0.027 2.4 | 89 1.350 1.325 0.025 | 88 [.160 [.147 [.147 | 87 1.330 1.324 0.006 | \$6 1.060 1.073 -0.013 | \$5 1.110 1.133 -0.923 | 0.360 0.367 -0.007 -1.9 | <u>10</u> |
| 0.250 0.263 -0.913 -5.2 | 82 0.630 0.679 -0.019 -2.8 | 81 1.170 1.183 -0.013 -1.1 | 20 1.100 1.100 0.000 | 79 1.350 1.330 0.029 1.5 | 72 1.130 1.106 0.024 2.1 | 77 1.350 1.315 0.035 2.6 | 76 1.140 1.103 0.037 3.2 | 75 1,340 1,217 0,043 3,2 | 74 1.130 1.101 0.029 | 73 1.340 1.315 0.025 | 72 1.120 1.106 0.014 | 71 1.330 1.328 9.002 | 70 1.070 1.071 -0.003 | 69 1.160 1.183 -0.023 | 68 0.680 0.700 -0.020 | 0.269 0.268 -0.003 -3.1 | <u>・</u> エ |
| | 67 0.400 0.410 -0.010 -2.5 | 66 1.130 1.153 -0.023 -2.0 | 65 1.140 1.153 -0.013 -1.1 | 64 1.110 1.104 0.006 0.5 | 63 1.070 1.058 0.012 1.1 | 62 1.130 1.106 0.024 2.1 | 61 1.360 1.325 0.035 2.6 | 60 1.110 1.077 0.033 3.0 | \$9 1.360 1.326 0.034 2.5 | 53 1.120 1.106 0.014 | 57 1.060 1.058 0.002 | 56 1.090 1.098 -0.003 | 55 1.130 1.149 -0.019 | 54 1.120 1.151 -0.031 | 53 0.400 0.410 -0.010 | | |
| • | 52 0.280 0.295 -0.015 -5.4 | 51 1.010 1.046 -0.036 -3.6 | 50 1.180 1.204 -0.024 -2.0 | 67 1.330 1.333 -0.003 -0.2 | 43 1.100 1.078 0.002 0.2 | 47 1.350 1.328 0.022 1.6 | 46 1.170 1.147 0.023 2.9 | 45 1.240 1.235 0.025 2.9 | 44 1.170 1.150 0.020 1.7 | 43 1.350 1.330 0.020 1.5 | 42 1.100 1.104 -0.004 -0.4 | 41 1.329 1.333 -0.013 -1.0 | 40 1.180 1.202 -0.022 | 39 1.010 1.045 -0.035 | 33 0.280 0.295 -0.015 | | _6 |
| | | 37 0.400 0.413 -0.013 -3.2 | 36 1.120 1.152 -0.032 -2.9 | 35 1.190 1.202 -0.012 -1.0 | 34 1.150 1.149 0.001 0.1 | 33 1.110 1.092 0.012 1.1 | 32 1.350 1.324 0.026 1.9 | 31 1.260 1.232 0.025 2.2 | 30 1.340 1.322 0.018 1.3 | 29 1.110 1.100 0.010 0.9 | 28 1.150 1.153 -0.003 -0.3 | 27 1.130 1.204 -0.024 -2.0 | 24 1.120 1.152 -0.032 -2.9 | 25 0.400 0.411 -0.011 -2.7 | | | _1 |
| | | | 24 0.400 0.411 -0.011 -2.7 | 23 1.030 1.045 -0.015 -1.5 | 22 1.140 1.151 -0.011 -1.0 | 21 1.190 1.183 0.007 0.6 | 20 1.030 1.073 0.007 0.6 | 19 1.090 1.077 0.013 1.2 | 1\$ 1.080 1.073 0.007 0.6 | 17 1.180 1.183 -0.003 -0.3 | 16 1.140 1.153 -0.013 -7.1 | 15 1.020 1.046 -0.026 -2.5 | 14 0.400 0.413 -0.013 -3.2 | | | | -2 |
| | | | , | 13 0.290 0.295 -0.005 -1.7 | 12 0.400 0.410 -0.010 -2.5 | 11 6,706 6,706 6,000 6,0 | 10 1.130 1.133 -0.003 -0.3 | 9 1.240 1.239 0.001 9.1 | \$ 1.130 1.133 -0.003 -0.3 | 7 0.690 0.699 -0.009 -1.3 | 6 0.409 0.419 -0.019 -2.5 | \$ 0.290 0.295 -0.005 -1.7 | | - | | | _2 |
| RMS Devi | ation: | 1.97% | | | | 4 6,270 6,268 6,1 6,7 | 3 0.340 0.367 -94 1.9 | 2 0.340 0.346 0.1 1.7 | 1 0.260 0.263 0, -1.2 | 003 | | | | ب | <u></u> | | -1 |



8

ş

.

.

` •

•

.

•

. .

· · · ·

•





Power Distribution - Full Power

| Measured: Source Power Level Exposure CEA Position Boron Conc. | BEACON 1+1_991021_ 94.0% 25.1 136 1064.4 | 1 130 * | Design: PCM 99016 R (100% 60.0 (137 (1004) | eř 2 Attačhmei | * 17 | B | | | | | | | | † | | | |
|---|---|---|---|---|---|---|---|---------------------------------------|---|---|--|---|--|---|---|---|------------------------|
| | • • • • • | | 5 | <u> </u> | \$ | 217 | 216 2260 271 0,011 4.2 | 215 376 0 374 0 1004 -6 | 1 1 370 214 374 0 1004 4 | 0.270 0.276 0.006 | | | | | | | _21 |
| | | | ` | 213 0.290 0.303 -0.013 -4.5 | 212 0.410 0.419 -0.009 -2.2 | 211 0.690 0.703 -0.013 -1.9 | 210 1.110 1.116 -0.006 -0.5 | 209 1.210 1.214 -0.004 | 208 1.110 1.117 -0.007 -0.6 | 207 0.690 0.764 -0.014 -2.0 | 206 0.419 0.419 -0.009 -2.2 | 205 0.290 0.302 -0.012 |] | | | , | _20 |
| | | Ĩ | 204 0.400 0.419 -0.019 -1.7 | 203 1.010 1.031 -0.021 -2.1 | 202 1.120 1.135 -0.015 | 201 1.170 1.168 0.002 0.2 | 200 1.070 1.068 0.002 0.2 | 199 1.030 1.077 0.003 0.3 | 198 1.060 1.068 -0.008 | 197 1.160 1.167 -0.007 -0.6 | 196 1.120 1.133 -0.013 | 195 1.010 1.030 -0.020 | 194 0.400 0.417 -0.017 -4 2 |] | | | _11 |
| | × | 193 0.400 0.417 -0.017 -4.2 | 192 1.110 1.138 -0.028 -2.5 | 191 1.160 1.183 -0.023 -2.9 | 190 1.130 1.144 -0.014 -1.2 | 189 1.100 1.098 0.002 0.2 | 188 1.320 1.310 0.010 0.5 | 187 1.230 1.227 0.003 0.2 | 184 1.320 1.310 8.019 0.8 | 125 1.070 1.076 -0.006 -0.6 | 184 1.130 1.141 -0.011 -1.0 | 183 1.160 1.182 -0.022 | 1\$2 1.120 1.138 -0.018 -1.6 | 181 0.410 0.419 -0.009 -2.2 |] - † | | 18 |
| | 180 0.270 0.302 -0.012 -4.1 | 179 1.000 1.030 -0.030 -3.0 | 178 1.150 1.182 -0.032 -2.8 | 177 1,300 1,313 -9,013 -1,9 | 176 1.100 1.109 -0.009 -0.8 | 175 1.330 1.324 0.006 0.5 | 174 1.170 1.153 0.017 1.5 | 173 1.250 1.237 0.013 | 172 1.160 1.149 0.011 0.9 | 171 1.330 1.322 0.008 0.6 | 170 1.100 1.103 .0.003 .0.03 | 169 1.300 1.313 -0.813 -1.0 | 168 1.170 1.183 -0.013 -1.1 | 167 1.010 1.031 -0.021 -2.1 | 146 0.290 0.303 -0.013 |] | _17 |
| Y 135 0.260 0.276 -0.016 -5.2 | 163 0,400 0,419 -0,019 -1,7 | 164 1.110 1.133 -4.023 -2.1 | 163 1.120 1.141 -0.021 -1.9 | 162 1.070 1.103 -0.013 -1.2 | 161 1.070 1.075 -0.005 -0.5 | 140 1.130 1.119 0.011 | 159 1.360 1.328 0.032 2.4 | 15# 1.110 1.091 0.019 1.7 | 157 1.350 1.327 0.023 1.7 | 156 1.130 1.118 0.012 1.1 | 155 1.080 1.075 0.005 0.5 | 154 1.100 1.109 -0.007 | 153 1.130 1.144 -0.014 -1.2 | 152 1.120 1.135 -0.015 -1.3 | 151 0.410 0.419 -0.009 -2.2 |] ^ | _19 |
| | 150 0.480 0.704 -0.024 -3.5 | 149 1.150 1.167 -0.017 -1.5 | 148 1.090 1.096 -0.006 -0.6 | 147 1.330 1.322 0.005 0.6 | 146 1.130 1.118 0.012 1.1 | 145 1.350 1.323 0.027 2.0 | 144 1.150 1.119 0.031 2.7 | 143 1.350 1.312 0.033 2.5 | 142 1.150 1.122 0.025 2.4 | 141 1.350 1.323 0.027 2.0 | 140 1.130 1.119 0.011 | 139 1.330 1.324 0.006 0.5 | 138 1.090 1.098 -0.008 | 137 1.160 - 1.168 -0.008 -0.7 | 136 0,690 0,703 -0,013 | | 35 |
| | 133 1.070 1.117 .0.027 .2.5 | 132 1.050 1.058 -0.908 -0.8 | 131 1.320 1.310 0.010 0.8 | 130 1.160 1.149 0.011 | 129 1.360 1.327 0.033 2.4 | 128 1.150 1.122 0.028 2.4 | 127 1.190 1.161 0.029 2.4 | 126 1.070 1.047 0.023 2.1 | 125 1.190 1.161 0.029 2.4 | 124 1.150 1.119 0.031 2.7 | 123 1,340 1,328 0.032 2,4 | 122 1.170 1.153 0.017 | 121 1.320 1.310 0.010 | 120 1.060 1.068 -0.005 | 119 1.100 1.116 -0.016 | 0.260 0.271 -0.011 -1.2 117 | <u>14</u> <u>12</u> |
| 0,360 0,374 -0,014 -3,9 101 | 116 1.200 1.214 -0.014 -1.2 | 115 1.070 1.077 -0.007 -0.7 | 114 1.230 1.227 0.003 8.2 | 113 1.240 1.237 0.023 1.8 | 112 1.120 1.091 0.029 2.6 | 111 1.350 1.312 0.038 2.8 | 110 1.070 1.047 0.023 2.9 | 109 0.97 0.949 0.021 2.2 | 108 1.070 1.047 0.023 2.1 | 107 1.350 1.312 0.038 2.8 | 106 1.110 1.091 0.019 1.7 | 105 1.250 1.237 0.013 | 104 1.230 1.227 0.003 0.2 | 103 1.070 1.077 -0.007 | 102 1.200 1.214 -0.014 | 0.360 0.374 -0.014 -3.9 | <u>12</u> 11 |
| 0.360 0.374 -0.014 -3.9 | 99 1.100 1.116 -0.016 -1.5 | 95 1,060 1,065 -0,003 -0,5 | 97 1.320 1.310 0.010 0.5 | 96 1.170 1.153 0.917 1.5 | 95 1.360 1.328 0.032 2.4 | 94 1.150 1.119 0.031 2.7 | 93 1.190 1.161 0.029 2.4 | 92 1.070 1.047 6.023 2.1 | 91 1.190 1.161 0.029 7.4 | 90 1.150 1.122 0.025 | \$\$ 1.350 1.327 0.023 | 83 1.160 1.149 0.011 | 87 1.310 1.310 0.000 | 84 1.060 1.068 -0.008 | 1.100 1.117 -0.017 | 0.360 0.374 -0.014 -3.9 | 10 |
| 0.260 0.271 -0.011 -4.2 | 82 0.690 0.703 -0.913 -1.9 | \$1 1.160 1.168 -0.008 -0.7 | \$0 1.100 1.098 0.002 0.2 | 79 1.340 1.324 9.016 1.2 | 72 1.140 1.119 0.021 | 77 1.360 1.323 0.037 2.7 | 76 1.150 1.122 0.028 | 75 [.350 1.312 0.038 | 74 1.150 1.119 0.031 | 73 1.350 1.323 0.027 | 72 1.130 1.118 0.012 | 71 1.330 1.322 0.003 | 70 1.090 1.096 -0.006 | 69 1.150 1.167 -0.017 | 68 0.490 0.704 -0.014 | 0.270 0.276 -0.006 -2.2 | * - - |
| | 67 0.410 0.419 -8.009 -2.2 | 44 1.120 1.135 -0.015 -1.3 | 45 1.140 1.144 -0.004 -0.4 | 64 1.110 1.109 0.001 0.1 | 43 1.080 1.075 0.005 0.5 | 42 1.140 1.118 0.022 1.9 | 61 1.340 1.327 0.033 2.4 | 40 1.120 1.071 0.027 2.6 | 2.7 2.9 59 58 1.360 1.130 1.322 1.119 9 0.032 0.011 | 57 1.050 1.075 0.005 0.5 | 56 1.100 1.103 -0.003 | 55 1.120 1.141 -0.021 | 54 1.110 1.133 -0.023 | 53 0.400 0.419 -0.019 | | _• | |
| | 52 0.290 0.303 -0.013 -4.5 | 51 1.010 1.031 -0.021 -2.1 | 50 1.179 1.183 -0.013 -1.1 | 47 1.310 1.313 -0.003 | 43 1.100 1.103 -0.003 -0.3 | 47 1.346 1.322 0.018 1.3 | 46 1.170 1.149 9.021 1.8 | 45 1.240 1.237 0.023 1.8 | 44 1.170 1.153 0.017 1.5 | 43 1.340 1.324 9.016 1.2 | 42 1.100 1.109 -0.009 | 41- 1.300 1.313 -0.013 -1.0 | 40 1.160 1.182 -0.022 -1.9 | 39 1.000 1.030 -0.030 | 33 0.290 0.302 -0.012 | | - |
| | | 37 0.410 0.419 -0.009 -2.2 | 36 1.120 1.138 -0.018 -1.6 | 35 1.170 1.182 -0.012 -1.0 | 54 1.140 1.141 -0.001 -0.1 | 33 1.100 1.096 0.004 0.4 | 32 1.330 1.310 0.020 1.5 | 31 1.240 1.227 0.013 1.0 | 30 1.330 1.310 0.020 1.5 | 29 1.100 1.098 0.002 0.2 | 28 1.140 1.144 -0.004 -0.4 | 27 1.160 1.183 -0.023 -2.0 | 26 1.110 1.138 -0.028 -2.5 | 25 0.400 0.417 -9.017 -4.2 | | | _4 |
| | | | 24 0.400 0.417 -0.017 -4.2 | 23 1.018 1.030 -0.020 -2.0 | 22 1.130 1.133 -4.003 -0.3 | 21 1.170 1.167 0.003 0.3 | 20 1.070 1.068 0.002 0.2 | 19 1.060 1.077 0.003 0.3 | 18 1.070 1.068 0.002 0.2 | 17 1.170 1.143 0.002 0.2 | 16 1.120 1.135 -0.015 -1.3 | 15 1.010 1.031 -0.021 -2.1 | 14 0.400 0.419 -0.019 -4.7 | | | ····· | -2 |
| | | | | 13 0.290 0.302 -0.012 -4.1 | 12 0.410 0.419 -0.009 -2.2 | 11 0.700 0.704 -0.004 | 10 1.120 1.117 0.003 0.3 | 9 1.220 1.214 0.006 0.5 | 8 1.110 1.116 .0.006 .0.5 | 7 0.690 0.703 -0.013 -1.9 | 6 0.410 0.419 -0.009 -2.2 | \$ 0.290 0.303 -0.013 -1.5 | | - | | | _2 |
| RMS Devi | ation: | 1.73% | | | | 4 0.270 0.276 .01 .2.2 | 3 0.370 0.374 -0.0 1.1 | 2 0.370 0.374 -0.1 -1.1 | 1 0.270 0.271 -0.4 | .001 | ·· | | | | | | ㅗ |

Key: Box # Measured Design Della % Diff.

.

.

,

d

Table 1Cycle 16 Reload Sub-Batch ID*

| . Sub-Batch | Number of Assemblies | Avg. Enrichment |
|-------------|----------------------|-----------------|
| S1 | 4 | 3.9 |
| \$2 | 1 | 3.88 |
| S4 | × 1 | 3.79 |
| S6 . | 7 | 3.76 |
| T1 | 8 | 4.43 |
| T2 | 20 | 4.41 |
| ТЗ | . 12 | 4.33 |
| T5 | 20 | 4.30 |
| U1, | 8 | 3.98 |
| U2 | 32 | 3.95 |
| U3 | 16 | 4.38 |
| U4 | 4 | 4.36 |
| U5 | 4 | 4.33 |
| U6 | 4 | 4.30 |
| . X1 | 24 | . 4.34 |
| X2 | 8 | 4.29 |
| . X3 | 24 | 4.26 |
| - X4 | 20 | 4.21 |

*Reference (9)

19

×

、 ·



Table 2

Approach to Criticality

| Dilution Rate | Initial Boron Concentration | Final Boron Concentration | Dilution Time (minutes) |
|---------------|--------------------------------|------------------------------|----------------------------|
| 132 gpm | 1592 | 1533 | 18 |
| 88 gpm | 1533 | 1433 | 48 |
| 44 gpm | 1433 | 1393 · | 46 |

, **v** • • • • • • n I

| Table 3 | | | | | | | | | |
|----------|-----------------|--|--|--|--|--|--|--|--|
| CEA Grou | o Worth Summary | | | | | | | | |

| CEA Group | Measured Worth (pcm) | Design * Worth (pcm) | Percent Difference |
|-------------------|-------------------------|-------------------------|--------------------|
| Reference Group A | 826.05 | 860.00 | -4.10 |
| 6 | 354.95 | 340.00 | 4.21 |
| 7 | 576.64 | 570.00 | 1.15 |
| 5 & B | 662.98 | 595.00 | 10.25 |
| 1 | 773.97 | 771.00 | 0.38 |
| 3 & 4 | 761.00 | 780.00 | -2.42 |
| 2 | 878.05 | 833.00 | 5.13 |
| - Total | 4834.25 | 4749.00 | 1.76 |

*Reference 7

Percent difference = (Measured-Design)/(Measured) *100

.21

۲۰۱ ۲۰۰۰ ۲۰ ۱۹ , • • • • • x • • • • • • • • • • . •

.

41