




<p>SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT</p>	<p>Seabrook Site – 50 Mile Radius Regional Climatological Data Stations</p>
	<p>Figure 2.3-1</p>



SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Summer Wind Rose for the 30 ft. Level (June 1972 – August 1972)	
		Figure 2.3-3




SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Fall Wind Rose for the 30 ft. Level (November 1971 and September, October 1972)	
		Figure 2.3-4




SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Annual Wind Rose for the 30 ft. Level (November 1971 - October 1972)	
	Figure	2.3-6




<p>SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT</p>	<p>Topographic Map within a Five Mile Radius of the Seabrook Site</p>	<p>Figure 2.3-7</p>
--	---	---------------------



SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Terrain Cross Section [2 Sheets]	
	Figure	2.3-8, Sh. 1 of 2




SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Terrain Cross Section [2 Sheets]	
	Figure	2.3-8, Sh. 2 of 2



SEABROOK STATION
 UPDATED FINAL SAFETY
 ANALYSIS REPORT


Topographic Map Showing the Location of the Meteorological Tower with Respect to the Reactor Area

Figure 2.3-9



MEANDER FACTOR IS VALID UP TO 800 METERS FROM SOURCE.

SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Meander as a Function of Wind Speed and Stability	
		Figure 2.3-10



SEABROOK STATION UPDATED FINAL SAFETY ANALYSIS REPORT	Plume and TIBL Interaction	
		Figure 2.3-11