

ACCELERATED DISTRIBUTION DEMONSTRATION SYSTEM

REGULATORY INFORMATION DISTRIBUTION SYSTEM (RIDS)

ACCESSION NBR: 8904130089 DOC. DATE: 89/03/30 NOTARIZED: NO DOCKET #
 FACIL: 50-315 Donald C. Cook Nuclear Power Plant, Unit 1, Indiana & 05000315
 AUTH. NAME AUTHOR AFFILIATION
 ALEXICH, M.P. Indiana Michigan Power Co. (formerly Indiana & Michigan Ele
 RECIPIENT AFFILIATION
 MURLEY, T.E. Document Control Branch (Document Control Desk)

SUBJECT: Forwards peaking factor limit rept for Unit 1 Cycle 11.

DISTRIBUTION CODE: A001D COPIES RECEIVED: LTR 1 ENCL 1 SIZE: 5
 TITLE: OR Submittal: General Distribution

NOTES:

	RECIPIENT		COPIES		RECIPIENT		COPIES	
	ID CODE/NAME		LTR	ENCL	ID CODE/NAME	LTR	ENCL	
	PD3-1 LA		1	1	PD3-1 PD	1	1	
	STANG, J		5	5				
INTERNAL:	NRR/DEST/ADS 7E		1	1	NRR/DEST/CEB 8H	1	1	
	NRR/DEST/ESB 8D		1	1	NRR/DEST/ICSB	1	1	
	NRR/DEST/MTB 9H		1	1	NRR/DEST/RSB 8E	1	1	
	NRR/DOEA/TSB 11		1	1	NUDOCS-ABSTRACT	1	1	
	OC/LFMB		1	0	OGC/HDS1	1	0	
	<u>REG FILE</u> 01		1	1	RES/DSIR/EIB	1	1	
EXTERNAL:	LPDR		1	1	NRC PDR	1	1	
	NSIC		1	1				

NOTE TO ALL "RIDS" RECIPIENTS:

PLEASE HELP US TO REDUCE WASTE! CONTACT THE DOCUMENT CONTROL DESK,
 ROOM P1-37 (EXT. 20079) TO ELIMINATE YOUR NAME FROM DISTRIBUTION
 LISTS FOR DOCUMENTS YOU DON'T NEED!

TOTAL NUMBER OF COPIES REQUIRED: LTR 22 ENCL 20

R
I
D
S
/
A
D
D
S

R
I
D
S
/
A
D
D
S

Indiana Michigan
Power Company
P.O. Box 16631
Columbus, OH 43216



AEP:NRC:1087

Donald C. Cook Nuclear Plant Unit 1
Docket No. 50-315
License No. DPR-58
CYCLE 11 PEAKING FACTOR LIMIT REPORT

U. S. Nuclear Regulatory Commission
Document Control Desk
Washington, D. C. 20555

Attn: T. E. Murley


March 30, 1989

Dear Dr. Murley:

This letter transmits the Peaking Factor Limit Report for Unit 1 Cycle 11 (attached). The report provides the burnup-dependent V(Z) function for Cycle 11, calculated for a delta-I band of $\pm 5\%$ at a core power level of 3250 MWt. The V(Z) function is referenced in Specification (T/S) 3.2.6, and is used in determining the allowable power level at which the reactor may operate. Per the NRC's Safety Evaluation Report for Unit 1 T/S Amendment 74 (reference page 18), the Peaking Factor Limit Report must be submitted at least 60 days prior to initial cycle criticality. The anticipated, initial Cycle 11 criticality date is June 5, 1989.

This document has been prepared following Corporate procedures that incorporate a reasonable set of controls to ensure its accuracy and completeness prior to signature by the undersigned.

Sincerely,


M. P. Alexich
Vice President

MPA/eh

8904130089 890330
PDR ADOCK 05000315
P PDC

A001
1/1

Dr. T. E. Murley

-2-

AEP:NRC:1087

Attachment

cc: D. H. Williams, Jr.
W. G. Smith, Jr. - Bridgman
R. C. Callen
G. Charnoff
G. Bruchmann
A. B. Davis - Region III
NRC Resident Inspector - Bridgman

ATTACHMENT TO AEP:NRC:1087

UNIT 1 CYCLE 11 PEAKING FACTOR LIMIT REPORT

Westinghouse
Electric Corporation

Nuclear Fuel
Business Unit



Commercial Nuclear
Fuel Division

Box 3912
Pittsburgh Pennsylvania 15230-3912

February 28, 1989

89AE*-G-0019

W-AEP/0608

Indiana Michigan Electric Company
c/o Eric G. Lewis
Engineer, Nuclear Materials and Fuel Management
American Electric Power Service Corporation
One Riverside Plaza, 20th Floor
Columbus, OH 43215

Dear Eric:

AMERICAN ELECTRIC POWER SERVICE CORPORATION
D. C. COOK UNIT 1
CYCLE 11 PEAKING FACTOR LIMIT REPORT

Attached please find the peaking factor limit report for D. C. Cook Unit 1, Cycle 11. The burnup dependent $V(Z)$ function has been calculated for a ΔI band of $\pm 5\%$ at a core power level of 3250 MWt. beginning-of-life to end-of-life of Cycle 11.

The calculation has been documented and independently verified.

A copy of the report is being provided on one (1) diskette for your convenience.

If you have any questions or comments, please call me.

Very truly yours,
L. A. Livingston
L. A. Livingston
Project Engineer
Fuel Projects

LAL:mld

Attachment

cc: D. H. Malin
V. D. Vanderburg
M. Whitley - D. C. Cook
R. Hennen - D. C. Cook



11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

D. C. COOK UNIT 1 CYCLE 11
V(2) FUNCTION

MESH NO.	AXIAL HEIGHT	BURNUP RANGES (MWD/MTU)								
		0 150	150 1000	1000 2000	2000 4000	4000 6000	6000 8000	8000 10000	10000 12000	12000 EOL
1.	0.00	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
2.	0.20	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
3.	0.40	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
4.	0.60	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
5.	0.80	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
6.	1.00	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
7.	1.20	1.0798	1.0798	1.0798	1.0813	1.0845	1.0892	1.0957	1.1039	1.1137
8.	1.40	1.0774	1.0776	1.0780	1.0800	1.0833	1.0880	1.0942	1.1018	1.1107
9.	1.60	1.0750	1.0754	1.0762	1.0785	1.0819	1.0865	1.0922	1.0991	1.1070
10.	1.80	1.0724	1.0730	1.0741	1.0767	1.0802	1.0845	1.0897	1.0958	1.1028
11.	2.00	1.0711	1.0718	1.0728	1.0752	1.0784	1.0822	1.0867	1.0920	1.0979
12.	2.20	1.0707	1.0712	1.0720	1.0739	1.0764	1.0795	1.0833	1.0876	1.0925
13.	2.40	1.0700	1.0703	1.0708	1.0723	1.0741	1.0765	1.0794	1.0827	1.0866
14.	2.60	1.0691	1.0693	1.0695	1.0704	1.0716	1.0731	1.0751	1.0775	1.0803
15.	2.80	1.0681	1.0681	1.0680	1.0682	1.0687	1.0695	1.0706	1.0720	1.0737
16.	3.00	1.0667	1.0667	1.0665	1.0665	1.0659	1.0656	1.0655	1.0657	1.0661
17.	3.20	1.0655	1.0655	1.0650	1.0648	1.0634	1.0626	1.0620	1.0617	1.0617
18.	3.40	1.0651	1.0651	1.0639	1.0630	1.0611	1.0602	1.0610	1.0626	1.0652
19.	3.60	1.0653	1.0653	1.0635	1.0620	1.0602	1.0604	1.0632	1.0677	1.0739
20.	3.80	1.0652	1.0652	1.0634	1.0618	1.0614	1.0628	1.0674	1.0740	1.0827
21.	4.00	1.0649	1.0649	1.0633	1.0619	1.0635	1.0657	1.0717	1.0802	1.0910
22.	4.20	1.0645	1.0645	1.0629	1.0617	1.0656	1.0681	1.0757	1.0861	1.0990
23.	4.40	1.0640	1.0640	1.0625	1.0617	1.0675	1.0705	1.0795	1.0916	1.1065
24.	4.60	1.0633	1.0633	1.0621	1.0620	1.0693	1.0726	1.0830	1.0966	1.1133
25.	4.80	1.0623	1.0623	1.0622	1.0622	1.0708	1.0745	1.0860	1.1010	1.1194
26.	5.00	1.0612	1.0621	1.0621	1.0622	1.0720	1.0760	1.0886	1.1048	1.1246
27.	5.20	1.0603	1.0618	1.0618	1.0618	1.0729	1.0771	1.0906	1.1079	1.1289
28.	5.40	1.0597	1.0612	1.0612	1.0613	1.0733	1.0777	1.0920	1.1101	1.1320
29.	5.60	1.0588	1.0604	1.0604	1.0617	1.0733	1.0779	1.0926	1.1114	1.1341
30.	5.80	1.0576	1.0593	1.0593	1.0619	1.0729	1.0775	1.0926	1.1117	1.1349
31.	6.00	1.0561	1.0581	1.0581	1.0616	1.0719	1.0765	1.0918	1.1111	1.1344
32.	6.20	1.0543	1.0565	1.0565	1.0608	1.0703	1.0749	1.0902	1.1094	1.1327
33.	6.40	1.0521	1.0544	1.0544	1.0596	1.0681	1.0727	1.0877	1.1066	1.1295
34.	6.60	1.0495	1.0519	1.0519	1.0579	1.0653	1.0697	1.0843	1.1027	1.1248
35.	6.80	1.0465	1.0491	1.0491	1.0552	1.0614	1.0657	1.0800	1.0982	1.1202
36.	7.00	1.0430	1.0450	1.0460	1.0537	1.0590	1.0626	1.0768	1.0947	1.1164
37.	7.20	1.0395	1.0425	1.0462	1.0535	1.0578	1.0605	1.0743	1.0915	1.1121
38.	7.40	1.0377	1.0441	1.0468	1.0526	1.0555	1.0575	1.0706	1.0869	1.1064
39.	7.60	1.0392	1.0460	1.0469	1.0511	1.0525	1.0537	1.0656	1.0809	1.0994
40.	7.80	1.0402	1.0475	1.0475	1.0491	1.0491	1.0508	1.0612	1.0746	1.0911
41.	8.00	1.0421	1.0487	1.0487	1.0463	1.0463	1.0512	1.0592	1.0695	1.0821
42.	8.20	1.0460	1.0493	1.0493	1.0474	1.0497	1.0532	1.0579	1.0638	1.0708
43.	8.40	1.0509	1.0512	1.0515	1.0525	1.0536	1.0549	1.0564	1.0581	1.0600
44.	8.60	1.0556	1.0563	1.0570	1.0583	1.0593	1.0600	1.0604	1.0606	1.0606
45.	8.80	1.0602	1.0610	1.0619	1.0634	1.0646	1.0654	1.0658	1.0659	1.0659
46.	9.00	1.0648	1.0656	1.0665	1.0680	1.0693	1.0702	1.0709	1.0712	1.0712
47.	9.20	1.0692	1.0701	1.0710	1.0726	1.0739	1.0750	1.0757	1.0761	1.0763
48.	9.40	1.0735	1.0744	1.0753	1.0770	1.0784	1.0795	1.0804	1.0810	1.0813
49.	9.60	1.0777	1.0784	1.0793	1.0809	1.0824	1.0838	1.0851	1.0862	1.0873
50.	9.80	1.0816	1.0822	1.0829	1.0844	1.0859	1.0876	1.0893	1.0911	1.0929
51.	10.0	1.0853	1.0858	1.0864	1.0879	1.0895	1.0914	1.0934	1.0956	1.0979
52.	10.2	1.0886	1.0892	1.0899	1.0915	1.0933	1.0953	1.0975	1.0999	1.1025
53.	10.4	1.0917	1.0923	1.0931	1.0948	1.0967	1.0988	1.1012	1.1037	1.1064
54.	10.6	1.0943	1.0950	1.0959	1.0977	1.0997	1.1019	1.1043	1.1068	1.1096
55.	10.8	1.0965	1.0972	1.0981	1.1000	1.1021	1.1044	1.1069	1.1096	1.1125
56.	11.0	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
57.	11.2	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
58.	11.4	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
59.	11.6	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
60.	11.8	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
61.	12.0	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000

Top and bottom 10% of core are excluded as per Technical Specifications.

