

ATTACHMENT 2 TO AEP:NRC:1067A

PROPOSED REVISED TECHNICAL SPECIFICATION PAGE

8901120449 881230
PDR ADOCK 05000315
P PDC

REACTIVITY CONTROL SYSTEMS

MINIMUM TEMPERATURE FOR CRITICALITY

LIMITING CONDITION FOR OPERATION

3.1.1.5 The Reactor Coolant System lowest operating loop temperature (Tavg) shall be $\geq 541^{\circ}\text{F}$ when the reactor is critical.

APPLICABILITY: Modes 1 and 2*[#].

ACTION:

With a Reactor Coolant System operating loop temperature (Tavg) $< 541^{\circ}\text{F}$, restore (Tavg) to within its limit within 15 minutes or be in HOT STANDBY within the next 15 minutes.

SURVEILLANCE REQUIREMENTS

4.1.1.5 The Reactor Coolant System temperature (Tavg) shall be determined to be $\geq 541^{\circ}\text{F}$:

- a. Within 15 minutes prior to achieving reactor criticality, and
- b. A least once per 30 minutes when the reactor is critical and the Reactor Coolant System Tavg is less than 545°F or when the low Tavg alarm is inoperable.

*See Special Test Exception 3.10.3

#With $K_{\text{eff}} \geq 1.0$.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100