REGULATORY INFORMATION DISTRIBUTION SYSTEM (RIDS) متنبية والمتناسية ACCESSION NBR:8211230412 DOC.DATE: 82/11/18 NOTARIZED: NO DOCKET # FACIL:50-250 Turkey Point Plant, Unit 3, Florida Power and Light C 05000250 50-251 Turkey Point Plant, Unit 4, Florida Power and Light C 05000251 AUTHOR AFFILIATION AUTH NAME UHRIG,R.E. Florida Power & Light Co. RECIPIENT AFFILIATION RECIP,NAME Division of Licensing EISENHUT, D.G.

SUBJECT: Forwards inservice insp relief Requests 6 & 7 originally transmitted 790918 & clarified w/addl info, in response to NRC 820316 & 0614 requests.

DISTRIBUTION CODE: A047S COPIES RECEIVED:LTR _/ ENCL _/ SIZE:______ TITLE: OR Submittal: Inservice Inspection/Testing

27

ENCL

25

NOTES:

	RECIPIENT ID CODE/NAM NRR ORB1 BC	E 01	COPIE LTTR 7		RECIPIENT ID CODE/NAU NRR CLIMBER	COPIES LTTR Encl 1 0		
INTERNAL:	ELD/HDS4 Nrr/de/Mteb RgN2	14	1 1 -1	0 1 1	REG FILE	15 04	1 1	1 1
.EXTERNAL:	ACRS NRC PDR NTIS	16 02	10 1 1	1 0 1 1	LPDR NSIC	03 05	1 1	1

۶.

TOTAL NUMBER OF COPIES REQUIRED: LTTR

rereaster a rarentia de leur ferra ferrada fonere en Ender 19 Eduction-Jan Taren andre elarte en telepus foner en Ernet C. ubunu259 - - - 59-2019 arren foner itante ar Flerrus foner and Ermit C. ubunu259 Auralia foner and Ender Araltelater

. . This is a now if shiral the state of the

clation where a strange of the easting

W Matt: Forwards indervice inder Petref Requests on a 7 originally in transmitted 770400 arched w/addl inform response to and redate a unit requests.

(lotatentied Gent; Pedro Americk ElGervierlin _ Ebbr - olke:______ 1111: # auented: Inservice Inspection/Insting

:0317

LUK EFFL			RECIPIENT ID FUDL/WAL		1140J 311J		REFERENT IN ERMIN AN				
11	r	18 . e	NIL ALIO SM.	7	١	10	all toxin 1996				
1 1	t I	ी । । ज	e enezionezza e Let filte	0 1 1	ية عالم ا	÷ф	FOR WARTS 1974 - NESNABA Synthes	● Ball 1 ¥ 4 € - 其			
í I	1 1	8 ki C v	L) BR Jote	1 () 1 1	UI 1 1	01 50	GXIGA 18 M Odda GXXX	€ \$61 ¹⁰ 10 × 1			

CO JUNE VS STUDIES AND DEPUT





November 18, 1982 L-82-514

Office of Nuclear Reactor Regulation Attention: Mr. Darrell G. Eisenhut, Director Division of Licensing U.S. Nuclear Regulatory Commission Washington, D.C. 20555

Dear Mr. Eisenhut:

Re: Turkey Point Units 3 & 4 Docket No. 50-250 & 50-251 Inservice Inspection Relief Request

Please find attached relief requests 6 & 7 originally transmitted by L-79-261 dated September 18, 1979 and clarified with additional information in response to your questions of March 16, 1982 by L-82-245 dated June 14, 1982. These requests are being transmitted following discussions with your staff.

Very truly yours,

h Elemes fr

Robert E. Uhrig Vice President Advanced Systems & Technology

REU/JEM/mvt

Attachments

8211230412 82111

PDR ADOCK

cc: Mr. James P. O'Reilly, Region II Mr. Harold F. Reis, Esquire

• • •

•

/ ,

х

,



Turkey Point Unit No. 4

RELIEF REQUEST NO. 6/7

- A. <u>Component Classification</u>:
 - Class 1
 - Code Examination Category 1) B-L-1, (Item No. B5.6) 2) B-L-2, (Item No. B5.7)

B. <u>Examination Requirement</u>:

- Code Item No. B5.6 Volumetric examination, to include 100% of pressure retaining welds, of one pump in each group of pumps performing similar functions in a system. The examinations shall be performed during each inspection interval, and maybe performed at or near the end of the inspection interval.
- 2) Code Item No. B5.7 Visual examination of the interval pressure boundary surfaces on one pump in each of the group of pumps performing similar functions in the system during each inspection interval. The examinations maybe performed at or near the end of the inspection interval.

C. <u>Relief Requested</u>: Reactor Coolant Pump (s)

In lieu of Volumetric Examinations, Florida Power & Light Co. proposes to perform:

- 1) 100% visual examination of the <u>external</u> surfaces only of one pump casing welds to the extent and frequency of Examination Category B-L-2.
- Partial surface examination of the <u>external</u> casing weld (s) of only one pump, conditions permitting - to the frequency of Examination Category B-L-2.
- D. Basis for Relief:
 - State-of-the-Art Ultrasonic Techniques have not been developed to meet the Code requirements. In the event that an ultrasonic examination technique is developed that meets the Code requirements, the intent of the Code will be followed. Florida Power & Light Company has representation on ASME Code committees, and keeps abreast of State-of-the-Art developments in all aspects of nondestructive examination methods in the industry.

1 . • , . . Ŀ • 1 , • . 1

Turkey Point Unit No. 4 RELIEF REQUEST NO. 6/7

- 2) Radiographic examination is not possible without the complete disassembly of the pump (see figure I). To perform this examination, large expenditures of manhours and man-rem are required with essentially no compensating increase in plant safety. Based on actual data compiled from the radiographic examination of the Turkey Point Unit No. 3 reactor coolant pump casing welds and visual examination of the internal pressure boundary surfaces on <u>one</u> pump, in excess of 5900 manhours and 46 man-rem exposure was expended in the disassembly, examinations and reassembly of the pump. These examinations are conducted under somewhat adverse conditions which have far reaching effects as depicted in Figure 2 thru Figure 5.
- 3) There is a very low probability, based upon industry experience, to disassembly pump(s) for maintenance purposes. There is no requirement by the pump manufacture (Westinghouse) to disassemble the pump(s) as part of normal maintenance or inspection. Accordingly, Florida Power & Light Company's procedures do not require disassembly of the pump(s) for maintenance of inspection purposes. There are no reported failures within the pump casings with these model pump(s). It's note worthy to mention that removal of the pump impeller does not provide access to the casing internal surfaces which would still prohibit the inspection (visual and volumetric) of the pump to Code requirements. See Figure I for items to be removed for Code ISI examination compliance.
- 4) Florida Power & Light Company feels that adequate safety margins are inherent in the basic pump design. The structural integrity afforded by the existing pump casing material will not significantly degrade over its lifetime. The reactor coolant pump casing material, cast stainless steel (ASTM A351-CF8M), is widely used in the nuclear industry and has performed extremely well. The presence of some delta ferrite (typically 5% or more) substantially increases resistance to intergranular corrosion and stress corrosion cracking. The delta ferrite also results in improved resistance to pitting corrosion.
- 5) Florida Power & Light Company feels that the satisfactory inspection results achieved in February 1982 (See D.2), coupled with the same inspections conducted by three (3) other utility company's and employing the same manufactures model pumps, provides additional assurance as to the pump's casing integrity.

. . . 1 ,

Turkey Point Unit No. 4 RELIEF REQUEST NO. 6/7


- Ε. Alternate Examinations:
 - Manufacture's Shop Radiographs, ASME Section III. Hydrostatic Tests, ASME Section XI. 1) 2) 3) 4)

 - Surface Examinations, ASME Section XI. Visual Examinations, ASME Section XI.

 - The extent of surface coverage to be achieved, and the alternate 5) examinations and tests, provide assurance of an acceptable level of quality and safety.


Implementation Schedule: . F.

At or near the end of the Inspection Interval.



1 - 4


<u>ا</u> ال




• •

•

.



54104 NO & Q & D P



. .

• •

•

* *

, , ,

· · · ·

. . .


•

•

.

** ->;

4



•

1

ч

.

	ELEVATIONS	14	'	30'	6	58	; '	*				14	1'	30'	6″	58	} ′
		PRIOR TO	DUR- 1N9	PRIOR TO	DUR- ING	PRIOR TO	DUR- 1NG					PRIOR TO	DUR- ING	PRIOK TO	DUR. ING	PRIOR TO	DUR- ING
A		100			· · ·	7	7	,	21			,					4
B		100	150	1		3	5		72								15.
С		80		4		4			23				•				15
D		90			1	7	7		Z4								15
E		70		4		4.5			75					21			15
F		70	75	.4	.6	.8			41	,							600
G		100		2		.4	4										•
н		5		.4	.5	2	3			NOTE!	ALL DO MREM/ }	SE P	PATE	s Ar	EIN		
I			۰ 	14		3.5	4				READING TAKEN	S FOR	VA 36	N9 W	ERE	NAL	
J					.6	.8	.8				2401	Aт	100%	1-2005	к ——		
K					· · · · ·	.4	.5							·			1 .
L						.4	[
M			3,			.7	1										
N			5			10	400										
0		ļ	25			10	400										
ρ		<u> </u>	2	 	ļ. 	10	400										·
Q		ļ	5		ļ	.10	400										
R			2.5		<u> </u>	.4											
Ş,			50		<u> </u>	۰5	.5										
Т			5		•	1.5	1.5										
u			2.5			10					, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
\vee		Ì				5											
W.						6	7										
X			, 			5	5				-						
Ч						10	15			•							
Z			'				5										

Needs Copres

NK 3