

ATTACHMENT # 4

DATA BASE DESCRIPTION
FOR THE
QUALIFIED SAFETY PARAMETER DISPLAY SYSTEM
FOR
TURKEY POINT, UNITS 3 & 4

QA Status: Verified

The safety related design information contained in this document has been reviewed and satisfies (where applicable) the items contained on check-list(s) 2, and 1 of the Quality Assurance of Design Manual. This review is so certified.

Independent Reviewer: Sam M. Miller

DATA BASE DESCRIPTION NUMBER 16081-ICE-3219, REVISION 00

Nuclear Power Systems
COMBUSTION ENGINEERING, INC.
Windsor, Connecticut

Prepared By George W. Starkweather
G. W. Starkweather (Lead Engineer, Safety Status
Monitoring Systems)

Date Jan 6,

Independently Reviewed By B. L. Mathies
B. L. Mathies (Safety Status Monitoring
Systems)

Date 1/6/83

Approved By K. R. Rohde
K. R. Rohde (Supervisor, Safety Status Monitoring Systems)

Date 1-12-83

Approved By J. L. Pucak
J. L. Pucak (Section Manager, Instrumentation Systems Design)

Date 1/12/83

Approved By T. P. Gates
T. P. Gates (Project Manager)

Date 1/13/83

This document is the property of Combustion Engineering, Inc. (C-E), Windsor, Connecticut, and is to be used only for the purposes of the agreement with C-E pursuant to which it is furnished.

Issue Date January 13, 1983

Page 1 of 28

8303140295 830310
PDR ADCK 05000250
PDR



RECORD OF REVISIONS

NO.	DATE	PAGES INVOLVED	PREPARED BY	INDEPENDENTLY REVIEWED BY	APPROVALS
00	1-13-83	All	B.W.Starkweather	B.L. Mathies	K.R. Rohde J.L. Pucak



ABSTRACT

This document describes the data base for the Qualified Safety Parameter Display System for Turkey Point, Units 3 & 4. This document has been quality assured according to the QADP, Revision 16.

NOTES

- (1) The input range is from a Type K (chromel-alumel) thermocouple. Signal values are obtained from Reference 5.

References:

- 1) A. W. Wilk, letter V-362 to T. P. Gates, November 12, 1982.
- 2) A. W. Wilk, letter V-333 to T. P. Gates, (File F 22056) August 11, 1982.
- 3) A. W. Wilk, letter V-341 to T. P. Gates, September 9, 1982.
- 4) B. L. Mathies, "HJTCS Reactor Vessel Level Constants for Turkey Point Units 3 and 4", Recorded Calculation 16081-ICE-36189, Revision 00, September 20, 1982.
- 5) ASTM Special Technical Publication 470, "Manual on the Use of Thermocouples in Temperature Measurement", August 1970.



DATA CONSTANTS
(FOR BOTH CHANNELS UNLESS NOTED)

<u>CONSTANT ID</u>	<u>DESCRIPTION</u>	<u>VALUE</u>	<u>UNITS</u>	<u>REF</u>
CINV ₁ *	Percent liquid inventory for sensor 1	67	%	4
CINV ₂	2	33	%	4
CINV ₃	3	19	%	4
CINV ₄	4	23	%	4
CINV ₅	5	18	%	4
CINV ₆	6	12	%	4
CINV ₇	7	12	%	4
CINV ₈	8	16	%	4
P _m	Maximum power to heaters	100	%	
T _{HB}	Breakpoint heated junction temperature for controllers 1 and 2	1100	°F	
T _{HM}	Minimum heated junction temperature for controllers 1 and 2	1400	°F	
DT _{UB}	Breakpoint differential temperature for controllers 1 and 2	500	°F	
DT _{UM}	Minimum differential temperature for controllers 1 and 2	700	°F	

* Sensors 1-2 in Head; 3-8 in Plenum.



SPDS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 7 of 28MANUEL A

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE							DBND	REFERENCE
				III LO	ENGINEERING	UNITS	ELECTRICAL	UNITS	DISPLAY	UNITS CONV	SET- POINTS	
TE-3-413A	THOT 1A	HOT LEG TEMPERATURE		III	750	°F	10	V			≥ 610	3°F 1
		LOOP A		LO	0		0				≤ 540	3°F
TE-3-423A	THOT 2A	HOT LEG TEMPERATURE		III	750	°F	10	V			≥ 610	3°F 1
		LOOP B		LO	0		0				≤ 540	3°F
TE-3-433A	THOT 3A	HOT LEG TEMPERATURE		III	750	°F	10	V			≥ 610	3°F 1
		LOOP C		LO	0		0				≤ 540	3°F
TE-3-410A	TCOLD 1A	COLD LEG TEMP		III	750	°F	10	V			≥ 555	3°F 1
		LOOP A		LO	0		0				≤ 540	3°F
TE-3-420A	TCOLD 2A	COLD LEG TEMP		III	750	°F	10	V			≥ 555	3°F 1
		LOOP B		LO	0		0				≤ 540	3°F
TE-3-430A	TCOLD 3A	COLD LEG TEMP		III	750	°F	10	V			≥ 555	3°F 1
		LOOP C		LO	0		0				≤ 540	3°F
PT-3-404	PRESSA	COOLANT SYSTEM PRESS		III	3000	PSIG	10	V			≥ 2310	30 1
				LO	0		0				≤ 1910	30



SPDS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3 & 4Page 8 of 28CHANNEL A

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE		ELECTRICAL	UNITS	DISPLAY	UNITS CONV	SET- POINTS	DDHD	REFERENCE
				HI	LO							
TE-3-6493A	TH1A	HJTC TEMPERATURE	III	2300	0F	50.99	mV					1
		LEVEL 1 - HEATED	LO	32		0						
TE-3-6493B	TU1A	HJTC TEMPERATURE	III	2300	0F	50.99	mV			2700	50F	1
		LEVEL 1 - UNHEATED	LO	32		0						
TE-3-6494A	TH2A	HJTC TEMPERATURE	III	2300	0F	50.99	mV					1
		LEVEL 2 - HEATED	LO	32		0						
TE-3-6494B	TU2A	HJTC TEMPERATURE	III	2300	0F	50.99	mV			2700	50F	1
		LEVEL 2 - UNHEATED	LO	32		0						
TE-3-6495A	TH3A	HJTC TEMPERATURE	III	2300	0F	50.99	mV					1
		LEVEL 3 - HEATED	LO	32		0						
TE-3-6495B	TU3A	HJTC TEMPERATURE	III	2300	0F	50.99	mV			2700	50F	1
		LEVEL 3 - UNHEATED	LO	32		0						
TE-3-6496A	TH4A	HJTC TEMPERATURE	III	2300	0F	50.99	mV					1
		LEVEL 4 - HEATED	LO	32		0						
TE-3-6496B	TU4A	HJTC TEMPERATURE	III	2300	0F	50.99	mV			2700	50F	1
		LEVEL 4 - UNHEATED	LO	32		0						
TE-3-6497A	TH5A	HJTC TEMPERATURE	III	2300	0F	50.99	mV					1
		LEVEL 5 - HEATED	LO	32		0						
TE-3-6497B	TU5A	HJTC TEMPERATURE	III	2300	0F	50.99	mV			2700	50F	1



16081-ICE - 1219, Rev 00

DCS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3 & 4Page 10 of 28.SHEET A

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE				DISPLAY	UNITS CONV	SET- POINTS	DBHD	REFERENCE
				III LO	ENGINEERING	UNITS	ELECTRICAL	UNITS				
TE-3-1E(T-1)	CET1AAB8	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		A-8 (core location)	LO	32		0				≤ 540	50°F	
TE-3-4E(T-4)	CET2AEH	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		E-4	LO	32		0				≤ 540	50°F	
TE-3-5E(T-5)	CET3AE7 (CET3AN11)	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		E-7 (N-11) *	LO	32		0				≤ 540	50°F	
TE-3-11E(T-11)	CET4AF11	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		F-11	LO	32		0				≤ 540	50°F	
TE-3-17E(T-17)	CET5AJ10	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		J-10	LO	32		0				≤ 540	50°F	
TE-3-18E(T-18)	CET6AJ12	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		J-12	LO	32		0				≤ 540	50°F	
TE-3-21E(T-21)	CET7AK8	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		K-8	LO	32		0				≤ 540	50°F	
TE-3-27E(T-27)	CET8AC8	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		C-8	LO	32		0				≤ 540	50°F	
TE-3-28E(T-28)	CET9AC12	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
		C-12	LO	32		0				≤ 540	50°F	
TE-2-24E(T-24)	CET10AD3	CORE EXIT TEMP	III	2300	°F	50.99	mV			2650	50°F	1, 2, 3
										≤ 540	50°F	



16081-1C1 - 3219 , Rev 00

PDS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 11 of 28INEL A

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE						SFT- PO TS	DBHD	REFERENCE	
				HI LO	ENGINEERING	UNITS	ELECTRICAL	UNITS	DISPLAY				UNITS CONV
TE-3-30E(T-30)	CET11A D5	CORE EXIT TEMP D-5	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-32E(T-32)	CET12A E10	CORE EXIT TEMP E-10	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-33E(T-33)	CET13A F13	CORE EXIT TEMP F-13	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-34E(T-34)	CET14A G2	CORE EXIT TEMP G-2	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-35E(T-35)	CET15A G8	CORE EXIT TEMP G-8	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-36E(T-36)	CET16A G15	CORE EXIT TEMP G-15	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-37E(T-37)	CET17A H3	CORE EXIT TEMP H-3	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-38E(T-38)	CET18A H5	CORE EXIT TEMP H-5	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
TE-3-40E(T-40)	CET19A H11	CORE EXIT TEMP H-11	III LO	2300 32	°F		50.99 0	mV			≥ 650 ≤ 540	5°F 5°F	1, 2, 3
			III	2300	°F		50.99	mV			≥ 650	5°F	1, 2, 3



16081 ICE-3219 Rev 00

-25 DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3 & 4

Page 12 of 28

REL A

[illegible]



16081-ICE-3219, Rev 00.

QSPDS DATA BASE: CALCULATED VARIABLES

INADEQUATE CORE COOLING INPUTS (continued)

Page 13 of 28

CHANNEL A

[illegible]



16081-ICE-3219, Rev 00

QSPDS DATA BASE: CALCULATED VARIABLES

INADEQUATE CORE COOLING INPUTS (continued)
PLANT

Page 14 of 28

CHANNEL A

[illegible]



INADEQUATE CORE COOLING INPUTS (continued)

PLANTPage 15 of 28

QSPDS DATA BASE: CALCULATED VARIABLES

CHANNEL A

[illegible]



QSPDS DATA BASE: CALCULATED VARIABLES

INADEQUATE CORE COOLING INPUTS (continued)

Page 16 of 28

CHANNEL A

[illegible]

PLANT

Page 17 of 28

A

[illegible]



SPDS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 18 of 28CHANNEL B

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE						UNITS CONV	SET- POINTS	DDHD	REFERENCE
				HI LO	ENGINEERING	UNITS	ELECTRICAL	UNITS	DISPLAY				
TE-3-413 B	THOT 1 B	HOT LEG TEMPERATURE		HI	750	°F	10	V			610	3°F	1
		LOOP A		LO	0		0				≤540	3°F	
TE-3-423 B	THOT 2 B	HOT LEG TEMPERATURE		HI	750	°F	10	V			≥610	3°F	1
		LOOP B		LO	0		0				≤540	3°F	
TE-3-433 B	THOT 3 B	HOT LEG TEMPERATURE		HI	750	°F	10	V			≥610	3°F	1
		LOOP C		LO	0		0				≤540		
TE-3-410 B	TCOLD 1 B	COLD LEG TEMP		HI	750	°F	10	V			≥555	3°F	1
		LOOP A		LO	0		0				≤540	3°F	
TE-3-420 B	TCOLD 2 B	COLD LEG TEMP		HI	750	°F	10	V			≥555	3°F	1
		LOOP B		LO	0		0				≤540	3°F	
TE-3-430 B	TCOLD 3 B	COLD LEG TEMP		HI	750	°F	10	V			≥555	3°F	1
		LOOP C		LO	0		0				≤540	3°F	
PT-3-406	PRESS B	COOLANT SYSTEM PRESS		HI	3000	PSIG	10	V			≥2310	30	1
				LO	0		0				≤1910	30	



SPDS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 19 of 28CHANNEL B

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE								SET- POINTS	DBND	REFERENCE
				HI LO	ENGINEERING	UNITS	ELECTRICAL	UNITS	DISPLAY	UNITS CONV				
TE-3-6501A	TH1B	HJTC TEMPERATURE		III	2300	°F	50.99	mV						1
		LEVEL 1 - HEATED		LO	32		0							
TE-3-6501B	TU1B	HJTC TEMPERATURE		III	2300	°F	50.99	mV			2700	5°F		1
		LEVEL 1 - UNHEATED		LO	32		0							
TE-3-6502A	TH2B	HJTC TEMPERATURE		III	2300	°F	50.99	mV						1
		LEVEL 2 - HEATED		LO	32		0							
TE-3-6502B	TU2B	HJTC TEMPERATURE		III	2300	°F	50.99	mV			2700	5°F		1
		LEVEL 2 - UNHEATED		LO	32		0							
TE-3-6503A	TH3B	HJTC TEMPERATURE		III	2300	°F	50.99	mV						1
		LEVEL 3 - HEATED		LO	32		0							
TE-3-6503B	TU3B	HJTC TEMPERATURE		III	2300	°F	50.99	mV			2700	5°F		1
		LEVEL 3 - UNHEATED		LO	32		0							
TE-3-6504A	TH4B	HJTC TEMPERATURE		III	2300	°F	50.99	mV						1
		LEVEL 4 - HEATED		LO	32		0							
TE-3-6504B	TU4B	HJTC TEMPERATURE		III	2300	°F	50.99	mV			2700	5°F		1
		LEVEL 4 - UNHEATED		LO	32		0							
TE-3-6505A	TH5B	HJTC TEMPERATURE		III	2300	°F	50.99	mV						1
		LEVEL 5 - HEATED		LO	32		0							
TE-3-6505B	TU5B	HJTC TEMPERATURE		III	2300	°F	50.99	mV			2700	5°F		1
		LEVEL 5 - UNHEATED		LO	32		0							



16081-ICE-3'19, Rev 00

DS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 20 of 28INSTRUMENT
AS NUMBER

PID

VARIABLE NAME

SENS
TYPEIII
LO

ENGINEERING

UNITS

ELECTRICAL

UNITS

DISPLAY

UNITS
CONVSET-
POINT

DBND

REFERENCE

TE-3-6506A

TH6B

HJTC TEMPERATURE

III

2300

°F

50.99

mV

1

LEVEL 6 - HEATED

LO

32

0

TE-3-6506B

TH6B

HJTC TEMPERATURE

III

2300

°F

50.99

mV

2700

5°F

1

LEVEL 6 - UNHEATED

LO

32

0

TE-3-6507A

TH7B

HJTC TEMPERATURE

III

2300

°F

50.99

mV

1

LEVEL 7 - HEATED

LO

32

0

TE-3-6507B

TH7B

HJTC TEMPERATURE

III

2300

°F

50.99

mV

2700

5°F

1

LEVEL 7 - UNHEATED

LO

32

0

TE-3-6508A

TH8B

HJTC TEMPERATURE

III

2300

°F

50.99

mV

1

LEVEL 8 - HEATED

LO

32

0

TE-3-6508B

TH8B

HJTC TEMPERATURE

III

2300

°F

50.99

mV

2700

5°F

1

LEVEL 8 - UNHEATED

LO

32

0



16081-ICE-3219, Rev 00

-DS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 21 of 28MODEL B

INSTRUMENT TAG NUMBER	PID	VARIABLE NAME	SENS TYPE	RANGE					UNITS CONV	SET- POINTS	DBND	REFERENCE
				III LO	ENGINEERING	UNITS	ELECTRICAL	UNITS				
TE-3-2E(T-2)	CET1BB5	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		B-5	LO		32		0			≤ 540	50°F	
TE-3-3E(T-3)	CET2BB10	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		B-10	LO		32		0			≤ 540	50°F	
TE-3-6E(T-6)	CET3BE12	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		E-12	LO		32		0			≤ 540	50°F	
TE-3-7E(T-7)	CET4BE14	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		E-14	LO		32		0			≤ 540	50°F	
TE-3-8E(T-8)	CET5BF3	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		F-3	LO		32		0			≤ 540	50°F	
TE-3-9E(T-9)	CET6BF5	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		F-5	LO		32		0			≤ 540	50°F	
TE-3-10E(T-10)	CET7BF9	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		F-9	LO		32		0			≤ 540	50°F	
TE-3-12E(T-12)	CET8BG1	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		G-1	LO		32		0			≤ 540	50°F	
TE-3-13E(T-13)	CET9BG6	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		G-6	LO		32		0			≤ 540	50°F	
TE-3-14E(T-14)	CET10BH8	CORE EXIT TEMP	III	LO	2300	°F	50.99	mV		≥ 650	50°F	1, 2, 3
		H-8	LO		32		0			≤ 540	50°F	



16081-ICE-3219, Rev 00

PDS DATA BASE: ANALOG INPUTS

PLANT TURKEY POINT 3&4Page 22 of 28INSTRUMENT
NO. B

INSTRUMENT NO.	PID	VARIABLE NAME	SENS TYPE	RANGE				UNITS CONV	SET- POINTS	DBND	REFERENCE
				III LO	ENGINEERING	UNITS	ELECTRICAL	UNITS	DISPLAY		
TE-3-15E(T-15)	CET11BH15	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		H-15	LO	32		0			≤ 540	5°F	
TE-3-16E(T-16)	CET12BJ2	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		J-2	LO	32		0			≤ 540	5°F	
TE-3-19E(T-19)	CET13BK3	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		K-3	LO	32		0			≤ 540	5°F	
TE-3-20E(T-20)	CET14BK5	CORE EXIT TEMP	III	2300	°F	50.99	mv		≥ 650	5°F	1, 2, 3
		K-5	LO	32		0			≤ 540	5°F	
TE-3-22E(T-22)	CET15BK11	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		K-11	LO	32		0			≤ 540	5°F	
TE-3-23E(T-23)	CET16BM19	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		M-9	LO	32		0			≤ 540	5°F	
TE-3-24E(T-24)	CET17BN6	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		N-6	LO	32		0			≤ 540	5°F	
TE-3-25E(T-25)	CET18BP8	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		P-8	LO	32		0			≤ 540	5°F	
TE-3-26E(T-26)	CET19BR7	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		R-7	LO	32		0			≤ 540	5°F	
TE-3-31E(T-31)	CET20BE8	CORE EXIT TEMP	III	2300	°F	50.99	mV		≥ 650	5°F	1, 2, 3
		E-8	LO	32		0			≤ 540	5°F	





QSPDS DATA BASE: CALCULATED VARIABLES

INADEQUATE CORE COOLING INPUTS (continued)

PLANT

Page 24 of 28

CHANNEL B

[illegible]



16081-1CE-3219, Rev 00

QSPDS DATA BASE: CALCULATED VARIABLES

INADEQUATE CORE COOLING INPUTS (continued)
PLANT

Page 25 of 28

CHANNEL B

[illegible]



16081-ICE-3219, Rev 00

INADEQUATE CORE COOLING INPUTS (continued)
PLANT

QSPDS DATA BASE: CALCULATED VARIABLES

CHANNEL B

Page 26 of 28

[illegible]



CHANNEL B

[illegible]



16081-ICE-3219, Rev 00

QSPDS DATA BASE: CALCULATED VARIABLES

INADEQUATE CORE COOLING INPUTS (continued)
PLANT

Page 28 of 28

CHANNEL B

[illegible]

