# CATEGORY

#### REGULATORY INFORMATION DISTRIBUTION SYSTEM (RIDS)

ACCESSION NBR:9811100364 DOC.DATE: 98/11/03 NOTARIZED: NO DOCKET # FACIL:50-400 Shearon Harris Nuclear Power Plant, Unit 1, Carolina 05000400 AUTH.NAME AUTHOR AFFILIATION SCAROLA,J. Carolina Power & Light Co. RECIP.NAME RECIPIENT AFFILIATION Records Management Branch (Document Control Desk) SUBJECT: Forwards Cycle 9 to COLR.Summary of changes to COLR are contained in encl 1.

DISTRIBUTION CODE: A001D COPIES RECEIVED:LTR  $\frac{1}{2}$  ENCL  $\frac{1}{2}$  SIZE: 5 + 1 A TITLE: OR Submittal: General Distribution

NOTES: Application for permit renewal filed.

,	RECIPIENT	COPIES		RECIPIENT	COPIES		G
	ID CODE/NAME PD2-1 LA	LTTR 1	ENCL 1	ID CODE/NAME PD2-1 PD	LTTR 1	ENCL 1	.0
	FLANDERS, S	Т	Т.				R
INTERNAL:	ACRS NRR/DE/ECGB/A NRR/DRCH/HICB NRR/DSSA/SRXB OGC/HDS2	1 1 1 1 1	1 1 1 0	FILE CENTER 01 NRR/DE/EMCB NRR/DSSA/SPLB NUDOCS-ABSTRACT	- 1 1 1 1	1 1 1	¥ 1
EXTERNAL:	NOAC	1	1	NRC PDR	1	1	

NOTE TO ALL "RIDS" RECIPIENTS: PLEASE HELP US TO REDUCE WASTE. TO HAVE YOUR NAME OR ORGANIZATION REMOVED FROM DISTRIBUTION LISTS OR REDUCE THE NUMBER OF COPIES RECEIVED BY YOU OR YOUR ORGANIZATION, CONTACT THE DOCUMENT CONTROL DESK (DCD) ON EXTENSION 415-2083

TOTAL NUMBER OF COPIES REQUIRED: LTTR 14 ENCL 13

MAY

05000400

D

Ο

C

U

Μ

Ε

٠N

т



Carolina Power & Light Company PO Box 165 New Hill NC 27562

NOV - 3 1998

James Scarola Vice President Harris Nuclear Plant

SERIAL: HNP-98-166

A001

United States Nuclear Regulatory Commission ATTENTION: Document Control Desk Washington, DC 20555

SHEARON HARRIS NUCLEAR POWER PLANT DOCKET NO. 50-400/LICENSE NO. NPF-63 CYCLE 9 CORE OPERATING LIMITS REPORT

Dear Sir or Madam:

In accordance with Technical Specifications (TS) 6.9.1.6.4, Carolina Power & Light Company (CP&L) hereby submits the Harris Nuclear Plant (HNP) Cycle 9 Core Operating Limits Report (COLR).

This COLR revision incorporates changes necessary as a result of Cycle 9 core changes. A summary of the COLR changes is contained in Enclosure 1. Enclosure 2 contains a copy of the Cycle 9 COLR.

In addition to the Cycle 9 COLR revision, HNP is correcting previous information submitted to the staff with regards to the Cycle 8 COLR, Revision 1. By letter dated September 21, 1998, HNP reported that the previous Moderator Temperature Coefficient (MTC) Surveillance Limit of -36.4 pcm/°F was calculated using an analytical method that was not specifically reviewed and approved by the NRC. Additional research has determined that the original Cycle 8 MTC Surveillance Limit values were in fact, calculated in accordance with NRC approved methodologies. This incorrect information was caused by an internal mis-communication which has been resolved. HNP regrets any inconvenience to the NRC caused by erroneous information contained in the September 21, 1998 letter. The MTC Surveillance Limit included in the Cycle 9 COLR supersedes these previous versions.

Please refer any questions regarding this submittal to Mr. J. H. Eads at (919) 362-2646.

Sincerely.

James Scarola

100053

PDR

MSE/mse Enclosures:

PDR

1. Summary of Cycle 9 COLR Changes

ĀDŪCK 05000440

2. Copy of the Cycle 9 COLR 7811100364 7811031



Mr. J. B. Brady, NRC Sr. Resident Inspector Mr. Mel Fry, Acting Director, N.C. DEHNR Mr. S. C. Flanders, NRC Project Manager Mr. L. A. Reyes, NRC Regional Administrator

c: .

٩.

## ENCLOSURE 1 TO SERIAL: HNP-98-166

### SHEARON HARRIS NUCLEAR POWER PLANT DOCKET NO. 50-400/LICENSE NO. NPF-63 CYCLE 9 CORE OPERATING LIMITS REPORT

1

2 ...

## SUMMARY OF CYCLE 9 COLR REVISIONS

Section	Description of Change		
2.2	Revised MTC Surveillance Limit from -37.65 pcm/°F to -37.8 pcm/°F.		
2.3	Revised the Shutdown Rod Insertion Limit from 225 steps to 222 steps.		
2.4	Revised the Control Rod Insertion Limit from 225 steps to 222 steps.		
2.6	Changed the maximum cycle energy of the V(Z) curve description from 513 EFPD to 489 EFPD.		
2.8	Boron Concentration for refueling changed from greater than or equal to 2300 ppm to greater than or equal to 2217 ppm.		
4.1	At the beginning of the cycle, increased the requirement for the total number of detector thimbles required from 38 to 45. Additionally, at the beginning of the cycle, specified that detector thimbles be operable at either location J-10 or L-14. A detector thimble at one of the following locations must also be operable at the beginning of the cycle, N-5, H-6, or J-7.		
Figure 2	Changed Figure 2 to reflect new rod parked position from 225 to 222 steps.		
Figure 5	Changed Figure 5 to reflect new V(Z) curve.		

ENCLOSURE 2 TO SERIAL: HNP-98-166

### SHEARON HARRIS NUCLEAR POWER PLANT DOCKET NO. 50-400/LICENSE NO. NPF-63 CYCLE 9 CORE OPERATING LIMITS REPORT

Attachment 9 to HNP Procedure PLP-106, "Technical Specification Equipment List Program and Core Operating Limits Report," Rev. 19