

Blount, Barbara

Subject:

FW: NRC-2017-0211

Attachments:

Comments to NRC Docket ID NRC-2017-0211.pdf; ATT00001.txt

Living 15 miles from San Onofre in South Laguna Beach, we have particular concerns for the quality and durability of the storage containers to be chosen to safeguard the highly radioactive remnants of the SO nuclear reactor.

I submit that the thoughtful analysis of SanOnofreSafety.org (pdf attached) is critically important for the NRC to consider in making any decisions, and I implore you to not ignore or put at risk the health of safety of 10s (or 100s) of thousands of people in making your important decision.

Thank you
Steve Guich

(150)

82 FR 52944
11/15/2017

SUNSI Review Complete

Template = ADM - 013

E-RIDS = ADM -03

Add = Jeremy Smith (JAS5)

Comments to NRC Docket ID NRC-2017-0211, NUREG-2215**NRC Standard Review Plan for Spent Fuel Dry Storage Systems and Facilities Draft, November 2017**

<https://www.nrc.gov/docs/ML1731/ML17310A693.pdf>

The NRC cannot meet its mission to “ensure adequate protection of public health and safety and the environment” if it continues to allow thin-wall welded canisters they admit are vulnerable to cracks, that cannot be fully inspected (inside or out), and cannot be repaired, maintained and monitored to prevent (not just detect) radiological leaks. There is no adequate or proven detailed plan required to address major radiological leaks, or to address on-site replacement of containers. Seismic requirements for partial cracks is not addressed. See below webpage for details on the Holtec UMAX System planned for San Onofre and why this is an example of a system with major problems that should not be approved.
<https://sanonofresafety.org/holtec-hi-storm-umax-nuclear-waste-dry-storage-system/>

Each canister contains about as much or more lethal Cesium-137 as released from the 1986 Chernobyl nuclear disaster, yet the NRC knows the boron metal in the canisters will not prevent the fuel from going critical if exposed to non-borated water from through wall cracks (in storage or transport).

NUREG-2215 states it requires “conservative assumptions”, “inspections”, and admits to many “unknowns”. NUREG-2215 is not “conservative”, does not require adequate “inspections”, and does not resolve the many “unknowns” that would be eliminated if the NRC mandated and enforced critical safety requirements to inspect, monitor, maintain and repair (both inside and out) to PREVENT leaks.

Proven dry storage technology exists that meets critical basic safety requirements we expect in a car. Does the NRC consider thin-wall canisters “conservative assumptions” compared to thick-wall casks? If so, why? Why does the NRC allow containers that do not meet these basic critical safety requirements?

Respectfully,

Donna Gilmore, SanOnofreSafety.org
 donnagilmore@gmail.com 949-204-7794

Basic Safety Requirements	Thin-wall canisters	Thick-wall casks
Thick walls	No. Only 1/2 to 5/8 th of an inch	Yes. 10 to 19.75 inches
Won't crack.	No	Yes
Ability to inspect inside & out, maintain, repair (fuel baskets, other parts)	No	Yes
Monitor to fix problems <i>before</i> leaks	No	Yes
ASME <i>container</i> certification	No	Yes
Defense in depth (redundancy)	No	Yes
Stored in concrete building	No	Yes
Gamma & neutron protection	Requires vented concrete overpack	Yes
Transportable	No transport with cracks. 10 CFR § 71.85	Yes
Proven technology	No. Conditions unknown. Most in use less than 15 yrs, a few 30 yrs.	Yes. Inspected and used over 40 years