

1982

TE HQ FILE COPY


SEMIANNUAL RADIOACTIVE EFFLUENT RELEASE REPORT RERR-12

SALEM NUCLEAR GENERATING STATION SALEM UNIT NOS. 1 & 2

UNIT 1 DOCKET NO. 50-272 UNIT 2 DOCKET NO. 50-311 OPERATING LICENSE NO. DPR-70 OPERATING LICENSE NO. DPR-75

AUGUST 1982

M P79 43/33



REPORT NO. RERR-12

UNIT NOS. 1 & 2
RADIOACTIVE EFFLUENT RELEASE REPORT
JAN - JUNE 1982

SALEM NUCLEAR GENERATING STATION
Public Service Electric and Gas Company

SALEM NUCLEAR GENERATING STATION UNIT 1 50-272 UNIT 2 50-311

UNIT NOS. 1 AND 2
RADIOACTIVE EFFLUENT RELEASE REPORT
January 1, 1982 to June 30, 1982

Introduction

This report, RERR-12, summarizes the releases of radioactive materials in liquid, gaseous and solid form from the Salem Nuclear Generating Station Units 1 and 2 for the period January 1, 1982 to June 30, 1982. As requested by the United States Nuclear Regulatory Commission (USNRC) this report was prepared in the format specified for all nuclear power plants as defined in USNRC Regulatory Guide 1.21.

Release of radioactive materials from the Salem station during the reporting period were within the limits set forth in the Environmental Technical Specifications. Calculated radiation exposures to off-site individuals were small fractions of the limits set forth in 10CFR20 and within Appendix I to 10CFR50 and 40CFR190 requirements.

Unit 1 generated 1,560,000 megawatt-hours of electrical energy (net) during the reporting period.

Unit 2 generated 4,493,310 megawatt-hours of electrical energy (net) during the reporting period.

Included is corrected page 10-A for report RERR-11 summarizing gaseous releases from Salem Unit 1.

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT RERR 12

A. SUMMARY INFORMATION

1.0 Regulatory Limits

Symbols utilized in the equations listed below under Sections 1.1 and 1.2 are the same as those used in the Salem Environmental Technical Specifications (ETS). The symbol Q as explained in Section 2.3.3 of the ETS is the release rate of the gaseous activity in units of curies per second. The K, L, M and N terms are actually site dependent dose conversion factors. The equations listed below in Sections 1.1 and 1.2 take into consideration the release point location, building wake effects and physical characteristics of the radionuclides released.

In addition 40CFR190 regulations require that the annual dose equivalent does not exceed 25 mrem to the whole body or any organ (except the thyroid which is limited to 75 mrem).

1.1 Fission and Activation Gases

Gaseous releases from the nuclear units are limited such that at no time will releases of gaseous radioactive materials cause a member of the general public to be exposed to an annual dose rate in excess of 500 mrem to the entire body or 3 rem to the skin in conformance with the requirements of 10CFR20.

Gaseous releases from the units are further restricted such that when releases are averaged over a calendar quarter no member of the general public will be exposed to an annual dose rate in excess of 20 millirads of gamma radiation or 40 millirads of beta radiation.

In addition, it is required that air doses averaged over a twelve month period be less than 40 and 80 millirads for gamma and beta radiation respectively.

At any instant the release rate of radioactive gases must satisfy the following equations whose basis is 10CFR20.

0.33
$$Q_{tv}*(L_v + 1.1 N_v) \leq 1$$

When averaged over a calendar quarter the release rate for radioactive gases must satisfy the following equation. The basis for these equations is 10CFR50 Appendix I.

13
$$Q_{tv}^*N_v \leq 1$$

6.3 $Q_{tv}^*M_v \leq 1$

The limiting Unit 1 release limit Q is calculated to be 1.07E+04 and 1.50E+04 microcuries/sec for both the 1st and 2nd quarters respectively.

The limiting Unit 2 release limit Q is calculated to be 1.36E+04 and 1.54E+4 microcuries/sec. for the 1st and 2nd quarters respectively.

When averaged over any twelve consecutive month period, the release rate for radioactive gases must satisfy the following equation. The basis for this equation is 10CFR50 Appendix I.

25
$$Q_{tv}*N_v \leq 1$$

13
$$Q_{tv}*M_v \leq 1$$

The release limits of radioactive gases for the Salem Nuclear Generating Station are not fixed numbers, but depend upon the radioactive isotopes present in the effluent.

1.2 Iodine and Particulates, Half Life > 8 days

The regulatory limits for iodines and particulates are listed below.

The release rates of iodine and particulates are restricted such that no member of the general public will receive a dose at a rate in excess of 1.5 rem/yr. to the thyroid.

Releases of iodines and particulates are further restricted to prevent any member of the general public from receiving a dose rate in excess of 30 mrem in a calendar quarter or 60 mrem in any twelve month period. The equations which govern these conditions are listed below:

At any instant of time the release rate for radioactive iodines and particulates material with a half life greater than 8 days is limited by the equation below. The basis for this equation is 10CFR20.

$$(1.5 \times 10^5) Q_{\rm V} \le 1$$

During any calendar quarter the release limit is governed by the equations listed below. The basis for these equations is 10CFR50 Appendix I.

2 curies of I-131 and $Q_V \times 13 \times (1.5 \times 10^5) < 1$

During any twelve month period radioactive releases should conform to the following constraints of 10CFR50 Appendix I.

25 x (1.5 x 10^5) x $Q_v \le 1$ and 4 curies of I-131

1.3 Liquid Effluents

The regulatory limits for radioactive liquids released from the plant are governed by 10CFR20, Appendix B, Table II, Column 2.

In addition, the following limits apply:

The cumulative release of radioactive effluents, excluding tritium and dissolved gases, shall be less than 10 Ci in a calendar quarter for each unit.

The cumulative release of radioactive effluents, excluding tritium and dissolved gases, shall be less than 20 Ci in any twelve consecutive months for each unit.

2.0 Maximum Permissible Concentrations

Regulatory Guide 1.21 requires that the licensee provide the MPC's used in determining allowable release rates for radioactive releases. We have addressed this guestion below.

- a. Fission Gases MPC values were not used to determine the maximum release rates.
- b. Iodines MPC values were not used to determine the maximum release rates.
- c. Particulates, Half Lives > 8 days MPC limits were not used to determine the maximum release rates.
- d. Liquid effluents MPC values as stated in 10CR20, Appendix B, Table 11, Column 2 were used.

3.0 Average Energy

Regulatory Guide 1.21 requires that the licensee provide the average energy of the radionuclide mixture in releases of fission and activation gases, if applicable.

Release limits for the SNGS are not based upon average energy, hence, this section does not apply.

- 4.0 Measurements and Approximation of Total Radioactivity
- 4.1 Liquid effluents are monitored in accordance with Table 2.3-3 of the Environmental Technical Specifications. During the period of record, all wastes from the chemical drain tank and the laundry and hot shower tanks were routed to the hold-up tanks for monitoring. Specifications require these tanks to be recirculated the equivalent of two tank volumes to produce uniform mixing and sample extraction and analyzation before any releases are made. Batch releases included releases from the waste monitor tanks, waste monitor hold-up tank, and the chemical and volume control tanks. Continuous releases included releases from intermittent blowdown of the steam generators. The predominate gamma emitting isotopes detected were Co58, Co60, Cs134, and Cs137. At no time did releases exceed limits.
- Gaseous effluent streams are monitored in accordance with Table 2.3-4 of the Environmental Technical Specifica-The plant vent is the final release point of all planned gaseous effluents and is continually monitored by four very sensitive Geiger Mueller tubes. The vent is also continuously sampled for iodine and particulates with a charcoal cartridge and filter paper connected in series to a low volume air sampler. The filter and charcoal are changed weekly, weather permitting, and analyzed on a multichannel analyzer in the laboratory. Sampling is also performed on all gas decay tanks and containment purges prior to release to the environment. The results of these analyses are used as the basis for the cumulative release of gaseous effluents into the environment. All tritium samples were taken by bubbling gas through water and then counting the tritiated water on a liquid scintillation counter.

4.3 The estimated total error of the reported continuous gaseous releases is within 50%. This error is due primarily to variability of waste stream flow rates and changes in isotopic distributions of waste streams between sampling periods. The estimated total error of the reported batch gaseous releases is within 10%.

The estimated total error of reported liquid releases is within 25%.

5.0 Batch Releases

Batch releases of gaseous and liquid effluent are provided in Tables 4A-1 and 4B-1 for Unit 1 and 4A-2 and 4B-2 for Unit 2.

6.0 Unplanned Releases

During this reporting period an unplanned release of 4.18E-04 curies of Xe-133 occurred from a leak of a temporary connector to a pipe in the spent fuel pool area. This incident was reported to the USNRC in a Licensee Event Report.

Part B. Gaseous Effluents

See Summary Tables lA-1 thru lC-1 representative of Salem Unit 1 operations.

See Summary Tables 1A-2 thru 1C-2 representative of Salem Unit 2 operations.

Part C. Liquid Effluents

See Summary Tables 2A-1 and 2B-1 representative of Salem Unit 1 operations.

See Summary Tables 2A-2 and 2B-2 representative of Salem Unit 2 operations.

Part D. Solid Waste

See Summary Table 3 Units 1 and 2

Part E. Radiological Impact on Man*

The calculated individual doses in this section are based on actual locations of nearby residents and farms. The population dose impact is based on historical site specific data i.e., food production, milk production, feed for milch animals and seafood production.

The doses were calculated using methods described in Regulatory Guide 1.109 and represent calculations for the six month reporting interval. Doses from batch and continuous releases were calculated using the meteorological dispersion coefficient X/Q for the six month reporting interval.

Liquid Pathways

Doses to individuals in the population from liquid releases are primarily from the seafood ingestion pathway. The total body dose to an individual was calculated to be 1.30E-2 mrem. The calculated population total body dose was 2.69E-1 person-rem. The highest organ dose from liquid releases was 1.30E-1 mrem to the gastrointestinal tract.

Air Pathways

The resulting whole body and skin doses to an individual were calculated to be 6.00E-4 mrem and 7.68E-5 mrem respectively. The calculated population total body dose was 4.12E-2 person-rem. The average total body dose to the population within fifty miles of the site was 7.70E-6 mrem/person.

Direct Radiation

Direct radiation may be estimated by TLD measurements. One method for comparing TLD measurements is by comparison with preoperational data. TLD measurements on site near the Service Water pumps (location 11S1) and near the Circulating Water pumps (location 10S1) averaged 5.93 and 5.80 mrads/months, respectively, apparently due to trace activity in the Refueling Water Storage Tank.

TLD's at onsite locations 2S2 and 5S1 which are 0.3 miles and 0.9 miles from the reactor containment, averaged 4.78 and 4.18 mrads/month respectively. The values for stations 2S1 and 5S1 are within the statistical variation associated with the preoperation program results.

All offsite monitoring locations remained within preoperational ranges. It should be noted that the nearest resident is 3.5 miles away. It can thus be concluded that there was no measurable dose to any offsite locations from direct radiation.

Part F. Meteorological Data

Cumulative joint wind frequency distribution by atmospheric stability class at the 300 foot elevation is provided for the first and second quarters of 1982 as Table 5 and 6.

TABLE TALT EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-SUMMATIO ALL RELEASES UNIT 1

٠	!	Unit	lst Quarter	2nd Quarter	Est.Total(1) Error %
Α.	Fission & Activation Gases				
	1. Total release	Ci	2.95E-01	2.50E-01	2.50E+01
	2. Average release rate for period	uCi/sec.	3.79E-02	3.18E-02	
	3. Percent of technical specification limit	8	3.54E-04	2.12E-04	
	(See ETS Spec. 2.3.3.b)				
3.	Iodines				
	1. Total iodine-131	Ci	5.49E-04	9.88E-04	2.50E+01
	2. Average release rate for period	uCi/sec.	7.06E-05	1.26E-04	
	3. Percent of technical specification (2Ci) limit	ક્ર	2.75E-02	4.94E-02	
г.	Particulates	÷			•
	1. Particulates with half-lives> 8 days	Ci	6.83E-06		2.50E+01
	2. Average release rate for period	uCi/sec.	8.78E-07	-	
	3. Percent of technical specification limit	8	1.33E-03		
	4. Gross alpha radioactivity (2)	Ci		-	

1.	Total release	Ci	2.12E-03	1.41E+00 2.50E+	01
2.	Average release rate for period	uCi/sec.	2.72E-04	1.79E-01	
3.	Percent of technical specification limit	8	N/A	N/A	

- For batch release's the estimated overall error is within 10%. Analyses indicate no measurable alpha emitting transuranics. (1)

TABLE IA-2 EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-SUMMATIO F ALL RELEASES UNIT

		Unit	lst Quarter	2nd Quarter	Est.Total(1) Error %
Α.	Fission & Activation Gases				-
	1. Total release	Ci	3.82E-01	1.04E+02	2.50E+01
	2. Average release rate for period	uCi/sec.	4.91E-02	1.32E+03	
	3. Percent of technical specification limit	, 8	3.61E-02	8.57E-00	
	(See ETS Spec. 2.3.3.b)				
B.	Todines				

1. Total iodine-131	Ci	5.95E-04	2.15E-04 2.50E+01
2. Average release rate for period	uCi/sec.	7.65E-05	2.74E-05
3. Percent of technical specification limit	ક	3.85E-03	1.08E-02

C. Particulates

1.	Particulates with half-lives> 8 days	Ci	1.29E-03	
2.	Average release rate for period	uCi/sec.	1.66E-04	-
3.	Percent of technical specification limit	8	2.52E-01	<u> </u>
4.	Gross alpha radioactivity (2)	Ci		_

Tritium

1. Total release	Ci	_	1.63E+00	
2. Average release rate for period	uCi/sec.	_	2.07E-01	
3. Percent of technical specification limit	ફ	N/A	N/A	

- (1) For batch releases the estimated overall error is within 10%.
- (2) Analyses indicate no measurable alpha emitting transuranics.

TABLE 1B-1 EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-ELEVATED RELEASES

UNIT 1

					CONTINUOUS MODE		CH MODE		
Nuclides Released				2nd Quarter	lst Quarter	2nd Quarter			
1.	Fission gases								
	Krypton-85		Ci			1.66E-01			
	Krypton-85m		Ci						
	Krypton-87		Ci						
	Krypton-88		Ci						
	Xenon-133		Ci	2.90E-04	5.68E-04	1.27E-01	2.44E-01		
	Xenon-135		Ci		1.17E-03	1.87E-03	1.31E-03		
	Xenon-135m		Ci				2.43E-03		
	Xenon-138		Ci						
	Xenon-133m		Ci			1.06E-03			
	Argon-41		Ci						
	Fluorine-18		Ci			5.99E-07			
	Unidentified		Ci						
	Total for period		Ci	2.90E-04	1.74E-03	2.96E-01	2.48E-01		
2.	Iodines	,							
	Iodine-131		Ci	5.49E-04	3.43E-04				
	Iodine-133		Ci		6.45E-04				
	Iodine-135		Ci			,			
	Total for period	· · · · · · · · · · · · · · · · · · ·	Ci	5.49E-04	9.88E-04				

TABLE 18-1 EFFLUENT AND WASTE DISPOSAL SEN NUAL REPORT (1982) ED RELEASES GASEOUS EFFLUENTS-ELB (Continued) UNIT 1

				CONTINUOUS MODE			H MODE :	<u>:</u>	
Nuc	lides Released		Unit 1	lst Quarter	2nd Quarter	lst Quarter	2nd Quarter		
3.	Particulates								
. ——	Chrominum-51		Ci						
	Manganese-54		Ci						
	Cobalt-58		Ci		,	3.65E-06			
	Cobalt-60		Ci			3.18E-06			
	Iron-59		Cí						
	Rubidium-88		Ci						
	Yttrium-88		Cí						
	Strontium-89		Ci						
	Strontium-90		Ci						
	Niobium-95	1							
	Zirconium-95	,	Ci						
	Tin-117m		Ci						
	Cesium-138.		Ci						
	Cesium-137		Ci						
	Cesium-139		Ci						
	Gross Alpha		Ci						
	Total For Period		Ci			6.83E-06			
4.	Tritium								
	Tritium		Ci	. E 0	1.41E+00	2.12E-03	. E 0		

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-ELEVATED RELEASES

UNIT 2

CONTINUOUS MODE

BATCH MODE

Nuc	lides Released		Unit	lst Quarter	2nd Quarter	lst Quarter	2nd Quarter	
1.	Fission gases							
	Krypton-85	· · · · · · · · · · · · · · · · · · ·	Ci		· · · · · · · · · · · · · · · · · · ·	5.16E-02		
	Krypton-85m		Ci					
	Krypton-87		Ci		·	·		
	Krypton-88		Ci					
	Xenon-133		Ci	1.38E-02	1.04E+02	3.09E-01		
	Xenon-135		Ci	7.29E-03	8.97E-03	1 .		
	Xenon-135m		Ci					
	Xenon-138		Ci					
	Xenon-133m	1	Ci					
	Argon-41		Ci					
	Fluorine-18		Ci					
	Unidentified		Ci					
	Total for period		Ci	2.11E-02	1.04E+02	3.61E-01		
2.	Iodines	1						
	Iodine-131	,	Ci	5.95E-04	4.99E-05			
	Iodine-133		Ci		1.65E-04			
	Iodine-135	1	Ci					
	Total for period		Ci	5.95E-04	2.15E-04			

TABLE 1B-2 EFFLUENT AND WASTE DISPOSAL SEM (1982) GASEOUS EFFLUENTS-ELE D RELEASES

(Continued) UNIT 2

	·	,	CONTINUO	JS MODE	ВАТС	H MODE	<u>:</u>
Nuclides Released		Unit 2	lst Quarter	2nd Quarter	lst Quarter	2nd Quarter	·
3.	Particulates						
	Chrominum-51	Ci					
	Manganese-54	Ci					
	Cobalt-58	Ci					
	Cobalt-60	Ci		· · · · · · · · · · · · · · · · · · ·	1.29E-03		
	Iron-59	Ci					
	Rubidium-88	Ci				·	
	Yttrium-88	Ci					
	Strontium-89	Ci		······································	- 		
	Strontium-90	Ci				· · · · · · · · · · · · · · · · · · ·	
	Niobium-95	Ci					
	Zirconium-95	Ci					
	Sr-85	Ci					
	Cesium-134	Ci					-
	Cesium-137	Ci					
	Cerium-139	Ci					
	Gross Alpha	Ci		· · · · · · · · · · · · · · · · · · ·	# ************************************		
	Total For Period	Ci		-	1.29E-03	~	
4.	Tritium	·!					·
	Tritium	Ci	0.00E+00	1.63E+00	0.00E+00	0.00E+00	·

TABLE 1C

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT 1982

UNITS 1 AND 2

GASEOUS EFFLUENTS-GROUND-LEVEL RELEASES

Nuclides Releases Unit 1st Quarter 2nd Quarter 1st Quarter 2nd Quarter

There were no ground level releases for the period of record.

TABLE 2A-1

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

UNIT 1

LIQUID EFFLUENTS-SUMMATION OF ALL RELEASES

lst

2nd

	Units	Quarter	Quarter	Est. Total Error, %
				,
Dississ and Satingtian anadusts				
Fission and activation products			 	
1. Total release (not including	Ci	1.10E+00	E 025 01	2 508101
tritium, gases, alpha) 2. Average diluted concentration	C1	1.10E+00	5.82E-01	2.50E+01
	·	1.17E-07	6.58E-08	•
during period 3. Percent of applicable limits	uC1/m1	1.1/E-0/	0.305-00	
	Q.	1 100.01	E 025100	
of Technical Specifications	8	1.10E+01	5.82E+00	
Tritium				
tal release	Ci	8.43E+01	1.25E+02	2.50E+01
2. Verage diluted concentration	<u> </u>	0.436.01	1.236102	2.306.01
during period	uCi/ml	9.00E-06	1.41E-05	
3. Percent of applicable limit	4 AC 1/111	N/A	N/A	
		/		
or account of apparation at a little				
	<u> </u>			
Dissolved and entrained gases	Ci			2.50E+01
Dissolved and entrained gases l. Total release	Ci	3.17E-01	3.50E-01	2.50E+01
Dissolved and entrained gases 1. Total release 2. Average diluted concentration	,	3.17E-01	3.50E-01	2.50E+01
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period	,	3.17E-01 3.38E-08	3.50E-01 3.95E-08	2.50E+01
Dissolved and entrained gases 1. Total release 2. Average diluted concentration	uCi/ml	3.17E-01	3.50E-01	2.50E+01
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit	uCi/ml	3.17E-01 3.38E-08	3.50E-01 3.95E-08	2.50E+01
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period	uCi/ml	3.17E-01 3.38E-08	3.50E-01 3.95E-08	2.50E+01 2.50E+01
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit Gross alpha radioactivity	uCi/ml	3.17E-01 3.38E-08 N/A	3.50E-01 3.95E-08 N/A	
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit Gross alpha radioactivity 1. Total release	uCi/ml	3.17E-01 3.38E-08 N/A	3.50E-01 3.95E-08 N/A	
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit Gross alpha radioactivity 1. Total release Volume of waste release (prior	uCi/ml %	3.17E-01 3.38E-08 N/A 0.00E+00	3.50E-01 3.95E-08 N/A 0.00E+00	
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit Gross alpha radioactivity 1. Total release	uCi/ml %	3.17E-01 3.38E-08 N/A	3.50E-01 3.95E-08 N/A	
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit Gross alpha radioactivity 1. Total release Volume of waste release (prior to dilution - Batch Release)	uCi/ml %	3.17E-01 3.38E-08 N/A 0.00E+00	3.50E-01 3.95E-08 N/A 0.00E+00	
Dissolved and entrained gases 1. Total release 2. Average diluted concentration during period 3. Percent of applicable limit Gross alpha radioactivity 1. Total release Volume of waste release (prior	uCi/ml % Ci liters	3.17E-01 3.38E-08 N/A 0.00E+00	3.50E-01 3.95E-08 N/A 0.00E+00 3.21E+06	

⁻ Not Applicable

TABLE 2A-2

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

UNIT 2

LIQUID EFFLUENTS-SUMMATION OF ALL RELEASES

lst

Units Quarter Quarter

2nd

Est. Total

				Error, %
•				
A. Fission and activation products				
 Total release (not including tritium, gases, alpha) 	Ci	1.12E+00	6.30E-01	2.50E+01
2. Average diluted concentration		1.126.00	0.305-01	2.305+01
during period	uCi/ml	8.68E-08	7.11E-08	
3. Percent of applicable limits				
of Technical Specifications	용	1.12E+01	6.30E+00	
D. Addison				
B. Total release	Ci	1.18E+02	1.14E+02	2.50E+01
2. Average diluted concentration		1.1011.02	1.1115.02	2.301.01
during period	uCi/ml	9.15E-06	1.29E-05	
3. Percent of applicable limit	ફ	N/A	N/A	
C. Dissolved and entrained sages				
C. Dissolved and entrained gases 1. Total release	Ci	5.48E-01	2.81E-01	2.50E+01
2. Average diluted concentration		3.40E 01	Z.01E-01	2.306+01
during period	uCi/ml	4.25E-08	3.17E-08	
3. Percent of applicable limit	8	N/A	N/A	
D. Gross alpha radioactivity				·
1. Total release	Ci_	0.00E+00	0.00E+00	2.50E+01
E. Volume of waste release (prior		•		
to Amelution - Batch Release)	liters	4.79E+06	3.12E+06	
co Milution Bacon Release)	110012		J.121100	
F. Volume of dilution water used		- •	. -	
during period - Batch Release	liters	1.29E+10	8.86E+09	2.50E+01

Not Applicable

TABLE 2B-1

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

LIQUID EFFLUENTS UNIT 1

	C	ONTINUOUS MO	DDE	BATCH MODE	E .
Nuclides Released	Unit	lst Quarter	2nd Quarter	lst Quarter	2nd Quarter
Strontium-89	Ci				•
Strontium-90	Ci				
Cesium-134	Ci			9.56E-03	3.95E-03
Cesium-137	Ci	,		1.10E-02	1.05E-02
Iodine-131	Ci			3.75E-02	3.03E-04
Iodine-132	Ci			3.03E-04	
Iodine-133	Ci			1.85E-04	1.65E-04
Iodine-134	Ci			1.65E-04	
Iodine-135	Ci			3.52E-04	
Cobalt-58	Ci			6.64E-01	2.97E-01
Cobalt-60	Ci			2.40E-01	1.76E-01
mium-109	Ci				
ganese-54	Ci			4.37E-02	8.22E-02
Cnromium-51	Ci			5.65E-02	4.07E-03
Cesium-136	Ci				
Zirconium-95	Ci			7.27E-03	1.13E-03
Tin-113	Ci				· · · · · · · · · · · · · · · · · · ·
Barium-140	Ci				
Lanthanum-140	Ci			2.41E-04	
Cerium-139	Ci			7.41E-05	
Cerium-141	Ci			1.35E-03	
Tungsten-187	Ci				
Niobium-95	Ci			1.33E-02	3.94E-03
Antimony-124	Ci			6.54E-03	9.28E-04
Antimony-125	Ci			3.17E-03	
Tritium	Ci			8.43E+01	1.25E+02
Iron-59	Ci			1.66E-03	7.79E-04
Sodium-24	Ci			9.70E-04	1.50E-04
Silver-110m	Ci				8.30E-04
. Total for period (above)					
excluding H3	Ci			1.10E+00	5.82E-01
Xenon-133m	Ci			3.05E-04	1.33E-03
Xenon-133	Ci			3.16E-01	3.41E-01
Xenon-135	Ci			5.04E-04	7.54E-03
Verypton-88	Ci	 			
on-41	Ci			· · · · · · · · · · · · · · · · · · ·	

TABLE 2B-2

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

LIQUID EFFLUENTS UNIT 2

	CONTINUOUS MODE			BATCH MODE		
Nuclides Released	Unit	lst Quarter	2nd Quarter	lst Quarter	2nd Quarter	
Strontium-89	Ci					
Strontium-90	Ci					
Cesium-134	Ci			3.25E-03	1.33E-02	
Cesium-137	Ci	·- ·		6.93E-03	2.14E-02	
Iodine-131	Ci			1.08E-01	7.07E-04	
Iodine-132	Ci		· · · · · · · · · · · · · · · · · · ·	7.51E-04		
Iodine-133	Ci			4.17E-04		
Cobalt-58	Ci			6.62E-01	3.18E-01	
Cobalt-60	Ci			2.14E-01	1.82E-01	
Cadmium-109	Ci			4.15E-03		
Manganese-54	Ci			3.76E-02	8.99E-02	
comium-51	Ci			4.90E-02		
ium-141	Ci			6.98E-04		
zirconium-95	Ci			5.18E-03	6.84E-04	
Tin-113	Ci			7.37E-05		
Barium-140	Ci					
Lanthanum-140	Ci				· · · · · · · · · · · · · · · · · · ·	
Cerium-134	Ci			9.65E-04		
Mercury-203	Ci			6.82E-05		
Niobium-95	Ci			1.15E-02	2.72E-03	
Antimony-124	Ci			9.00E-03	3.61E-04	
Antimony-125	Ci			6.17E-03	4.85E-04	
Tritium	Ci			1.18E+02	1.14E+02	
Iron-59	Ci			1.09E-03		
Sodium-24	Ci			7.24E-04	8.89E-05	
Tellerium-125m	Ci			1.69E-03		
Tellerium-132	Ci			7.26E-04		
Total for period (above)						
excluding H3	Ci			1.12E+00	6.30E-01	
Xenon-133m	Ci			1.82E-04		
Xenon-133	Ci			5.47E-01	2.77E-01	
Xenon-135	Ci			9.21E-04	4.35E-03	
Krypton-88	Ci		 			
Argon-41	Ci					

TABLE 3

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT 1982 JANUARY - JUNE 1982 UNITS 1 AND 2

SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

SOLID WASTE SHIPPED OFFSITE FOR BURIAL OR DISPOSAL (Not irradiated fuel)

1.	тур	Type of waste Unit		6-month Period	Est. Total Error, %		
	a.	Spent resins, filters sludges, evaporator bottoms	m3 Ci	1.85E+02 2.03E+02	1.50E+01		
	b.	Dry compressible waste, contaminated equip.	m3 Ci	7.86E+02 7.53E+00	1.50E+01		
	c.	Irradiated components, control rods,	m3 Ci	0.00E+00 0.00E+00			
	d.	Others (describe)	m3 Ci	0.00E+00 0.00E+00			

2 Estimate of major nuclide composition (by type of waste)

Cobalt - 58	79.9%	1.62E+02
Cobalt - 60	12.4%	2.52E+01
Manganese - 54	3.0%	6.09E+00
Cs-134	2.5%	5.075E+00
Cs-137	2.2%	5.486E+00
Cobalt - 58	79.9%	6.016E+00
Cobalt - 60	12.4%	0.934E+00
Manganese - 54	3.0%	0.226E+00
Cs-134	2.5%	0.188E+00
Cs-137	2.2%	0.166E+00
		• E
		• E

3. Solid Waste Disposition

Number of Shipments	Mode of Transportation	Destination
49	Truck	Barnwell, South Carolina
11	Truck	Hanford, Wash.

NATED FUEL SHIPMENTS (Disposition)

Number of Shipments	Mode of Transportation	Destination
None	N/A	N/A

TABLE 4A-1

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates January 1 March 31, 1982
- 2. Type of release (Gas)
- 3. Number of releases during the 1st Quarter 2.0E+01
- 4. Total time duration for all releases of type listed above 5.03E+03 minutes
- 5. Maximum duration for releases of type listed above 1.53E+03 minutes
- 6. Average duration for all releases of type listed above 2.51E+02 minutes
- 7. Minimum duration for release of type listed above $\frac{6.5E+01}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4A-2

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates January 1 March 31, 1982
- Type of release (Gas)
- 3. Number of releases during the 1st Quarter 5.0E+0
- 4. Total time duration for all releases of type listed above 6.43E+02 minutes
- 5. Maximum duration for releases of type listed above 1.37E+02 minutes
- Average duration for all releases of type listed above 1.29E+02 minutes
- 7. Minimum duration for release of type listed above 1.20E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4A-1 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates April 1 June 30, 1982
- 2. Type of release (Gas)
- 3. Number of releases during the 2nd Quarter 2.8E+01
- 4. Total time duration for all releases of type listed above 2.01E+03 minutes
- 5. Maximum duration for releases of type listed above $\frac{1.32E+02}{minutes}$
- 6. Average duration for all releases of type listed above 7.17E+01 minutes
- Minimum duration for release of type listed above 6.0E+01 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4A-2 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates April 1 June 30, 1982
- 2. Type of release (Gas)
- 3. Number of releases during the 2nd Quarter 0.0E+0
- 4. Total time duration for all releases of type listed above 0.0E+02 minutes
- 5. Maximum duration for releases of type listed above $\frac{0.0E+0}{minutes}$
- 6. Average duration for all releases of type listed above 0.0E+0 minutes
- . Minimum duration for release of type listed above 0.0E+0 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4B-1

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates January 1 March 31, 1982
- 2. Type of release (Liquid)
- 3. Number of releases during the 1st Quarter 5.8E+01
- 4. Total time duration for all releases of type listed above 1.26E+04 minutes
- 5. Maximum duration for releases of type listed above $\frac{3.96E+02}{minutes}$
- 5. Average duration for all releases of type listed above 2.17E+02 minutes
- 7. Minimum duration for release of type listed above $\frac{1.57E+02}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. $\frac{1.98E+05}{gpm}$

TABLE 4B-2

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates January 1 March 31, 1982
- Type of release (Liquid)
- Number of releases during the 1st Quarter 7.6E+01
- 4. Total time duration for all releases of type listed above 1.72E+04 minutes
- 5. Maximum duration for releases of type listed above 4.18E+O2 minutes
- Average duration for all releases of type listed above 2.27E+02 minutes
- 7. Minimum duration for release of type listed above 1.45E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. 1.95E+05 gpm

TABLE 4B-1 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates April 1 June 30, 1982
- Type of release (Liquid)
- 3. Number of releases during the 2nd Quarter 5.2E+01
- 4. Total time duration for all releases of type listed above 1.03E+04 minutes
- 5. Maximum duration for releases of type listed above 3.01E+02 minutes
- 6. Average duration for all releases of type listed above 1.98E+02 minutes
- 7. Minimum duration for release of type listed above 1.03E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release $\frac{2.24E+05}{gpm}$

TABLE 4B-2 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates April 1 June 30, 1981
- 2. Type of release (Liquid)
- 3. Number of releases during the 2nd Quarter 5.0E+01
- 4. Total time duration for all releases of type listed above 1.10E+04 minutes
- 5. Maximum duration for releases of type listed above $\frac{4.35E+02}{minutes}$
- 6. Average duration for all releases of type listed above 2.20E+02 minutes
- /. Minimum duration for release of type listed above 1.21E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release $\frac{2.18E+05}{gpm}$

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: ALL STABILITIES EXCLUDING MISS SPEED/DIR DATA

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE	CHPH) A:	T 300 FE	EET	
UIND					•		
DIREC-	٠						
TION	13	4-7	8-12	13-18	19-24	>24	TOTAL
N	4	19	56	44	4	:1.	128
NNE	3	17	37	64	22	0	143
NE	2	1.3	40	43	15	4	1.17
ENE	3	1.7	36	1.0	1.	1.	68
E	4	1.6	28	1. 1.	4	2	6 5
ESE	2	4	7	6	2	1.	22
SE	3	9	20	35	31	1.3	1.1.1
SSE	5	7	31	42	31	1.8	134
S	3	21	24	35	24	1.O	117
SSW	1.	1.5	25	54	9	10	114
SW	4	3. 1.	25	47	1.3	5	105
พรพ	4	5	20	24	5	21	79
W	3	8	38	53	48	53	203
MMM	2	1.3	34	76	72	39	236
ИW	1	ర	28	70	61	30	196
Мим	2	1.4	46	55	27	3	147
TOTAL	46	195	495	669	369	211.	1985

PERIODS OF CALM (HOURS): 4
HOURS OF MISSING DATA: 136

TABLE 5
Page 1 of 8

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: EXTREMELY STABLE DELTA T >4.0 "

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			W	INDSPEED	(MPH)	AT 300	FEET	
WIND							·	
DIREC-							s. 49. A	
TION	1-3	4-7		8-12	13-18	19-24	>24	TOTAL
N	, o	O		0	1.	0	0	1.
NNE	0	O		0	0	0	0	0
NE	0	0		0	0	0	0	Ö
ENE	0	O		0	0	0	0	0
E.	0	0		0	0	Ö	0	0
ESE	()	0		1.	0	0	0	1.
SE	0	0		1.	3	2	2	8
SSE	()	0		1.	4	2	1.5	22
S	()	2		1	7	9	3	22
SSW	0	0		0	6	0	. 2	8
S₩	0	O		٥	O	1.	0	:1.
พรพ	0	O		0	0	0	0	0
W	O	0		0	1.	2	O .	3
WNW	0	0		0	0	2	0	.2
ИM	0	. 0		1.	1.	0	0	2
МИМ	0	O		1.	0	0	0	1.
TOTAL	O	2		ර	23	18	22	71

PERIODS OF CALM (HOURS): O HOURS OF MISSING DATA: O

TABLE 5

Page 2 of 8

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: MODERATELY STABLE DELTA T 1.5 TO 4.0 1

LAPSE RATE IN DEG C/100 METERS

EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE	D (MPH) O	r 300 FE	EΥ	
MIMD			-				
DIREC-							
MOIT	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
И	0	O	2	8	0	0	1.0
NNE	0	0	1.	1.	1.	0	3
NE	0	()	()	3	() ·	0	3
ENE	1	0	1.	2	0	()	4
E	0	2	5	3	1.	0	1. 1.
ESE	0	1,	2	3	2	0	8
SE	0	0	5	4	1.3	8	30
SSE	0	1	3	ዎ	プ	0	20
S	()	5	7	8	8	. 2	30
SSW	0	1.	3	1.3	2	5	24
SW -	()	0	1.	1. 1.	4	1.	17
WSW	0	1.	1.	1.	1.	0	4
W	0	1.	1.	3	. 3	0	8
WNW	0	0	2	1.	3	0	6
NW	1	0	1.	ර	3	0	1. 1.
MMM	O	0	O	ర	O .	. 0	6
TOTAL	2	12	35	82	48	16	195

PERIODS OF CALM (HOURS): 1
HOURS OF MISSING DATA: 6

TABLE 5

Page 3 of 8

FERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: SLIGHTLY STABLE DELTA T -0.5 TO 1.5 1

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSFEED	(MPH) AT	300 FE	EΥ	
MIND							
DIREC-							
MOIT	13	4-7	8-12	13-18	19-24	>24	TOTAL
N	3	8	22	1.9	:1 .	1.	54
NNE	1	6	1.4	34	7	0	62
NE	0	. ტ	23	1.6	3 .	0	48
EME	0	1.1	1.6	5	1.	1.	34
I :::	2	7	8	6	3	2	28
ESE	1	2	4	2	0	1.	1.0
SE	3	6	フ	17	10	3	46
SSE	.4	5	9	1.3	8	0	39
S	0	7	1.0	1.7	6	5	45
SSW	Ö	7	1.4	27	ブ	2	57
SW	2	ර	1.5	32	3	1.	59
WSW	1	2	1. O	フ	2	8	30
W	1	2	- 19	23	18	1.0	73
WNW	1	5	8	46	31	ద	97
NΜ	0 .	4	12	35	31	1.3	95
иим	2	7	1.7	18	8	0	52
TOTAL	21	91	208	317	139	53	829

PERIODS OF CALM (HOURS): 1 HOURS OF MISSING DATA: 20

TABLE 5

Page 4 of 8

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: NEUTRAL DELTA T -1.5 TO -0.5 ^

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE) (MPH) A	T 300 FEI	ΞŢ	
MIND							
DIREC- TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	1.	1.1	31	15	3	0	61
NNÉ	1.	1. 1.	21	27	1.4	0	74
NE	1	6	17	1.9	1.0	4	57
ENE	1	6	19	3	0	0	29
E	2	7	1.5	2	•	0	26
ESE	1	1	0	1.	· •	0	3
SE	0	2	7	1. 1.	5	0	25
95E	i	1	17	1.4	1.4	3	50
S	3	7	6	3	1.	0	20
SSW	1	6	6	8	0	1.	22
SW	$\dot{\tilde{\mathbf{z}}}$	5	8	4	5	3	27
WSW	3	2	8	16	. 3	12	43
W	2	5	1.8	25	20	43	113
MNM	1.	7	20	24	29	30	111
MM	0	2	1.1	23	23	15	74
NNM	Ö	7	26	26	15	3	フフ
1.41AM	V	,	Au W	an v-	******		
TOTAL	20	86	230	221	141 4.	1.1.4	812

PERIODS OF CALM (HOURS): 2
HOURS OF MISSING DATA: 101

TABLE 5

Page 5 of 8

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: SLIGHTLY UNSTABLE DELTA T -1.7 TO -1.5 C

LAPSE RATE IN DEG C/100 METERS

EVALUATED USING DELTA T 300-33 FT

300 FEET ELEVATION:

	WINDSPEED (MPH) AT 300 FEET									
UIND										
DIREC-							****			
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL			
N	0	O	0	1	0	0	1.			
NNE	1	Ö	1.	1.	O	0	3			
NE	Ö	O	()	2	O	0	2			
ENE	Ö	Ö	0	0	O .	0	0			
	Ö	Ö	Ö	0	Q -	0	0			
ESE	ŏ	Ö	Ö	Ö	Ö	0	0			
SE	Ö	i	Ö	Ö	1.	0	2			
SSE	ŏ	Ő	ï	2	Ö.	0	3			
8	ŏ	Ö	Ö	Ö	Ö	0	.0			
SSW	Ŏ	ŏ	Ö	Ö	Ö	0	0			
SW	Ŏ	ő	Ö	Ö	O	0	0			
WSW	Ŏ	ň	Ö	Ö	0	1.	1.			
WSW	Ŏ.	Ŏ	Ő	ï	i.	Ö	2			
MMM	ň	1	.3	Š	5	, 0	1.4			
	()	, ()	٥	5	1.	1.	4			
MM MM	٥	0	1	3	3	ō	Ÿ			
MMM	V	V	.1-				·			
TOTAL	1.	2	6	1.7	i.1.	2	39			

PERIODS OF CALM (HOURS): 0 HOURS OF MISSING DATA: 1

> TABLE 5 Page 6 of 8

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: MODERATELY UNSTABLE DELTA T -1.9 TO -1.7 ~

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE	D (MPH) AT	300 FE	ĒΫ́,	
WIND DIREC-							
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	O	0	1.	0	0	0	1.
NNE	0	0	0	1.	0	0	. 1.
NE	1.	0	0	Ö .	0	. 0	1.
ENE	O	0	0	0	0	0	O
E	0	0	()	0	O	0	0
ESE	0	0	. 🗘	O	0	0	O
SE	0	0	0	0	0	0	0
SSE	0	0	. · ()	0	()	O .	0
S	0	0	0	Ó	0	Ö	0
SSW	O	1.	()	()	O	0	1.
SW	()	0	1.	0	O	0	1.
พรพ	0	O	:1.	0	0	0	1.
W.	0	O	0	0	1.	0	1.
เมพเม	Ö	0	O	0	2	3	5
NW	()	0	3	3	3	1	10
MMM	0	0	1.	2	1.	0	4
TOTAL	1.	1.	7	6	7	4	26

PERIODS OF CALM (HOURS): 0
HOURS OF MISSING DATA: 6

TABLE 5
Page 7 of 8

PERIOD OF RECORD: 1 182 TO 33182

STABILITY CLASS: EXTREMELY UNSTABLE DELTA T <-1.9 0

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

1 1 T \$175			WINDSPEE	D (MPH) AT	r 300 FEI	ΞΥ	
WIND DIREC-							
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
И	0	0	O	0	0	٥	0
NNE	0	0	0	0	0	٥	Ö
ΝE	0	1.	0	3	2	Ø	ర
ENE	1	()	()	0	()	0	1.
E	0	0	0	O :	(0	()
ESE	0	0	()	0	0	0	O
SE	0	0	0	. 0	O	0	0
SSE	0	()	0	0	O	0	0
8	0	0	O	0	0	Ö	0
SSW	0	()	2	0	O	0	2
SW	O	0	· •	0	0	0	0
พรพ	0	0	0	0	()	0	0
W	O	O	()	()	3	0	. 3
MMM	0	0	1	0	0	O	1
NW	()	()	· O	0	0	0	O
MNM	O	0	O	0	0	0	()
TOTAL	1	1.	3	3 ,	5	0	1.3

PERIODS OF CALM (HOURS): O HOURS OF MISSING DATA: 2

· TABLE 5

Page 8 of 8

FERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: EXTREMELY UNSTABLE DELTA T <-1.9 1

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

•		•	WINDSPEE	D (MPH) AT	300 FE	ΞŢ	
WIND				•	•		
DIREC-							
MOIT	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	()	()	O	O	O -	0	0
NNE	()	()	()	()	() ·	0	O
NE	0	0	3	0	0	()	3
ENE	0	0	0	0	0	0	0
EE	O	()	0	0	0	0	0
ESE	O	0	0	0	0	0	O
SE	0	0	0	0	ο .	0	0
SSE	0	0	0	0	0	0	()
9	0	()	0	Ö	0	0	0
SSW	0	0	()	0	0	0	0
SW	Ö	0	O	0	0	0	0
WSW	0	0	0	· O	0	0	()
W	O	0	O	3	()	Q	3
MMM	0	()	1.	1.	2	1.	5
NW	()	0	()	2	3	1.3	18
MMM	()	· 0	O	()	3.	0	1.
TOTAL	O	0	4	6	ద	1.4	30

PERIODS OF CALM (HOURS): 0
HOURS OF MISSING DATA: 0

TABLE 6

Page 1 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: MODERATELY UNSTABLE DELTA T -1.9 TO -1.7 ~

LAPSE RATE IN DEG C/100 METERS

EVALUATED USING DELTA T 300-33 FT

			WINDSPEE	n (HPH) a	AT 300 FEE	ΞΥ	
WIND DIREC- TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL.
И	0	0	O .	1.	1	0	2
NNE.	ö	Ö	0	0	0	O	Ö
NE	ő	Ö	1.	0	Q	0	1.
ENE	Ŏ	Ö	O	0	0	O	O
E	ŏ	Ö	()	0	0	0	Ö
ESE	ő	Ö	0	0	0	0	0
SE	Ŏ	Ö	0	0	1.	Ö	1.
SSE	ő	Ö	0	Ö	0	0	O
8	Ö	0	O	O	. 0	0	O
SSW	Ö	0	0	O	. ()	0	0
5W	Ö	Ö	O	0	, O	0	0
พรพ	ŏ ′	Ö	0	O	, ; O	Q	0
W	Ö	O	3	2	2	. 0	7
พพพ	0 .	0	1.	3	3	3	1.0
MM	ő	Ö	1.	1.	5	3	1.0
MMM	ŏ	1.	1.	1.	4	2	9
TOTAL	0	1.	7	8	1.6	8	40

PERIODS OF CALM (HOURS): 0
HOURS OF MISSING DATA: 1

Table 6
Page 2 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: SLIGHTLY UNSTABLE DELTA T -1.7 TO -1.5 ^

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE	n (HPH) a	r 300 FEE	ΞŢ	
WIND				t			
DIREC-							
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	()	1.	2	٥	0	0	3
NNE.	Ö	1.	2	3	0	0	6
NE	Ö	O	0	0	0	O .	0
ENE	Ö	Ö	0	0	0	0	0
Œ	Ö	O	Ö	Ö Ü	O	0	0
ESE	Ö	. 0	0	0	0	0	0
SE	Ö	Ö	1.	0	0	0	:1.
SSE	Ö	()	0	Q .	0	O	()
S	Ö	0	()	() · · · ·	0	O	0
SSW	Ö	0	0	O	O	O	O
SW	Ö .	Ö	0	0	()	0	0
พรพ	Ö	0	1.	O	() ·	0	:1.
W	Ö	1	4	O	1.	0	6 -
พิพพ	Ö	Ö	5	1.	()	0	6
ИM	Ö	1	1.	2	3	3	10
พพพ	Ö.	1.	5	.4	. გ	0	16
TOTAL	0	5	21	10	1.0	3	49

PERIODS OF CALM (HOURS): O HOURS OF MISSING DATA: 1

TABLE 6

Page 3 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: ALL STABILITIES EXCLUDING MISS SPEED/DIR DATA

LAPSE RATE IN DEG C/100 METERS

EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

AAT NEE.			WINDSPEE	D (MPH) A	r 300 fe	EET	
WIND							
DIREC-	4 "Y	A ***	<i>m</i>				
TION	1 - 3	4-7	8-12	13-18	19-24	>24	TOTAL
N	3	1.8	42	34	20	1.3	130
MME	4	1.3	24	19	3	Ö	63
NE	1.	7	34	50	2	0	94
ENE	0	22	29	1.5	0	0	66
E	3	27	42	24	0	0	96
ESE	3	8	1.3	1.9	7	2	52
SE	- 5	22	25	61	53	27	193
SSE	4	31	33	50	50	1.9	187
S	8	21	34	39	32	1.0	144
SSW	9	25	22	40	25	1.0	131
SW	1.	40	39	41	1.8	15	154
พรพ	3	21	30	33	1.6	1.	104
W	Ą	29	51	59	24	12	179
พทพ	З.	1.3	34	47	37	29	161
NW	1.	1.8	34	53	48	34	188
MMM	0	33	δ 1	40	35	6	175
TOTAL	50	348	.547	624	370	178	2117

PERIODS OF CALM (HOURS): O HOURS OF MISSING DATA: 45

TABLE 6
Page 4 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: NEUTRAL

DELTA T -1.5 TO -0.5 7

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEED	(MPH)	AT 300	FEET .	
WIND DIREC-							
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	2	9	27	20	8	5	71
NNE	2	3	18	1.3	0	Ö	.36
ME	1	3	17	26	1.	0	48
ENE	()	1. 1.	1.6	1.0	Ö	0	37
E	2	9	1.4	1.3	0	Ö	38
ESE	2	0	3	4	3	1.	1.3
SE	3	8	4	19	20	1.3	67
SSE	2	1.0	10	19	31	. 4	76
8	4	5	4	1. 1.	8 ا	0	32
SSW	6	1.0	3	4	1	()	24
S₩	0	12	8 .	1.4	: 4	2	40
WSW	1.	7	16	1.8	5	1.	48
W	0	12	22	20	9	3	ర ర
พพพ	()	.4	1.6	1.9	19	20	78
ЫИ	1	6	1.4	1.8	1.1	8	58
NNW	0	23	37	19	13	3	95
TOTAL	28	132	229	247	133	60	827

PERIODS OF CALM (HOURS): 0 HOURS OF MISSING DATA: 26

TABLE 6
Page 5 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: SLIGHTLY STABLE DELTA T -0.5 TO 1.5 ~

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE	n (MPH) à	T 300 FE	ET	
WIND DIRECT					•		
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	1.	6	9	8	9	8	41.
NNE	2	9	1 .	3	3	O	18
ME	0	3	1. 1.	23	1.	O	38
ENE	0	7	1.2	5	0	0	24
i::	1.	1.4	27	1. O	0	0	52
ESE	1.	8	1.0	1.5	A	1.	39
SE	2	1. O	1.7	38	29	1.3	109
SSE	2	1.4	1.8	22	7	1. 1.	74
S	4	15	20	7	1.5	0	61
SSW	2	1.0	1.3	29	1.9	フ	80
SW	1.	24	20	22	1. 1.	6	84
WSW	2	1.2	1.1.	1.5	2 .	٥	42
W	2	1.4	21	28	. 8	8	82
MMM	1.	8	1.0	18	10	5	52
NW	0	9	16	26	24	7	82
MMM	O	చ	1.4	1.1	1.0	1.	42
TOTAL	21	1.69	230	280	152	68	920

PERIODS OF CALM (HOURS): 0 HOURS OF MISSING DATA: 16

TABLE 6

Page 6 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: MODERATELY STABLE DELTA T 1.5 TO 4.0 ~

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEEL) (MPH) AT	300 FEI	Ξ.Υ	
UIMI							
DUREC-	•						
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	0	2	4	5	2	0	13
NNE	0	0	3	0	0	0	3
NE	Ö	1.	2	1.	Ø	0	4
ENE	0	4	1.	0	Ö	0	5
Æ	()	4	1.	1.	O	0	6
ESE	0	()	0	0	O	()	()
SE	0	4	3	4	3	0	1.4
SSE	0	7 .	4	8	1. O	3	33
S	0	1.	8	1.7	9	6	41.
SSW	1.	5	6	გ -	5	3	26
SW	()	4	9	5	2	7	27
WSW	()	2	2	0	9	O	1.3
ls)	2	2	1.	ద	4	0	15
WNW	0	1.	3.	5	3	0	1.0
NW	0	1.	2	4	2	0	9
NNM	()	2	4	5	:1.	0	12
TOTAL	3	40	51	68	50	19	231

PERIODS OF CALM (HOURS): O HOURS OF MISSING DATA: 1

TABLE 6

Page 7 of 8

PERIOD OF RECORD: 4 182 TO 63082

STABILITY CLASS: EXTREMELY STABLE DELTA T >4.0 ^

LAPSE RATE IN DEG C/100 METERS EVALUATED USING DELTA T 300-33 FT

ELEVATION: 300 FEET

			WINDSPEE	n (HPH) a	7 300 FEI	ΞT	
WIND							
HIREC-					•		
TION	1-3	4-7	8-12	13-18	19-24	>24	TOTAL
N	0	O	0	0	0	0	. 0
NNE	0	0	Ö	0	0	O .	0
NE	()	Q	()	0	0	0	0
EINE	Ö	0	()	O	0	O	0
E	0	0	()	0	0	0	0
ESE	O	0	() ·	O	Ö	. 0	O
SE	0	Ö	0	0	0	1.	3.
99E	0	0	1.	O	2	1.	4
8	Ö	· ()	2	4	Ö	4	10
SSW	0	0	0	1.	. 0	0	1.
SW	O	O	2	O	1.	0	3
พรพ	()	()	0	()	Ø	()	0
μJ	0	()	()	0	O .	Ö	()
MMW	()	0	()	0	0	0	()
ΜW	0	1.	0	0	0	0	1.
MMM	0	Ó .	O	0	O	0	O
TOTAL	O	1.	5	5	3	ర	. 20

PERIODS OF CALM (HOURS): O HOURS OF MISSING DATA: O

TABLE 6
Page 8 of 8

REVISION TO RERR-11

TABLE 1B-1 EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1981) GASEOUS EFFLUENTS-ELEVATED RELEASES UNIT 1

			UNIT				
			CONTINUO	US MODE	ВАТС	CH MODE	
Nuc	lides Released	Unit	3rd Quarter	4th Quarter	3rd Quarter	4th Quarter	
	TIGOD ROTOGOOG		Qual col		Qual tel	Zuar cor	
1.	Fission gases	,				,	
	Krypton-85	Ci					
	Krypton-85m	Ci			4.79E-04		
	Krypton-87	Ci					
	Krypton-88	Ci	ì				
	Xenon-133	Ci	2.76E+02	1.55E-02	1.57E+02	7.02E+01	
	Xenon-135	Ci	1.09E+01	2.84E-02	1.77E+00	7.34E-01	
	Xenon-135m	Ci				4.53E-02	
	Xenon-138	Ci					
	Xenon-133m	Ci	2.58E-04	<u> </u>	1.32E+00	7.31E-01	
	Argon-41	Ci					
	Fluorine-18	Ci					
	Unidentified	Ci					
	Total for period	Ci	2.87E+02	4.39E-02	1.60E+02	7.17E+01	
2.	Iodines				,		
	Iodine-131	Ci	4.49E-04	4.93E-04			
	Iodine-133	Ci	7.17E-04				
	Iodine-135	Ci					
					·····		

Total for period

1.17E-03

4.93E-04

Ci