REPORT NO. RERR-13

TE HO FINE COPY

UNIT NOS. 1 & 2
RADIOACTIVE EFFLUENT RELEASE REPORT
JULY - DECEMBER 1982

SALEM NUCLEAR GENERATING STATION
Public Service Electric and Gas Company

M P79 43/33 1-gs

8309140004 830824 PDR ADOCK 05000272 PDR PDR



1982

SEMIANNUAL RADIOACTIVE EFFLUENT RELEASE REPORT RERR-13

SALEM NUCLEAR GENERATING STATION SALEM UNIT NOS. 1 & 2

UNIT 1 DOCKET NO. 50-272 UNIT 2 DOCKET NO. 50-311 OPERATING LICENSE NO. DPR-70 OPERATING LICENSE NO. DPR-75

FINAL

JULY 1983

SALEM NUCLEAR GENERATING STATION
UNIT NOS. 1 AND 2
RADIOACTIVE EFFLUENT RELEASE REPORT
July 1, 1982 to December 31, 1982

Introduction

This report, RERR-13, summarizes the releases of radioactive materials in liquid, gaseous and solid form from the Salem Nuclear Generating Station Units 1 and 2 for the period July 1, 1982 to December 31, 1982. As requested by the United States Nuclear Regulatory Commission (USNRC) this report was prepared in the format specified for all nuclear power plants as defined in USNRC Regulatory Guide 1.21.

The report is prepared in the format of Regulatory Guide 1.21, Appendix B, as required by Specification 5.6.1.2 of the Salem Environmental Technical Specifications. Preceding the tables summarizing the gaseous and liquid discharges and solid waste shipments is our response to parts A-F of the "Supplemental Information" section of the Regulatory Guide 1.21, Appendix B.

As required by Regulatory Guide 1.21, our Technical Specification limits are described in detail within this report along with a summary description of how measurements and approximations of the total activity discharged were developed.

To facilitate determination of compliance with 40CFR190 requirements, the following information on electrical output is provided.

Unit 1 generated 1,843,381 megawatt-hours of electrical energy (net) during the reporting period.

Unit 2 generated 3,448,270 megawatt-hours of electrical energy (net) during the reporting period.

Due to a major modification in our Company's computer processing equipment, tabulations of releases were not available for inclusion in our earlier report. This report provides the information which was not available for inclusion in our earlier report.

Part A. PRELIMINARY SUPPLEMENTAL INFORMATION

1.0 Regulatory Limits

We are required to summarize our regulatory limits in each report. Symbols utilized in the equations listed below under Sections 1.1 and 1.2 are the same as those used in the Salem Environmental Technical Specifications (ETS). The symbol Q as explained in Section 2.3.3 of the ETS is the release rate of the gaseous activity in units of curies per second. The K, L, M and N terms are actually site dependent dose conversion factors. The equations listed below in Sections 1.1 and 1.2 take into consideration the release point location, building wake effects and physical characteristics of the radionuclides released.

In addition 40CFR190 regulations require that the annual dose equivalent does not exceed 25 mrem to the whole body or any organ (except the thyroid which is limited to 75 mrem).

1.1 Fission and Activation Gases Release Limits

- Gaseous releases from the nuclear units are limited such that at no time will releases of gaseous radioactive materials cause a member of the general public to be exposed to an annual dose rate in excess of 500 mrem to the entire body or 3 rem to the skin in conformance with the requirements of 10CFR20.
- b) Gaseous releases from the units are further restricted such that when releases are averaged over a calendar quarter no member of the general public will be exposed to an annual dose rate in excess of 20 millirads of gamma radiation or 40 millirads of beta radiation.
- c) In addition, it is required that air doses averaged over a twelve month period be less than 40 and 80 millirads for gamma and beta radiation respectively.

We use the following equations to demonstrate compliance with these limits:

2.0
$$Q_{tv}^*K_{v} \leq 1$$

$$0.33 \, Q_{tv}^*(L_v + 1.1 \, N_v) \leq 1$$

When averaged over a calendar quarter the release rate for radioactive gases must satisfy the following equation. The asis for these equations is 10CFR50 Appendix I.

13
$$Q_{tv}^*\overline{N}_v \leq 1$$

6.3 $Q_{tv}^*\overline{M}_v \leq 1$

The limiting Unit 1 release limit Q is calculated to be 5.78E+04 and 5.87E04 microcuries/sec for both the 3rd and 4th quarters respectively.

The limiting Unit 2 release limit Q is calculated to be 5.87 E+04 and 5.62E+04 microcuries/sec. for the 3rd and 4th quarters respectively.

When averaged over any twelve consecutive month period, the release rate for radioactive gases must satisfy the following equation. The basis for this equation is 10CFR50 Appendix I.

$$25. Q_{tv} * \overline{N}_{v} \leq 1$$

13
$$Q_{tv}*\overline{M}_{v} \leq 1$$

The release limits of radioactive gases for the Salem Nuclear Generating Station are not fixed numbers, but depend upon the radioactive isotopes present in the effluent.

1.2 Iodine and Particulates, Half Life > 8 days

The regulatory limits for iodines and particulates are listed below.

The release rates of iodine and particulates are restricted such that no member of the general public will receive a dose at a rate in excess of 1.5 rem/yr. to the thyroid.

Releases of iodines and particulates are further restricted to prevent any member of the general public from receiving a dose rate in excess of 30 mrem in a calendar quarter or 60 mrem in any twelve month period. The equations which govern these conditions are listed below:

At any instant of time the release rate for radioactive iodines and particulates material with a half life greater than 8 days is limited by the equation below. The basis for his equation is 10CFR20.

$$(1.5 \times 10^5) Q_{V} \le 1$$

During any calendar quarter the release limit is governed by e equations listed below. The basis for these equations is CFR50 Appendix I.

2 curies of I-131 and
$$Q_v \times 13 \times (1.5 \times 10^5) \le 1$$

During any twelve month period radioactive releases should conform to the following constraints of 10CFR50 Appendix I.

25 x (1.5 x
$$10^5$$
) x $Q_v \le 1$ and 4 curies of I-131

1.3 Liquid Effluents Release Limits

We are not permitted to discharge radioactive liquids such that we exceed the values in 10CFR20, Appendix B, Table II, Column 2.

addition, the following limits apply:

The cumulative release of radioactive effluents, excluding tritium and dissolved gases, shall be less than 10 Ci in a calendar quarter for each unit.

The cumulative release of radioactive effluents, excluding tritium and dissolved gases, shall be less than 20 Ci in any twelve consecutive months for each unit.

2.0 Maximum Permissible Concentrations (MPC)

Regulatory Guide 1.21 requires that the licensee provide the MPC's used in determining allowable release rates for radio-active releases.

- a) MPC values were not used to determine the maximum release rates for fission gases, iodines, or particulates.
- b) MPC values as stated in 10CR20, Appendix B, Table 11, Column 2 were used for liquids.

3.0 Average Energy

regulatory Guide 1.21 requires that the licensee provide the average energy of the radionuclide mixture in releases of fission and activation gases, if applicable.

Release limits for the SNGS are not based upon average energy, hence, this section does not apply.

- 4.0 Measurements and Approximation of Total Radioactivity
- Liquid effluents are monitored in accordance with Table 4.1 2.3-3 of the Environmental Technical Specifications. During the period of record, all wastes from the chemical drain tank and the laundry and hot shower tanks were routed to the hold-up tanks for monitoring prior to re-Technical Specifications require these tanks to be recirculated the equivalent of two tank volumes to produce uniform mixing before sampling and analyzsis before any releases are made. Batch releases are defined as releases from the waste monitor tanks, waste monitor hold-up tank, and the chemical and volume control tanks. Continuous releases are defined as releases from intermittent blowdown of the steam generators. The predominate gamma emitting isotopes detected in sampling were Co58, Co60, Cr51, and Mn54. Specific activity from analyses were mutiplied by the volume of effluent discharged to the environment in order to estimate the total liquid activity discharged.
- Gaseous effluent streams are monitored and sampled in accordance with Table 2.3-4 of the Environmental Technical Specifications. The plant vent is the final release point of all planned gaseous effluents and is continuous monitored by four very sensitive Geiger Mueller (GM) tubes. The GM tubes are intended as a surveillance device. The vent is also continuously sampled for iodine and particulates with a charcoal cartridge and filter paper connected in series to a low volume air The filter and charcoal are changed weekly, and sampler. analyzed on a multichannel analyzer in the laboratory. Sampling is also performed on all gas decay tanks and containment purges, prior to their release to the en-The plant vent is sampled for noble gases vironment. monthly. All tritium samples were taken by bubbling gas through water and then counting the tritiated water on a liquid scintillation counter.

The detection requirements of Table 2.3-2 of the ETS are achieved or exceeded. Isotopes existing at concentrations below the achieved detection limit are not treated as being present.

Continuous Mode gaseous releases are quantified by routine (monthly or weekly) sampling and isotopic analyses of the plant vent. Specific activities for each isotope detected are multiplied by the total vent flow volume for the entire sampling period in order to estimate the normal continuous release of radioactivity through the plant vent if any exists.

Batch Mode releases are quantified by the sample of each gas decay tank or containment purge prior to discharge. Specific activities for each isotope are multiplied by the total volume of gas discharged.

Elevated RMS readings while the channel is in an alarm state are treated as batch mode releases. If specific activity data from grab samples taken while the release was in progress is not available, then the abnormal release will be quantified by the use of the plant vent radiation monitors. The monitors response is converted in a "specific activity" using historical efficiency factors. The "specific activity" is multiplied by the volume of effluent discharged while the channel was in an alarm state in order to estimate the total activity discharged.

4.3 The estimated total error of the reported continuous gaseous releases is within 50% when concentrations exceed detectable levels. This error is due primarily to variability of waste stream flow rates and changes in isotopic distributions of waste streams between sampling periods. The estimated total error of the reported batch gaseous releases is within 10%.

Error estimates for continuous releases where sample activity is below the detectable concentration levels are not included since error estimates at the LLD are not defined.

The estimated total error of reported liquid releases is within 25%.

5.0 Batch Releases

Batch releases of gaseous and liquid effluent are provided in Tables 4A-1 and 4B-1 for Unit 1 and 4A-2 and 4B-2 for Unit 2.

6.0 Unplanned Releases

During this reporting period two unplanned releases were identified and quantified as batch gaseous releases.

Part B. Gaseous Effluents

see Summary Tables 1A-1 thru 1C-1 representative of Saleminit 1 operations.

See Summary Tables 1A-2 thru 1C-2 representative of Salem Unit 2 operations.

Part C. Liquid Effluents

See Summary Tables 2A-1 and 2B-1 representative of Salem Unit 1 operations.

See Summary Tables 2A-2 and 2B-2 representative of Salem Unit 2 operations.

Part D. Solid Waste

See Summary Table 3 Units 1 and 2

Part E. Radiological Impact on Man

The calculated individual doses in this section are based on actual locations of nearby residents and farms. The population dose impact is based on historical site specific data i.e., food production, milk production, feed for milch animals and seafood production.

The doses were calculated using methods described in Regulatory Guide 1.109 and represent calculations for the six month reporting interval. Doses from batch and continuous releases were calculated using the meteorological dispersion coefficient X/Q for the six month reporting interval.

Liquid Pathways

Doses to individuals in the population from liquid releases are primarily from the seafood ingestion pathway. The total body dose to an individual was calculated to be 7.26E-03 mrem. The calculated population total body dose was 1.56E-1 person-rem. The highest organ dose from liquid releases was 5.73E-02 mrem to the gastrointestinal tract.

Air Pathways

The resulting whole body and skin doses to an individual were calculated to be 4.27E-03 mrem and 5.32E-03 mrem respectively. The calculated population total body dose was 8.85E-01 person-rem. The average total body dose to the population within fifty miles of the site was 1.65E-04 mrem/person.

Direct Radiation

Direct radiation may be estimated by TLD measurements. One method for comparing TLD measurements is by comparison with preoperational data. TLD measurements on site near the Service Water pumps (location 11S1) and near the Circulating Water pumps (location 10S1) averaged 9.05 and 6.48 mrads/months, respectively, apparently due to trace activity in the Refueling Water Storage Tank.

TLD's at onsite locations 2S2 and 5S1 which are 0.3 miles and 0.9 miles from the reactor containment, averaged 4.23 and 4.59 mrads/month respectively. The values for stations 2S1 and 5S1 are within the statistical variation associated with the preoperation program results.

All offsite monitoring locations remained within preoperational ranges. It should be noted that the nearest resident is 3.5 miles away. It can thus be concluded that there was no measurable dose to any offsite locations from direct radiation.

Part F. Meteorological Data

Cumulative joint wind frequency distribution by atmospheric stability class at the 300 foot elevation is provided for the third and fourth quarters of 1982 as Table 5 and 6.

FOUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) CASEOUS EFFLUENTS-SUMMATION OF ALL RELEASES

GASEOUS EFFLUENTS-SUMMATION OF ALL RELEASES UNIT 1

		Units	3rd Quarter	4th Quarter	Est.Total(1) Error %
Α.	Fission & Activation Gases				
•	1. Total release	Ci	6.91E+01	1.64E+02	2.50E+01
	2. Average release rate for period	uCi/sec.		2.01E+01	
	3. Percent of technical specification limit	ક	1.44E-02	3.64E-02	
	(See ETS Spec. 2.3.3.b)				
		.•			
В.	Iodines				1
	1. Total iodine-131	Ci	4.25E-03	1.87E-03	2.50E+01
	2. Average release rate for period	uCi/sec.	5.35E-04	2.35E-04	
	3. Percent of technical specification (2Ci) limit	ક	2.13E-01	4.35E-02	
C •.	Particulates				<u> </u>
	1. Particulates with half-lives> 8 days	Ci	1.87E-04	2.23E-06	2.50E+01
	2. Average release rate for period	uCi/sec.	2.36E-05	2.81E-07	
	3. Percent of technical specification limit	ક	4.60E-03	5.48E-05	
	4. Gross alpha radioactivity (2)	Ci	0.00E+00	0.00E+00	
D.	Tritium				
	1. Total release	Ci	2.96E-01	3.27E+02	2.50E+01
	2. Average release rate for period	uCi/sec.	3.72E-02	4.11E+01	
	3. Percent of technical specification limit	ક	N/A	N/A	

- (1) For batch releases the estimated overall error is within 10%.
- (2) Analyses indicate no measurable alpha emitting transuranics.

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-SUMMATION OF ALL RELEASES

TT	N	т	T
υ	ĽΝ	Д,	Т

		Units	3rd Quarter	4th Quarter	Est.Total(1) - Error %
Α.	Fission & Activation Gases				
	1. Total release	Ci	1.00E+03	6.85E-01	2.50E+01
	2. Average release rate for period	uCi/sec.	1.26E+02	7.61E-02	
	3. Percent of technical specification limit	ક્ર	2.15E-02	1.35E-04	
	(See ETS Spec. 2.3.3.b)				
В.	Iodines				
	l. Total iodine-131	Ci	1.74E-03	7.00E-04	2.50E+01
	2. Average release rate for period	uCi/sec.	2.19E-04	8.81E-05	
	3. Percent of technical specification limit	ક			
С.	Particulates				
	1. Particulates with half-lives> 8 days	Ci	<lld< td=""><td><lld< td=""><td>2.50E+01</td></lld<></td></lld<>	<lld< td=""><td>2.50E+01</td></lld<>	2.50E+01
	2. Average release rate for period	uCi/sec.		-	
	3. Percent of technical specification limit	ફ	_		
	4. Gross alpha radioactivity	Ci	0.00E+00	0.00E+00	· · · · · · · · · · · · · · · · · · ·
D.	Tritium				
	l. Total release	Ci		· · · · · · · · · · · · · · · · · · ·	
	2. Average release rate for period	uCi/sec.			
	3. Percent of technical specification limit	ક			

. (1) For batch releases the estimated overall error is within 10%.

TABLE 1B-1 EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-ELEVATED RELEASES

UNIT 1

			CONTINUO	US MODE	BATC	H MODE	
Nuc	clides Released	Units	3rd Quarter	4th Quarter	3rd Quarter	4th Quarter	
1.	Fission gases						
	Krypton-85	Ci	1.62E-03		1.04E-01	3.07E-01	
_	Krypton-85m	Ci				4.15E-01	
	Krypton-87	Ci	7.64E-06	1			
	Krypton-88	Ci	6.12E-03		6.03E-04	2.34E-01	
	Xenon-133	Ci	2.41E-01	1.83E-04	6.73E+01	1.55E+02	
	Xenon-135	Ci	1.17E-01		1.11E+00		
	Xenon-135m	Ci	1.46E-02			7.64E+00	
	Xenon-138	Ci					
	Xenon-133m	Ci	2.28E-04		5.53E-01	1.64E+00	
	Argon-41	Ci				2.58E-02	
	Fluorine-18	Ci	4.20E-06		4.70E-05		·
	Xe-131m	Ci					
	Total for period	Ci	3.81E-01	1.83E-04	6.91E+01	1.64E+02	
2.	Iodines						,
	Iodine-131	Ci	1.41E-03	1.30E-03			,
	Iodine-133	Ci	2.84E-03	5.70E-04			
	Iodine-135	Ci					
	Total for period	Ci	4.25E-03	1.87E-03			· · · · · · · · · · · · · · · · · · ·

TABLE 1B-1

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-EL (Continue UNIT 1

		CONTINUOUS MODE		BATO	CH MODE	
Nuclides Released	Units	3rd Quarter	4th Quarter	3rd Quarter	4th Quarter	
3. Particulates				· · · · · · · · · · · · · · · · · · ·	······································	···
(Half life > 8 days)						
Chrominum-51	Ci					
Manganese-54	Ci					
Cobalt-58	Ci					
Cobalt-60			 			
	Ci				2 225 06	
Iron-59	Ci			3 045 04	2.23E-06	
Yttrium-88	Ci			1.84E-04		
Strontium-89	Ci					
Strontium-90	Ci		· · · · · · · · · · · · · · · · · · · 			
Niobium-95	Ci					
Zirconium-95	Ci					
Tin-117m	Ci	·				
Cesium-137	Ci	2.70E-06				
Cerium-139	Ci	· · · · · · · · · · · · · · · · · · ·				
Gross Alpha	Či					
Total For Period	Ci	2.70E-06	<lld< td=""><td>1.84E-04</td><td>2.23E-06</td><td></td></lld<>	1.84E-04	2.23E-06	
4. Tritium						
Tritium	Ci	<lld< td=""><td><lld< td=""><td>2.96E-01</td><td>3.27E+02</td><td></td></lld<></td></lld<>	<lld< td=""><td>2.96E-01</td><td>3.27E+02</td><td></td></lld<>	2.96E-01	3.27E+02	

TABLE 1B-Z EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982) GASEOUS EFFLUENTS-ELEVATED RELEASES UNIT 2

			CONTINUO	US MODE	BATC	H MODE
			3rd	4th	3rd	4th
Nuc	clides Released	Units	Quarter	Quarter	Quarter	Quarter
1.	Fission gases			 		
	Krypton-85	Ci			2.18E-01	3.96E-02
	Krypton-85m	Ci				
	Krypton-87	Ci				
	Krypton-88	Ci				
	Xenon-133	Ci	1.00E+03	1.85E-04	2.54E+00	5.64E-01
	Xenon-135	Ci	3.97E-02	8.87E-04	1.70E-03	
	Xenon-135m	Ci				
	Xenon-138	Ci				
	Xenon-133m	Ci	6.24E-05		1.13E-02	
	Argon-41	Ci				
	Fluorine-18	Ci				
	Xenon - 131m	Ci				
	Total for period	Ci	1.00E+03	1.07E-03	2.77E+00	6.04E-01
2.	Iodines					
	Iodine-131	Ci	1.35E-03	5.97E-04		
	Iodine-133	Ci	3.94E-04	1.03E-04		
	Iodine-135	Ci	· · · · · · · · · · · · · · · · · · ·		····	· · · · · · · · · · · · · · · · · · ·
	Total for period	Ci	1.74E-03	7.00E-04	,	

TABLE 1B-2

EFFLUENT AND WASTE DISPOSAL SEMLANNUAL REPORT (1982) GASEOUS EFFLUENTS-EL ED RELEASES

(Contine

			CONTINUC	OUS MODE	BAT	CH MODE	
Nuc	lides Released	Units	3rd Quarter	4th Quarter	3rd Quarter	4th Quarter	
3.	Particulates						
	(Half life > 8 days)						
	Chrominum-51	Ci					
	Manganese-54	Ci					
	Cobalt-58	Ci					
	Cobalt-60	Ci					
	Iron-59	Ci					
	Yttrium-88	Ci					
	Strontium-89	Ci	,				
	Strontium-90	Ci					
	Niobium-95	Ci					
	Zirconium-95	Ci					
	Sr-85	Ci					
	Cesium-134	Ci		•			
	Cesium-137	Ci	· · · · · · · · · · · · · · · · · · ·				
	Cerium-139	Ci					
	Gross Alpha	Ci					
	Total For Period	Ci	<lld< td=""><td><lld< td=""><td></td><td></td><td></td></lld<></td></lld<>	<lld< td=""><td></td><td></td><td></td></lld<>			
4.	Tritium	·	- 				
	Tritium	Ci	<lld< td=""><td>1.92E+00</td><td></td><td></td><td>···</td></lld<>	1.92E+00			···

TABLE 1C

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT 1982

UNITS 1 AND 2

GASEOUS EFFLUENTS-GROUND-LEVEL RELEASES

Nuclides Releases Unit 3rd Quarter 4th Quarter 3rd Quarter 4th Quarter

There were no ground level releases for the period of record.

TABLE 2A-1

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

UNIT 1

LIQUID EFFLUENTS-SUMMATION OF ALL RELEASES

4th

		4 L II	ru				
Total	Est. To Error,	Quarter	arter		Units		
			•				
						Fission and activation products	Α.
						1. Total release (not including	
50E+01	2.50E+	1.18E+00	4E-01	_ 3	Ci	tritium, gases, alpha)	
				_	- • •	2. Average diluted concentration	
		3.13E-07	1E-07	_1	uCi/ml	during period	
					_	3. Percent of applicable limits	
		1.18E+01	4E+00	3	- ¥	of Technical Specifications	
						musi k dayar	D
508401	2.50E+	1.43E+02	0E+02		Ci	Tritium l. Total release	В.
JUETUI	Z.30E	1.43ETUZ	05,702		<u> </u>	Average diluted concentration	
		3.79E-05	5E-04	٦	uCi/ml	during period	
	· · · · · · · · · · · · · · · · · · ·	N/A	N/A		<u>uci/mi</u>	3. Percent of applicable limit	
		14/ 11				J. refeelt of applicable limit	
						. Dissolved and entrained gases	C.
50E+01	2.50E+	1.92E-01	9E+00	1	Ci	l. Total release	
		· · · · · · · · · · · · · · · · · · ·				2. Average diluted concentration	
	-	5.09E-08	8E-07	. 3	uCi/ml	during period	
		N/A	N/A		ક્ર	3. Percent of applicable limit	
			· · · · · · · · · · · · · · · · · · ·				
						. Gross alpha radioactivity	D.
50E+01	2.50E+	0.00E+00	0E+00	0	Ci	1. Total release	
		······································					
					•	. Volume of waste release (prior	Ε.
		5.03E+06	9E+0 <u>6</u>	5	liters	to dilution - Batch Release)	
						· Volume of dilution water used	F.
50E+01	2.50E+	3.77E+09	1E+09	3	_liters	during period - Batch Release	ļ
_		5.03E+06	9E+06	5	liters	1. Total release Volume of waste release (prior to dilution - Batch Release) Volume of dilution water used	E•

A - Not Applicable

TABLE 2A-2

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

UNIT 2

LIQUID EFFLUENTS-SUMMATION OF ALL RELEASES

3rd 4th

•	Units	Quarter	Quarter	Est. Total Error, %
			·	
A. Fission and activation products				·
1. Total release (not including		2 245 01	1 125.00	2 505.03
tritium, gases, alpha)	Ci	3.34E-01	1.13E+00	2.50E+01
2. Average diluted concentration	01/1	0 005 00	0 075 00	
during period	uC1/m1	2.98E-08	8.07E-08	
3. Percent of applicable limits		2 245.00	1 120.01	
of Technical Specifications		3.34E+00	1.13E+01	
B. Tritium	,			
_l. Total release	Ci	2.33E+02	5.97E+01	2.50E+01
. Average diluted concentration			·	
during period	uCi/ml	2.08E-05	4.26E-06	
3. Percent of applicable limit	8	N/A	N/A	
C. Dissolved and entrained gases				
1. Total release	Ci	1.38E+00	1.36E+00	2.50E+01
Average diluted concentration				
during period		1.23E-07	9.71E-08	
3. Percent of applicable limit	8	N/A	N/A	
D. Gross alpha radioactivity		0.00		0 500.01
1. Total release	Ci	0.00	0.00	2.50E+01
				_
E. Volume of waste release (prior	144	4 21DLCC	E EARLOC	
E. Volume of waste release (prior to dilution - Batch Release)	liters	4.31E+06	5.54E+06	
to dilution - Batch Release)	liters	4.31E+06	5.54E+06	
		4.31E+06 1.12E+10	5.54E+06 1.40E+10	2.50E+01

N/A - Not Applicable

TABLE 2B-1

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

LIQUID EFFLUENTS UNIT 1

•	CC	NTINUOUS MC	BATCH MODE		
Nuclides Released	Unit	3rd Quarter	4th Quarter	3rd Quarter	4th Quarter
Strontium-89	Ci				
Strontium-90	Ci				
Cesium-134	Ci			1.83E-02	7.66E-03
Cesium-137	Ci			2.78E-02	9.64E-03
Iodine-131	Ci			2.45E-02	2.41E-03
Iodine-132	Ci				4.25E-04
Iodine-133	Ci			5.10E-03	6.13E-05
Iodine-134	Ci				
Cobalt-57	Ci			7.01E-05	2.18E-04
Cobalt-58	Ci			8.02E-02	6.55E-01
Cobalt-60	Ci			1.61E-01	3.32E-01
Ruthenium-103	Ci				7.11E-04
Manganese-54	Ci			3.41E-02	4.55E-02
omium-51	Ci				7.76E-02
-113	Ci				2.20E-04
Zirconium-95	Ci				3.04E-03
Molybdenum-99	Ci			4.03E-05	9.98E-04
Barium-140	Ci				
Lanthanum-140	Ci		· · · · · · · · · · · · · · · · · · ·	3.66E-04	6.88E-03
Cerium-139	Ci				
Tellurium-132	Ci				6.52E-04
Niobium-97	Ci				9.51E-03
Niobium-95	Ci			7.40E-04	1.03E-02
Antimony-124	Ci				5.12E-04
Antimony-125	Ci			4.48E-04	3.19E-03
Tritium	Ci			3.70E+02	1.43E+02
Iron-59	Ci				6.13E-03
Sodium-24	Ci			7.85E-04	
Silver-110m	Ci			4.15E-04	3.46E-03
Total for period (above)					
excluding H3	Ci			3.54E-01	1.18E+00
Xenon-133m	Ci			7.86E-03	
Xenon-133	Ci			1.25E+00	1.89E-01
Xenon-135	Ci			3.16E-02	2.88E-03
Krypton-85m	Ci			6.55E-05	
Argon-41	Ci				



TABLE 2B-2

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT (1982)

LIQUID EFFLUENTS UNIT 2

CONTI		NTINUOUS MO	DE	BATCH MODE	Ξ
Nuclides Released	Unit	3rd Quarter	4th Quarter	3rd Quarter	4th Quarter
Strontium-89	Ci		· · · · · · · · · · · · · · · · · · ·		
Strontium-90	Ci				
Cesium-134	Ci	 		2.19E-02	1.22E-02
Cesium-137	Ci	 		3.10E-02	1.71E-02
Iodine-131	Ci			1.88E-02	6.70E-03
Iodine-132	Ci				
Iodine-133	Ci			4.74E-03	8.52E-04
Cobalt-58	Ci			8.76E-02	6.24E-01
Cobalt-60	Ci			1.34E-01	3.31E-01
Cadmium-109	Ci	·			
Manganese-54	Ci			3.15E-02	4.30E-02
Chromium-51	Ci			4.95E-04	5.72E-02
Molybdenum-99	Ci			4.32E-05	1.30E-04
Zirconium-95	Ci			1.85E-04	3.62E-03
1113	Ci				8.18E-05
i um-140	Ci				
Lanthanum-140	Ci			7.79E-04	5.95E-03
Cesium-136	Ci			5.76E-04	
Niobium-97	Ci				1.08E-02
Niobium-95	Ci			6.72E-04	7.95E-03
Antimony-124	Ci				7.13E-04
Antimony-125	Ci			9.62E-04	2.56E-03
Tritium	Ci			2.33E+02	5.97E+01
Iron-59	Ci				4.52E-03
Sodium-24	Ci			3.37E-04	
Silver 110m	Ci			·	3.92E-03
Tellerium-132	Ci				
Total for period (above)					
excluding H3	Ci			3.34E-01	1.13E+00
Xenon-133m	Ci			7.35E-03	1.13E+00
Xenon-133	Ci			1.35E+00	2.25E-01
Xenon-135	Ci			2.60E-02	4.45E-03
Krypton-85m	Ci				8.05E-05
Argon-41	Ci				

TABLE 3

EFFLUENT AND WASTE DISPOSAL SEMIANNUAL REPORT 1982 JULY - DECEMBER 1982 UNITS 1 AND 2 SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

SOLID WASTE SHIPPED OFFSITE FOR BURIAL OR DISPOSAL (Not irradiated fuel)

1.	Тур	e of waste	Units	6-month Period	Est. Total Error, %
	a.	Spent resins, filters sludges, evaporator bottoms	m3 Ci	1.75E+02 1.05E+02	1.50E+01
	b.	Dry compressible waste, contaminated equip.	m3 Ci	7.63E+02 3.58E+00	1.50E+01
	c.	Irradiated components, control rods,	m3 Ci	0.00E+00 0.00E+00	-
	đ.	Others (describe)	m3 Ci	0.00E+00 0.00E+00	

Estimate of major nuclide composition (by type of waste)

a.	Cobalt - 58	79.9%	8.4E+01
	Cobalt - 60	12.4%	1.3E+01
	Manganese - 54	3.0%	3.2E+00
	Cesium - 134	2.5%	2.6E+00
	Cesium - 137	2.2%	2.3E+00
b.	Cobalt - 58	79.9%	2.90E+00
	Cobalt - 60	12.4%	0.44E+00
	Manganese - 54	3.0%	0.11E+00
	Cesium - 134	2.5%	0.09E+00
	Cesium - 137	2.2%	0.08E+00
			·
			

3. Solid Waste Disposition

Number of Shipments	Mode of Transportation	Destination
37	Truck	Barnwell, South Carolina
13	Truck	Hanford, Wash.

RADIATED FUEL SHIPMENTS (Disposition)

Number of Shipments	Mode of Transportation	Destination
None	N/A	N/A

TABLE 4A-1

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates July 1 September 30, 1982
- 2. Type of release (Gas)
- 3. Number of releases during the 3rd Quarter 1.5E+01
- 4. Total time duration for all releases of type listed above 5.74E+03 minutes
- 5. Maximum duration for releases of type listed above $\frac{1.56E+03}{minutes}$
- 6. Average duration for all releases of type listed above 3.82E+02 minutes
- 7. Minimum duration for release of type listed above $\frac{6.00E+01}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4A-2

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates July 1 September 30, 1982
- 2. Type of release (Gas)
- 3. Number of releases during the 3rd Quarter 9.00E+0
- 4. Total time duration for all releases of type listed above 1.42E+03 minutes
- 5. Maximum duration for releases of type listed above $\frac{3.10E+02}{minutes}$
- 6. Average duration for all releases of type listed above 1.58E+02 minutes
- 7. Minimum duration for release of type listed above $\frac{1.12E+02}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4A-1 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- Dates October 1 December 31, 1982
- Type of release (Gas)
- 3. Number of releases during the 4th Quarter 1.5E+01
- 4. Total time duration for all releases of type listed above 3.92E+03 minutes
- 5. Maximum duration for releases of type listed above 1.13E+03 minutes
- 6. Average duration for all releases of type listed above 2.61E+02 minutes
- 7. Minimum duration for release of type listed above $\frac{6.50E+01}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4A-2 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates October 1 December 31, 1982
- 2. Type of release (Gas)
- 3. Number of releases during the 4th Quarter 5.0E+00
- 4. Total time duration for all releases of type listed above $\frac{5.30E+02}{minutes}$
- 5. Maximum duration for releases of type listed above 1.10E+02 minutes
- 6. Average duration for all releases of type listed above 1.06E+02 minutes
- 7. Minimum duration for release of type listed above 1.02E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. N/A

TABLE 4B-1

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates July 1 September 30, 1982
- 2. Type of release (Liquid)
- 3. Number of releases during the 3rd Quarter 7.90+01
- 4. Total time duration for all releases of type listed above $\frac{1.63E+04}{\text{minutes}}$
- 5. Maximum duration for releases of type listed above $\frac{4.33E+02}{minutes}$
- 6. Average duration for all releases of type listed above 2.07E+02 minutes
- 7. Minimum duration for release of type listed above $\frac{1.65E+02}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. $\frac{2.15E+05}{qpm}$

TABLE 4B-2

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates July 1 September 30, 1982
- 2. Type of release (Liquid)
- 3. Number of releases during the 3rd Quarter 6.80+01
- 4. Total time duration for all releases of type listed above $\frac{1.37E+04}{minutes}$
- 5. Maximum duration for releases of type listed above $\frac{3.44E+02}{minutes}$
- 6. Average duration for all releases of type listed above $\frac{2.02E+02}{\text{minutes}}$
- 7. Minimum duration for release of type listed above 1.65E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release. $\frac{2.15E+05}{gpm}$

TABLE 4B-1 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 1

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- Dates October 1 December 31, 1982
- Type of release (Liquid)
- 3. Number of releases during the 4th Quarter 7.90E+01
- 4. Total time duration for all releases of type listed above 1.63E+04 minutes
- 5. Maximum duration for releases of type listed above $\frac{8.18E+02}{minutes}$
- 6. Average duration for all releases of type listed above $\frac{2.06E+02}{\text{minutes}}$
- 7. Minimum duration for release of type listed above $\frac{1.36E+02}{minutes}$
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release $\frac{2.22E+05}{gpm}$

TABLE 4B-2 (Cont'd)

SALEM NUCLEAR GENERATING STATION (1982) UNIT 2

SUMMARY SHEET FOR RADIOACTIVE EFFLUENTS RELEASED IN A BATCH MODE

- 1. Dates October 1 December 31, 1982
- Type of release (Liquid)
- 3. Number of releases during the 4th Quarter 8.6E+01
- 4. Total time duration for all releases of type listed above 1.78E+04
 minutes
- 5. Maximum duration for releases of type listed above $\frac{4.23E+02}{minutes}$
- 6. Average duration for all releases of type listed above $\frac{2.07E+02}{\text{minutes}}$
- 7. Minimum duration for release of type listed above 1.65E+02 minutes
- 8. For liquid batch releases only, provide the average stream flow (dilution flow) during the period of release $\frac{2.09E+05}{gpm}$

ARTIFICIAL ISLAND 7/82-9/8		7/82-9/82		JOINT	DISTRI	DISTRIBUTION OF WIND DIRECTION AND SPEED LOCATION 300FT						DEG C (300-		LAPSE RATE LE-1.9 CLASS A		
		1-3		4=7		SPEEDS (1	(I/HR)	13-18		•	9-24		2 5 PLUS	SUM	PERCENT	
		1-3				0-15		13010		•				- '		
DIRECTION	SUM	PERCENT	SUM	PERCENT	នបអ	PERCENT	នប្រក	PERCENT	នបូរ	H PER	CENT	SUM	PERCENT			
N	o	0.0	0	0.0	0	0.0	0	0.0	(0	0.0	0	0.0	0	0.0	
NNE	ő		ō	0.0	0		. 0		(ם ·	0.0	0	0.0	0	.0.0	
NE	ō		ō	0.0	ō	0.0	0		(3	0.0	0	0.0	· O	0.0	
ENE	Ô		ŏ	0.0	ā		0			0	0.0	0	0.0	0	0.0	
E	ò	~	ŏ	0.0	ō	0.0	0		1	Ö	0.0	0		0	0.0	
ESE	ŏ		ŏ	0.0	ā		0			Ö	0.0	0		0	0.0	
SE	ő		Ŏ	0.0	٥		0			0	0.0	0		0	0.0	
SSE	ő		á	0.0	ō		0		(0	0.0	0		0	0.0	
Š	ő		ñ	0.0	ō		0		(Ď	0.0	0		0	0.0	
รรพ	0		ñ	0.0	ō		0		(5	0.0	0	0.0	0	0.0	
SW	0		ő	0.0	ŏ	0.0	0		. (- 0	0.0	ō	0.0	0	0.0	
WSW	ő	0.0	ŏ	0.0	õ	0.0	ō	0.0	(0	0.0	Q	0.0	0	0.0	
	ŏ	0.0	ñ	0.0	0	0.0	0		í	0	0.0	0	0.0	0	0.0	
MNM	ő	0.0	ŏ	0.0	ō	0.0	ō		Ċ	5	0.0	ō	0.0	0	0.0	
NW	ő	0.0	ŏ	0.0	ō		0			0	0.0	0		0	0.0	
NNM	ō		ŏ	0.0	ō		0		Ć	•	0,0	0		0	0.0	
	0	0.0	0	0.0	o	0.0	0	0.0		D	0.0	0	0.0	0	0.0	

MEAN WIND SPEED 0.0 CALM HOURS 0 PERCENT CALM 0.0 MISSING 0

TABLE 5
PAGE 1 of 8

ARTIFICIAL	ISLAND	7/82-9/82	JOINT DISTRIBUTION OF WIND DIRECTION AND SPEED LOCATION 300FT								DEG C	/100M 30FT)	LAPSE RATE	
		•				SPEEDS (MI	/HR)					- F D. 118	ellu	BERGENT
		1 = 3		4-7		8-12		13-18		19-24		25 PLUS	SUM	PERCENT
OIRECTION	SUM	PERCENT	SUM	PERCENT	SUM	PERCENT	ន ប្រអ	PERCENT	នបូម	PERCENT	3 U4	PERCENT		
N	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
NNE	ñ		ă	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
NE	0		ŏ	0.0	0	0.0	0		0	0.0	0	0.0	0	0.0
EN E	ő	- •	ō	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
E	Ŏ	• •	ā	0.0	. 0	0.0	0		0	0.0	0	0.0	0	0.0
ESE	ő		ŏ	0.0	0	0.0	0		0	0.0	0	0.0	0	0.0
SE	0	•	ō	0.0	0	0.0	. 0		1	.0	0	0.0	1	.0
SSE	ŏ		õ	0.0	2	. 1	0		0	0.0	0	0.0	2	1.
S	ŏ		Ó	0.0	0	0.0	0		0	0.0	0		0	0.0
รรพ	ō		Ŏ	0.0	1	.0	0		0	0.0	0	0.0	1	, o
SW	ő		Š	. 1	1	.0	0	0.0	0	0.0	0	0.0	3	. 1
พรพ	ă		õ	0.0	1	• 0	Q		0	0.0	0		1	.0
W	ā	_	Ó	0.0	0	0.0	3	. 1	0		0		3	. 1
WNW	ō		ò	0.0	0	0.0	0	0.0	0		0		Ō	0.0
NW	·ò		Ó	0.0	0		0	0.0	0		0	0.0	0	0.0
Мии	0		0		0		0	0.0	0	0.0	0	0 . 0	0	0.0
	0	0.0	2	. 1	5	.2	3	. 1	1	•0	0	0.0	11	,5

MEAN WIND SPEED 12.1
CALM HOURS 0
PERCENT CALM 0.0
MISSING 0

TABLE 5
PAGE 2 of 8

ARTIFICIAL	ISLAND	7/82-9/82		JOINT	DISTRI	BUTION OF LOCA	WINO D ATION 3	IRECTION A	AND SPE	ED .	DEG C	/100M 30FT)	LAPSE RATE	
						SPEEDS (M)	(/HR)							
		1 = 3		4 = 7		8-12		13-18		19-24		25 PLUS	SUM	PERCENT
DIRECTION	5 UH	PERCENT	SUM	PERCENT	SUM	PERCENT	вин	PERCENT	нив	PERCENT	зин	PERCENT		
N	0	0.0	0	0.0	0	0.0	1	.0	0	0.0	0	0.0	1	.0
NNE	0	0.0	Ω	0.0	0	0.0	•		0	0.0	0	0.0	0	0.0
ΝE	0		. 0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
ENE	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
E	0	0.0	0	0.0	0	0.0	0	0.0	. 0	0.0	0	0.0	0	0.0
· ESE	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
SE	0	0.0	. 0	0.0	3	.1	1	.0	4	ž	0	0,0	6	.4
SSE	0	0.0	0	0.0	4	, a	5	.1	. 0	0.0	0	0.0	6	. 3
5	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
SSW	0	0.0	2	.1	1	.0	0	0.0	0	0.0	0	0.0	3	. 1
SW	0	0.0	ž	. 1	Ō	0.0	0	0.0	1	.0	0	0.0	3	.1
WSW	0	0.0	1	.0	3	. 1	1	.0	Ó	0.0	0	0.0	5	.2
W	0	0.0	ō	0.0	0	0.0	1	.0	2	.1	0	0.0	3	. 1
MNM	0	0.0	0	0.0	0	0.0	0	0.0	n	0.0	0	0.0	0	0.0
NW	Ō	0.0	0	0.0	0	0.0	٥	0.0	0	0.0	. 0	0.0	0	0.0
NNW	0	0.0	0	0.0	0		1	.0	ŋ		0	0.0	1	•0
	0	0.0	5	• 5	11	.5	7	•3	7	.3	0	0.0	30	1.5
MEAN WIND S CALM HOURS PERCENT CAL MISSING		12.9					·							

ARTIFICIAL	ISLAND	7/82-9/82		THIOL	DISTRI	BUTION OF LOC	D ONIW E MOITA:	IRECTION OOFT	AND SPE	ED	DEG C.		LAPSE RATE	
		. ~				SPEEDS (M	I/HR)	17.40	•	10-24	٠	25 PLUS	SUM	PERCENT
		1 - 3		4-7		8-12		13-18		19-24		23 7603	3411	PERCENT
DIRECTION	5 UM	PERCENT	รบห	PERCENT	รบห	PERCENT	ន ប្រអ	PERCENT	SUM	PERCENT	SUM	PERCENT		
N	1	•0	11	. 5	28	1.4	20	1.0	5	. 2	0	0.0	65	3.2
NNE	0	0.0	9	. 4	21	1.0	19	, 9	1	.0	0	0.0	50	2,5
NE	2	1	4	. 2	13	. 6	18	. 9	0	0.0	0	0.0	37	1.6
ENE	ā	, 1	6	. 3	7	. 3	5	. 2	0	0.0	0	0.0	20	1.0
Ε	0	0.0	7	. 3	3	. 1	0	0.0	0	0.0	0	0.0	10	. 5
ESE	n	0.0	Ó	0.0	0		2	.1	0	0.0	0	0.0	2	1
ŞE	0	0.0	6	. 3	4		37	1.8	18	. 9	2	. 1	67	3.3
SSE	5	. 2	15	1.0	16		47	2.3	13	. 6	0	0.0	101	5.0
S	3	. 1	21	1.0	13	. 6	26 22 25	1,3	9	. 4	2	. 1	74	3.7
SSW	1	ō	17	. 8	21 30	1.0	22	1.1	8	. 4	0	0.0	69	3.4 '
SW	0	0.0	30	1,5	30	1.5	25	1.2	5	. 2	0	0.0	90	. 4.5
WSW	0	0.0	15	, 7	55 5 <i>5</i>	1.1	10 22	. 5	5	. 2	0	0.0	52	5.6
W	5	. 1	6	. 3	22	1.1	22	1.1	9	. 4	5	.1	63	3.1
พพพ์	0	0.0	3	. 1	20	1.0	10	.5	0	0.0	5	. 1	35	1.7
NM	1	.0	13	. 6	13	. 6	16	. 8	. 0	0.0	ı	• 0	44	5.5
иим	0	0.0	8	. 4	31	1.5	12	.6	n	0.0	0	0.0	51	2.5
	17	. 8	177	8.8	264	13.2	591	14.5	72	3,6	9	. 4	830	41.4

MEAN WIND SPEED 11.8
CALM HOURS 0
PERCENT CALM 0.0
MISSING 63

TABLE 5
PAGE 4 of 8

ART	[FI	CI	۱L ا	SL	AND	7/	82-	91	82
-----	-----	----	------	----	-----	----	-----	----	----

JOINT DISTRIBUTION OF WIND DIRECTION AND SPEED

LAPSE RATE LOCATION BOOFT DEG C/100M -0.4/ 1.5 CLASS E (300-30FT) SPEEDS (MI/HR) 4-7 19-24 25 PLUS SUM PERCENT 1-3 8-12 13-18 SUM PERCENT SUM PERCENT SUM PERCENT DIRECTION SUM PERCENT SUM PERCENT SUM PERCENT N 76 3.5 13 20 50 1.0 11 1.0 • 5 59 2.9 NNE 20 1.0 27 .0 0.0 1.3 23 27 0.0 69 3.4 ΝE 10 1.1 1.3 32 ENE 1.6 5 . 2 13 . 6 . 3 39 1.9 Ε 16 . 8 0.0 0.0 ESE 4 . 2 16 . 8 . 2 . 3 SE 21 1.0 46 2.3 .0 . 4 29 SSE 1.4 23 77 3.8 10 1.1 4 • 0 S 4 11 1.4 85 16 91 4.5 1.4 SSW 0 9 23 63 27 1,3 0.0 122 6.1 1.1 3.1 . 8 3 W 14 33 37 0.0 101 5.0 1.6 1.8 16 WSW 13 24 48 2.4 1.2 1 3.2 14 23 1.1 18 0.0 64 . 9 .0 WNW 39 1.9 8 50 1.0 10 , 5 0.0 0.0 NW 7 24 1.2 23 68 3.4 . 1 1.1 2.5 3 NNW 11 . 5 15 . 7 17 .0 . 8

540

17.0

127

6.3

23

1.1

997

49.8

MEAN WIND SPEED 12.7 CALM HOURS PERCENT CALM .0 MISSING 38

39

1.9

154

7 . 7

314

15.7

TABLE 5

PAGE 5 of 8

ARTIFICIAL	ISLAND	7/82-9/82		TNIOL	DISTRI	BUTION	OF WIN	10 0; 30 30	IRECTION AND DOFT	SPE	ED	DEG C.		LAPSE RATE 1.6 / 4.0	CLASS F
		1+3		4 = 7		SPEED 8.	S(MI/HR 12	ij	13-18		19-24		25 PLUS	SUM	PERCENT
DIRECTION	SUM	PERCENT	aum	PERCENT	SUM	PERCE	NT	SUM	PERCENT	SUM	PERCENT	SUM	PERCENT		
2 2 2 8 8 8 2 2 2 2 2 2 2 2 2 2 2 3 3 3 3	000000000000000000000000000000000000000	0.0	100133200114100110001	0.0	10 23 20 00 44 55 11 10 00 22 52	0	511100220001212	9 19 4 2 0 1 0 3 1 0 0 3 4 0 0 8	.4 .7 .2 .1 0.0 0.0 0.0 0.0 0.0 0.0 0.0	131100000000000000000000000000000000000	0.0000000000000000000000000000000000000	000000000000000000000000000000000000000		21 20 8 23 5 13 5 6 2 4 10 5 4	1.0
MEAN WIND S	7 PEED	.3	17	. 8	41	Ş	.0	50	2.5	16	. 8	3	., •1	134	6.7
CALM HOURS PERCENT CAL MISSING		0.0													

TABLE 5.

PAGE 6 of 8

ARTIFICIAL	ISLAND	7/82-9/82		JOINT	DISTRI	BUTION OF LO	F WIND D CATION 3	IRECTION OOFT	AND SPE	ED	DEG C		LAPSE RATE	CLASS G
						SPEEDS (HI/HR)						6114	2525117
		1 = 3		4-7		8-12		13-18	•	19-24		S2 PLUS	SUM	PERCENT
DIRECTION	ЗЦМ	PERCENT	នបអ	PERCENT	នមម	PERCENT	នបូម	PERCENT	ธบฺ	PERCENT	SUM	PERCENT		
N	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0,0	0	0.0
NNE	0	0.0	0	0.0	0		0		0		0	0.0	0	0.0
ΝE	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
ENE	0	0.0	0	0.0	0	0.0	0	0.0	0		٥	0.0	0	0.0
Ε	0	0.0	0	0.0	0	0.0	0	0.0	0		0		0	0.0
ESE	O	0.0	0	0.0	0		0	0.0	0		0	0.0	0	0.0
SE	0	0.0	0	0.0	0	0.0	0		0		0		0	0.0
SSE	0	0.0	0	0.0	0		0	0.0	0		0		0	0.0
S	0	0.0	0	0,0	0	0.0	0		0	0.0	0	0.0	0	0.0
SSW	0	0.0	0	0.0	0		0	0.0	0		0	0.0	0	0.0
3 W	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
WSW	0	0.0	0	0.0	0		0		0	0.0	0		0	0.0
W	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
WNW	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
ИМ	0	0.0	0	0.0	0	- •	0		0		.0	0.0	0	0.0
МИМ	0	0.0	0	0.0	0	0.0	0	0.0	0	0 •0	0	0.0	0	0.0
	0	0.0	0	0.0	0	0.0	o	0.0	o	0.0	0	0.0	0	0.0

MEAN WIND SPEED 0.0 CALM HOURS 0 PERCENT CALM 0.0 MISSING 0

a species se

TABLE 5
PAGE 7 of 8

ARTIFICIAL	ISLAND 7	/82 - 9/82		JOINT	DISTRI	BUTION OF LOCA	WIND DIF TION 300	RECTION A	IND SPEE		DEG C/1 (300-30		LAPSE RATE	LL STABILITI	ES
		1-3		4-7		SPEEDS (MI 8-12	/HR)	13-18		19-24	a	5 PLUS	SUM	PÉRCENT	
DIRECTION	SUM P	ERCENT	9UH	PERCENT	SUM	PERCENT	SUM F	PERCENT	នួក	PERCENT	SUM P	ERCENT			
N N N N N N N N N N N N N N N N N N N	5 6 2 4 1 1 5 7 2 1 3 6 1 3 1	.2 .1 .2 .1 .2 .7 .3 .1	234544445388991110:	1.1 .7 .7 .7 1.2 .2 .7 1.7 1.6 1.4 2.4 1.4	51392 142637444759 1447590	2.5 2.1 1.9 1.6 2.3 2.3 2.3 2.3 2.9	50 61 49 13 7 47 75 62 38 48 29 38	2.5 2.4 6 2.3 2.7 2.7 2.1 2.4 1.9 2.4	26 10 7 0 29 16 27 23 6 19 0 11	1.3 .2 .5 .5 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0	80002443300244	0.00 0.00 0.11 0.00 1.12 0.01	163 129 115 60 91 27 129 168 201 199 110 143 79	8.1 6.4 5.7 3.0 2.5 1.0 6.3 9.9 10.0 9.9 5.5 7.1 3.9	
NNW	63	3.1	21 355	1.0	50 635	2.5 31.7	691	34.5	253	11,1	35 MI	1.7 951NG H	2002	100.0	

MEAN WIND SPEED 12.3

TOTAL NUMBER OF CALM HOURS 1 PERCENT .0

TABLE 5

PAGE 8 of 8

ARTIFICIAL	ISLAND	10/82-12/82		JOINT	DISTRI	FO BUTION O	F WIND O	IRECTION OOFT	AND SPE	EO	DEG C (300-	/100M 30FT)	LAPSE RATE	CLASS A
				n •		SPEEDS (47.44				5 DI 118	SUM	PERCENT
		1-3		4-7		8-12		13-18		19-24		SS PLUS	3UM	PENGENI
DIRECTION	SUM	PERCENT	SUM	PERCENT	SUM	PERCENT	SUP	PERCENT	SUM	PERCENT	SUM	PERCENT		
N	0	0.0	0	0.0	0	0.0	ď	0.0	0	0.0	0	0.0	0	0.0
NNE	0	0.0	0	0,0	. 0	0.0	0		0		0	0.0	0	0.0
NE	0	0.0	0	0.0	0	0.0			ā		Ō	0.0	. 0	0.0
ENÈ	0	0.0	٥	0.0	0	. 0.0		0.0	0		0	0.0	0	0.0
Ε	0	0.0	0	0.0	0	0.0		0.0	0		0	0.0	0	0.0
ESE	0	0.0	0	0.0	0	0.0			0		. 0	0.0	0	0.0
ESE . SE	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0	0	0.0
. 5 5£	0	n.0	0	0.0	0	0.0			0		0	0.0	0	0.0
S	0	0.0	0	0.0	0	0.0			.0		0	0.0	O	0.0
SSW	0	ດູ້ດ	0	0.0	0	0.0	0		0	0.0	0	0.0	0	0.0
3 w	0	0.0	0	0.0	0	0.0		0.0	0	0,0	0	0.0	0	0.0
WSW	0	0.0	0	0.0	0	0.0	0		0		. 0	0.0	0	0.0
W	0	0.0	0	0.0	0	0.0			. 0	0.0	0	0.0	0	0.0
MNM	0	0.0	0	0.0	1	. 1	a	0.0	0		. 0	0.0	1	. 1
NW	0	0.0	0	0,0	1	.1	2	1	0	0.0	0	0.0	3	.2 .1.
ийм	0	0.0	0	0.0	0	0.0	C	0.0	. 5	.1	0	0.0	5	, 1 .
	o	0.0	0	0.0	2	.1	a	.1	2	.1	0	0.0	6	. 3

MEAN WIND SPEED 15.2 CALM HOURS 0 PERCENT CALM 0.0 MISSING 0

TABLE 6
PAGE 1 of 8

ARTIFICIAL ISLA	58/51-58/01 OF
-----------------	----------------

JOINT DISTRIBUTION OF WIND DIRECTION AND SPEED LOCATION 300FT

DEG C/100M (300=30FT) LAPSE RATE -1.6/ -1.7 CLASS 8

					S	PEEDS (MI	/HR)							
		1 = 3		4-7		8-12		13-18		19-24	25	PLUS	SUM	PERCENT
DIRECTION	នប្រក	PERCENT	SUM #	PERCENT	SUM P	ERCENT	SUM PE	RCENT	Эцм ре	RCENT	SUM PE		V =11	
N	000000000000000		000000000000000000000000000000000000000	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	000000000000000000000000000000000000000	0.0	2000000000000		00000000000000		00000000000000000		000011100011211	0.0
иим	ŏ	0.0	ő	0.0	Ŏ.	0.0	Õ	0.0	ò	0.0	ŏ	0.0	ō	0.0
	0	0.0	3	• 5	4	, 2	4	• 5	1	.1	0	0.0	. 12	.7

MEAN WIND SPEED 11.8
CALM HOURS 0
PERCENT CALM 0.0
MISSING 0

TABLE 6
PAGE 2 of 8

ARTIFICIAL	ISLAND	10/82-12/82		TNIOL	DISTRI	BUTION OF Loc	UNIH NOITA	DIR 300	ECTION AND	BPEE		DEG CA	/100M BOFT)	LAPSE RATE -1.6/ -1.5	CLASS
		1 = 3		4-7		SPEEDS(M			13-18		19-24		25 PLUS	SUM	PERCENT
DIRECTION	ЗИМ	PERCENT	SUM	PERCENT	SUM	PERCENT	8	ин Р	ERCENT	8UM	PERCENT	SUM	PERCENT		
N	0	0.0	0	-	1	.1		2	, 1	0	0.0	. 0	0.0	3	• 2
NNE	0	0.0	1	. 1	0	0.0		0	0.0	0	0.0	0	0.0	1	
NE Ene	0	0.0	0	0.0	0	0.0		0	0.0	0	0.0	0	0.0	0	.1 0.0 0.0
ENE	0	0.0 0.0	0	•	0	0.0		0	0.0	0	0.0	0	0.0	0	0.0
ESE	ŏ	0.0	ő		0	0.0	-	ŏ	0.0 0.0	ŏ	0.0	0	0.0	0	0.0
SE	0	0.0	ō		Ô	0.0		ĭ	.1	Ö	0.0	0	0.0	i	.1
SSE	0	0.0	0		0	0.0		Ō	0.0	ō	0.0	. 0	0.0	Ö	0.0
· S	0	0.0	0	• •	0	0.0		0	0.0	0	0.0	0	0.0	0	0.0
SSW	0	0.0	0	0.0	0	0.0		0	0.0	٥	0.0	0	0.0	0	0.0
We.	0	0.0	0	0.0	0	0.0		1	. 1	.0	0.0	0	0.0	1	• 1
W S W	0	0.0	0	0.0	1	.1		0	0.0	5	2.1	1	• 1	4	.2
WNW	0	0.0 0.0	1	0.0	0	0.0	-	2	0.0	0	0.0	0	0.0	1	•1
NW	0	0.0	0		0	0.0		1	•1 •1	3	0.0	0	0.0 0.0	u u	
NNk	ō	0.0	Ö		ŏ			3	.5	Õ	0.0	ő	0.0	3	.2
	0	0.0	2	.1	2	.1		10	.6	5	. 3	. 1	.1	20	1.1
MEAN WIND S		15.8	_	••	-	• •	,	10	• 6	7	• 3	1	• 1	eu	1.1
CALM HOURS PERCENT CAL MISSING	, М	0,0											,		

TABLE 6

PAGE 3 of 8

ARTIFICIAL	ISLAND	10/82-12/82
------------	--------	-------------

JUINT DISTRIBUTION OF WIND DIRECTION AND SPEED LOCATION 300FT

DEG C/100M (300-30FT) LAPSE RATE -1.4/ -0.5 CLASS D

•

					SI	PEEDS (MI	/HR)	,						
		1 = 3		4-7		8-12		13-18		19-24	2	5 PLUS	នបក	PERCENT
DIRECTION	SUM P	ERCENT	SUM PE	RCENT	BUM PE	RCENT	SUM PE	ERCENT	SUM PE	ERCENT	SUH PE	RCENT		
NEE E E E E E E E E E E E E E E E E E E	0 1 1 1 1 1 0 4 1 0 1	0.0	3 4 1 1 3 11 6 7 4 4	2221212634222	15 10 12 3 3 0 6 9 12 10 7 2	8 6 7 2 2 0 3 5 7 6 4 1 5	2266 1007 918 3458	1.235.100.000.451.0000.451.000.451.000.451.0000.451.0000.451.0000.451.0000.451.0000.451.0000.451.0000.451.0000.	9 0 0 0 1 4 1 4 2 4 8	50000000000000000000000000000000000000	000000000000		523 68 218 33 415 116 28	1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0
M M M M M M M M	2 1 1	. 1 . 1	6 4 7	. 3 . 2 . 4	7 13 5	.7	9 5 8	.5	1 4 8 1 4	.8 .5 .8	8 10 4	.5 .6 .2	46 41 39	2.5 2.5
	16	. 9	73	4.1	122	6.9	111	6.3	69	3.9	25	1.4	416	23,4

MEAN WIND SPEED 13.5 CALM HOURS 0 PERCENT CALM 0.0 MISSING 77

TABLE 6

PAGE 4 of 8

ARTIFICIAL	ISLAND	10/82-12/82		JOINT	DISTRI	BUTI		C COLW E MOITA	IRECTION OOFT	AND SPE	ED .	DEG C.	/100M 30FT)	LAPSE R	TE	CLASS E
		1=3		. 4-7		SPE	EDS (M:	I/HRJ	13-18	•	19-24		25 PLUS	S	JM	PERCENT
DIRECTION	SUM	PERCENT	SUH	PERCENT	SUM	PER	ENT	ุ่งบห	PERCENT	8 U M	PERCENT	ŞUM	PERCENT			•
ZZZ ERRERBUBEZZZ ZZZ ZZZ ZZZ ZZZ ZZZ ZZZ ZZZZ ZZZ	3 1 4 4 7 0 1 0 1 1 2 4 1	2 1 2 2 0 0 1 0 0 1 0 0 1 1 1 1 1	15 17 15 16 12 18 12 7 8 5 2 5 5 3	.8 .1 .8 .7 .7 .7 .7 .5 .7 .5 .8 .8 .8 .8 .8 .8 .8 .8 .8 .8 .8 .8 .8	14 8 10 9 3 6 18 22 28 27 15 15		.8 .5 1.1 .5 .2 .3 1.0 1.2 1.6 1.5 .8 .7 .4 .9	17 23 21 9 4 2 10 18 37 43 46 7 36 40 28	1.0 1.3 2.5 2.1 6.0 2.4 2.4 2.4 2.5 1.6	26 1 16 10 0 0 1 1 9 21 20 5 3 4 35 21	1.6 .1 .9 .1 0.0 0.0 .1 .5 1.2 1.3 .2 2.0 1.2	14 11 4 0 0 0 7 11 8 2 0 1 3	.8 .2 0.0 0.0 0.0 0.0 .4 .6 .5 .1 0.0 1	1	115 148 148 148 149 149 149 149 149 149 149 149 149 149	5.1 2.5 3.5 1.6 1.7 3.4 5.0 5.7 3.3 4.6
	31	1.7	123	6.9	530	. 1	13.0	366	20.6	166	9.4	78	4.4	9	94	56.0
MEAN WIND S CALM HOURS PERCENT CAL MISSING		14.7 2 .1 235				-										

TABLE 6 PAGE 5 of 8

ARTIFICIAL	ISLAND	10/82-12/	/82	TNIOL	DISTRI	BUTION OF Loca	TION 3	IRECTION A	ND SPE	ED	DEG C/1	100M)FT)	LAPSE RATE	
						SPEEDS (HI	(/HR)			•				
		1-3		4-7		6=12		13-18		19=24	a	5 PLU8	SUM	PERCENT
DIRECTION	Sum	PERCENT	SUM	PERCENT	ន័ប្រអ	PERCENT	Зим	PERCENT	อบผ	PERCENT	SUM P	ERCENT		
N	0	0.0	5	.1	4	.2	9	.5	2	.1	•	. 1	1.6	1.0
NNE	0	0.0	Ō	0.0	5		14	. 5	Ž	i	ð	0.0	54	1:5
NE	2	• 1	1	. 1	0	0.0	2	.1	1	• 1	0	0.0	. 6	. 3
ENE	3	. 1	7	• 4	6	. 3	5	. 1	2	, • <u>1</u>	0	0.0	19	1.1
t .	Ç	0.0	1	• 1	4	• 2	0	0.0	0	0.0	. 0	0.0	2	• 3
ESE	9	0.0	1	• 1	1	• 1	0	0.0	- 0	0.0	. 0	0.0	2	• 1
SE	C	0.0	5	. 3	5	• 1	4	• <u>s</u>	. 0	0.0	. 0	0.0	11	
SSE	1	. 1	. 6	.3	7	. 4	5	. 3	3	, ž	1	.1	23	1.3
8	2	.1	5	. 3	12	• [21	1.2	6	5	0	0.0	. 46	2.6
SSW	Ç	0.0	3	2.2		• 7	18 12	1.0	17	1.0		. 3	53 33	3.0
SW	1	. 1	0	0.0	1	• 1	1 <	• •		•5	11	- 0	. 33	1.9
WSW	Ç	0.0	1	. 1	4	• 2	1	• 1	3	. • 1	0	0.0	!	. 4
*W	9	0.0	0	0.0	. 2	. 1	2	.2	1	2.1	0	0.0	•	. 3
MNM	C	0.0	3	.s	0	0.0	4	• 5	0	0.0	0	0.0		. 4
ИМ	Ç		1	. 1	1	• 1	3	.2	0	0.0	0	0.0	7	.3
NMM	C	0.0	1	.1	1	1	3	. 2	1	1	(i	0.0	6	. 3
	ė	.5	37	2.1	59	3,3	101	5.7	44	2.5	19	1,1	268	15.1

MEAN WIND SPEED 14.5 CALM HOURS 0 PERCENT CALM 0.0 MISSING 36

TABLE 6

PAGE 6 of 8

ARTIFICIAL	ISLAND	10/82-12/82		JOINT	DISTRI	BUTION (OF WIND OCATION	0 [F	RECTION AND OFT	SPE	ED.	DEG C/		LAPSE RATE GT. 4.0	CLASS G
		1 - 3		4-7		SPEEDS			13-18		19-24		25 PLU3	SUM	PERCENT
DIRECTION	Зим	PERCENT	SUM	PERCENT	SUM	PERCENT	t s	UM F	PERCENT	BUM	PERCENT	8 UM	PERCENT		
N NNE	n 0	0.0	5	.1	2	. 1		0	0.0	0	0.0	0.	0.0	4	, a
NE	0	0.0	0	0.0 0.0	0	0.0		3	.i	0	0.0	0	0.0	1 6	•1 •3
ENE	ŏ	0.0	ā	0.0		0.0		ī	.1	i		0	0.0	ž	.1
Ε	0	0.0	Ö	0.0	ĩ			ō	0.0	ŏ	0.0	ŏ	0.0	ī	. 1
ESE	0	0,0	٥	0.0	1	. 1	1	0	0.0	0	0.0	0	0.0	1	. 1
SE	0	0.0	0	0.0	0	. 0.0	0	0	0.0	0	0.0	0	0.0	0	, 0.0
SSE	0	0.0	0	0.0	1	• 1		0	0.0	1	. 1	0	0.0	2	.1
S	0	0.0	0	0.0	5	• 3	3	4	• 5	. 3	• 2	4	.2	16	. • 9
SSW	0	0.0	0	.0.0	1			15	• 7	6	.3	0	0.0	19	1.1
. SW WSW	0	0.0	0	0.0	1 0	0.0		0	.1 0.0	0	, 0.0	0	0.0	. 0	0.0
· W	0	0.0	٥	0.0	0	0.0	, n	Ö	0.0	0	0.0	0	0.0	. 0	0.0
WNW	ã	0.0	ĭ	1	ŏ	0.0		ŏ	0.0	ŏ	0.0	á	0.0	ĭ	. 1
NW	0	0.0	i	i	Ō			Ō	0.0	1	.1	Ō	0.0	ž	. 1
МИИ	0	0.0	0	0.0	0	0.0	0 .	0	0.0	0	0.0	0	0.0	0	0.0
	0	0.0	4	. s	15	. (3	22	1.2	12	.7	4	.2	57	3.8
MEAN WIND S CALM HOURS PERCENT CAN MISSING		15.5 0 0.0 19								· ·'.·					

TABLE 6 PAGE 7 of 8

ARTIFICTAL	TELANO	10/03	

JOINT DISTRIBUTION OF WIND DIRECTION AND SPEED LOCATION BOOFT

DEG C/100M LAPSE RATE (300-30FT) AL

ALL STABILITIES

DIRECTION	1=3			4 = 7	SPEEDS(MI/HR) 8-12 13-18				19-24	: 2	25 PLUS		DERAGNI	
	9 нив	PERCENT	SUM P	ERCENT	SUM P	ERCENT	Зин р	ERCENT	T SUM PERCENT		SUM PERCENT		8UM	PERCENT
NEEE E SE S S S S S S S S S S S S S S S	3 2 7 7 8 1 2 1 7 1 2 2 2 6 2 2	2 1 4 .5 .1 .1 .1 .1 .1	22 6 12 23 17 20 25 23 17 12 10 9 15 11	1.2 .7 1.3 1.0 .5 1.1 1.4 1.5 1.0	3235 247 155 136 136 131 216 131	2.0 1.3 1.4 1.6 1.0 3.8 2.0 2.9 2.7 2.0 1.3 1.3	54234 4234 4230 7643 439 439	9587212853676132 11443 2322	39 17 40 00 21 17 31 47 15 10 149 34 16	2 . 2 . 2 . 2 . 2 . 2 . 2 . 2 . 2 . 2 .	1724 0000 000 1514 1311 256	1.07 .2 0.0 0.0 0.0 0.0 0.0 0.5 .8 .8 .7 .1	169 97 75 46 17 61 119 203 142 95 152 144 97	2554.6 2.6 2.6 2.6 2.6 2.6 3.7 11.6 3.7 11.6 3.6 6.6 15.6 6.6 15.6
	55	3.1	242	13,6	434	24,5	616	34.7	299	16.8	127	7.2	1773	99.9
							•		•		M T	SSING HOUR	18 433	

MEAN WIND SPEED 14.4

TOTAL NUMBER OF CALM HOURS 2 PERCENT .

TABLE 6

PAGE 8 of 8