

Attachment 2

Proposed Technical Specifications

9801020025 971218
PDR ADOCK 05000280
P PDR

4.1 OPERATIONAL SAFETY REVIEW

Applicability

Applies to items directly related to safety limits and limiting conditions for operation.

Objective

To specify the minimum frequency and type of surveillance to be applied to unit equipment and conditions.

Specification

- A. Calibration, testing, and checking of instrumentation channels and interlocks shall be performed as detailed in Tables 4.1-1, 4.1-1A, and 4.1-2.
- B. Equipment tests shall be performed as detailed in Table 4.1-2A and as detailed below.
 - 1. In addition to the requirements of 4.0.5, each Pressurizer PORV and block valve shall be demonstrated OPERABLE by:
 - a. Performing a complete cycle of each PORV with the reactor coolant average temperature $>350^{\circ}\text{F}$ once per 18 months. |
 - b. Performing a complete cycle of the solenoid air control valve and check valves on the air accumulators in the PORV control system once per 18 months. |
 - c. Operating each block valve through one complete cycle of travel at least once per 92 days. This surveillance is not required if the block valve is closed in accordance with 3.1.6.a, b, or c.

Other channels are subject only to the "drift" errors induced within the instrumentation itself and, consequently, can tolerate longer intervals between calibration. Process systems instrumentation errors resulting from drift within the individual instruments are normally negligible.

During the interval between periodic channel tests and daily check of each channel, a comparison between redundant channels will reveal any abnormal condition resulting from a calibration shift, due to instrument drift of a single channel.

During the periodic channel test, if it is deemed necessary, the channel may be tuned to compensate for the calibration shift. However, it is not expected that this will be required at any fixed or frequent interval.

Thus, minimum calibration frequencies of once-per-day for the nuclear flux (power level) channels, and once per 18 months for the process system channels are considered acceptable.

Testing

The minimum testing frequency for those instrument channels connected to the safety system is based on an average unsafe failure rate of $2/5 \times 10^{-6}$ failure/hr per channel. This is based on operating experience at conventional and nuclear units. An unsafe failure is defined as one which negates channel operability and which, due to its nature, is revealed only when the channel is tested or when it attempts to respond to a proper signal.

The refueling water storage tank is sampled weekly for Cl^- and/or F^- contaminations. Weekly sampling is adequate to detect any inleakage of contaminated water.

The control room ventilation system is required to establish a positive differential pressure in the control room for one hour following a design basis loss-of-coolant accident using a bottled air supply as the source of air. The ability of the system to meet this requirement is tested by pressurizing the control room using the ventilation system fans and comparing the volume of air required to that stored. The test is conducted once per 18 months normally coinciding with the refueling outage of either Unit 1 or Unit 2.

TABLE 4.1-1(Continued)
MINIMUM FREQUENCIES FOR CHECK, CALIBRATIONS AND TEST OF INSTRUMENT CHANNELS

<u>Channel Description</u>	<u>Check</u>	<u>Calibrate</u>	<u>Test</u>	<u>Remarks</u>
43. Engineered Safeguards Actuation Interlocks				
a. Reactor trip, P-4	N.A.	N.A.	R	
b. Pressurizer pressure, P-11	N.A.	R	R	
c. Low, low T _{avg} , P-12	N.A.	R	R	

S - Each Shift

M - Monthly

D - Daily

P - Prior to each startup if not done within the previous week

N.A. - Not Applicable

R - Once per 18 months

Q - Every 90 effective full power days

* See Specification 4.1.D

Amendment Nos.

TABLE 4.1-2
ACCIDENT MONITORING INSTRUMENTATION SURVEILLANCE REQUIREMENTS

<u>INSTRUMENT</u>	<u>CHANNEL CHECK</u>	<u>CHANNEL FUNCTIONAL TEST</u>	<u>CHANNEL CALIBRATION</u>
1. Auxiliary Feedwater Flow Rate	P		R
2. Inadequate Core Cooling Monitor	M		R
3. PORV Position Indicator (Primary Detector)	M		R
4. PORV Position Indicator (Backup Detector)	M		R
5. PORV Block Valve Position Indicator	M		R
6. Safety Valve Position Indicator	M		R
7. Safety Valve Position Indicator (Backup Detector)	M		R
8. Containment Pressure	M		R
9. Containment Water Level (Narrow Range)	M		R
10. Containment Water Level (Wide Range)	M		R
11. Containment High Range Radiation Monitor	M	Q	R
12. Process Vent High Range Effluent Monitor	M	Q	R
13. Ventilation Vent High Range Effluent Monitor	M	Q	R
14. Main Steam High Range Radiation Monitor	M	Q	R
15. Auxiliary Feedwater Pump Turbine Exhaust Radiation Monitor	M	Q	R
16. Recirculation Spray Heat Exchanger Service Water Outlet Radiation Monitors	M	Q(1)	R

(1) Channel Functional testing shall include the associated sample pump.

M - Monthly

P - Prior to each startup if not done within the previous week

Q - Quarterly

R - Once per 18 months

Amendment Nos.

TABLE 4.1-2A
MINIMUM FREQUENCY FOR EQUIPMENT TESTS

<u>DESCRIPTION</u>	<u>TEST</u>	<u>FREQUENCY</u>	<u>FSAR SECTION REFERENCE</u>
1. Control Rod Assemblies	Rod drop times of all full length rods at hot conditions	Prior to reactor criticality: a. For all rods following each removal of the reactor vessel head b. For specially affected individual rods following any maintenance on or modification to the control rod drive system which could affect the drop time of those specific rods, and c. Once per 18 months	7
2. Control Rod Assemblies	Partial movement of all rods	Quarterly	7
3. Refueling Water Chemical Addition Tank	Functional	Once per 18 months	6
4. Pressurizer Safety Valves	Setpoint	Per TS 4.0.5	4
5. Main Steam Safety Valves	Setpoint	Per TS 4.0.5	10
6. Containment Isolation Trip	* Functional	Once per 18 months	5
7. Refueling System Interlocks	* Functional	Prior to refueling	9.12
8. Service Water System	* Functional	Once per 18 months	9.9
9. Fire Protection Pump and Power Supply	Functional	Monthly	9.10
10. Primary System Leakage	* Evaluate	Daily	4
11. Diesel Fuel Supply	* Fuel Inventory	5 days/week	8.5
12. Deleted			
13. Main Steam Line Trip Valves	Functional (Full Closure)	Before each startup (TS 4.7) The provisions of Specification 4.0.4. are not applicable.	10

Amendment Nos.

TABLE 4.1-2A(CONTINUED)
 minimum Frequency for equipment Tests

<u>DESCRIPTION</u>	<u>TEST</u>	<u>FREQUENCY</u>	<u>FSAR SECTION REFERENCE</u>
14a. Service Water System Valves in Line Supplying Recirculation Spray Heat Exchangers	Functional	Once per 18 months	9.9
b. Service Water System Valves Isolating Flow to Non-essential loads on Intake Canal Low Level Isolation	Functional	Once per 18 months	9.9
15. Control Room Ventilation System	* Ability to maintain positive pressure for 1 hour using a volume of air equivalent to or less than stored in the bottled air supply	Once per 18 months	9.13
16. Reactor Vessel Overpressure Mitigating System (except backup air supply)	Functional & Setpoint	Prior to decreasing RCS temperature below 350°F and monthly while the RCS is < 350°F and the Reactor Vessel Head is bolted	4.3
	CHANNEL CALIBRATION	Once per 18 months	
17. Reactor Vessel Overpressure Mitigating System Backup Air Supply	Setpoint	Once per 18 months	4.3
18. Power-Operated Relief Valve Control System	Functional, excluding valve actuation	Monthly	4.3
	CHANNEL CALIBRATION	Once per 18 months	

Amendment Nos.

TABLE 4.1-2A(CONTINUED)
MINIMUM FREQUENCY FOR EQUIPMENT TEST

<u>DESCRIPTION</u>	<u>TEST</u>	<u>FREQUENCY</u>	<u>UFSAR SECTION REFERENCE</u>
19. Primary Coolant System	Functional	1. Periodic leakage testing ^{(a)(b)} on each valve listed in Specification 3.1.C.7a shall be accomplished prior to entering POWER OPERATION after every time the plant is placed in COLD SHUTDOWN for refueling, after each time the plant is placed in COLD SHUTDOWN for 72 hours if testing has not been accomplished in the preceding 9 months, and prior to returning the valve to service after maintenance, repair or replacement work is performed.	
20. Containment Purge MOV Leakage	Functional	Semi-Annual (Unit at power or shutdown) if purge valves are operated during interval ^(c)	
21. Containment Hydrogen Analyzers	a. CHANNEL FUNCTIONAL TEST b. CHANNEL CALIBRATION	Once per 92 days Once per 18 months	
	1. Sample gas used: One volume percent (±0.25%) hydrogen, balance nitrogen Four volume percent (±0.25%) hydrogen, balance nitrogen		
	2. CHANNEL CALIBRATION will include startup and operation of the Heat Tracing System		
22. RCS Flow	Flow ≥ 273,000 gpm	Once per 18 months	14
23. Delete			

(a) To satisfy ALARA requirements, leakage may be measured indirectly (as from the performance of pressure indicators) if accomplished in accordance with approved procedures and supported by computations showing that the method is capable of demonstrating valve compliance with the leakage criteria.
(b) Minimum differential test pressure shall not below 150 psid.
(c) Refer to Section 4.4 for acceptance criteria.
* See Specification 4.1.D.

Amendment Nos.

TABLE 4.2-1

SECTION A. MISCELLANEOUS INSPECTIONS

<u>Item No.</u>	<u>Required Examination Area</u>	<u>Required Examination Methods</u>	<u>10-Year Interval Inspection</u>	<u>Remarks</u>
1.1	Deleted			
1.2	Low Head SIS piping located in valve pit	Visual	Non-applicable	This pipe shall be visually inspected once per 18 months.
1.3	Primary Pump Flywheel	See remarks	See remarks	Examination to be conducted in accordance with regulatory position C.4.b of regulatory guide 1.14 Rev. 1, August 1975
1.4	Low Pressure Turbine Rotor	Visual and Magnetic Particle or Dye Penetrant	See remarks	100% of blades every six operating years. Inspections are normally performed concurrent with LP turbine rotor disk and hub inspections.

Amendment Nos.

TABLE 4.2-1(continued)

SECTION B. SENSITIZED STAINLESS STEEL

<u>Item No.</u>	<u>Required Examination Area</u>	<u>Required Examination Methods</u>	<u>10-Year Interval Inspection</u>	<u>Remarks</u>
2.1.1	Class 1 circumferential, longitudinal, branch pipe connection, and socket welds	As required by T.S. 4.0.5	The welds examined by volumetric or surface techniques shall be conducted at three times the frequency required by T.S. 4.0.5	A minimum of 5% of the welds shall be examined once per 18 months. At least 75% of the total population of welds shall be examined each interval. The same welds may be selected in subsequent intervals for examination. See Note 1.
2.1.2	Class 2 circumferential, longitudinal, branch pipe connection, and socket welds	As required by T.S. 4.0.5	The welds examined by volumetric or surface techniques shall be conducted at three times the frequency required by T.S. 4.0.5	A minimum of 2.5% of the welds shall be examined once per 18 months. At least 22.5% of the total population of welds shall be examined each interval. The same welds may be selected in subsequent intervals for examination. See Note 1.
2.1.3	Class 1 and Class 2 sensitized stainless steel pieces	Visual (VT-2) as required by T.S. 4.0.5	As required by T.S. 4.0.5	In addition to the Code required examinations the affected piping shall be visually (VT-2) examined during the flushing requirements of T.S. Tables 4.1-3A and 4.1-3B.

Amendment Nos.

2. By verifying that each motor-operated valve in the recirculation spray flow paths performs satisfactorily when tested in accordance with Specification 4.0.5.
 3. At least once per 10 years, coincident with the closest refueling outage, by performing an air or smoke flow test and verifying each spray nozzle is unobstructed.
- C. Each weight-loaded check valve in the containment spray and outside containment recirculation spray subsystems shall be demonstrated OPERABLE once per 18 months by cycling the valve one complete cycle of full travel and verifying that each valve opens when the discharge line of the pump is pressurized with air and seats when a vacuum is applied.
- D. A visual inspection of the containment sump and the inside containment recirculation spray pump wells and the engineered safeguards suction inlets shall be performed once per 18 months and/or after major maintenance activities in the containment. The inspection should verify that the containment sump and pump wells are free of debris that could degrade system operation and that the sump components (i.e., trash racks, screens) are properly installed and show no sign of structural distress or excessive corrosion.

Basis

The flow testing of each containment spray pump is performed by opening the normally closed valve in the containment spray pump recirculation line returning water to the refueling water storage tank. The containment spray pump is operated and a quantity of water recirculated to the refueling water storage tank. The discharge to the tank is divided into two fractions; one for the major portion of the recirculation flow and the other to pass a small quantity of water through test nozzles which are identical with those used in the containment spray headers.

The purpose of the recirculation through the test nozzles is to assure that there are no particulate material in the refueling water storage tank small enough to pass through pump suction strainers and large enough to clog spray nozzles.

Due to the physical arrangement of the recirculation spray pumps inside the containment, it is impractical to flow-test them other than during a unit outage. Flow testing of these pumps requires the physical modification of the pump discharge piping and the erection of a temporary dike to contain recirculated water. The length of time required to setup for the test, perform the test, and then reconfigure the system for normal operation is prohibitive to performing the flow-test on even the cold shutdown frequency. Therefore, the flow-test of the inside containment recirculation spray pumps will be performed once per 18 months during a unit outage.

The inside containment recirculation spray pumps are capable of being operated dry for approximately 60 seconds without significantly overheating and/or degrading the pump bearings. During this dry pump check, it can be determined that the pump shafts are turning by rotation sensors which indicate in the Main Control Room. In addition, motor current will be compared with an established reference value to ascertain that no degradation of pump operation has occurred.

- b. Automatic start of each diesel generator, load shedding, and restoration to operation of particular vital equipment, initiated by a simulated loss of off-site power together with a simulated safety injection signal. Testing will demonstrate load shedding and load sequencing initiated by a simulated loss of off-site power following a simulated engineered safety features signal. Testing will also demonstrate that the loss of voltage and degraded voltage protection is defeated whenever the emergency diesel is the sole source of power to an emergency bus and that this protection is automatically reinstated when the diesel output breaker is opened. This test will be conducted once per 18 months to assure that the diesel generator will start within 10 sec and assume load in less than 30 sec after the engine starting signal.
- c. Availability of the fuel oil transfer system shall be verified by operating the system in conjunction with the monthly test.
- d. Each diesel generator shall be given a thorough inspection once per 18 months utilizing the manufacturer's recommendations for this class of stand-by service.

2. Acceptance Criteria

The above tests will be considered satisfactory if all applicable equipment operates as designed.

B. Fuel Oil Storage Tanks for Diesel Generators

1. A minimum fuel oil storage of 35,000 gal shall be maintained on-site to assure full power operation of one diesel generator for seven days.

C. Station Batteries

1. Tests and Frequencies

- a. The specific gravity, electrolytic temperature, cell voltage of the pilot cell in each battery, and the D.C. bus voltage of each battery shall be measured and recorded weekly.
- b. Each month the voltage of each battery cell in each battery shall be measured to the nearest 0.01 volts and recorded.
- c. Every 3 months the specific gravity of each battery cell, the temperature reading of every fifth cell, the height of electrolyte of each cell, and the amount of water added to any cell shall be measured and recorded.
- d. Twice a year, during normal operation, the battery charger shall be turned off for approximately 5 min and the battery voltage and current shall be recorded at the beginning and end of the test.
- e. Once per 18 months each battery shall be subjected to a simulated load test without battery charger. The battery voltage and current as a function of time shall be monitored.
- f. Once per 18 months connections shall be checked for tightness and anti-corrosion coating shall be applied to interconnections.

2. Acceptance Criteria

- a. Each test shall be considered satisfactory if the new data when compared to the old data indicate no signs of abuse or deterioration.

- b. The load test in (d) and (e) above shall be considered satisfactory if the batteries perform within acceptable limits as established by the manufacturers discharge characteristic curves.

D. EMERGENCY DIESEL GENERATOR BATTERIES

1. Tests and Frequencies

- a. The specific gravity, electrolytic temperature, cell voltage of the pilot cell in each battery and the D.C. bus voltage of each battery shall be measured and recorded weekly.
- b. Each month the voltage of each battery cell in each battery shall be measured to the nearest 0.01 volts and recorded.
- c. Every 3 months the specific gravity of each battery cell, the temperature reading of every fifth cell, the height of electrolyte of each cell, and the amount of water added to any cell shall be measured and recorded.
- d. Once per 18 months, each battery shall be subjected to a normal load or simulated load test without battery charger. The battery voltage and current as a function of time shall be monitored.
- e. Once per 18 months, connections shall be checked for tightness and anti-corrosion coating shall be applied to interconnections.

2. Acceptance Criteria

- a. Each test shall be considered satisfactory if the new data when compared to the old data indicate no signs of abuse or deterioration.
- b. The load test in (d) above shall be considered satisfactory if the batteries perform within acceptable limits as established by the manufacturers discharge characteristic curves.

- c. Power may be restored to any valve or breaker referenced in Specifications 4.11.C.4.a and 4.11.C.4.b for the purpose of testing or maintenance provided that not more than one valve has power restored at one time, and the testing and maintenance is completed and power removed within 24 hours.
5. Once per 18 months by:
- a. Verifying that each automatic valve capable of receiving a safety injection signal, actuates to its correct position upon receipt of a safety injection test signal. The charging and low head safety injection pumps may be immobilized for this test.
 - b. Verifying that each charging pump and safety injection pump circuit breaker actuates to its correct position upon receipt of a safety injection test signal. The charging and low head safety injection pumps may be immobilized for this test.
 - c. Verifying, by visual inspection, that each low head safety injection pump suction inlet from the containment sump is free of debris that could degrade system operation. Perform each refueling outage and/or after major maintenance activities in the containment.

Basis

Complete system tests cannot be performed when the reactor is operating because a safety injection signal causes containment isolation. The method of assuring operability of these systems is therefore to combine system tests to be performed during unit outages, with more frequent component tests, which can be performed during reactor operation.

4.12 AUXILIARY VENTILATION EXHAUST FILTER TRAINS

Applicability

Applies to the testing of safety-related air filtration systems.

Objective

To verify that leakage efficiency and iodine removal efficiency are within acceptable limits.

Specifications

A. Tests and Frequency

1. Each redundant filter train circuit shall be operated every month if it has not already been in operation.
2. Once per 18 months, the operability of the entire safety-related portion of the auxiliary ventilation system shall be demonstrated.
3. Auxiliary ventilation system exhaust fan flow rate through each filter train in the LOCA mode of operation shall be determined initially, after any structural maintenance on the HEPA filter or charcoal adsorber housings, once per 18 months, or after partial or complete replacement of the HEPA filters or charcoal adsorbers.

The procedure for determining the air flow rate shall be in accordance with Section 9 of the ACGIH Industrial Ventilation document and Section 8 of ANSI N510-1975.

4. A visual inspection of the filter train and associated components shall be conducted before each in-place air flow distribution test, DOP test, or activated charcoal adsorber leak test in accordance with the intent of Section 5 of ANSI N510-1975.

5. An air distribution test across the prefilter bank shall be performed initially and after any major modification, major repair, or maintenance of the air cleaning system affecting the filter bank flow distribution. The air distribution test shall be performed with an anemometer located at the downstream side and at the center of each carbon filter.
6. In-place cold DOP tests for HEPA filter banks shall be performed:
 - a. Initially;
 - b. Once per 18 months;
 - c. Following painting, fire, or chemical release in any ventilation zone communicating with the system;
 - d. After each complete or partial replacement of the HEPA filter cells; and
 - e. After any structural maintenance on the filter housing.

The procedure for in-place cold DOP tests shall be in accordance with ANSI N510-1975, Section 10.5 or 11.4. The flow rate during the in-place cold DOP tests shall be 36,000 CFM \pm 10 percent. The flow rate shall be determined by recording the flow meter reading in the control room.

7. In-place halogenated hydrocarbon leakage tests for the charcoal adsorber bank shall be performed:
 - a. Initially;
 - b. Once per 18 months;

- c. Following painting, fire, or chemical release in any ventilation zone communicating with the system;
- d. After each complete or partial replacement of charcoal adsorber trays; and
- e. After any structural maintenance of the filter housing.

The procedure for in-place halogenated hydrocarbon leakage tests shall be in accordance with ANSI N510-1975, Section 12.5. The flow rate during the in-place halogenated hydrocarbon leakage tests shall be 36,000 CFM \pm 10 percent. The flow rate shall be determined by recording the flow meter reading in the control room.

- 8. Laboratory analysis on in-place charcoal samples shall be performed:
 - a. Initially, whenever a new batch of charcoal is used to fill adsorbers trays;
 - b. Once per 18 months;
 - c. After 720 hours of system operation; and
 - d. Following painting, fire, or chemical release in any ventilation zone communicating with the system or after any structural maintenance on the HEPA filter or charcoal adsorber housings.

The procedure for iodine removal efficiency tests shall follow ASTM D3803. The test conditions shall be in accordance with those listed in Specification 4.12.B.7.

9. The pressure drop across the HEPA filter and adsorber banks shall be checked:
 - a. Initially;
 - b. Once per 18 months thereafter for systems maintained in a standby status and after 720 hours of system operation; and
 - c. After each complete or partial replacement of filters or adsorbers.

B. Acceptance Criteria

1. The minimum period of air flow through the filters shall be 15 minutes per month.
2. The system operability test of Specifications 4.12.A.2 shall demonstrate automatic start-up, shutdown and flow path alignment.
3. The air flow rate determined in Specification 4.12.A.3 shall be:
 - a. 36,000 cfm \pm 10 percent with system in the LOCA mode of operation.
 - b. The ventilation system shall be adjusted until the above limit is met.
4. Air distribution test across the prefilter-bank shall show uniformity of air velocity within \pm 20 percent of average velocity. The ventilation system shall be adjusted until the limit is met.

4. A review and evaluation shall be performed and documented to justify continued operation with an unacceptable snubber. If continued operation cannot be justified, the snubber shall be declared inoperable and the action requirements of Specification 3.20 shall be met.

C. Functional Tests

1. Once per 18 months, a representative sample of 10% of the total of each type snubber used in the plant shall be functionally tested using either an in-place test machine or a bench test.
2. The representative sample selected for functional testing shall include the various configurations, operating environments and the range of size and capacity of snubbers. This representative sample shall not, to the extent practicable, include those snubbers tested in a previous representative sample.
3. At least 25% of the snubbers in the representative sample shall include snubbers from the following three categories:
 - a. the first snubber away from each reactor vessel nozzle,
 - b. snubbers within 5 feet of heavy equipment (valve, pump, turbine, motor, etc),
and
 - c. snubbers within 10 feet of the discharge from a safety relief valve.

- c. Snubber release rate, where required, is within the specified range in compression and tension. For snubbers specifically required not to displace under continuous load, the ability of the snubber to withstand load without displacement shall be verified.

F. Snubber Service Life Monitoring

1. A record of the service life of each snubber, the date at which the designated service life commences, and the installation and maintenance records on which the designated service life is based shall be maintained as required by the Virginia Electric and Power Company Operational Quality Assurance Program Topical Report.
2. Concurrent with the first inservice visual inspection and at least once per 18 months thereafter, the installation and maintenance records for each snubber shall be reviewed to verify that the indicated service life has not been exceeded or will not be exceeded prior to the next scheduled snubber service life review. If the indicated service life will be exceeded prior to the next scheduled snubber service life review, the snubber service life shall be reevaluated or the snubber shall be replaced or reconditioned so as to extend its service life beyond the date of the next scheduled service life review. This reevaluation, replacement or reconditioning shall be indicated in the records.

To provide assurance of snubber functional reliability, a representative sample of the installed snubbers will be functionally tested once per 18 months. Functional testing is to be in accordance with the ASME Section XI Inservice Inspection program approved by the NRC. Observed failures of these sample snubbers shall require functional testing of additional units.

Hydraulic snubbers and mechanical snubbers may each be treated as a different entity for the above surveillance programs.

The service life of a snubber is evaluated via manufacturer input and information through consideration of the snubber service conditions and associated installation and maintenance records (newly installed snubber, seal replaced, spring replaced, in high radiation area, in high temperature area, etc...). The requirement to monitor the snubber service life is included to ensure that the snubbers periodically undergo a performance evaluation in view of their age and operating conditions. These records will provide statistical bases for future consideration of snubber service life. The requirements for the maintenance of records and the snubber service life review are not intended to affect plant operation.

4.20 CONTROL ROOM AIR FILTRATION SYSTEM

Applicability

Applies to the testing of safety-related air filtration systems of the control room and relay room.

Objective

To verify that leakage efficiency and iodine removal efficiency are within acceptable limits.

Specification

A. Tests and Frequency

1. The control room air filtration system flow rate test shall be performed:
 - a. Initially;
 - b. Once per 18 months;
 - c. Following painting, fire, or chemical release in any ventilation zone communicating with the system during system operation;
 - d. After each complete or partial replacement of the HEPA filter or charcoal adsorbers; and
 - e. After any structural maintenance the HEPA filter or charcoal adsorber housings; and
 - f. After any major modification or repair of the air cleaning system.

2. The procedure for determining the air flow rate shall be in accordance with Section 9 of the ACGIH Industrial Ventilation document and Section 8 of ANSI N510-1975. A visual inspection of the filter train and its associated components shall be conducted before each in-place airflow distribution test, DOP test, or activated charcoal adsorber leak test in accordance with the intent of Section 5 of ANSI N510-1975.
3. In-place cold DOP tests for HEPA filter banks shall be performed:
 - a. Initially;
 - b. Once per 18 months;
 - c. Following painting, fire, or chemical release in any ventilation zone communicating with the system during system operation;
 - d. After each complete or partial replacement of the HEPA filter cells; and
 - e. After any structural maintenance of the filter housing.
4. The procedure for in-place cold DOP tests shall be in accordance with ANSI N510-1975, Section 10.5 or 11.4. The flow rate during this test shall be that value determined under Specification 4. 20. A. 1 and shall be within the range specified in Specification 4. 20. B. 1.

5. In-place halogenated hydrocarbon leakage tests for the charcoal adsorber bank shall be performed:
 - a. Initially;
 - b. Once per 18 months;
 - c. Following painting, fire, or chemical release in any ventilation zone communicating with the system during system operation;
 - d. After each complete or partial replacement of charcoal adsorber trays; and
 - e. After any structural maintenance on the filter housings.
6. The procedure for in-place halogenated hydrocarbon leakage tests shall be in accordance with ANSI N510-1975 Section 12.5. The flow rate during this test shall be that value determined under Specification 4.20.A.1 and shall be within the range specified in that value determined under Specification 4. 20. B. 1.
7. Laboratory analysis on charcoal samples shall be performed:
 - a. Initially; whenever a new batch of charcoal is used to fill adsorber trays;
 - b. Once per 18 months;
 - c. After 720 hours of system operation; and
 - d. Following painting, fire, or chemical release in any ventilation zone communicating with the system during system operation.

8. The procedure for iodine removal efficiency tests shall follow ASTM D3803. The test conditions shall be in accordance with those listed in Specification 4. 20. B. 4.
9. The pressure drop across the HEPA filter and adsorber banks shall be checked:
 - a. Initially;
 - b. Once per 18 months; and
 - c. After each complete or partial replacement of filters or adsorbers.
10. Each filter train circuit shall be operated every month. Filter Train Operation shall be initiated manually from the control room.

B. Acceptance Criteria

1. Fan flow tube test shall show a flow rate through any single filter train of 1000 ± 10 percent cfm.
2. In-place cold DOP tests on HEPA filters shall show greater than or equal to 99.5 percent DOP removal. Leaking sources shall be identified, repaired and retested. Any HEPA filter found defective shall be replaced.
3. In-place halogenated hydrocarbon leakage tests on charcoal adsorber banks shall show greater than or equal to 99 percent halogenated hydrocarbon removal. Leakage sources shall be identified, repaired and retested.

Attachment 3

Significant Hazards Consideration Determination

SIGNIFICANT HAZARDS CONSIDERATION

Virginia Electric and Power Company has reviewed the requirements of 10 CFR 50.92 as they relate to the proposed Technical Specifications change for the Surry Units 1 and 2. We have determined that a significant hazards consideration is not involved as discussed below:

The proposed change to clarify refueling interval surveillance frequencies is a purely administrative change. The equipment surveillance requirements contained in Section 4 of the Surry Technical Specifications currently include inconsistent terminology when specifying surveillance testing to be performed on a refueling interval frequency. The inconsistent terminology is confusing and lends itself to potential misinterpretation with regard to verbatim compliance. Therefore, the refueling interval surveillance frequencies specified in Section 4 are being clarified to ensure system/component surveillances are consistently specified and are performed at the appropriate frequency. The proposed clarification is consistent with the specified frequency provided in Revision 1 of NUREG-1431, "Standard Technical Specifications, Westinghouse Plants," dated April 1995. In addition, minor typographical errors are also being corrected and an obsolete reference is being deleted.

In the Federal Register, Vol. 51, No. 44, dated March 6, 1986, "Rules and Regulations," the NRC provided guidance for the determination of significant hazards considerations. Under item (e) regarding examples of Technical Specifications amendments that are considered not likely to involve significant hazards consideration, the following example was listed:

- (i) A purely administrative change to technical specifications: for example, a change to achieve consistency throughout the technical specifications, correction of an error, or a change in nomenclature.

The proposed change is purely administrative in that the Technical Specifications are being revised to achieve consistency in the terminology used to identify refueling interval surveillances as "once per 18 months." The time interval to perform surveillances is not being increased, therefore, there is no effect on the equipment being tested as a result of the proposed Technical Specifications change.

Criterion 1 - Operation of Surry Units 1 and 2 in accordance with the proposed Technical Specifications change does not involve a significant increase in the probability or consequences of an accident previously evaluated.

The probability of an accident is not increased as a result of the proposed Technical Specification change since surveillance intervals are being clarified, not changed, and will continue to validate system/component availability, operability and performance during the appropriate unit mode. The proposed change is administrative in nature, therefore, station operations are not being affected. The consequences of an accident

SIGNIFICANT HAZARDS CONSIDERATION (continued)

previously evaluated are not increased since station operations are not being changed, and no physical modifications are being made to plant systems or components.

Criterion 2 - The proposed Technical Specifications change does not create the possibility of a new or different kind of accident from any accident previously evaluated.

As noted above, the proposed change is administrative in nature. A new or different type of accident is not being created since no new accident precursors are being introduced and equipment surveillances will continue to be performed as required to ensure proper system/component operation. Plant systems are not being modified, system operations are not being affected, and equipment surveillance intervals are not being increased. Consequently, the proposed change does not create the possibility of a new or different kind of accident from any accident previously evaluated.

Criterion 3 - The proposed Technical Specifications change does not involve a significant reduction in a margin of safety.

This is an administrative change. Clarification of refueling surveillance interval terminology to ensure consistency in application does not affect plant equipment performance. Surveillance intervals are not being increased, and equipment surveillance tests performed on a refueling interval frequency (i.e. once per 18 months) will continue to ensure system/component performance as assumed in the existing safety analyses. Therefore, the proposed Technical Specification change does not involve a reduction in the margin of safety.