VIRGINIA ELECTRIC AND POWER COMPANY RICHMOND. VIRGINIA 23261

July 8, 1977

Regulatory Docket File

Mr. William McDonald, Director
Office of Management Information and
Program Control
U. S. Nuclear Regulatory Commission
Washington, D. C. 20555

Serial No. 279/021974 PO&M/TAP:dgt

Docket Nos. 50-280

50-281

License Nos. DPR-32

DPR-37

Dear Mr. McDonald:

Operating information for Surry Power Station, Unit Nos. 1 and 2, for the month of June 1977 is attached.


Very truly yours,

C. M. Stallings

Vice President-Power Supply and Production Operations

Attachments

cc: Mr. Norman C. Moseley



DATE Luly 1, 1977

COMPLETED BY E. P. DeWandel

DOCKET NO. 50-280

OPERATING STATUS

1	REPORTING PERIOD: 0001 770601	THROUGH	2400 77	70630
	HOURS IN REPORTING PERIOD: 720	Inkoodii		
	CURRENTLY AUTHORIZED POWER LEVEL (MWth)	2441 MAX DEPENDAR	LE CAPACITY (MWe-	NET) 775
	LOWEST POWER LEVEL TO WHICH SPECIFICALLY R	•		
	REASONS FOR RESTRICTION (IF ANY):	LUIRICIED (II ART) (III WE	110 t /	
7.	ALABOTOR RESIMETION (II ANT).	:		•
		THIS		CUMULATIVE
		REPORTING PERIOD	YR TO DATE	TO DATE
		KEI OKIING I EKIOD	TK TO BATE	TODATE
5.	HOURS REACTOR WAS CRITICAL	720	2978.8	25,553.2
• .	REACTOR RESERVE SHUTDOWN HOURS	0	0	0
	HOURS GENERATOR ON LINE	720	2906.1	24.806.1
	UNIT RESERVE SHUTDOWN HOURS	0	0	0
	GROSS THERMAL ENERGY	· ·		
	GENERATED (MWH)	1,757,503	7,040,335	56,128,691
	GROSS ELECTRICAL ENERGY	·		
	GENERATED (MWH)	580,035	2,332,375	18,410,738
	NET ELECTRICAL ENERGY GENERATED			
•	(MWH)	551.480	2.220.065	17,463,830
	REACTOR AVAILABILITY FACTOR (1)	100%	68.6%	64.4%
	UNIT AVAILABILITY FACTOR (2)	100%	66.9%	62.6%
	UNIT CAPACITY FACTOR (3)	98.8%	66.0%	56.8%
	UNIT FORCED OUTAGE RATE (4)	0%	2.9%	20.2%
	SHUTDOWNS SCHEDULED TO BEGIN IN NEXT 6 MON	THS (STATE TYPE, DATE,	AND DURATION OF	EACH):
	Steam Generator Inspection - 11-	-19-77 - 6 weeks		
17.	F SHUT DOWN AT END OF REPORT PERIOD, ESTIM	ATED DATE OF STARTUP:	N/A	
	UNITS IN TEST STATUS (PRIOR TO COMMERCIAL OF		·	·
	· · · · · · · · · · · · · · · · · · ·			
			DATE LAS	
•			FORECAST	r ACHIEVED
		INITIAL CRITICALITY	•	
		INITIAL ELECTRICAL		•
		POWER GENERATION	<u> </u>	·
• •				• . • .
• •		COMMERCIAL OPERATION		· · · · · · · · · · · · · · · · · · ·
•	• • •	•		
/11	HOURS REA	CTOR WAS CRITICAL	00	
	REACTOR AVAILABILITY FACTOR = HOURS IN R	EPORTING PERIOD		•
(1)	HOURS GEN	ERATOR ON LINE	•	
(1)		X 1	00	•
	UNIT AVAILABILITY FACTOR = HOURS IN R	PPORTING PERIOD		
	HOURS IN R		•	
(2)	HOURS IN R. UNIT CAPACITY FACTOR NET ELECTR	RICAL POWER GENERATED	·	
(2)	HOURS IN R. UNIT CAPACITY FACTOR NET ELECTR		ET) X HOURS IN RE	PORTING PERIOD
(2)	UNIT CAPACITY FACTOR WET ELECTE MAX. DEPEN FORCED OUTAGE PATE FORCED OUTAGE PATE	RICAL POWER GENERATED		PORTING PERIOD

DOCKET NO. _50-280

UNIT _Surry #1

DATE _July 1, 1977

COMPLETED BY E. P. DeWandel

AVERAGE DAILY UNIT POWER LEVEL

MONT	TH JUNE 1977		
DAY	AVERAGE DAILY POWER LEVEL (MWe-net)	DAY	AVERAGE DAILY POWER LEVEL (MWe-net)
1	770.7	17	770.0
2	770.6	-18	765.7
3	769.7	19	765.4
4	765.3	20	765.8
· 5	752.9	21	767.2
6	766.9	22	766.5
. 7	768.2	23	767.0
: 8	769.8	24	767.9
9	769.6	25	767.4
10	772.1	26	766.1
11	771.8	27	763.4
12	770.2	28	761.9
13	767.1	29	760.0
14	745.6	30	757.4
15	768.6	31	
16	767.8		

DAILY UNIT POWER LEVEL FORM INSTRUCTIONS

On this form, list the average daily unit power level in MWe-net for each day in the reporting month. Compute to the nearest whole megawatt.

These figures will be used to plot a graph for each reporting month. Note that by using maximum dependable capacity for the net electrical rating of the unit, there may be occasions when the daily average power level exceeds the 100% line (or the restricted power level line). In such cases, the average daily unit power output sheet should be footnoted to explain the apparent anomaly.

. UNIT SHUTDOWNS

DOCKET NO. 50-280

UNIT NAME Surry #1

DATE 7-1-77

COMPLETED BY E. P. DeWande1

NO.	DATE	TYPE F-FORCED S-SCHEDULED	DURATION (HOURS)	REASON (1)	METHOD OF SHUTTING DOWN THE REACTOR (2)	CORRECTIVE ACTIONS/COMMENTS
•		THERE WERE	NO SHUTDOW	NS DURING JUNI	: , 1977	
		!				
•						(1) REASON (2) METHOD
•						A. EQUIPMENT FAILURE (EXPLAIN) B. MAINT, OR TEST C-REFUELING D-REGULATORY RESTRICTION E-OPERATOR TRAINING AND SCRAM SCRAM
•		•	,			LICENSI: EXAMINATION F-ADMINISTRATIVE G-OPERATIONAL ERROR (EXPLAIN) H-OTHER (EXPLAIN)
	•					

SUMMARY:

UNIT Surry Unit #2

DATE July 1, 1977

COMPLETED BY E. P. DeWandel

DOCKET NO. 50-281

OPERATING STATUS

1.	REPORTING PERIOD: 0001 770	601	THROUGH _	2400	770630		
	HOURS IN REPORTING LERIOD.	20					<u> </u>
2.	CURRENTLY AUTHORIZED POWER LEV	'EL (MWth) 24	41 MAX. DEPENDA	ABLE CAP	ACITY (MW	-NET)	<u>75 </u>
3.	LOWEST POWER LEVEL TO WHICH SPEC	IFICALLY RES	TRICTED (IF ANY) (MY	We-NET):			
4.	REASONS FOR RESTRICTION (IF ANY):	•	• •				
•		•		-		•	•
٠.		•	THIS	•		CUMUI	ATIVE
	• •	· RE	PORTING PERIOD	YR TO	DATE	TO D	ATE
5.	HOURS REACTOR WAS CRITICAL		<u>720</u> ,	29	15.1	_23,	
6.	REACTOR RESERVE SHUTDOWN HOURS	S _.	0	-	0		0
7.	HOURS GENERATOR ON LINE		720	28	97.6	22,	843
8.	UNIT RESERVE SHUTDOWN HOURS		0		0		_0
9.	GROSS THERMAL ENERGY			<u> </u>			•
	GENERATED (MWH)		1,754,029	<u>_6,9</u>	<u>48,76</u> 3	52,29	3,390
10.	GROSS ELECTRICAL ENERGY		•		•		
	GENERATED (MWH)		572,225	2,2	93,220	17,16	4,594
11.	NET ELECTRICAL ENERGY GENERATED	D .	5.0 170			4 6 67	,
	(MWH)		543,470		79,063	16,27	
12.	REACTOR AVAILABILITY FACTOR (1)		100%		.1%	<u>63.</u>	
13.	UNIT AVAILABILITY FACTOR (2)	·	100%		.7%	62.	
14.	UNIT CAPACITY FACTOR (3)		97.4%		.7%	57.	
15.	UNIT FORCED OUTAGE RATE (4)		0%		.3%	26.	/%
16.	SHUTDOWNS SCHEDULED TO BEGIN IN Steam Generator Inspecti	NEXT 6 MONT on and Ref	HS (STATE TYPE, DATE ueling - 8-05-7	E. AND DU	RATION OF	EACH):	·
17.	IF SHUT DOWN AT END OF REPORT PER	NOD ESTIMAT	ED DATE OF STARTUI	p.			
18.	UNITS IN TEST STATUS (PRIOR TO COM				NG:		
							. ===
	••		t .		DATE LA		ATE
		• •		•	FORECA	ST AC	HIEVED
٠.		IN	ITIAL CRITICALITY				
		IN	ITIAL ELECTRICAL				
			WER GENERATION				· ·
•			-				
		CO	MMERCIAL OPERATIO	N			
-		•	•				
/15	DEACTOR ANALIABILITY FACTOR	HOURS REACT	OR WAS CRITICAL	v 100		:	
(1)	REACTOR AVAILABILITY FACTOR = -		ORTING PERIOD	X 100			
		HOURS GENER	ATOR ON LINE		•		
(2)	UNIT AVAILABILITY FACTOR = -		ORTING PERIOD	X 100	•	•	
••							• . •
(3)	UNIT CAPACITY FACTOR = •		AL POWER GENERATE				
	•	MAX. DEPENDA	ABLE CAPACITY (MWe-	-NET) X H	OURS IN R	EPORTING	PERIO
(4)	UNIT FORCED OUTAGE RATE *	FORCED OUTA				X 100	•
(4)	UNIT FORCED OUTAGE RATE *		GE HOURS ATOR ON LINE + FOR	CED OUTA	GE HOURS	X 100	

DOCKET NO. _50-281

UNIT Surry #2

DATE _July 1, 1977

COMPLETED BY E. P. DeWandel

AVERAGE DAILY UNIT POWER LEVEL

MONT	TH JUNE 1977	-	
DAY	AVERAGE DAILY POWER LEVEL (MWe-net)	DAY	AVERAGE DAILY POWER LEVEL (MWe-net)
	764.7	17	.752.6
2	764.6	18	741.0
3	765.4	19	743.5
4	765.5	20	756.5
5	762.1	21	756.6
- 6	762.1	22	756.7
7	764.5	23	753.0
8	764.0	24	754.9
9	749.3	25	758.7
10	764.3	26	746.7
11	761.1	27	741.4
12	763.2	28	729.4
13	761.7	29	719.0
14	759.8	. 30	741.0
15	762.3	31	•
16	759.1	*	

DAILY UNIT POWER LEVEL FORM INSTRUCTIONS

On this form, list the average daily unit power level in MWe-net for each day in the reporting month. Compute to the nearest whole megawatt.

These figures will be used to plot a graph for each reporting month. Note that by using maximum dependable capacity for the net electrical rating of the unit, there may be occasions when the daily average power level exceeds the 100% line (or the restricted power level line). In such cases, the average daily unit power output sheet should be footnoted to explain the apparent anomaly.

SAWOCITUHS TIAU

DOCKET NO. 50-281

UNIT NAME Surry 2

DATE 7-1-77

COMPLETED BY E. P. DeWandel

REPORT MONTH JUNE, 1977

NO.	DATE	TYPE F-FORCED S-SCHEDULED	DURATION (HOURS)	REASON (1)	METHOD OF SHUTTING DOWN THE REACTOR (2)	CORRECTIVE ACTIONS/COMMENTS
·		THERE V	TERE NO SHI	TDOWNS DURING	HINE 1.977	
•		!		DOWNS DOWNS		
						(1) REASON (2) METHOD A- EQUIPMENT FAILURE (EXPLAIN) 1-MANUAL B- MAINT, OR TEST 2-MANUAL C-REFUELING SCRAM
						D-REGULATORY RESTRICTION E-OPERATOR TRAINING AND LICENSE EXAMINATION F-ADMINISTRATIVE G-OPERATIONAL ERROR (EXPLAIN)
						H-OTHER (EXPLAIN)

SUMMARY: