· / · LICENSEE EVENT REPORT	
CONTROL BLOCK: []]] [[PLEASE PRINT OR TYPE ALL REQUIRED INFORMATION]	
0 1 N Y J A F 1 2 0 0 - 0 0 0 0 - 0 0 0 3 4 1 1 1 1 4 5 6 57 CAT 58	
CON'T O 1 SOURCE L O O O O O O O O O	
0 2 Please See Attachment	
03	
04	
ot L	
06	
0 7	
7 8 9	8
SYSTEM CAUSE SUBCODE S	
LER RO EVENT YEAR SEQUENTIAL REPORT NO. CODE TYPE NO. NO. NO.	
ACTION FUTURE EFFECT SHUTDOWN METHOD HOURS 22 ATTACHMENT SUBMITTED FORM SUB. SUPPLIER MANUFACTURE TAKEN ACTION ON PLANT METHOD TOWN METHOD ACTION ON PLANT METHOD TOWN METHOD TOWN METHOD TOWN METHOD TOWN SUBMITTED FORM SUB. SUPPLIER MANUFACTURE TOWN SUBMITTED TOWN SUBMITTED TOWN SUBMITTED TOWN SUPPLIER MANUFACTURE TOWN SUPPLIER	7 4
CAUSE DESC . ON AND CORRECTIVE ACTIONS (27)	
Please See Attachment	_
	_
12	_
113	_
7 8 9	80
FACILITY STATUS 4 POWER OTHER STATUS 30 METHOD OF DISCOVERY DESCRIPTION 32	
ACTIVITY CONTENT RELEASED OF RELEASE AMOUNT OF ACTIVITY 35 NA LOCATION OF RELEASE 36 NA NA	80
7 B 9 PERSONNEL EXPOSURES NUMBER TYPE DESCRIPTION (39) NA	80
7 8 9 PERSONNEL INJURIES 13 NUMBER DESCRIPTION 41 NA	80
1 8 9 11 12 LOSS OF OR DAMAGE TO FACILITY 43 TYPE DESCRIPTION 7 910050 3 45	80
1 9 Z 42 NA 7 8 9 10 PUBLICITY	80
ISSUED DESCRIPTION 45 NA 1108 206 NRC USE ONLY	1 1
W. Verne Childs 315-342-3840	80

PHONE: _

NAME OF PREPARER -

POWER AUTHORITY OF THE STATE OF NEW YORK AMES A. FITZPATRICK NUCLEAR POWER PLANT

DOCKET NO. 50-333

ATTACHMENT	TO	LER	79-05	8/03L-0
------------	----	-----	-------	---------

Fage	1	of	1

During plant heat up, as a part of normal startup operations, the HPCI System turbine was intentionally uncoupled from the pump to allow over speed testing of the turbine in accordance with F-ST-4K titled "HPCI Turbine Over Speed Testing." This action, while required by the Insurance Underwriters, caused the HPCI System to be placed in a degraded mode identified in Technical Specifications Appendix A, Paragraph 3.5.C.l.a.

Since the HPCI System is designed for the protection in the event of certain small break LOCA conditions between 150 and 1120 psig, the intentional disabling of the system at a pressure of less than 150 psig, did not represent any significant hazard to the public health and safety.

During the conduct of F-ST-4K, which was satisfactory and was witnessed by a representative of the Insurance Underwriters, reactor pressure was maintained below 150 psig. Following completion of the test the pump and turbine were recoupled and the system demonstrated operable to meet the requirements of Technical Specifications Appendix A, Paragraph 4.5.C.