


# ornl

NUREG/CR-1061  
ORNL/NUREG/TM-348

OAK  
RIDGE  
NATIONAL  
LABORATORY



## Quarterly Progress Report on Fission Product Behavior in LWRs for the Period April-June 1979

A. P. Malinauskas

OPERATED BY  
UNION CARBIDE CORPORATION  
FOR THE UNITED STATES  
DEPARTMENT OF ENERGY

Prepared for the U.S. Nuclear Regulatory Commission  
Office of Nuclear Regulatory Research  
Under Interagency Agreements DOE 40-551-75 and 40-552-75

1365 191

7911200

151

Printed in the United States of America. Available from  
National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Road, Springfield, Virginia 22161

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

1365 192

NUREG/CR-1061  
ORNL/NUREG/TM-348  
Dist. Category R3

Contract No. W-7405-eng-26

CHEMICAL TECHNOLOGY DIVISION

QUARTERLY PROGRESS REPORT ON FISSION PRODUCT BEHAVIOR IN LWRs FOR  
THE PERIOD APRIL-JUNE 1979

A. P. Malinauskas, Program Manager

R. A. Lorenz                      M. F. Osborne  
J. L. Collins                      R. L. Towns

Manuscript Submitted: September 1979

Date Published: October 1979

Prepared for the  
U. S. Nuclear Regulatory Commission  
Division of Reactor Safety Research  
Office of Nuclear Regulatory Research  
Washington, D. C. 20555  
Under Interagency Agreements DOE 40-551-75 and 40-552-75

NRC FIN No. B0127

Notice: This document contains information of a preliminary nature.  
It is subject to revision or correction and therefore does  
not represent a final report.

OAK RIDGE NATIONAL LABORATORY  
Oak Ridge, Tennessee 37830  
operated by  
UNION CARBIDE CORPORATION  
for the  
DEPARTMENT OF ENERGY

1365 193

CONTENTS

FOREWORD.....	v
SUMMARY.....	1
1. INTRODUCTION.....	1
2. TEST BWR-1 (960°C RUPTURE).....	2
3. TEST BWR-2 (850°C RUPTURE).....	2
4. TEST BWR-3 (DIFFUSIONAL RELEASE AT 1200°C).....	5
5. REFERENCES.....	13

1365 194

## FOREWORD

This report documents progress made during the period April-June 1979. Previous reports in the series are identified below:

1. Quarterly Progress Report on Reactor Safety Programs Sponsored by the Division of Reactor Safety Research for July-September 1974, ORNL-TM-4729, Vol. 1 (December 1974).
2. Quarterly Progress Report on Reactor Safety Programs Sponsored by the NRC Division of Reactor Safety Research for October-December 1974, ORNL-TM-4805, Vol. 1 (April 1975).
3. Quarterly Progress Report on Reactor Safety Programs Sponsored by the NRC Division of Reactor Safety Research for January-March 1975, ORNL-TM-4912, Vol. 1 (July 1975).
4. Quarterly Progress Report on Reactor Safety Programs Sponsored by the NRC Division of Reactor Safety Research for April-June 1975, ORNL-TM-5021 (September 1975).
5. A. P. Malinauskas, R. A. Lorenz, M. F. Osborne, J. L. Collins, and S. R. Manning, Quarterly Progress Report on Fission Product Release from LWR Fuel for the Period July-September 1975, ORNL-TM-5143 (November 1975).
6. R. A. Lorenz, J. L. Collins, and S. R. Manning, Quarterly Progress Report on Fission Product Release from LWR Fuel for the Period October-December 1975, ORNL-TM-5290 (March 1976).
7. J. L. Collins, M. F. Osborne, A. P. Malinauskas, R. A. Lorenz, and S. R. Manning, Knudsen Cell-Mass Spectrometer Studies of Cesium-Urania Interactions, ORNL/NUREG/TM-24 (June 1976).
8. R. A. Lorenz, M. F. Osborne, J. L. Collins, S. R. Manning, and A. P. Malinauskas, Behavior of Iodine, Methyl Iodide, Cesium Oxide, and Cesium Iodide in Steam and Argon, ORNL/NUREG/TM-25 (July 1976).
9. R. A. Lorenz, J. L. Collins, S. R. Manning, and A. P. Malinauskas, Quarterly Progress Report on Fission Product Release from LWR Fuel for the Period January-March 1976, ORNL/NUREG/TM-30 (July 1976).
10. R. A. Lorenz, J. L. Collins, S. R. Manning, O. L. Kirkland, and A. P. Malinauskas, Quarterly Progress Report on Fission Product Release from LWR Fuel for the Period April-June 1976, ORNL/NUREG/TM-44 (August 1976).
11. R. A. Lorenz, J. L. Collins, and O. L. Kirkland, Quarterly Progress Report on Fission Product Release from LWR Fuel for the Period July-September 1976, ORNL/NUREG/TM-73 (December 1976).

1365 195

12. R. A. Lorenz, J. L. Collins, and O. L. Kirkland, Quarterly Progress Report on Fission Product Release from LWR Fuel for the Period October-December 1976, ORNL/NUREG/TM-88 (March 1977).
13. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period January-March 1977, ORNL/NUREG/TM-122 (June 1977).
14. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period April-June 1977, ORNL/NUREG/TM-139 (September 1977).
15. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period July-September 1977, ORNL/NUREG/TM-170 (January 1978).
16. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period October-December 1977, ORNL/NUREG/TM-186 (March 1978).
17. R. A. Lorenz, J. L. Collins, and A. P. Malinauskas, Fission Product Source Terms for the LWR Loss-of-Coolant Accident: Summary Report, NUREG/CR-0091 (ORNL/NUREG/TM-206) (June 1978).
18. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period January-March 1978, NUREG/CR-0116 (ORNL/NUREG/TM-208) (June 1978).
19. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period April-June 1978, NUREG/CR-0370 (ORNL/NUREG/TM-242) (September 1978).
20. R. A. Lorenz, J. L. Collins, and S. R. Manning, Fission Product Release from Simulated LWR Fuel, NUREG/CR-0274 (ORNL/NUREG/TM-154) (October 1978).
21. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period July-September 1978, NUREG/CR-0493 (ORNL/NUREG/TM-280) (December 1978).
22. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period October-December 1978, NUREG/CR-0682 (ORNL/NUREG/TM-308) (April 1979).
23. A. P. Malinauskas et al., Quarterly Progress Report on Fission Product Behavior in LWRs for the Period January-March 1979, NUREG/CR-0917 (ORNL/NUREG/TM-332) (August 1979).

SUMMARY

Tests BWR-2 and BWR-3 were performed during this report period; each test employed segment 4 from fuel rod F-6, bundle PH-006, which had been irradiated to ~12,700 MWd/MT during cycle 1 of the Peach Bottom-2 boiling water reactor (BWR). The test segment was pressure-ruptured at 850°C in test BWR-2 and later heated at 1200°C for 25 min in flowing steam in test BWR-3. The results obtained to date in the BWR Test Series can be summarized as follows:

Test	Test conditions		Percent of total inventory release			
	Rupture	Diffusion	<sup>85</sup> Kr	<sup>137</sup> Cs	<sup>129</sup> I	UO <sub>2</sub>
BWR-1	960°C at 1.23 MPa (179 psi)	960°C for 1 min	1.7 <sup>a</sup>	1.71	1.18	0.02
BWR-2	850°C at 3.40 MPa (500 psi)	850°C for 1 min	1.0 <sup>b</sup>	1.70	2.54	0.02
BWR-3	c	1200°C for 25 min	1.1 <sup>d</sup>	1.85	—	0.00

<sup>a</sup>An additional amount, estimated at 15.1% of the total inventory, was released from this fuel rod segment during operation in the Peach Bottom-2 Reactor (ref. 1).

<sup>b</sup>An additional amount, estimated at 13.1% of the total inventory, was released from this fuel rod segment during operation in the Peach Bottom-2 Reactor.

<sup>c</sup>This segment was the same one that was ruptured at 850°C in test BWR-2.

<sup>d</sup>This amount of <sup>85</sup>Kr is in addition to the 1.0% released during test BWR-2 and the 13.1% estimated to have been released while in the Peach Bottom-2 Reactor.

1. INTRODUCTION

The BWR Fuel Test Series utilizes 30.5 cm-long fuel rod segments cut from rod F-6, bundle PH-006, which had been irradiated during cycle 1 of the Peach Bottom-2 Reactor. This fuel rod, whose characteristics have been described previously,<sup>1</sup> was selected because it is believed to be representative of light water reactor fuel rods which have relatively

1365 197

high concentrations of cesium and iodine in the pellet-to-clad gap space. Our preliminary source-term model<sup>2</sup> correlates mass release with gap inventory raised to the 0.8 power; however, this correlation is largely based on earlier tests which were conducted with irradiated fuel rod segments having low gap inventories.<sup>3</sup>

## 2. TEST BWR-1 (960°C RUPTURE)

Additional results have been obtained for test BWR-1. Reexamination of the temperature measurements showed that the rupture temperature was 960°C rather than 970°C as previously reported.<sup>1</sup> Based on the analysis of <sup>129</sup>I, 1.18% of the total iodine was released (see Table 1). The peak deposit of iodine in the thermal gradient tube corresponded to the location of the cesium peak. Only 0.36% of the released iodine reached the charcoal cartridges, thus indicating a very low release of the reactive forms of iodine. The amounts of <sup>137</sup>Cs collected in the thermal gradient tube and filter pack, and of <sup>85</sup>Kr collected in the charcoal traps, are presented graphically in Fig. 1 as a function of time and fuel rod temperature.

Some cesium and iodine were also released in the form of fuel dust that was ejected at the time of rupture; 119 µg of <sup>137</sup>Cs was measured in loose fuel particles tapped off the furnace tube liner. Analyses of <sup>154</sup>Eu as a tracer for fuel indicated that these particles contained 44.4 mg of UO<sub>2</sub>. Since this amount of fuel should have contained only 21 µg of <sup>137</sup>Cs, it appears that the ejected fuel dust may have been enriched in cesium as a result of its proximity to the pellet surface. The total amount of ejected dust, as determined from <sup>154</sup>Eu concentration measurements, amounted to 69 mg of UO<sub>2</sub>.

## 3. TEST BWR-2 (850°C RUPTURE)

Test BWR-2 was performed by pressurizing segment 4 of rod F-6<sup>1</sup> to 515 psig (3.54 MPa) with purified argon while holding it at a temperature of ~600°C in the test apparatus; the rod was then heated to 850°C to cause rupture of the Zircaloy cladding in a flowing steam atmosphere. The



Table 1. Distribution of iodine in test BWR-1<sup>a</sup>

Location	Temperature (°C)	Amount of <sup>129</sup> I found in each location			Total Iodine found (µg)
		Mass (µg) <sup>b</sup>	Percent of total <sup>c</sup>	Percent of released	
Fuel rod segment	960	(3.147 × 10 <sup>4</sup> ) <sup>d</sup>			(4.163 × 10 <sup>4</sup> ) <sup>d</sup>
Furnace tube	e	169.73 ± 3.90 <sup>f</sup>	5.39 × 10 <sup>-1</sup>	45.69	224.53
Thermal gradient tube	750-220	78.61 ± 0.13	2.50 × 10 <sup>-1</sup>	21.16	103.99
Filter pack components	125				
Stainless steel inlet fitting		5.35 ± 0.02	1.70 × 10 <sup>-2</sup>	1.44	7.08
First filter paper		116.40 ± 1.70	3.70 × 10 <sup>-1</sup>	31.33	153.98
Second and third filter papers		0.07 ± 0.001	2.22 × 10 <sup>-4</sup>	0.02	0.09
Charcoal No. 1a		1.30 ± 0.01	4.13 × 10 <sup>-3</sup>	0.35	1.72
Charcoal No. 1b		0.03 ± 0.001	9.53 × 10 <sup>-5</sup>	0.01	0.04
Charcoal No. 1c		0.0	0.0	0.0	0.0
Charcoal No. 2a		0.0	0.0	0.0	0.0
Charcoal No. 2b		0.0	0.0	0.0	0.0
Charcoal No. 3		0.0	0.0	0.0	0.0
AgX		0.0	0.0	0.0	0.0
Condenser	0	0.0	0.0	0.0	0.0
Freeze trap	-78	0.0	0.0	0.0	0.0
Cold charcoal traps (two)	-78	0.0	0.0	0.0	0.0
Total		371.49 ± 5.76	1.18	100.00	491.4 ± 7.6

<sup>a</sup>Steam flow rate, 1806 cm<sup>3</sup>/min (STP); helium flow rate, 205 cm<sup>3</sup>/min (STP); pressure, 760 torr. Decay time, 3 years (to March 26, 1979). Some additional iodine was released in the form of UO<sub>2</sub> dust.

<sup>b</sup>Amounts less than 1.0 × 10<sup>3</sup> × 10<sup>3</sup> µg are given as 0.0.

<sup>c</sup>Percent of radioactive nuclide in fuel rod segment.

<sup>d</sup>Calculated for 13,000-MWd/MT burnup of original uranium, 334 g of uranium originally in 12-in. segment, and a 3-year decay period.

<sup>e</sup>Approximately 750°C maximum at center; 600°C at outlet end.

<sup>f</sup>Error estimates are based solely on the results of replicate chemical analyses.

1365 199




Fig. 1. Collection of  $^{137}\text{Cs}$  in the thermal gradient tube and filter pack, and of  $^{85}\text{Kr}$  in the charcoal traps, during test BWR-1.

1365 200

temperature was maintained for 1 min before turning off the induction heating. Figure 2 is a photograph of the ruptured rod. The amount of cladding expansion and the hole size ( $\sqrt{2} \text{ mm}^2$ ) are similar to those observed in previous experiments in the same apparatus.

The distributions of cesium and iodine which were collected in the different components of the apparatus are presented in Tables 2 and 3. These distributions were typical for pressure-ruptured tests. Approximately 1.70% and 2.54% of the total cesium and the total iodine inventories, respectively, were found.

The amounts of cesium collected in the thermal gradient tube and filter pack, and of  $^{85}\text{Kr}$  collected in the charcoal traps, are illustrated graphically in Fig. 3 as a function of time and fuel rod temperature. The distributions of cesium and iodine in the thermal gradient tube are shown in Fig. 4. (Peak deposits in the 350 to 450°C temperature range are typical for both cesium and iodine in our tests.) The release of  $^{85}\text{Kr}$  (11.4 mCi) amounted to 1.01% of the total inventory.

#### 4. TEST BWR-3 (DIFFUSIONAL RELEASE AT 1200°C)

Test BWR-3 was performed to measure the release of fission products at 1200°C from a previously pressure-ruptured fuel rod segment. The rod used in this test was the same as that which was ruptured in test BWR-2. An electric resistance heater surrounding the furnace tube was substituted for the induction heater so that the entire 30.5-cm length could be heated nearly uniformly.

Approximately 1.85% of the total cesium inventory in the test piece was released. The distribution of cesium on the apparatus components is given in Table 4. The amounts of  $^{137}\text{Cs}$  collected in the thermal gradient tube and filter pack, and the  $^{85}\text{Kr}$  collected in the charcoal traps, are presented in Fig. 5 as a function of time and fuel rod temperature. Cesium and krypton releases occurred during both the slow heatup and the cooldown periods. The total effective time for cesium release at 1200°C was determined to be 25 min when the heatup and cooldown periods were taken into account. Measurements of gamma activity in the thermal gradient tube

ORNL - PHOTO 1905-79




Fig. 2. View of ruptured fuel rod segment from test BWR-2.

POOR ORIGINAL

1365 202

Table 2. Distribution of cesium in test BWR-2<sup>a</sup>

Location	Temperature (°C)	Amount of <sup>137</sup> Cs found in each location			Total cesium found (μg)
		Mass (μg) <sup>b</sup>	Percent of total <sup>c</sup>	Percent of released	
Fuel rod segment	850	(1.714 x 10 <sup>5</sup> ) <sup>d</sup>			(4.074 x 10 <sup>5</sup> ) <sup>d</sup>
Furnace tube					
Quartz liner	e	2039.00	1.19	70.01	4846.5
Quartz fuel rod holder		447.30	0.26	15.36	1063.2
Thermal gradient tube	740-275	89.36	5.21 x 10 <sup>-2</sup>	3.07	212.40
Filter pack components	130				
Stainless steel inlet fitting		16.14	9.42 x 10 <sup>-3</sup>	0.55	38.36
First filter paper		320.104	0.19	10.99	760.85
Second filter paper		0.087	5.08 x 10 <sup>-5</sup>	0.003	0.21
Third filter paper		0.105	6.13 x 10 <sup>-5</sup>	0.004	0.25
Charcoal No. 1a		0.141	8.23 x 10 <sup>-5</sup>	0.005	0.34
Charcoal No. 1b		0.038	2.22 x 10 <sup>-5</sup>	0.0013	0.09
Charcoal No. 1c		0.016	9.33 x 10 <sup>-6</sup>	0.0005	0.04
Charcoal No. 2a		0.009	5.25 x 10 <sup>-6</sup>	0.0003	0.02
Charcoal No. 2b		0.0	0.0	0.0	0.0
Charcoal No. 3		0.0	0.0	0.0	0.0
AgX		0.0	0.0	0.0	0.0
Condenser	0	0.0	0.0	0.0	0.0
Freeze trap	-78	0.0	0.0	0.0	0.0
Cold charcoal traps (two)	-78	0.0	0.0	0.0	0.0
Total		2912.3	1.699	100.00	6922.2

<sup>a</sup>Steam flow rate, 1375 cm<sup>3</sup>/min (STP); helium flow rate, 245 cm<sup>3</sup>/min (STP); pressure, 760 torr. Decay time, 3 years (to March 26, 1979). Some additional cesium was released in the form of UO<sub>2</sub> dust.

<sup>b</sup>Amounts less than 1.0 x 10<sup>-5</sup> μg are given as 0.0.

<sup>c</sup>Percent of radioactive nuclide in fuel rod segment.

<sup>d</sup>Calculated for 12,740-Mwd/MT burnup of original uranium, 334 g of uranium originally in 12-in. segment, and a 3-year decay period.

<sup>e</sup>Approximately 650°C maximum at center; ~500°C at outlet end.

1365 205

Table 3. Distribution of iodine in test BWR-2<sup>a</sup>

Location	Temperature (°C)	Amount of <sup>129</sup> I found in each location			Total iodine found (µg)
		Mass (µg) <sup>b</sup>	Percent of total <sup>c</sup>	Percent of released	
Fuel rod segment	850	(3.084 x 10 <sup>4</sup> ) <sup>d</sup>			(4.080 x 10 <sup>4</sup> ) <sup>d</sup>
Furnace tube	e	571.09 ± 26.30 <sup>f</sup>	1.852	73.05	755.46
Thermal gradient tube	740-275	47.72 ± 0.45	1.55 x 10 <sup>-1</sup>	6.10	63.13
Filter pack components	130				
Stainless steel inlet fitting		6.55 ± 0.22	2.12 x 10 <sup>-2</sup>	0.84	8.66
First filter paper		156.00 ± 6.00	5.06 x 10 <sup>-1</sup>	19.95	206.36
Second and third filter papers		0.22 ± 0.01	7.13 x 10 <sup>-4</sup>	0.03	0.29
Charcoal No. 1a		0.24 ± 0.01	7.78 x 10 <sup>-4</sup>	0.03	0.32
Charcoal No. 1b		0.0	0.0	0.0	0.0
Charcoal No. 1c		0.0	0.0	0.0	0.0
Charcoal No. 2a		0.0	0.0	0.0	0.0
Charcoal No. 3		0.0	0.0	0.0	0.0
AgX		0.0	0.0	0.0	0.0
Condenser	0	0.0	0.0	0.0	0.0
Freeze trap	-78	0.0	0.0	0.0	0.0
Cold charcoal traps (two)	-78	0.0	0.0	0.0	0.0
Total		781.82 ± 32.98	2.535	100.00	1034.2 ± 43.6

<sup>a</sup>Steam flow rate, 1375 cm<sup>3</sup>/min (STP); helium flow rate, 245 cm<sup>2</sup>/min (STP); pressure, 760 torr. Decay time, 3 years (to March 26, 1979).

<sup>b</sup>Amounts less than 1.0 x 10<sup>-3</sup> µg are given as 0.0.

<sup>c</sup>Percent of radioactive nuclide in fuel rod segment.

<sup>d</sup>Calculated for 12,740-MWd/MT burnup of original uranium, 334 g of uranium originally in 12-in. segment, and a 3-year decay period.

<sup>e</sup>Approximately 650°C maximum at center; ~ 500°C at outlet end.

<sup>f</sup>Error estimates are based solely on the results of replicate chemical analyses.

1365 204




Fig. 3. Collection of  $^{137}\text{Cs}$  in the thermal gradient tube and filter pack, and of  $^{85}\text{Kr}$  in the charcoal traps, during test BWR-2.

1365 205




Fig. 4. Concentration profiles of cesium and iodine in the thermal gradient tube from test BWR-2.

1365 206



Table 4. Distribution of cesium in test BWR-3<sup>a</sup>

Location	Temperature (°C)	Amount of <sup>137</sup> Cs found in each location			Total cesium found (μg)
		Mass <sup>b</sup> (μg)	Percent of total <sup>c</sup>	Percent of release	
Fuel rod segment	1200	(1.685 x 10 <sup>5</sup> ) <sup>d</sup>			(4.005 x 10 <sup>5</sup> ) <sup>d</sup>
Furnace tube	1200				
Quartz liner		444.41	2.64 x 10 <sup>-1</sup>	14.29	1056.30
Quartz fuel rod holder		904.50	5.37 x 10 <sup>-1</sup>	29.09	2149.87
Thermal gradient tube	1050-200	765.82	4.55 x 10 <sup>-1</sup>	24.63	1820.24
Filter pack components	125				
Stainless steel inlet fitting		40.80	2.42 x 10 <sup>-2</sup>	1.31	96.98
First filter paper		954.11	5.66 x 10 <sup>-1</sup>	30.68	2267.78
Second filter paper		0.08	4.75 x 10 <sup>-5</sup>	2.57 x 10 <sup>-3</sup>	0.19
Third filter paper		0.05	2.97 x 10 <sup>-5</sup>	1.61 x 10 <sup>-3</sup>	0.12
Charcoal No. 1a		2.0 x 10 <sup>-6</sup>	1.19 x 10 <sup>-9</sup>	6.43 x 10 <sup>-8</sup>	4.65 x 10 <sup>-6</sup>
Charcoal No. 1b		0.0	0.0	0.0	0.0
Charcoal No. 1c		0.0	0.0	0.0	0.0
Charcoal No. 2a		0.0	0.0	0.0	0.0
Charcoal No. 2b		0.0	0.0	0.0	0.0
Charcoal No. 3		0.0	0.0	0.0	0.0
AgX		0.0	0.0	0.0	0.0
Condenser	0	0.0	0.0	0.0	0.0
Freeze trap	-78	0.0	0.0	0.0	0.0
Cold charcoal traps (two)	-78	0.0	0.0	0.0	0.0
Total		3109.77	1.846	100.00	7391.47

<sup>a</sup> Steam flow rate, 1000 cm<sup>3</sup>/min (STP); helium flow rate, 300 cm<sup>3</sup>/min (STP); pressure, 760 torr. Decay time, 3 years (to March 26, 1979). This fuel rod segment was also used in test BWR-2.

<sup>b</sup> Amounts less than 1.0 x 10<sup>-6</sup> μg are given as 0.0.

<sup>c</sup> Percent of radioactive nuclide in fuel rod segment.

<sup>d</sup> Calculated for burnup of 12,740 MWd/MT of original uranium, 334 g of uranium originally in 12-in. segment, and a 3-year decay period.

1365 207




Fig. 5. Collection of  $^{137}\text{Cs}$  in the thermal gradient tube and filter pack, and of  $^{85}\text{Kr}$  in the charcoal traps, during test BWR-3.

1365 208

and filter pack indicated that half of the cesium was released in the 13-min period during which the fuel rod was at a temperature  $>1180^{\circ}\text{C}$ .

The distribution of cesium in the thermal gradient tube is shown in Fig. 6. The small broad peak at 600 to  $650^{\circ}\text{C}$  is similar to the one that was observed in test HBU-11.<sup>3</sup> (Test HBU-11 was essentially identical to test BWR-3 except for the use of high-burnup PWR fuel from the H. B. Robinson-2 Reactor.)

Significant krypton release began when the temperature of the fuel rod reached about  $900^{\circ}\text{C}$ . (Note that this segment had previously been heated to a maximum of  $850^{\circ}\text{C}$  in test BWR-2.) The total releases of  $^{85}\text{Kr}$  were 1.08% in test BWR-3, 1.01% in test BWR-2, and an estimated 13.1% while in the Peach Bottom-2 Reactor.

#### 5. REFERENCES

1. A. P. Malinauskas, R. A. Lorenz, J. L. Collins, M. F. Osborne, and R. L. Towns, Quarterly Progress Report on Fission Product Behavior in LWRs for the Period January-March 1979, NUREG/CR-0917 (ORNL/NUREG/TM-332) (August 1979).
2. R. A. Lorenz, J. L. Collins, and A. P. Malinauskas, Fission Product Source Terms for the LWR Loss-of-Coolant Accident: Summary Report, NUREG/CR-0091 (ORNL/NUREG/TM-206) (June 1978).
3. R. A. Lorenz, J. L. Collins, A. P. Malinauskas, O. L. Kirkland, and R. L. Towns, Fission Product Release from Highly Irradiated LWR Fuel, NUREG/CR-0722 (ORNL/NUREG/TM-287) (in preparation).

1365 209




Fig. 6. Distribution of cesium in the thermal gradient tube during test BWR-3.

1365 210

NUREG/CR-1061  
ORNL/NUREG/TM-348  
Dist. Category R3

INTERNAL DISTRIBUTION

- |        |                   |        |                               |
|--------|-------------------|--------|-------------------------------|
| 1.     | M. Bender         | 29.    | R. P. Wichner                 |
| 2-4.   | J. J. Collins     | 30.    | R. G. Wymer                   |
| 5.     | D. E. Ferguson    | 31.    | Document Reference Section    |
| 6.     | C. B. Lindemer    | 32-33. | Central Research Library      |
| 7-12.  | R. A. Lorenz      | 34.    | Laboratory Records - RC       |
| 13-21. | A. P. Malinauskas | 35.    | Laboratory Records Department |
| 22.    | M. F. Osborne     | 36.    | ORNL Patent Section           |
| 23.    | G. W. Parker      | 37.    | E. L. Gaden (consultant)      |
| 24.    | H. Postma         | 38.    | L. J. Colby (consultant)      |
| 25.    | M. G. Stewart     | 39.    | K. D. Timmerhaus (consultant) |
| 26.    | R. L. Towns       | 40.    | G. R. Choppin (consultant)    |
| 27.    | D. B. Trauger     | 41.    | L. E. Swabb, Jr. (consultant) |
| 28.    | S. K. Whatley     |        |                               |

EXTERNAL DISTRIBUTION

- 42-46. Director, Division of Reactor Safety Research, Nuclear Regulatory Commission, Washington, DC 20555
- 47. Office of Assistant Manager, Energy Research and Development, DOE, ORO
- 48. J. Sisler, Division of Environmental Control Technology, DOE
- 49. K. Campe, Office of Nuclear Reactor Regulation, NRC
- 50. W. Lahs, Office of Nuclear Regulatory Research, NRC
- 51-52. Technical Information Center, DOE
- 53-392. Given distribution as shown in category R3 (NTIS - 10 copies)

1365 211