



Department of Energy  
Washington, D.C. 20545

*Docket Room*  
**PDR** 71-5467

OCT 30 1979



Mr. C. E. MacDonald, Chief  
Transportation Branch  
Division of Fuel Cycle and  
Material Safety  
U. S. Nuclear Regulatory Commission  
Washington, D.C. 20555

Dear Mr. MacDonald:

To update Attachment D to the Certificate of Compliance  
USA/5467/AF (DOE-OR), Revision 4, I am forwarding replacements  
for your record copies.

Sincerely,

*Donald M. Ross*

Donald M. Ross, Chief  
Occupational Safety Branch  
Operational and Environmental  
Safety Division

Enclosure:  
(8 copies - Attachment D)

cc:  
R. R. Rawl, DOT - w/encl.

**FEE EXEMPT**

1497 515

14585

7912050 458

Packaging and Shipping Limits  
for Mark VR, VE and 15 Cores and Slugs

MATERIAL TYPE	BOX TYPE, NLO DRAWING NO	NO. PER BOX, MAXIMUM	MAXIMUM WEIGHT PER BOX, POUNDS		MAX AMOUNT OF U PER SHIP., TONS
			NET	GROSS	
Mark VR inner canned slugs	G-4214	105	1070	1125	6.9
Mark VR outer canned slugs	G-4214	45	650	705	16.3
Mark VE inner canned slugs	G-4214	105	1010	1065	3.4
Mark VE outer canned slugs	G-4214	45	610	665	3.4
Mark 15 inner bare cores	G-4292*	60	980	1080	1.3
Mark 15 inner canned slugs	G-4292*	60	1015	1115	1.3
Mark 15 outer bare cores	G-4292*	30	580	680	4.1
Mark 15 outer canned slugs	G-4292*	30	610	710	4.1

\*A wooden false bottom will be placed in each box to reduce the inside usable height from 16 1/8 to 11 1/2 inches.

1497 316

1458r