

INTERIM REPORT

Accession No. 7907300585

Contract Program or Project Title: Light Water Reactor Thermal Hydraulic Development Program

Subject of this Document: June Monthly Highlight Letter

Type of Document: Monthly Highlight Letter

Author(s): Owen C. Jones, Jr.

Date of Document: July 18, 1979

Responsible NRC Individual
and NRC Office or Division: Dr. Y. V. Hsu
Division of Reactor Safety Research
Systems Engineering Branch
U. S. Nuclear Regulatory Commission
Washington, D. C. 20555

This document was prepared primarily for preliminary or internal use. It has not received full review and approval. Since there may be substantive changes, this document should not be considered final.

Brookhaven National Laboratory
Upton, NY 11973
Associated Universities, Inc.
for the
U.S. Department of Energy

Prepared for
U.S. Nuclear Regulatory Commission
Washington, D. C. 20555
Under Interagency Agreement EY-76-C-02-0016
NRC FIN No. A-3045

488 085

INTERIM REPORT

NRC Research and Technical
Assistance Report

Monthly Highlights

for

June 1979*

Light Water Reactor Thermal Hydraulic Development Division

Budget Activity 60-19-10-01

Owen C. Jones, Jr.
Thermal Hydraulic Development Division
Department of Nuclear Energy
Brookhaven National Laboratory
Upton, New York 11973

NRC Research and Technical
Assistance Report

*Work carried out under the auspices of the United States Nuclear Regulatory Commission.

7907300585

483 036

1.1 Analytical Modeling (B.J.C. Wu and N. Abuaf)

Evaluation of our experimental data using the computer program developed recently continued. Typical values of the net vapor generation rate Γ_v are shown in Fig. 1c. In addition, the measured pressure and void distributions and least squares fits are also displayed (Figs. 1a, 1b).

The modeling of the isentropic homogeneous expansion in the nozzle was also pursued. Since this modeling can not predict any nonequilibrium in the flow, a second approach consisting of a three step process is being tried. In this approach, first the liquid is assumed to go through an isentropic flow in the converging section down to the nozzle throat; second, the shock jump conditions are applied at the throat; and third, the two phase mixture is assumed to follow an isentropic expansion in the diverging section.

From the TRAC calculations performed, the local vapor generation rates, Γ_v , were also calculated and are being compared to the results obtained from the computer calculations of the experimental data.

1.2 Flashing Experiments (N. Abuaf, B.J.C. Wu,, G. A. Zimmer, and J. H. Klein)

The electronic parts of the five beam gamma densitometer are debugged and ready for operation.


Four of the Thulium ¹⁷⁰ sources purchased from Amersham Incorporated were irradiated at the HFBR at BNL for a five day period. This activation would push the total activity of each source to the level of curies.

Part of this month was spent in preparation of the facilities for the Brookhaven Laboratory's free weekend tours which are open to the general public. The tour of Reactor Safety Programs experimental facilities took place on June 30 and July 1, 1979. Approximately 450 people visited the


facilities during the two days. The visitors were given a description of the BNL Reactor Safety activities and how the information derived from the program assists NRC in their reactor licensing decisions.

488 088


488 089



(a)



(b)



(c)

Figure 1 - Results of Vapor Generation Rate Calculation on Runs 80/801. (a) Measured Pressure (Squares) and Curve Fit (b) Measured Void Fraction (Squares) and Curve Fit (c) Vapor Generation Rate Γ_v .

POOR ORIGINAL

Distribution Light Water Reactor Thermal Hydraulic Development Program

BNL RSP Division Heads
BNL RSP Group Leaders
BNL RSE Personnel

S. Fabric, NRC
Y. Y. Hsu, NRC
W. Y. Kato, BNL
H. J. Kouts, BNL
R. M. Scroggins, NRC
T. G. Theofanus, Purdue University
N. Zuber, NRC

U.S. NRC Division of Technical Information and Control

488 090