Form NRC-618 (12-73) 10 CFR 71

U.S. NUCLEAR REGULATORY COMMISSION CERTIFICATE OF COMPLIANCE

For Radioactive Materials Packages

| his certificate is issued to satisfy Sectio | | | | |
|---|--|---|---|---|
| his certificate is issued to satisfy Sectio | | | | |
| laterials Regulations (49 CFR 170-189 a ransportation Dangerous Cargoes Regula | ns 173.393a, 173.39 and 14 CFR 103) an ations (46 CFR 146 | 94, 173.395, and 173.396 of the nd Sections 146–19–10a and 14 –149), as amended. | Department of Tra 6–19–100 of the l | nsportation Hazardou Department of |
| he packaging and contents described in ederal Regulations, Part 71, "Packaging ertain Conditions." | item 5 below, meet of Radioactive Ma | ts the safety standards set forth i terials for Transport and Transpo | n Subpart C of Titl ortation of Radioac | e 10, Code of tive Material Under |
| his certificate does not relieve the cons ransportation or other applicable regula vill be transported. | ignor from complian tory agencies, includ | ice with any requirement of the ding the government of any coun | regulations of the L stry through or into | J.S. Department of which the package |
| ate is issued on the basis of a safety ana | lysis report of the p | package design or application- | | |
| repared by (Name and address): | 3.(b) Title | and identification of report or a | oplication: | |
| lectric Company 780 n, North Carolina 28401 | General El March 12, | ectric Company appli 1973, as supplemente et No. 71-9009 | ication date ed. | d |
| | he packaging and contents described in ederal Regulations, Part 71, "Packaging Pertain Conditions." his certificate does not relieve the consi- ransportation or other applicable regula will be transported. ate is issued on the basis of a safety ana trepared by (Name and address): lectric Company 780 n, North Carolina 28401 | he packaging and contents described in item 5 below, meet ederal Regulations, Part 71, "Packaging of Radioactive Ma ertain Conditions." his certificate does not relieve the consignor from compliar ransportation or other applicable regulatory agencies, includivil be transported. ate is issued on the basis of a safety analysis report of the p trepared by (Name and address): lectric Company 780 n, North Carolina 28401 3.(c) Dock | he packaging and contents described in item 5 below, meets the safety standards set forth i ederal Regulations, Part 71, "Packaging of Radioactive Materials for Transport and Transport Partain Conditions." This certificate does not relieve the consignor from compliance with any requirement of the is ransportation or other applicable regulatory agencies, including the government of any count will be transported. The package design or application- trepared by (Name and address): 1ectric Company 780 n, North Carolina 28401 3.(c) Docket No. 71-9009 | he packaging and contents described in item 5 below, meets the safety standards set forth in Subpart C of Title ederal Regulations, Part 71, "Packaging of Radioactive Materials for Transport and Transportation of Radioactive ertain Conditions." his certificate does not relieve the consignor from compliance with any requirement of the regulations of the L ransportation or other applicable regulatory agencies, including the government of any country through or into will be transported. ate is issued on the basis of a safety analysis report of the package design or application— trepared by (Name and address): lectric Company 780 n, North Carolina 28401 3.(c) Docket No. 71-9009 |

5. Description of Packaging and Authorized Contents, Model Number, Fissile Class, Other Conditions, and References

- (a) Packaging
 - (1) Model No.: FL 10-1
 - (2) Description

Two 16-gage 55-gallon drums welded end to end, approximately 68 inches long and 22-1/2 inches in diameter. The outer drum closure shall be accomplished by at least a 12-gage bolt-locking ring with drop-forged lugs, one of which is threaded to receive at least 5/8-inch diameter bolt and lock nut. The pressure vessel support mechanism consists of wood supports, steel inner sleeve and nut ring to receive the containment vessel, and fire resistant phenolic foam, formed in place in accordance with AEC Materials and Equipment Specification SP-9 to an average finished density of at least 8 pounds per cubic foot for the main body and 10 pounds per cubic foot for the cap. Gas relief holes shall be provided in the outer steel drum.

1687 114

8001040 475

The containment vessel is a 304L stainless steel 5-inch schedule 40 pipe, approximately 53-1/2 inches long, with a 304L stainless steel 1/2-inch thick welded bottom plate and a 304L stainless steel 300 pound slipon flange and blind flange which is fastened by eight 3/4-inch steel bolts. The flange closure is gasketed by two flouroelastomer 0-rings with a pressure tap between the two 0-rings grooves. During shipment, the 0-ring groove pressure tap Page 2 - Certificate No. 9009 - Revision No. 4 - Docket No. 71-9009

5.(a)(2) Description (continued)

1

is sealed with a pipe plug with threads wrapped in teflon tape. A 1/4-inch stainless steel valve is screwed into the blind flange of the containment vessel. The valve is sealed by a pipe cap (threads wrapped with teflon tape) and is protected by a 2-1/2-inch high section 5-inch Schedule 40 pipe welded to the top of the flange. The packaging has a maximum gross weight of 500 lbs.

(3) Drawings

The FL 10-1 package is described by International Nuclear Company (INCO) Drawing No. DSD-479-D, Rev. C, and the containment vessel described by INCO Drawing No. DSD-480-D, Rev. C. The containment vessel seal is described by INCO Drawing No. DED-169-B, Rev. 2.

- (b) Contents
 - (1) Type and form of material
 - Uranyl nitrate solutions having a concentration of uranium 235 and uranium 233 not exceeding 350 grams per liter and an H/U-235 atomic ratio not less than 80, provided that the U-233 and plutonium content is not more than 1% of the U-235 content; or
 - (ii) Uranyl nitrate solutions having a combined concentration of uranium 233 and uranium 235 not exceeding 250 grams per liter and an H to fissile material atomic ratio not less than 80 provided (1) the U-233 content is not greater than 20% of the combined U-233 and U-235 content, and (2) the plutonium content is not more than 1% of the combined U-233 or U-235 content; or
 - (iii) Plutonium nitrate solutions having a concentration not exceeding 250 grams fissile plutonium per liter; or
 - (iv) Uranyl sulfate solution (U0₂SO₄) containing uranium-235; or
 - (v) Dry compounds and mixtures of fissile plutonium-uranium-235.
 - (2) Maximum quantity of material per package

Plutonium in excess of twenty (20) curies per package must be in the form of metal, metal alloy, or reactor elements; or must be in accordance with Item 9 below; and:

(i) For the contents described in 5(b)(1)(i), (ii), and (iii):

Maximum decay heat load not to exceed 21 watts, and 10.5 liters of solution.

1687 115

Page 3 - Certificate No. 9009 - Revision No. 4 - Docket No. 71-9009

5.(b) Contents (continued)

٩.

(ii) For the contents described in 5(b)(1)(iv):

Maximum decay heat load not to exceed 18 watts and 950 grams fissile material.

(iii) For the contents described in 5(b)(1)(v):

Maximum decay heat load not to exceed 30 watts, and 4.5 kilograms fissile material.

(c) Fissile Class

I

- 6. The solution contents of the package shall be contained with a bottle having one of the following specifications:
 - (i) Slit vent polyethylene bottle per CAPE-1170-37,
 - (ii) Duo-vent polyethylene bottle per Nuclear Fuel Services, Inc., Specification U-1 and Drawing No. 5B-U-740, or
 - (iii) Stainless steel bottle as shown on General Electric Company Drawings Nos. FRO-140 and FRO-140A.
- The polyethylene bottles may be packaged within the metal inner container described by Chester-Jensen Company, Inc., Drawings Nos. 1092M-1, 1093M-1, 1095M-1 and 1096M-1, Issue 1, dated April 26, 1971.
- 8. The packaging for the polyethylene bottles shall include a flexibile restraining device (such as recommended in ARH-1819 "Vibration Testing of L-3 and L-10 Shipping Lontainers") placed between the cap assembly of the polyethylene bottle and the closure flange of the pressure vessel to assure that the polyethylene bottle will vibrate at the same frequency as the pressure vessel during transport.
- 9. Dry compounds and mixtures which shall be packaged within sealed metal cans or DOT specification 2R containers (49 CFR §178.34); and placed within an inner container constructed and leak tested as specified on General Electric Illustration AFL 1105. Following the gas leak testing specified on the Illustration, all inner container welds shall be leak tested using a liquid penetrant method in accordance with Article 6, Section V, ASME Code. Alternatively, the inner container shown in the Illustration may be constructed of 300 series stainless steel pipe with an outside diameter of 4.500 inches with a 0.120 inch wall thickness.
- Appropriate steps shall be taken to assure that from the time of sealing to the time of delivery to the consignee, the pressure in the containment vessel will not exceed 40 psig.

Page 4 - Certificate No. 9009 - Revision No. 4 - Docket No. 71-9009

- 11. Prior to each shipment of more than Type A quantities of radioactive material, the space between the double O-ring seal shall be tested at 100 psig and leak detection | performed by a method capable of detecting a leak greater than 10⁻³ atm cc/sec at standard temperature and pressure. No package with a detectable leak shall be delivered to a carrier for transport.
- 12. In addition to the requirements of subpart D of 10 CFR 71, a test shall be performed on each containment vessel and associated 1/4-inch SS valve (without its associated pipe cap) initially and once each year at 300 psig and the leak detection performed by a method capable of detecting a leak greater than 10⁻⁶ atm cc/sec at standard temperature and pressure. Any chamber that fails to pass the test shall be withdrawn from service and repaired to meet the test.
- The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR §71.12(b).
- 14. Expiration date: August 31, 1983.

REFERENCES

General Electric Company application dated March 12, 1973.

Supplements dated: April 13, 1973; March 21, 1974; and April 16, 1979.

Westinghouse Electric Corporation letter dated October 3, 1979.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

Charles F. Kene Queld

Charles E. MacDonald, Chief Transportation Certification Branch Division of Fuel Cycle and Material Safety

Date: DEC 1 8 1979

1687 117