

## UNITED STATES NUCLEAR REGULATORY COMMISSION REGION V

FRA

1950 N. CALIFORNIA BOULEVARD SUITE 202, WALNUT CREEK PLAZA WALNUT CREEK, CALIFORNIA 94596

THRE

May 29, 1979

Docket Nos. 50-528 50-529

50-530

Arizona Public Service Company P. O. Box 21666 Phoenix, Arizona 85036

Attention: Mr. E. E. Van Brunt, Jr.

Vice President, Construction Projects

Gentlemen:

This Information Notice is provided as an early notification of a possibly significant matter. It is expected that recipients will review the information for possible applicability to their facilities. No specific action or response is requested at this time. If further NRC evaluations so indicate, an IE Circular or Bulletin will be issued to recommend or request specific licensee actions. If you have questions regarding the matter, please contact the Director of the appropriate NRC Regional Office.

Sincerely

Director

Enclosure:

IE Information Notice No. 79-13

cc w/enclosures: F. W. Hartley, APS 2288 236

# UNITED STATES NUCLEAR REGULATORY COMMISSION OFFICE OF INSPECTION AND ENFORCEMENT WASHINGTON, D.C. 20555

May 29, 1979

IE Information Notice No. 79-13

INDICATION OF LOW WATER LEVEL IN THE OYSTER CREEK REACTOR

#### Summary

A loss of feedwater transient at the Oyster Creek facility on May 2, 1979, resulted in a significant reduction in water inventory within the reactor core shroud area as measured by one set of water level instruments (triple low level), while the remaining level instruments, sensing from the reactor annulus area indicated water levels above any protective feature setpoint (Figure 1). The water level within the core shroud area was reduced below the "triple low level" setpoint of 4-feet, 8-inches above the top of the fuel.

Subsequent analysis by the licensee has determined that the minimum collapsed water level (solid, without steam voids) over the top of the fuel was 1 to 1-1/2 feet.

Coolant sample analyses and offgas release rates indicate that no fuel damage occurred.

#### General

Oyster Creek is a non-jet pump BWR with licensed power of 1930 MWt. The plant was first made critical May 3, 1969.

### Status Before Transient

Operating at near full power with the main parameters at levels as follows:

1895 MWt power level
79" Yarway (13'4" over top of fuel) reactor water level
1020 psig reactor pressure
7.1x10° 4#/nr feed flow
14.8x10<sup>4</sup> gpm recirculation flow rate (4 pumps)
2288 237
12 psid core Ap

Equipment Out of Service (OOS)

"D" recirc pump OOS due to sea "B" startup transformer OOS fo

DUPLICATE DOCUMENT

Entire document previously entered into system under:

ANO

No. of pages:

11