



APPLICABLE TO:
PUBLICATION NO. NEDO-24081
T. I. E. NO. _____
TITLE LOCA Analysis for Peach
Bottom APS Unit 2
ISSUE DATE December 1977

ERRATA And ADDENDA SHEET

NO. 4
DATE December 1979
NOTE: Correct all copies of the applicable publication as specified below.

ITEM	REFERENCES (SECTION, PAGE PARAGRAPH, LINE)	INSTRUCTIONS (CORRECTIONS AND ADDITIONS)
1.	Page 4-10	Replace with revised page 4-10.
2.	Page 4-11/4-12	Replace with revised page 4-11/4-12.

POOR ORIGINAL

Table 4-3c

MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

Plant: PB-2Fuel Type: 8D274L

<u>Average Planar Exposure (Mwd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
200	11.2	1758	0.006
1,000	11.3	1765	0.006
5,000	11.9	1845	0.008
10,000	12.1	1862	0.008
15,000	12.2	1890	0.009
20,000	12.1	1891	0.009
25,000	11.6	1853	0.007
30,000	10.9	1773	0.005

Table 4-3d
 MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

Plant: PB-2Fuel Type: 8D274H*

<u>Average Planar Exposure (Mwd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
200	11.1	1755	0.006
1,000	11.2	1755	0.006
5,000	11.7	1830	0.007
10,000	12.1	1869	0.008
15,000	12.2	1894	0.009
20,000	12.0	1892	0.009
25,000	11.5	1848	0.007
30,000	10.9	1778	0.006
35,000	9.9	1664	0.003
40,000	9.3	1591	0.003

*Applicable to 80, 100 and 120 mil channels.

Table 4-3e
 MAPLHGR VERSUS AVERAGE PLANAR EXPOSURE

Plant: PB-2Fuel Type: LTA260

<u>Average Planar Exposure (Mwd/t)</u>	<u>MAPLHGR (kW/ft)</u>	<u>PCT (°F)</u>	<u>Oxidation Fraction</u>
200	11.4	1829	0.007
1,000	11.5	1839	0.008
5,000	12.1	1913	0.010
10,000	12.2	1929	0.011
15,000	12.3	1958	0.012
20,000	12.1	1961	0.012
25,000	11.7	1911	0.010
30,000	11.3	1882	0.009
35,000	10.3	1752	0.006
40,000	9.7	1678	0.004