CONTROL BLOCK   Image: A control of the state of the	NRC FOF (7-77)	LICENSEE EVENT REPORT 80 051 3 0 550
Image:	•	CONTROL BLOCK:
CONT   Provest   L 0 0 15 0 10 10 13 16 16 0 0 0 41 21 11 80 0 0 15 0 15 0 15 8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		G A E I H 2 0 0 0 - 0 0 0 0 - 0 0 0 0 - 0 0 0 0 - 0 0 0 0 0 - 0
Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator observed     Image: State of the startup/hot-standby mode, an operator of startup operator of the startup oper		REPORT LL G 0 5 0 0 0 3 6 6 0 0 4 2 1 8 0 0 0 5 0 6 8 0 9 SOURCE 60 61 DOCKET NUMBER 60 69 EVENT DATE 75 REPORT DATE 80
Image: Signature of the second service of the second serv	0 2	With the reactor in the startup/hot-standby mode, an operator observed
Image: State of the state	03	that a D/W-Torus Temp. Recorder was inoperative, which did not comply with
Image: Solid and 650 F, which did not correspond to other indications that were   Image: Solid and 650 F, which did not correspond to other indications that were     Image: Solid and 650 F, which did not correspond to other indications that were   Image: Solid and 650 F, which did not correspond to other indications that were     Image: Solid and 650 F, which did not correspond to other indications that were   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event     Image: Solid and Formation affected. This is a repetitive event   Image: Solid and Formation affected. This is a repetitive event <tr< td=""><td>0 4</td><td>Tech Specs requirement 3.3.6.4-1. All temperature readings were between</td></tr<>	0 4	Tech Specs requirement 3.3.6.4-1. All temperature readings were between
Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no effects upon public health and safety due to this     Image: comparable. There were no the comparable of the occurrence has been attributed to a loose wire on the     Image: comparable of the occurrence has been attributed to a loose wire on the     Image: comparable of the occurrence has been attributed to a loose wire on the     Image: comparable of the occurrence has been attributed to a loose wire on the     Image: comparable of the occurrence of	0 5	50° and 65° F, which did not correspond to other indications that were
0 T   event nor was safe plant operation affected. This is a repetitive event     0 T   es last reported on LER 50-366/1979-137.     0 T   state reported on LER 5000000000000000000000000000000000000	0 6	operable. There were no effects upon public health and safety due to this
Image: State reported on LER 50-366/1979-137.   Jo     Image: State reported on LER 50-366/1979-137.   Jo     Image: State reported on LER 50-366/1979-137.   State reported on LER 50-366/1979-137.     Image: State reported on LER 50-366/1979-137.   State reported on LER 50-366/1979-137.     Image: State reported on LER 50-366/1979-137.   State report of the state repo	0 7	event nor was safe plant operation affected. This is a repetitive event
y   y	0 8	as last reported on LER 50-366/1979-137.
Image:	7 B	SYSTEM CAUSE CAUSE COMPONENT CODE COMPONENT CODE SUBCODE SUBCODE COMPONENT CODE SUBCODE SUBCOD
11   "common" terminal block on the recorder. The connection was tightened     11   and all indication points were found to read correctly.     13	10	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
Image: second	1 1	"common" terminal block on the recorder. The connection was tightened
Image: Status Imag	12	and all indication points were found to read correctly.
Image: Second status <td>13</td> <td></td>	13	
PACIENT   SPOWER   OTHER STATUS   GO   Discovery   Discovery   Discovery   GO     1   5   C   GO   01   NA   IA   GO   <	(14) 7 8	BO METHOD OF
ACTIVITY CONTENT   AMOUNT OF ACTIVITY (35)   LOCATION OF RELEASE (36)     1 6   7   8   9     1 6   7   10   11   44     1 7   9   10   11   44     1 7   9   11   12   13     1 7   9   11   12   13     1 7   9   11   12   13     1 8   9   11   12   13     1 8   9   11   12   13     1 8   9   11   12   13     1 9   11   12   13   60     1 9   11   12   13   60     1 9   11   12   13   60     1 9   11   12   13   60     1 9   1   14   12   13   60     1 9   1   12   13   60   14     1 9   1   13   14   14   14     1 9   1   14   14   14   14	15	C O
NUMBER TYPE DESCRIPTION (39)   1 7 8   9 PERSONNEL INJURIES   NUMBER DESCRIPTION (41)   0 0   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 12   1 13   1 14   1 14   1 15   1 16   1 10   10 10   10 10   10 10   10 10   10 10   10 10   10 10   10 10   10 10   10 10   10 10   10   10	1 6 7 8	LEASED OF RELEASE AMOUNT OF ACTIVITY 35 Z 33 Z 34 NA
PERSONNEL INJURIES NA   1 B D D   1 B 0 0   1 B 0 0   1 B 0 0   1 B 1 12   LOSS OF OH DAMAGE TO FACILITY (4)   1 B 1   1	17	NUMBER     Type     DESCRIPTION (39)       0     0     0     (37)     Z     (39)     NA       11     12     13     13     60
Image: Solution of the contract of the contra	1 8	
10 PUBLICITY NRC USE ONLY   15000 DESCRIPTION (45) NA   10 NA IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	10	NA
NAME OF PREPARER R. T. Nix PEHONE: 912-367-7781	20	FUBLICITY NRC USE ONLY   ISUED DESCRIPTION (45)   N (44) NA
	7 8	NAME OF PREPARER R. T. Nix PEHONE: 912-367-7781

## NARRATIVE REPORT

Georgia Power Company Plant E. I. Hatch Baxley, Georgia 31513

Reportable Occurrence Report No. 50-366/1980-063.

On April 21, 1980, with the reactor in the startup/hot-standby mode, an operator observed a Drywell and Torus temperature recorder, 2T47-R626, was inoperative, which did not comply with Tech Specs requirement 3.3.6.4-1. All temperature readings for the recorder were between 5G° F and 65° F, which did not correspond to other indications of 80° F to 105° F on 2T47-R627 and 2T47-R620.

The cause of the occurrence has been attributed to a loose wire on the "common" terminal block of the recorder. The connection was tightened and all indication points were found to read correctly.

There were no effects upon public health and safety due to this event nor was safe plant operation affected. This is a repetitive event as last reported on Reportable Occurrence Report No. 50-366/1979-137. The generic review of the event did not reveal any inherent problems.