



CHEM-NUCLEAR SYSTEMS INC.

P.O. Box 1866 • Bellevue, Washington 98009 • (206) 827-07.11

March 23, 1980

Charles E. MacDonald, Chief Transportation Branch Division of Fuel Cycle & Material Safety U. S. Nuclear Regulatory Commission Washington, D.C. 20555

Reference: Docket No. 71-9108

Dear Mr. MacDonald:

We respectfully request an amendment of Certificate of Compliance No. 9108 to authorize the use of SAE, Grade 8, 3/4 - 10 x 25" long bolts (Minimum Tensile Strength - 150,000 psi, Minimum Yield Strength - 120,000 psi) for securing the primary lid to the cask body.

Drawing No. 1036-D-01, Revision H, calls out a 3/4" - 10 x 3" bolt which bottoms out before the lid is secured. The 25" bolt will not reduce the thread engagement in any way. Note No. 15 on the drawing calls out this bolt change.

We are enclosing eight (8) copies of Revision J (Revision levels I and O are not used) to Drawing No. 1036-D-01.

As required by Section 170.31 (11)(c) of 10CFR 71, we are enclosing our check in the amount of \$690.00 as payment for a minor amendment.

Sincerely,

CHEM-NUCLEAR SYSTEMS, INC.

J. Stewart Corbett

Manager, Licensing & Safety

JSC/cm

cc: Lou Reynolds - Regulatory Affairs

Karl Kinkade - Engineering Bill Mayes - Transportation

Enclosures (9)

Applicant. Received Shackman