

**INFORMATION ONLY**

8005190543

DUKE POWER COMPANY  
PROCEDURE PREPARATION  
PROCESS RECORD(1) ID No: EP/1/A/5000/0  
Change(s) 0 to  
0 Incorporated(2) STATION: McGuire Nuclear Station(3) PROCEDURE TITLE: Loss of Reactor Coolant(4) PREPARED BY: Sam Horn DATE: 2/29/80(5) REVIEWED BY: Neal McCreary DATE: 3-5-80Cross-Disciplinary Review By: \_\_\_\_\_ N/R: EDM

(6) TEMPORARY APPROVAL (IF NECESSARY):

By: \_\_\_\_\_ (SRO) Date: \_\_\_\_\_

By: \_\_\_\_\_ Date: \_\_\_\_\_

(7) APPROVED BY: Tom J. McCreary Date: 3-5-80

(8) MISCELLANEOUS:

Reviewed/Approved By: \_\_\_\_\_ Date: \_\_\_\_\_

Reviewed/Approved By: \_\_\_\_\_ Date: \_\_\_\_\_

**INFORMATION ONLY**

DUKE POWER COMPANY  
McGUIRE NUCLEAR STATION  
LOSS OF REACTOR COOLANT

- CASE I: Leak or rupture within the capability of both Centrifugal Charging Pumps
- CASE II: Leak or rupture from the vapor space of the pressurizer.
- CASE III: Leak or rupture of such magnitude that the charging pumps cannot maintain pressurizer level and pressure.

CASE "I"

LEAK OR RUPTURE WITHIN THE CAPABILITY OF BOTH CENTRIFUGAL CHARGING PUMPS

1.0 Symptoms

- 1.1 VCT level decrease or abnormal increase in frequency of auto makeup.
- 1.2 Possible pressurizer level decrease initially.
- 1.3 Possible pressurizer pressure decrease initially.
- 1.4 If in containment:
  - 1.4.1 Containment sump level increase.
  - 1.4.2 Containment temperature increase.
  - 1.4.3 Containment humidity increase.
  - 1.4.4 EMF-38 "Containment HI Part. Rad." alarm.
  - 1.4.5 EMF-39 "Containment HI Gas. Rad." alarm.
  - 1.4.6 EMF-40 "Containment HI Iod. Rad." alarm.

2.0 Immediate Action

2.1 Automatic

- 2.1.1 Charging flow increases.
- 2.1.2 Pressurizer backup heaters energize.
- 2.1.3 Containment ventilation isolation if EMF-38, 39, or 40 HI Rad alarm.
- 2.1.4 Possible safety injection actuation and Phase "A" Isolation.

2.2 Manual

- 2.2.1 Ensure all necessary automatic actions occur.
- 2.2.2 If pressurizer level is decreasing, or if normal charging is at maximum flow, change from 75 gpm to 45 gpm orifice.
- 2.2.3 Start additional charging pumps as necessary to maintain pressurizer level if SI has not actuated.
- 2.2.4 Isolate all JHI Accumulator discharge valves.

CAUTION: Inaccurate Pressurizer and S/C Level Readings will occur during accident conditions involving breaks inside containment. (This is caused by depressurization and/or reference leg heating). Refer to McGuire Data Book Curves

\_\_\_\_\_ , and curves \_\_\_\_\_

for correct conversions for actual level. Use backup instrumentation (i.e.: CA Flow, SM Pressure, NC Pressure and Wide Range Th, Tc).

### 3.0 Subsequent Action

CAUTION: Do not place systems in manual unless misoperation in automatic is apparent. If any system is placed in manual, make frequent checks for proper operation.

#### 3.1 Identify and isolate leak if possible.

3.1.1 Close all pressurizer PORV's and their associated isolation valves.

#### 3.2 If SI actuated, trip all reactor coolant pumps before reaching 1250 psig.

#### 3.3 If containment pressure is <1 psig, but not before 10 minutes after actuation, reset the SI signal, reset the D/G load sequencers and stop ECCS pumps only if the following conditions exist:

3.3.1 Pressurizer pressure  $\geq 2000$  psig and increasing, and:

3.3.2 Pressurizer level  $\geq 50\%$ , and:

3.3.3 At least one S/G has an indicated level in the narrow range, and:

3.3.4 The NC System is subcooled by  $\geq 32^\circ\text{F}$ .

CAUTION: Manually re-initiate safety injection if pressurizer pressure decreases to 1845 psig or pressurizer level decreases below 20% or highest NC Loop Th is  $>618^\circ\text{F}$ .

#### 3.4 Energize pressurizer heaters as necessary to maintain NC System pressure.

#### 3.5 If for any reason all reactor coolant pumps are tripped, ensure that core decay heat is being removed by natural circulation. Refer to OP/O/A, 6150/14 (Decay Heat Removal By Natural Circulation).

#### 3.6 If Phase "A" containment isolation and/or containment ventilation isolation occurred contact the HP Department to sample the containment atmosphere for gaseous, particulate, and iodine levels. If recommended by the HP Department after sample analysis reset Phase "A" containment isolation and verify containment monitors LEMT-38 (Containment Particulate-Low Range), LEMT-39 (Containment Gas-Low Range) and LEMT-40 (Containment Iodine-Low Range) are not in an alarm condition, reset Containment Ventilation isolation signals.

#### 3.7 Realign systems to normal when conditions warrant.

#### 3.8 Perform a Reactor Coolant System leakage calculation to determine the magnitude of the leak (if leak has been isolated).

NOTE: Makeup to the Volume Control Tank must be stopped during the calculation interval.

#### 3.9 Consult McGuire Technical Specifications (3.-6.1), considering both the magnitude and nature of the leak, and determine if operation may continue.

#### 3.10 Refer to EP O/A, 5000, 31 (Notification of Unusual Events).

- 3.11 If shutdown is required, begin unit shutdown per OP/1/A/6100/02 (Controlling Procedure for Unit Shutdown).
- 3.12 If for any reason pressurizer level cannot be maintained, open UHI Accumulator Isolation valves and manually actuate SI. Refer to CASE III of this procedure.

## CASE II

### LEAK OR RUPTURE FROM THE VAPOR SPACE OF THE PRESSURIZER

#### 1.0 Symptoms

- 1.1 "PZR Safety Discharge Hi Temp" alarm.
- 1.2 "PZR PORV Disch. Hi Temp" alarm.
- 1.3 PZR Lo Pressure.
- 1.4 Increasing PRT temp.
- 1.5 Increasing PRT pressure.
- 1.6 Increasing PRT level.
- 1.7 Decreasing pressurizer pressure without expected level decrease.

#### 2.0 Immediate Action

##### 2.1 Automatic

- 2.1.1 Safety injection actuation and Phase "A" Isolation.
- 2.1.2 Reactor trip-turbine trip.
- 2.1.3 E/S Sequencer actuation.
- 2.1.4 CA pumps start and feed steam generators.
- 2.1.5 Feedwater Isolation.

CAUTION: Inaccurate Pressurizer and S/G Level readings will occur during accident conditions involving breaks inside containment. (This is caused by depressurization and/or reference leg heatup). Refer to McGuire Data Book Curves \_\_\_\_\_, \_\_\_\_\_, and curves \_\_\_\_\_ for correct conversions for actual level. Use backup instrumentation (i.e.: CA Flow SM Pressure, NC Pressure and Wide Range Th, To).

##### 2.2 Manual

- 2.2.1 Ensure all automatic actions occur.
- 2.2.2 If reactor fails to trip, refer to Reactor Trip Procedure (EP/1/A/5000/01).
- 2.2.3 If Turbine fails to trip, refer to Turbine Trip Procedure (EP/1/A/5000/02).
- 2.2.4 If CA fails to start, manually start pumps and establish flow to S.G's.

- 2.2.5 Determine from alarms/indications if a pressurizer PORV is failed open or has failed to reseal at 2315 psig after relieving on high pressurizer pressure.
- 2.2.6 Close all pressurizer PORV's and their associated isolation valves.
- 2.2.7 Verify pressurizer spray valves are closed.

### 3.0 Subsequent Action

CAUTION: Do not place systems in manual unless misoperation in automatic is apparent. If any system is placed in manual, make frequent checks for proper operation.

- 3.1 If it is determined that a pressurizer safety valve has failed open or if the failed open pressurizer PORV's isolation valve cannot be closed, refer to CASE III of this procedure.
- 3.2 Verify all ECCS components have assumed their safeguards status. Manually align any that did not.
- 3.3 If SI actuated, trip all reactor coolant pumps before reaching 1150 psig or within 5 minutes after Phase B isolation.
- 3.4 If containment pressure is 71 psig, but not before 10 minutes after actuation, reset the SI signal and the D/G load sequencers only if the following exist:  
Reset SI and stop ECCS pumps as necessary if:  
Pressurizer pressure  $\geq 2000$  psig and increasing, and:  
Pressurizer level  $\geq 50\%$ , and:  
At least one S/G has an indicated level in the narrow range and:  
The NC System is subcooled by  $\geq 32^\circ\text{F}$ .  
CAUTION: Manually re-initiate safety injection if pressurizer pressure decreases to 1845 psig or pressurizer level decreases below 20% or highest NC Loop Th  $\geq 618^\circ\text{F}$ .
- 3.5 Energize pressurizer heaters as necessary to maintain NC System pressure.
- 3.6 Reset Phase "A" Isolation and verify that containment monitors IEMF-38 (Containment Particulate-Low Range), IEMF-39 (Containment Gas-Low Range) and IEMF-40 (Containment Iodine-Low Range) are not in an alarm condition.
- 3.7 Reset containment ventilation isolation signals.
- 3.8 Re-establish normal charging and letdown per OP/1/A/6200/01 (Chemical and Volume Control System).
- 3.9 Realign systems to normal when conditions warrant.
- 3.10 Refer to EP/0/A/5000/32 (Alert).

### CASE III

LEAK OR RUPTURE OF SUCH MAGNITUDE THAT THE CHARGING PUMPS CANNOT MAINTAIN PRESSURIZER LEVEL

### 1.0 Symptoms

- 1.1 Rapid decrease in PCR pressure and level.

- 1.2 "Ice Condenser Doors Open" alarm.
- 1.3 Containment sump level increase.
- 1.4 Containment temperature increase.
- 1.5 Containment pressure increase.
- 1.6 Containment humidity increase.
- 1.7 "EMF-38 Containment Hi Part Rad" alarm.
- 1.8 "EMF-39 Containment Hi Gas Rad" alarm.
- 1.9 "EMF-40 Containment Hi Iod. Rad" alarm.

## 2.0 Immediate Action

### 2.1 Automatic

- 2.1.1 Safety injection actuation and Phase "A" Isolation.
- 2.1.2 Reactor trip-turbine trip.
- 2.1.3 Phase B Isolation and containment spray at 3 psig Cont. pressure.
- 2.1.4 E/S Sequencer actuation.
- 2.1.5 CA pumps start and feed steam generators.
- 2.1.6 Feedwater Isolation.

### 2.2 Manual

- 2.2.1 Ensure all automatic actions occur.
- 2.2.2 If Reactor fails to trip, refer to Reactor Trip Procedure (EP/1/A/5000/01).
- 2.2.3 If Turbine fails to trip, go to Turbine Trip procedure (EP/1/A/5000/02).
- 2.2.4 If CA fails to start, manually start pumps and establish flow to S/G's.

CAUTION: Inaccurate Pressurizer and S/D Level readings will occur during accident conditions involving breaks inside containment. (This is caused by depressurization and/or reference leg heatup). Refer to McGuire Data Book Curves \_\_\_\_\_, \_\_\_\_\_ and curves \_\_\_\_\_ for correct conversions for actual level. Use backup instrumentation (i.e.: CA Flow, SM Pressure, NC Pressure and Wide Range Th, To).

## 3.0 Subsequent Action

CAUTION: Do not place systems in manual unless misoperation in automatic is apparent. If any system is placed in manual, make frequent checks for proper operation.

- 3.1 Verify all Emergency Core Cooling components have assumed their safeguard status. Manually align any that did not.
- 3.2 Trip the reactor coolant pumps if SI activated, before reaching 1050 psig.

- 3.2.1 During Upper Head Injection Groups 3 & 4 completely lighted, Groups 1, 2, 5, 6, & 7 completely dark.
- 3.2.2 After Upper Head Injection Group 3, 4, & 6 completed lighted, Groups 1, 2, 5, & 7 completely dark.
- 3.2.3 If either train of the BOP ESF Components monitor lights in Group 1 and Group 4 are out of sequence with the other lights in their respective group, the OAC must be interrogated to obtain a printout of misaligned BOP ESF Components.

NOTE: If the Phase A Containment Isolation Monitor Lights are also out of sequence, manually initiate Phase A Containment Isolation.

- 3.3 Announce occurrence over plant paging system.
- 3.4 If Phase B isolation occurs, the RV pumps must be stopped. The Reactor Coolant pumps must be tripped within 5 minutes if not previously tripped.  
NOTE: Verify Phase "B" isolation and actuation of containment spray at 3 psig containment pressure if not done previously.
- 3.5 Verify proper operation of the Annulus Ventilation System (OP/L/A/6-50/02).
- 3.6 Verify Upper Head Injection Accumulator Tank discharge at 1240 psig and discharge isolation valves automatically close and gag after tank contents are discharged.
- 3.7 Verify all four Cold Leg Accumulators discharge between 400 and 450 psig.
- 3.8 If the OAC is inoperable, perform BOP ESF Components alignment checklist, Enclosure 5.1.
- 3.9 Perform Post Accident Checklist, Enclosure 5.2.
- 3.10 Refer to EP/O/A/5000/33 (Site Emergency).
- 3.11 If logic test on FWST level is in progress, notify I & E Department to place circuit back to normal.
- 3.12 Align control board switches to conform with plant status.
- 3.13 When the FWST level decreases to the low level alarm point (12'6") but not earlier than 10 minutes after safety injection actuation, perform the following to establish containment sump, cold leg recirculation:
  - 3.13.1 Manually reset the Safety Injection signal and the Diesel Generator Load Sequencers.
  - 3.13.2 Change Residual Heat Removal Pumps suction from the FWST to the Containment Recirc. Sump:  
NOTE: If manual swap of RD pumps suction is not accomplished prior to 8.0 ft. FWST Lvl., insure automatic swap occurs prior to reaching 7 ft. FWST Lvl.
    - 3.13.2.1 Open LND-15- (Containment Sump Line 15 Isolation). As it opens, verify the closing of LND- (NO Loop 3 to RD Pump 15 Containment Isol. Outside).

- 3.13.2.2 Open LNI-185 (Containment Sump Line 1A Isolation). As it opens, verify the closing of LND-19 (NC Loop 1C to ND Pump 1A Containment Isol. Outside).
- NOTE: If FWST emergency Lo Level (0.9 ft.) is reached before change over to the recirculation sump is completed, secure all pumps taking suction on the FWST.
- 3.13.3 Reinstate control power to LFW-27 (FWST to ND Pump Isolation).
- 3.13.4 Close:
- LFW-27 (FWST to ND Pump Isolation).
  - LND-30 (ND HX 1A Outlet Crossover Block)
  - LND-15 (ND HX 1B Outlet Crossover Block)
- 3.13.5 Stop Containment spray pumps 1A and 1B.
- 3.13.6 Close LNS-20 (NS Pump 1A Suction from RWST Block).
- 3.13.7 Open LNS-18 (NS Pump 1A Suction from Containment Sump Block).
- 3.13.8 Open LPN-134 (NS Heat Exchanger 1A Supply Isolation).
- 3.13.9 Start Containment Spray Pump 1A.
- 3.13.10 Close LNS-3 (NS Pump 1B Suction from RWST Block).
- 3.13.11 Open LNS-1 (NS Pump 1B Suction from Containment Sump Block).
- 3.13.12 Open LPN-235 (NS Heat Exchanger 1B Supply Isolation).
- 3.13.13 Start Containment Spray Pump 1B.
- 3.13.14 Close:
- LNI-115 (Safety Inj. Pump 1A Miniflow Line Isol.).
  - LNI-114 (Safety Inj. Pump 1B Miniflow Line Isol.).
- 3.13.15 Reinstate control power to LNI-147 (Safety Inj. Pumps Miniflow Hdr. to RWST).
- 3.13.16 Close LNI-147 (Safety Inj. Pumps Miniflow Hdr. to RWST).
- 3.13.17 Open LNI-136 (ND HX 1B to Safety Inj. Pump 1B).
- 3.13.18 Reinstate control power to LNI-100 (RWST to Safety Inj. Pumps).
- 3.13.19 Close LNI-100 (RWST to Safety Inj. Pumps).
- 3.13.20 Wait until the "FWST Lo-Lo Lvl" alarm (0.9') is received before proceeding to the next step.
- 3.13.21 Open LND-58 (ND HX 1A Outlet to Centrifugal Charging Pumps 1A & 1B Block).
- 3.13.22 Open LNI-332 and LNI-333 (Safety Inj. Pump Suction Crossover from NV).
- Open LNI-334 (Safety Injection Pump Suction Crossover from NV Isol.).
- 3.13.23 Close LNV-221 and LNV-222 (Centrifugal Charging Pumps Suction from FW System).
- 3.13.24 Start Hydrogen Recombiners in accordance with OP O/A/6-50 10 (Hydrogen Skimmer, Cont. Air Return, Hydrogen Recombiner and Hydrogen Purge System) when Hydrogen concentration reaches 1%.

- 3.13.25 After one hour, if offsite power has not been interrupted, stop the Emergency Diesel Generators per OP/1/A/6350/02 (Diesel Generator).
- 3.13.26 If a loss of offsite power occurs while in the Cold Leg Recirculation mode, refer to section 4.0 of this procedure.
- 3.14 Notify Chemistry Department and HP Department to obtain pH sample of containment sump water and to begin periodic sampling of containment for hydrogen concentration.
- 3.15 If containment pressure increases to 13.0 psi following depletion of the ice in the ice condenser, align the Residual Heat Removal spray headers as follows:
- 3.15.1 Verify that LND-30 (ND HX 1A Outlet Crossover Block) and LND-15 (ND HX 1B Outlet Crossover Block) are closed.
- NOTE: Do not initiate ND System Spray until at least one hour after Safety Injection has been initiated.
- 3.15.2 Reinstate power to the following valves:
- LNI-173 (ND Hdr. to NC Cold Leg Loops 1 and 2)
- LNI-178 (ND Hdr. to NC Cold Leg Loops 3 and 4)
- 3.15.3 Close LNI-173 (ND Hdr. to NC Cold Leg Loops 1 and 2).
- 3.15.4 When LNI-173 is fully closed, open LNS-43 (ND Pump 1A Disch. to NS Nozzles Containment Isolation Outside).
- 3.15.5 Close LNI-178 (ND Hdr. to NC Cold Leg Loops 3 and 4).
- 3.15.6 When LNI-178 is fully closed, open LNS-38 (ND Pump 1B Disch. to NS Nozzles Containment Isolation Outside).
- 3.16 When containment pressure has decreased to an allowable level, the Residual Heat Removal Pumps discharge may be realigned to the Reactor Coolant System Cold Legs as follows:
- 3.16.1 Close LNS-43 (ND Pump 1A Disch. to NS Nozzles Containment Isolation Outside).
- 3.16.2 When LNS-43 is fully closed, open LNI-173 (ND Hdr. to NC Cold Leg Loops 1 and 2).
- 3.16.3 Close LNS-38 (ND Pump 1B Disch. to NS Nozzles Containment Isolation Outside).
- 3.16.4 When LNS-38 is fully closed, open LNI-178 (ND Hdr. to NC Cold Leg Loops 3 and 4).
- NOTE: Cold Leg Recirculation Phase Monitor Light Configuration.
- Group 2 and 4 completely lighted.
- Groups 1, 3, 5, 6, and 7 completely dark.
- NOTE: Group 6 should be lighted during recirculation mode if Upper Head Head Injection has actuated and secured.

3.16.5 Start Hydrogen Purge System per OP/O/A/6450/10 (Hydrogen Skimmer Cont. Air Return, Hydrogen Recombiner and Hydrogen Purge System) if Hydrogen Concentration increases to 3.5%. Reduce concentration to <3% and realign.

3.17 Approximately 15 hours after the accident, realign the Safety Injection System for Hot Leg recirculation as follows:

3.17.1 Reinstate power to the following valves:

LNI-173 (ND Hdr. to NC Cold Leg Loops 1 and 2)

LNI-178 (ND Hdr. to NC Cold Leg Loops 3 and 4)

LNI-183 (ND Hdr. to NC Hot Legs Isolation)

LNI-121 (Safety Injection Pump 1A Hot Leg Injection Header Isol.)

LNI-162 (Safety Injection Pumps Cold Leg Inj. Hdr. Iso.)

LNI-152 (Safety Inj. Pump 1B Hot Leg Inj. Hdr. Iso.)

3.17.2 Close LNI-173 (ND Hdr. to NC Cold Leg Loop 1 and 2).

3.17.3 Open LND-30 (ND EX 1A Outlet Crossover Block).

3.17.4 Open LNI-183 (ND Hdr. to NC Hot Legs Isolation).

3.17.5 Close LNI-178 (ND Hdr. to NC Cold Leg Loops 3 and 4).

3.17.6 Open LND-15 (ND EX 1B Outlet Crossover Block).

3.17.7 Stop Safety Injection Pump 1A.

3.17.8 Close LNI-118 (Safety Injection 1A Cold Leg Inj. Line Iso.).

3.17.9 Open LNI-121 (Safety Inj. Pump 1A Hot Leg Inj. Header Isolation).

3.17.10 Start Safety Injection Pump 1A and verify flow to the Reactor Coolant System through the Hot Leg Header.

3.17.11 Stop Safety Injection Pump 1B.

3.17.12 Close:

LNI-162 (Safety Inj. Pumps Cold Leg Inj. Hdr. Isol.)

LNI-150 (Safety Inj. Pump 1B Cold Leg Inj. Lines Isol.)

3.17.13 Open LNI-152 (Safety Inj. Pump 1B Hot Leg Inj. Header Isolation).

3.17.14 Start Safety Injection Pump 1B and verify flow to the Reactor Coolant System through the Hot Leg Header.

NOTE: The Residual Heat Removal and Safety Injection pump are now aligned for Hot Leg recirculation.

NOTE: Monitor Light Configuration during Hot Leg Recirculation.  
Groups 2, 4, 5, 6 completely lighted  
Groups 1, 3, 7 completely dark

3.18 Verify that when containment pressure decreases to less than .15 psig containment spray pumps shutdown.

#### 4.0 Recovery from Loss of Offsite Power While in Cold Leg Recirculation

4.1 One minute after the loss of power occurred reset the Diesel Generator Load Sequencers.

NOTE: Wait one minute before resetting to allow all loads to be sequenced in.

4.2 Secure the following loads.

- 4.2.1 Centrifugal Charging Pumps A & B
- 4.2.2 Pressurizer Backup Heaters
- 4.2.3 Boron Injection Tank Heaters
- 4.2.4 Boron Injection Recirculation Pumps A & B
- 4.2.5 Boric Acid Transfer Pumps
- 4.2.6 Pipe Tunnel Booster Fans
- 4.2.7 Control Rod Drive Vent Fans
- 4.2.8 Lower Containment Cooling Units
- 4.2.9 Upper Containment Cooling Units
- 4.2.10 Upper Containment Return Air Fans
- 4.2.11 Incore Instrument Room Air Handling Units

4.3 Restart the following loads in the sequence listed.

NOTE: In order not to overload the Diesel Generator, start one load, then wait 15 sec., check voltage, amperage and load on the Diesel Generator, then start the next load.

- 4.3.1 Residual Heat Removal Pumps A & B.
- 4.3.2 Safety Injection Pumps A & B.
- 4.3.3 Centrifugal Charging Pumps A & B
- 4.3.4 Annulus Ventilation Fans A & B, and verify proper operation per OP/1/A/6450/02 (Annulus Ventilation System).
- 4.3.5 Annulus Ventilation Preheaters A & B.
- 4.3.6 Containment Air Return Fans A & B.
- 4.3.7 Containment Spray Pumps A & B.
- 4.3.8 If the following were operating prior to the loss of power, restart them.
  - 4.3.8.1 Hydrogen Recombiners A & B.
  - 4.3.8.2 Hydrogen Skimmer Fans A & B.
- 4.3.9 Start Spent Fuel Cooling Pump A or B if desired.

4.4 Verify the proper operation of the following loads.

- 4.4.1 Vital Battery Chargers EVCA, EVCB, EVCC, EVCD.
- 4.4.2 Load Centers ELMA, ELMB, ELMC, ELMD.
- 4.4.3 Power Panelboards EMA and EMB.
- 4.4.4 ND and NS Room Sump Pumps.
- 4.4.5 A/C System Switchgear Room Fans SCR-AHU-A, B, C, and D.
- 4.4.6 D/G A and B Auxiliaries.
- 4.4.7 Blowers for the following IMF Monitors.
  - 4.4.7.1 IMF-32 (Condenser Air Ejector)
  - 4.4.7.2 IMF-35, 36, and 37 (Unit Vent Particulate, Gas and Iodine)
  - 4.4.7.3 IMF-38, 39, and 40 (Containment Particulate, Gas and Iodine)
  - 4.4.7.4 IMF-41 (Auxiliary Building Ventilation)

- 4.4.7.5 EMF-42 (Fuel Building Ventilation)
- 4.4.7.6 EMF-43A (Control Room Air Intake A)
- 4.4.7.7 EMF-43B (Control Room Air Intake B)
- 4.4.8 Auxiliary Building Filtered Exhaust Fans A and B.
- 4.4.9 Comp. Cooling pumps A1, A2, B1 and B2.
- 4.4.10 Nuclear Service Water Pumps A and B.
- 4.4.11 Auxiliary Feedwater Pumps A and B.
- 4.4.12 Control Area Air Conditioning System.
- 4.4.13 Battery Room Exhaust Fans 1 and 2.
- 4.4.14 Ground Water Drainage System Pumps.

5.0 Enclosures

- 5.1 BOP ESF Components Alignment Checklist.
- 5.2 Post Accident Valve Checklist.

DUKE POWER COMPANY  
MAGUIRE NUCLEAR STATION  
UNIT # 1

PAGE 1 OF 5

EP/1/A/5000/03  
LOSS OF REACTOR COOLANT  
BOP ESF COMPONENTS  
ALIGNMENT CHECKLIST  
ENCLOSURE 5.1

| VALVE NO. | COMPONENT NAME                                  | POSITION | INITIAL |
|-----------|-------------------------------------------------|----------|---------|
| 1BB-1-B   | STM. GEN. 1A BLOWDOWN CONTAINMENT OUTSIDE ISOL. | CLOSED   |         |
| 1BB-2-B   | STM. GEN. 1B BLOWDOWN CONTAINMENT OUTSIDE ISOL. | CLOSED   |         |
| 1BB-3-B   | STM. GEN. 1C BLOWDOWN CONTAINMENT OUTSIDE ISOL. | CLOSED   |         |
| 1BB-4-B   | STM. GEN. 1D BLOWDOWN CONTAINMENT OUTSIDE ISOL. | CLOSED   |         |
| 1BB-1-A   | STM. GEN. 1A BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-2-A   | STM. GEN. 1B BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-3-A   | STM. GEN. 1C BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-4-A   | STM. GEN. 1D BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-10-A  | STM. GEN. 1A BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-11-A  | STM. GEN. 1B BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-12-A  | STM. GEN. 1C BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1BB-13-A  | STM. GEN. 1D BLOWDOWN CONTAINMENT INSIDE ISOL.  | CLOSED   |         |
| 1CF-17    | STM. GEN. 1B FDW CONTROL                        | CLOSED   |         |
| 1CF-20    | STM. GEN. 1C FDW CONTROL                        | CLOSED   |         |
| 1CF-22    | STM. GEN. 1B FDW CONTROL                        | CLOSED   |         |
| 1CF-32    | STM. GEN. 1A FDW CONTROL                        | CLOSED   |         |
| 1CF-24    | STM. GEN. 1D FDW CONTAINMENT ISOLATION          | CLOSED   |         |
| 1CF-28    | STM. GEN. 1C FDW CONTAINMENT ISOLATION          | CLOSED   |         |
| 1CF-30    | STM. GEN. 1B FDW CONTAINMENT ISOLATION          | CLOSED   |         |
| 1CF-33    | STM. GEN. 1A FDW CONTAINMENT ISOLATION          | CLOSED   |         |
| 1CF-104   | STM. GEN. 1A FDW CONTROL BYPASS CONTROL         | CLOSED   |         |
| 1CF-105   | STM. GEN. 1B FDW CONTROL BYPASS CONTROL         | CLOSED   |         |
| 1CF-106   | STM. GEN. 1C FDW CONTROL BYPASS CONTROL         | CLOSED   |         |
| 1CF-107   | STM. GEN. 1D FDW CONTROL BYPASS CONTROL         | CLOSED   |         |
| 1FW-1-A   | REFUELING WATER LOOP ISOLATION                  | CLOSED   |         |

DUKE POWER COMPANY  
McGUIRE NUCLEAR STATION  
UNIT # 1

PAGE 1 OF 8

EP 1/A/5000/03  
LOSS OF REACTOR COOLANT  
SOP ESF COMPONENTS  
ALIGNMENT CHECKLIST  
ENCLOSURE 5.1

| VALVE NO. | COMPONENT NAME                                         | POSITION | INITIAL |
|-----------|--------------------------------------------------------|----------|---------|
| 1FW-11-B  | REFUELING WATER LOOP ISOLATION                         | CLOSED   |         |
| 1FW-12-A  | FIRST RECIRCULATION LOOP ISOLATION                     | CLOSED   |         |
| 1FW-12-B  | FIRST RECIRCULATION LOOP ISOLATION                     | CLOSED   |         |
| 1XC-1-A   | AUX. BLDG. NON-ESS. RETURN AUTO ISOL.                  | CLOSED   |         |
| 1XC-1-B   | AUX. BLDG. NON-ESS. RETURN AUTO ISOL.                  | CLOSED   |         |
| 1XC-3-A   | REACTOR BLDG. NON-ESS. RETURN AUTO ISOL.               | *CLOSED  |         |
| 1XC-3-B   | REACTOR BLDG. NON-ESS. RETURN AUTO ISOL.               | *CLOSED  |         |
| 1XC-50-A  | TRAIN 1A TO AUX. BLDG. NON-ESS. SUPPLY HDR. AUTO ISOL. | CLOSED   |         |
| 1XC-50-B  | TRAIN 1B TO AUX. BLDG. NON-ESS. SUPPLY HDR. AUTO ISOL. | CLOSED   |         |
| 1XC-50-A  | ND EX 1A AUTO SUPPLY                                   | OPEN     |         |
| 1XC-51-B  | ND EX 1B AUTO SUPPLY                                   | OPEN     |         |
| 1XC-129-B | TRAIN 1B TO RB NON-ESS. SUPPLY HDR. AUTO ISOL.         | *CLOSED  |         |
| 1XC-130-A | TRAIN 1A TO RB NON-ESS. SUPPLY HDR. AUTO ISOL.         | *CLOSED  |         |
| 1XC-309-B | EXCESS LETDOWN EX SUPPLY PENT. ISOLATION (OUTSIDE)     | CLOSED   |         |
| 1XC-310-B | EXCESS LETDOWN EX RETURN PENT. ISOLATION (OUTSIDE)     | CLOSED   |         |
| 1XC-320-A | NCOT EX SUPPLY HDR. PENT ISOL. (OUTSIDE)               | CLOSED   |         |
| 1XC-321-B | NCOT EX RETURN HDR. PENT ISOL. (INSIDE)                | CLOSED   |         |
| 1XC-330-A | NCOT EX RETURN HDR. PENT ISOL. (OUTSIDE)               | CLOSED   |         |
| 1XC-330-B | NC PUMP SUPPLY HEADER PENT ISOL. (OUTSIDE)             | *CLOSED  |         |
| 1XC-330-B | NC PUMP RETURN HEADER PENT ISOL. (INSIDE)              | *CLOSED  |         |
| 1XC-330-A | NC PUMP RETURN HEADER PENT ISOL. (OUTSIDE)             | *CLOSED  |         |
| 1XC-330-B | REACTOR BLDG. DRAIN HDR. INSIDE CONT. ISOL.            | CLOSED   |         |
| 1XC-330-A | REACTOR BLDG. DRAIN HDR. OUTSIDE CONT. ISOL.           | CLOSED   |         |
| 1XC-160   | REACTOR MAKEUP WATER CONT. SUPPLY ISOL. OUTSIDE        | CLOSED   |         |
| 1XC-195   | NC PUMP MOTOR OIL CONTAINMENT ISOL. OUTSIDE            | CLOSED   |         |
| 1XC-196   | NC PUMP MOTOR OIL CONTAINMENT ISOL. INSIDE             | CLOSED   |         |

\*PHASE 1 ISOLATION

DUKE POWER COMPANY  
McGUIRE NUCLEAR STATION  
UNIT # 1

PAGE 1 OF 3

EP/1/A/5000/03  
LOSS OF REACTOR COOLANT  
BOP ESF COMPONENTS  
ALIGNMENT CHECKLIST  
ENCLOSURE 5.1

| TAG/VE NO. | COMPONENT NAME                                       | POSITION | INITIAL |
|------------|------------------------------------------------------|----------|---------|
| LNM-188-A  | WT PUMP 1A TO WHI ACCUMULATOR FILL LINE ISOL.        | CLOSED   |         |
| LNM-3-A    | PER LIQUID SAMPLE LINE INSIDE CONT. ISOL.            | CLOSED   |         |
| LNM-6-A    | PER STEAM SAMPLE LINE INSIDE CONT. ISOL.             | CLOSED   |         |
| LNM-7-B    | PER SAMPLE HEADER OUTSIDE CONT. ISOLATION            | CLOSED   |         |
| LNM-12-A   | NO HOT LEG #1 SAMPLE LINE INSIDE CONT. ISOLATION     | CLOSED   |         |
| LNM-15-A   | NO HOT LEG #4 SAMPLE LINE INSIDE CONT. ISOLATION     | CLOSED   |         |
| LNM-16-B   | NO HOT LEGS SAMPLE HDR. OUTSIDE CONT. ISOLATION      | CLOSED   |         |
| LNM-17-B   | WT ACCUMULATOR 1A SAMPLE LINE INSIDE CONT. ISOLATION | CLOSED   |         |
| LNM-18-B   | WT ACCUMULATOR 1B SAMPLE LINE INSIDE CONT. ISOLATION | CLOSED   |         |
| LNM-19-B   | WT ACCUMULATOR 1C SAMPLE LINE INSIDE CONT. ISOLATION | CLOSED   |         |
| LNM-21-B   | WT ACCUMULATOR 1D SAMPLE LINE INSIDE CONT. ISOLATION | CLOSED   |         |
| LNM-22-A   | WT ACCUMULATORS SAMPLE HDR. OUTSIDE CONT. ISOLATION  | CLOSED   |         |
| LNM-187-A  | SG 1A UPPER SHELL SAMPLE CONT. ISOL. INSIDE          | CLOSED   |         |
| LNM-190-A  | SG 1B BLOWDOWN LINE SAMPLE CONT. ISOL. INSIDE        | CLOSED   |         |
| LNM-191-B  | SG 1A SAMPLE HDR. CONT. ISOL. OUTSIDE                | CLOSED   |         |
| LNM-197-B  | SG 1B UPPER SHELL SAMPLE CONT. ISOL. INSIDE          | CLOSED   |         |
| LNM-200-B  | SG 1B BLOWDOWN LINE SAMPLE CONT. ISOL. INSIDE        | CLOSED   |         |
| LNM-201-A  | SG 1B SAMPLE HDR. CONT. ISOL. OUTSIDE                | CLOSED   |         |
| LNM-207-A  | SG 1C UPPER SHELL SAMPLE CONT. ISOL. INSIDE          | CLOSED   |         |
| LNM-210-A  | SG 1C BLOWDOWN LINE SAMPLE CONT. ISOL. INSIDE        | CLOSED   |         |
| LNM-211-B  | SG 1C SAMPLE HDR. CONT. ISOL. OUTSIDE                | CLOSED   |         |
| LNM-217-B  | SG 1D UPPER SHELL SAMPLE CONT. ISOL. INSIDE          | CLOSED   |         |
| LNM-220-B  | SG 1D BLOWDOWN LINE SAMPLE CONT. ISOL. INSIDE        | CLOSED   |         |
| LNM-221-A  | SG 1D SAMPLE HDR. CONT. ISOL. OUTSIDE                | CLOSED   |         |
| LEN-1-B    | RC SUPPLY A SHUTOFF                                  | CLOSED   |         |
| LEN-2-A    | RC SUPPLY A SHUTOFF                                  | CLOSED   |         |

DUKE POWER COMPANY  
 HANCOCK NUCLEAR STATION  
 UNIT # 1

PAGE 07 2

EP/1/A/5000/03  
 LOSS OF REACTOR COOLANT  
 BOP ISF COMPONENTS  
 ALIGNMENT CHECKLIST  
 ENCLOSURE 5.1

| VALVE NO. | COMPONENT NAME                              | POSITION | INITIAL |
|-----------|---------------------------------------------|----------|---------|
| 12N-4-A   | RC SUPPLY B SHUTOFF                         | CLOSED   |         |
| 12N-4-B   | RC SUPPLY B SHUTOFF                         | CLOSED   |         |
| 12N-1-A   | ENCLP SUPPLY A SHUTOFF                      | CLOSED   |         |
| 12N-1-B   | ENCLP SUPPLY B SHUTOFF                      | OPEN     |         |
| 12N-10-A  | LOW LEVEL SUPPLY B SHUTOFF                  | CLOSED   |         |
| 12N-11-B  | LOW LEVEL SUPPLY B SHUTOFF                  | CLOSED   |         |
| 12N-12-A  | LOW LEVEL SUPPLY A SHUTOFF                  | OPEN     |         |
| 12N-12-B  | LOW LEVEL SUPPLY A SHUTOFF                  | OPEN     |         |
| 12N-13-A  | RN CHANNEL SUPPLY CROSSOVER ISOLATION       | CLOSED   |         |
| 12N-13-B  | RN CHANNEL SUPPLY CROSSOVER ISOLATION       | CLOSED   |         |
| 12N-14-A  | RN CHANNEL 1A SUPPLY ISOLATION              | OPEN     |         |
| 12N-14-B  | RN CHANNEL 1B SUPPLY ISOLATION              | OPEN     |         |
| 12N-15-A  | NONESSENTIAL HEADER SUPPLY 1A ISOLATION     | *CLOSED  |         |
| 12N-15-B  | NONESSENTIAL HEADER SUPPLY 1B ISOLATION     | CLOSED   |         |
| 12N-16-A  | 2B NONESSENTIAL SUPPLY ISOLATION            | CLOSED   |         |
| 12N-17-A  | NONESSENTIAL HEADER SUPPLY 1B ISOLATION     | CLOSED   |         |
| 12N-18-B  | 2B NONESSENTIAL RETURN ISOLATION            | CLOSED   |         |
| 12N-19-A  | 2B NONESSENTIAL RETURN ISOLATION            | CLOSED   |         |
| 12N-20-A  | 1A DIESEL GENERATOR EX SUPPLY ISOLATION     | OPEN     |         |
| 12N-21-A  | COMPONENT COOLING EX 1A SUPPLY ISOLATION    | OPEN     |         |
| 12N-22-A  | 1B PUMP 1A COOLER COMPLEX SUPPLY ISOLATION  | OPEN     |         |
| 12N-23-A  | 1B PUMP 1A COOLER COMPLEX SUPPLY ISOLATION  | OPEN     |         |
| 12N-24-A  | 1B PUMP MOTOR 1A 1B COOLER SUPPLY ISOLATION | OPEN     |         |
| 12N-25-A  | 1B PUMP MOTOR 1A 1B COOLER SUPPLY ISOLATION | OPEN     |         |
| 12N-26-A  | 1B PUMP MOTOR 1A 1B COOLER SUPPLY ISOLATION | OPEN     |         |

\*PHASE B ISOLATION

DUKE POWER COMPANY  
 MAGUIRE NUCLEAR STATION  
 UNIT # 1

PAGE 1 OF 1

IS 172/5000/03  
 LOSS OF REACTOR COOLANT  
 BOP ESF COMPONENTS  
 ALIGNMENT CHECKLIST  
 ENCLOSURE 3.1

| TALTE NO. | COMPONENT NAME                                  | POSITION | INITIAL |
|-----------|-------------------------------------------------|----------|---------|
| LRN-147-A | RC DISCHARGE A ISOLATION                        | OPEN     |         |
| LRN-148-B | RC DISCHARGE A ISOLATION                        | OPEN     |         |
| LRN-149-A | ENSWP DISCHARGE A ISOLATION                     | CLOSED   |         |
| LRN-150-A | RN CHANNEL DISCHARGE CROSSOVER ISOLATION        | CLOSED   |         |
| LRN-151-B | RN CHANNEL DISCHARGE CROSSOVER ISOLATION        | CLOSED   |         |
| LRN-152-B | ENSWP DISCHARGE B ISOLATION                     | OPEN     |         |
| LRN-153-B | LB DIESEL GENERATOR EX SUPPLY ISOLATION         | OPEN     |         |
| LRN-157-B | RC EX LB SUPPLY ISOLATION                       | OPEN     |         |
| LRN-164-B | NV PUMP LB COOLER COMPLEX SUPPLY ISOLATION      | OPEN     |         |
| LRN-215-B | NI PUMP LB COOLER COMPLEX SUPPLY ISOLATION      | OPEN     |         |
| LRN-227-B | NS PUMP MOTOR LB ES COOLER SUPPLY ISOLATION     | OPEN     |         |
| LRN-231-B | ND PUMP MOTOR LB ES COOLER SUPPLY ISOLATION     | OPEN     |         |
| LRN-240-B | NE PUMP MOTOR LB ES COOLER SUPPLY ISOLATION     | OPEN     |         |
| LRN-251-B | NONESSENTIAL SUPPLY TO RB OUTSIDE ISOL.         | *CLOSED  |         |
| LRN-252-A | NONESSENTIAL SUPPLY TO RB INSIDE ISOL.          | *CLOSED  |         |
| LRN-276-A | NONESSENTIAL RETURN FROM RB INSIDE ISOL.        | *CLOSED  |         |
| LRN-277-B | NONESSENTIAL RETURN FROM RB OUTSIDE ISOL.       | *CLOSED  |         |
| LRN-279-B | UNIT 1 AB VENTILATION SYSTEM ISOLATION          | CLOSED   |         |
| LRN-283-A | RC DISCHARGE B ISOLATION                        | CLOSED   |         |
| LRN-284-B | RC DISCHARGE B ISOLATION                        | CLOSED   |         |
| LRN-290-A | ESSENTIAL HEADER 1A RETURN ISOL.                | OPEN     |         |
| LRN-291-B | ESSENTIAL HEADER 1B RETURN ISOL.                | OPEN     |         |
| LRN-299-A | UNIT 1 AB VENTILATION SYSTEM RETURN ISOL.       | CLOSED   |         |
| LRN-301-A | CONTAINMENT VENTILATION SYSTEM SUPPLY ISOLATION | *CLOSED  |         |
| LRN-302-B | CONTAINMENT VENTILATION SYSTEM SUPPLY ISOLATION | *CLOSED  |         |

\*PHASE B ISOLATION

DUKE POWER COMPANY  
McGUIRE NUCLEAR STATION  
UNIT # 1

PAGE 6 OF 8

EP/1/A/5000/03  
LOSS OF REACTOR COOLANT  
BOP ISF COMPONENTS  
ALIGNMENT CHECKLIST  
ENCLOSURE 5.1

| VALVE NO. | COMPONENT NAME                                         | POSITION | INITIAL |
|-----------|--------------------------------------------------------|----------|---------|
| LRV-12-A  | LOWER CONT. VENT. UNIT SUPPLY CONT. ISOL. (OUTSIDE)    | *CLOSED  |         |
| LRV-13-B  | LOWER CONT. VENT. UNIT SUPPLY CONT. ISOL. (INSIDE)     | *CLOSED  |         |
| LRV-14-A  | LOWER CONT. VENT. UNIT DISCHARGE CONT. ISOL. (INSIDE)  | *CLOSED  |         |
| LRV-15-B  | LOWER CONT. VENT. UNIT DISCHARGE CONT. ISOL. (OUTSIDE) | *CLOSED  |         |
| LRV-16-A  | UPPER CONT. VENT. UNIT SUPPLY CONT. ISOL. (OUTSIDE)    | *CLOSED  |         |
| LRV-16-B  | UPPER CONT. VENT. UNIT SUPPLY CONT. ISOL. (INSIDE)     | *CLOSED  |         |
| LRV-161-A | UPPER CONT. VENT. UNIT DISCHARGE CONT. ISOL. (INSIDE)  | *CLOSED  |         |
| LRV-161-B | UPPER CONT. VENT. UNIT DISCHARGE CONT. ISOL. (OUTSIDE) | *CLOSED  |         |
| LSM-1     | MAIN STEAM 1B ISOLATION                                | *CLOSED  |         |
| LSM-2     | MAIN STEAM 1C ISOLATION                                | *CLOSED  |         |
| LSM-3     | MAIN STEAM 1B ISOLATION                                | *CLOSED  |         |
| LSM-7     | MAIN STEAM 1A ISOLATION                                | *CLOSED  |         |
| LSM-9     | MAIN STEAM 1C ISOLATION BYPASS CONTROL                 | *CLOSED  |         |
| LSM-10    | MAIN STEAM 1C ISOLATION BYPASS CONTROL                 | *CLOSED  |         |
| LSM-11    | MAIN STEAM 1B ISOLATION BYPASS CONTROL                 | *CLOSED  |         |
| LSM-12    | MAIN STEAM 1A ISOLATION BYPASS CONTROL                 | *CLOSED  |         |
| LVE-5-A   | CONT. H. PURGE TO ANNULUS INSIDE CONT. ISOL.           | CLOSED   |         |
| LVE-6-B   | CONT. H. PURGE TO ANNULUS OUTSIDE CONT. ISOL.          | CLOSED   |         |
| LVE-8-A   | CONT. H. PURGE BLOWER INLET                            | CLOSED   |         |
| LVE-10-A  | CONT. H. PURGE BLOWER OUTLET CONT. ISOL. OUTSIDE       | CLOSED   |         |
| LVE-119-B | "A" HEADER CONTAINMENT OUTSIDE ISOLATION               | CLOSED   |         |
| LVE-148-B | INSTRUMENT AIR UPPER CONTAINMENT OUTSIDE ISOL.         | CLOSED   |         |
| LVE-150-B | INSTRUMENT AIR LOWER CONTAINMENT OUTSIDE ISOL.         | CLOSED   |         |
| LVE-160-B | "B" HEADER CONTAINMENT OUTSIDE ISOLATION               | CLOSED   |         |

\*PHASE B ISOLATION

DUKE POWER COMPANY  
 MONTICELLO NUCLEAR STATION  
 DATE # \_\_\_\_\_

PAGE \_\_\_\_\_ OF \_\_\_\_\_

EP/1/A/5000/03  
 LOSS OF REACTOR COOLANT  
 BOP ISF COMPONENTS  
 ALIGNMENT CHECKLIST  
 ENCLOSURE 5.1

| TALITE NO. | COMPONENT NAME                                           | POSITION | STATUS |
|------------|----------------------------------------------------------|----------|--------|
| 1VS-11-B   | UNIT 1 CONTAINMENT STATION AIR OUTSIDE ISOL.             | CLOSED   |        |
| 1VF-1-B    | UPPER CONTAINMENT PURGE SUPPLY #1 OUTSIDE ISOL.          | CLOSED   |        |
| 1VF-1-A    | UPPER CONTAINMENT PURGE SUPPLY #1 INSIDE ISOL.           | CLOSED   |        |
| 1VF-2-B    | UPPER CONTAINMENT PURGE SUPPLY #2 OUTSIDE ISOL.          | CLOSED   |        |
| 1VF-2-A    | UPPER CONTAINMENT PURGE SUPPLY #2 INSIDE ISOL.           | CLOSED   |        |
| 1VF-3-B    | LOWER CONTAINMENT PURGE SUPPLY #1 OUTSIDE ISOL.          | CLOSED   |        |
| 1VF-3-A    | LOWER CONTAINMENT PURGE SUPPLY #1 INSIDE ISOL.           | CLOSED   |        |
| 1VF-4-B    | LOWER CONTAINMENT PURGE SUPPLY #2 OUTSIDE ISOL.          | CLOSED   |        |
| 1VF-4-A    | LOWER CONTAINMENT PURGE SUPPLY #2 INSIDE ISOL.           | CLOSED   |        |
| 1VF-10-A   | UPPER CONTAINMENT PURGE EXHAUST #1 INSIDE ISOL.          | CLOSED   |        |
| 1VF-11-B   | UPPER CONTAINMENT PURGE EXHAUST #1 OUTSIDE ISOL.         | CLOSED   |        |
| 1VF-11-A   | UPPER CONTAINMENT PURGE EXHAUST #1 INSIDE ISOL.          | CLOSED   |        |
| 1VF-12-B   | UPPER CONTAINMENT PURGE EXHAUST #2 OUTSIDE ISOL.         | CLOSED   |        |
| 1VF-12-A   | UPPER CONTAINMENT PURGE EXHAUST #2 INSIDE ISOL.          | CLOSED   |        |
| 1VF-13-B   | UPPER CONTAINMENT PURGE EXHAUST #2 OUTSIDE ISOL.         | CLOSED   |        |
| 1VF-13-A   | UPPER CONTAINMENT PURGE EXHAUST #2 INSIDE ISOL.          | CLOSED   |        |
| 1VF-14-B   | LOWER CONTAINMENT PURGE EXHAUST #1 OUTSIDE ISOL.         | CLOSED   |        |
| 1VF-14-A   | LOWER CONTAINMENT PURGE EXHAUST #1 INSIDE ISOL.          | CLOSED   |        |
| 1VF-15-B   | LOWER CONTAINMENT PURGE EXHAUST #2 OUTSIDE ISOL.         | CLOSED   |        |
| 1VF-15-A   | LOWER CONTAINMENT PURGE EXHAUST #2 INSIDE ISOL.          | CLOSED   |        |
| 1VF-16-B   | LOWER CONTAINMENT PURGE EXHAUST #2 OUTSIDE ISOL.         | CLOSED   |        |
| 1VF-16-A   | LOWER CONTAINMENT PURGE EXHAUST #2 INSIDE ISOL.          | CLOSED   |        |
| 1VF-17-A   | ENCORE INSTR. ROOM PURGE SUPPLY INSIDE ISOL.             | CLOSED   |        |
| 1VF-18-B   | ENCORE INSTR. ROOM PURGE SUPPLY OUTSIDE ISOL.            | CLOSED   |        |
| 1VF-19-A   | ENCORE INSTR. ROOM PURGE EXHAUST INSIDE ISOL.            | CLOSED   |        |
| 1VF-20-B   | ENCORE INSTR. ROOM PURGE EXHAUST OUTSIDE ISOL.           | CLOSED   |        |
| 1VQ-1-A    | CONT. AIR RELEASE & ADDITION LOWER COMPT. INSIDE ISOL.   | CLOSED   |        |
| 1VQ-1-B    | CONT. AIR RELEASE & ADDITION LOWER COMPT. OUTSIDE ISOL.  | CLOSED   |        |
| 1VQ-2-B    | CONT. AIR RELEASE & ADDITION UPPER COMPT. OUTSIDE ISOL.  | CLOSED   |        |
| 1VQ-2-A    | CONT. AIR RELEASE & ADDITION UPPER COMPT. INSIDE ISOL.   | CLOSED   |        |
| 1VX-11-A   | CONTAINMENT SAMPLE BLOWER SUCTION (A) CONT. ISOL. INSIDE | CLOSED   |        |
| 1VX-12-B   | CONTAINMENT SAMPLE BLOWER SUCTION (B) CONT. ISOL. INSIDE | CLOSED   |        |

PAGE 3

| <u>VALVE NO.</u> | <u>COMPONENT NAME</u>                              | <u>POSITION</u> | <u>STATUS</u> |
|------------------|----------------------------------------------------|-----------------|---------------|
| VNL-06-A         | REACTOR BLDG. COND PUMP DISCH. INSIDE CONT. ISOL.  | CLOSED          |               |
| VNL-06-B         | REACTOR BLDG. COND PUMP DISCH. OUTSIDE CONT. ISOL. | CLOSED          |               |
| VNL-107-A        | CONT. VENT UNIT DRAINS INSIDE CONT. ISOL.          | *CLOSED         |               |
| VNL-107-B        | CONT. VENT UNIT DRAINS OUTSIDE CONT. ISOL.         | *CLOSED         |               |
| VNL-115-B        | CONDENSATE OUTSIDE ISOL.                           | CLOSED          |               |

\*PHASE 1 ISOLATION:

EP/L/A/5000/03  
LOSS OF REACTOR COOLANT  
POST ACCIDENT VALVE CHECKLIST  
ENCLOSURE 3.2

[illegible]