LE MICENA REQUILITORY COMMIS ORDER HUMBER 50-85-56 STANDARD ORDER FOR DOE WORK SATE TOR 24 1986 BLIES TOP (DOE Office) BBUED BY: (NAC Office) ACCOUNTING CITATION Thuquerque Operations diffice SHADANATION STABOL Office of Nuclear Material The state of the s 31X0200.505 Safety and Safeguards (NMSS) BAN WINDE BEOMING ORGANIZATION AND LOCATION 50-19-02-00 os Alamos National Laboratory (LANL) os Alamos, New Mexico. 87545 A7153-5 WORK PERSON - THIS ORDER · TITLE A DEX ESTIMATED C Consequences, of Sabotage at Non-Power Reactors 9/30/86 DELIGATION AVAILABILITY PROVIDED BY: THE DADER 177.000 TOTAL OF GROERS PLACED PRIOR TO THIS DATE WITH THE PERFORMING GROANIZATION UNDER THE LAND "APPROPRIATION SYMBOL" AND THE FIRST POUR DIGITS OF THE "SAR HUMBER" CITED ABOVE. 770,000 TOTAL OPDERS TO SAFE TOTAL ALD 947,000 AMOUNT INCLUDED IN "O" APPLICABLE TO THE "FIN NUMBER" SITED IN THIS CADER. 177,000 TO RUNDE WILL NOT BE REPROGRAMMED SETWEEN FINE. LINE O' CONSTITUTES A LIMITATION ON OBLIGATIONS AUTHORIZED.

TO RUNDE MAY BE REPROGRAMMED NOT TO EXCEED \$ 10H OF RIN LEVEL UP TO SECK LINE C CONSTITUTES A LIMITATION ON OBLIGATIONS AUTHORIZED. UNGARD TERMS AND CONDITIONS (see HRC Manual Chapter "ICE, Appaired Part of ARE PART OF THIS ORDER UNLESS OTHERWISE NOTED achients Pollowing attachments are hereby under part of this. MORN ON THIS ORDER INVOLVES CLASSIFED
INCORNATION VICE FORM 187 IS ATTACHED.
WITHEN ON THIS ORDER INVOLVES UNCLASSIFED
SAFEGUARDS, PROPRIETARY, OR OTHER SENSITIVE
MORNATION
MORNATION
FORTIT 187 PROVI ded with SOEN 50-84-116 STATEMENT OF WORK ADDITIONAL TERMS AND CONDITIONS OTHER WE RECOVERABLE HORSE Reference: SOEN 50-84-116 dated 9/6/84. This order provides FY85 funding for continuation of this project in accondance of FUNDS with the attached statement of work and your NRC Form 139 pared 157 84 80 -70-11-05 Dept of Energy, AL 40-70- N-05 A7153 \$ 177,000.00 316 K Cha A IMBUMA AUTHORIT ACCEPTING ORGANIZATION SIGNATURE K. S. Brown, Jr., Director Planning and Program Analysis Staff, Morley, Director James A. NMSS Energy Technologies Division ORM 173 (144) 02/7/85 8911140293 891101 PDR FOIA KUPERMAB9-451 PD

PDR

STATEMET UP WURK

ATTACHMENT SOEW 50-35-56

CONSEQUENCES OF SABOTAGE AT NONPOWER REACTORS

FIN NO: A7153-5

8&R NO: 50-19-02-00

1. Background

In 1979, Los Alamos Scientific Laboratory conducted a study on the consequences of sabotage at nonpower reactors. It was concluded that, within the constraints of this study, only one nonpower reactor had any potential for the release of significant amounts of fission product materials in the event of sabotage. Because of terrorist activities in other parts of the world, concerns by the ACRS about manipulation of reactor control systems, and concerns by a public interest group about the effects of incendiary devices on reactor components, staff believes that it would be prudent to supplement this study with further technical information to assure that the margin of safety provided to the public is maintained.

2.0 Work Required

Los Alamos National Laboratory shall determine and evaluate the risks and potential consequences of both a loss of coolant incident and the direct quantities and types of explosives, (b) the production of heat from incandiary devices, and (c) the unauthorized manipulation of reactor controls and fuels at nonpower (NPRS) operating at 20 MW, 10 MW, 5 MW and 2 MW.

Specifically designed mathematical models or other appropriate methods shall be used to designed mathematical models or other appropriate methods shall be used to determine the potential consequences of the events associated with (a), and (c) above. Assessments shall include the consequences associated with core meltdown, partial core meltdown, and disintegration and/or crushing of the core and shall be compared against 10 CFR Parts 20 and LO standards. Where applicable, the extent of fission product release shall be based upon NRC's re-evaluation of source term assumptions and findings.

Facilities shall be grouped by common design feature and analysis of a representative from each group shall be performed in the sequence of descending power.

Licensee	Cocket No.	Power Leve	el Reactor Type
National Bureau of Standards	50-184	20 MW	ank
University of Missouri	50-186	10 MW	Tank
Georgia Institute of Technology	50-160	5 MW	Tank
Massachusetts Institute of Technology	50-20	5 MW	Tank
Union Carbide.	50-54	5 MW	2001
Rhr te Island Atomic Energy Commission	50-193	2 MW	P001
State University of New York	50-57	2 MW	Poo1
University of Michigan	50-2	2 MW	Pool
University of Virginia	50-62	2 MW	P001

Tos ATamos National Caboratory shall perform the following tasks:

Z.L. Task No.

A review of existing information in available sources such as the NRC docket files augmented by site-specific information provided by NRC staff and on site inspection visits shall be conducted to: (a) familiarize task personnel with characteristics peculiar to each reactor, and (b) obtain information necessary to aid in the calculation of the radiological consequences for each of the NPRs listed above, as appropriate.

Z.Z Task No. Z

Mathematical models and/or other appropriate methods, such as a master-logic diagram fault-tree approach similar to those used in other safety studies by LANL, shall be developed and/or used to:

- a. calculate the radiological release resulting from a total core meltdown, partial core meltdown core, disintegration and/or crushing, or
 other means which could severely damage the fuel in the reactor core.
 Since the key consideration is the fission product release associated
 with such incidents, the effects of using low enriched uranium versus
 high enriched uranium on the fission product release shall be evaluated.
- b. determine, as a function of distance from the reactor, the total radiation dose (rem) to the whole body and the radiation dose (rem) to the thyroid from iodine exposure, and identify any facility which could exceed 10 CFR Parts 20 and 100 standards, and
- c. Determine the characteristics of the event that would limit it to less than Parts 20 and 100 standards.

Certain other parameters and assumptions should be considered when performing this task. These include, and are limited to the following except as may be approved by the NMSS Project Manager (PM) in the future:

- a. The models or methods used to calculate the damage and the releases shall assume that the reactor has been operating at the maximum power level authorized by NRC license and that equilibrium of fission products was attained prior to the incident. Note: If significant damage to the core or subsequent release is calculated to occur after a period of reactor shutdown, this shall also be evaluated.
- b. In those cases in which the fission product inventory of the NPR is determined to be insufficient to create a risk to the public health and safety, or those in which the fuel configuration or composition, and/or the reactor construction or other factors is such as to limit the fuel damage and fission product release to a level that is insufficient to create a risk to the public health and safety, the study for that facility snall be terminated, and the basis for the conclusion documented,

- c. No assumptions are made regarding the sabateurs' capabilities nor is there any design basis threat associated with this task.
- d. For baseline considerations, it should be assumed that all reactor safety features fail upon initiation of the incident, and
- e. The mean meteoroTogfcaT conditions at the site and the surrounding area should be considered when calculating the atmospheric dispersion of a release.

2.3 Task No. 3

After Tasks No. 1 and 2 have been accomplished, mathematical models or other appropriate methods shall be developed to calculate the amount of explosives and the amount of incendiary material needed to cause the maximum and the limiting events described in Task No. 2 above. Calculations shall be made for the placement of explosives and incendiary devices attached to reactor components and outside the structure containing the reactor.

Certain parameters and assumptions should be considered in those calculations. These include, and are limited to the following except as may be approved by the NMSS PM in the future:

- a. The type of explosives and incendiary devices used to cause an event are assumed to be easily obtainable.
- b. Two opposing conditions shall be considered in performing Task 3:
 - The adversary shall have access to all reactor components in carrying out the sabotage event.
 - Safeguards credit shall be given for all physical barriers interposed between the explosives/incendiaries and the reactor fuel, and

2.4 Task No. 4

Upon completion of Task No. 3, for those cases in which the fission product release and estimated doses exceed 10 CFR Parts 20 and 100 standards, calculate the amount of explosives and the amount of incendiary material needed to cause the release. The calculations shall be made for placement of explosives and incendiary devices attached to reactor components and outside the structure containing the reactor.

The parameters and assumptions employed in Task No. 3 shall be utilized in this task.

No. 5 Upon completion of Task No. 3, a review and evaluation of reactor control systems and fuels shall be made to determine whether an unauthorized me mipulation of such controls could cause any detrimental effects that may be fdentiffed for Task No. 2. Only credible scenarios and analytical assumptions shall be used and shall be reviewed and approved by the NMSS PM before the analyses are made.

want the same 2.6 Task No. 6 -

Upon completion of Task No. 3, calculate the mitigating effects of full and partial operation of existing safety features associated with the operation of the reactor (these features are ignored under Task 3 to determine maximum 'consequences'. Identify additional safety measures and modifications as well as administrative procedures and practices which could be adopted and determine the degree to which these additional considerations would mittgate the consequences. Exclude specific safeguards measures from consideration in this task.

3.0 Reporting Requirements

3.1 Monthly Letter Status Report

A monthly report shall be given which summarizes the progress of the tasks being performed including:

- a. The work performed during the previous month.
- o Personnel time expenditures during the previous month.
- o Problems encountered and the proposed solutions.
- o Activities planned for the ensuing two months.
- o Costs generated against the work effort during the previous month (including direct salaries, materials and services, ADP support, subcontracts, travel, general or other related items).
- o Current obligation status information

The first monthly report shall provide the initial projections or indicate "no change in the cost and uncosted obligation projection." The report shall be due by the 15th of each month with distribution as follows:

Donald M. Carlson, SG, NMSS - one copy Office of the Director, NMSS (ATTN: Program Support) - one copy

3.2 Interim Reports

A draft interim report shall be furnished to the NMSS PM upon completion of each major task (i.e., Tasks Nos. 2, 3, 4 and 5). After review by appropriate NRC personnel, the PM will provide comments on the drift report to LANL within sixty (60) days of receipt of each report. A revised interim report shall be submitted if deemed necessary by the NMSS PM.

EANL shall furnish two copies of a draft final report to the NMSS PM by June 30. 1986. The format of these documents shall be as specified for formet technical reports for NRC Manual Chapter 1102 and will provide: ----

- a. The an-site and off-site fission product release and dosage calculatrons associated with a total loss of coolant. -
- b. The quantities of explosives and incendiary material or description of acts necessary to cause a limiting case incident. the same and property
- c. The placement of explosives and incendiary materials in relation to the reactor.
- d. The description of unauthorized manipulation of reactor controls and fuel to cause a limiting case incident.
- e. The resulting consequences, and
- f. Appropriate alternative measures which can be implemented to mitigate a significant event (e.g., reactor facility modifications, administrative procedures, etc.).

After review by appropriate NRC personnel, the PM will provide comments on the draft report to LANL within 60 days of receipt of the report.

The performing organization shall revise the draft report based on the PM's comments and submit two camera-ready copies of the final report to the Document Management Branch, Technical Information and Document Control, NRC to be published as NUREG/CR series reports, and a duplicate to the NMSS PM.

All draft reports, as well as final reports, shall be screened for Classified Information and appropriately marked in accordance with "NRC Classification Guide for Information Dealing with the Release and Dispersion of Radioactive Material (NRC-RORM-1)," dated September 1982 and NRC Manual Chapter 1102.

3.4 Program Plan

Within one month after initiation of task orders, LANL shall provide a detailed work plan which identifies study milestones and their projected date of accomplishment. Upon NRC review and approval of this plan, it will then become the operating schedule for the overall task.

4.0 Meetings

LANL representative(s) shall meet with the NMSS Project Manager two to four times a year. Upon completion of the draft final report, LANL representatives, upon request of the NMSS PM, shall brief NMSS staff in Washington, DC.

All travel requires approval of the NMSS Project Manager.

5. NRC Furnished Material

None, except information in available sources such as NRC docket files.

G.C Level of Effort

It is expected that approximately three and one half staff years of technical support will be required to satisfy the provisions of the Statement of Work.

7.C Perfod at Performance

Performance for the overall task shall commence on the effective date of this agreement and continue through September 30, 1986.

8.0 Quality Assurance

For all draft and final technical reports delivered under this agreement, the LANL shall assure that an independent review and verification of all numerical computations and mathematical equations and deviations are performed by qualified contractor personnel other than the original author(s) of the reports. If the LANL proposes to verify/check less than 100 percent of all computations and mathematical equations and derivations in the report(s), (such as might be the case when there are a large number of routine, repetitive calculations), the LANL must first obtain written approval from the NMSS PM.

Computer-generated calculations will not require verification where the computer program has already been verified.

In addition, for all reports, including those which do not contain numerical analyses, a management review shall be conducted prior to submission to the NRC.

9.0 Technical Direction

Mr. Donald M. Carlson (FTS 427-4712) is designated the NMSS Project Manager for the purpose of assuring that the services required under this Statement of Work are delivered in accordance herewith. All technical instructions to the performing organization shall be issued through the NMSS PM. As used herein, technical instructions are those which provide details, suggest possible lines of inquiry, or otherwise complete the general scope of work set forth herein. Technical instructions shall not constitute new assignments or mork or changes of such nature as to justify an adjustment in Cost or period of performance. Directions for changes in cost or period of performance will be provided after receipt of an appropriate Standard Order for Work (SOW) (NRC Form 173) from the Director of the Office of Nuclear Material Safety and Safeguards (NMSS).

10.0 Disposal of Propert,

Prior to close out of this project, a reconciled report shall be developed by DOE to record available equipment and material purchased with NRC funds. This report should be developed as soon as possible after project completion or termination decision has been made, but not later than 60 days after the termination date. The report should be submitted to the NRC Division of Facilities and Operations Support, ADM, and the NMSS Project Manager.

11.0 DOE Acquired Material

The performing organization must notify the NMSS Project Manager prior to acquisition of any capital, ADP, or word processing equipment.