SIXTY-DAY RESPONSE

TO

NRC IE BULLETIN 80-11

DATED MAY 8, 1980

FOR

CONSUMERS POWER COMPANY

BIG ROCK POINT NUCLEAR PLANT

PREPARED BY: BECHTEL POWER CORPORATION

JUNE 30, 1980

SIXTY-DAY RESPONSE

TO

NRC IE BULLETIN 80-11

CONTENTS

- 1. INTRODUCTION
- 2. IDENTIFICATION OF SAFETY-RELATED MASONRY WALLS AND THEIR SYSTEMS
 - A. Wall Inspection
 - B. Wall Plans with Identification Numbers
- 3. PRIORITIZED PROGRAM
 - A. Prioritized Order of Review
 - B. Completion Schedule
- 4. RE-EVALUATION CRITERIA
 - A. General
 - B. Analysis
 - C. Justification of Re-Evaluation Criteria
- 5. REFERENCES

APPENDIX

A. Wall Plans and Information Tables for Potentially Safety-Related Masonry Walls

Figures - Page A-26, Plan Below Elevation 598'

Page A-27, Plan Below Elevation 618'

SIXTY-DA! RESPONSE

TO

NRC IE BULLETIN 80-11

1. INTRODUCTION

This report has been prepared in response to NRC IE Bulletin 80-11, dated May 8, 1980. It has been prepared by Bechtel Power Corporation, Ann Arbor, Michigan, for Consumers Power Company's (CPCo's) Big Rock Point Nuclear Plant.

This report submits information requested in Items 1, 2a, and 3 of NRC IE Bulletin 80-11, dated May 8, 1980.

A total of 24 potentially safety-related masonry wall segments have been identified. A masonry wall may be composed of several segments. For purposes of identification, total count, and re-evaluation, a masonry wall segment has been defined as a uniform, straight run of wall between support or terminal points.

2. IDENTIFICATION OF SAFETY-RELATED MASONRY WALLS AND THEIR SYSTEMS

Safety-related systems, components, and structures have been generally defined as those listed on the Big Rock Point plant Q list. The boundaries of seismic analyses performed in the course of responding to NRC IE Bulletin 79-14 have also been used where applicable in the determination of whether an item is safety related.

CPCo has designated potentially safety-related masonry walls at the Big Rock Point plant. CPCo has also performed a search for potentially safety-related masonry walls in safety-related areas not shown on the design drawings.

Safety-related systems which are either attached to, penetrate, or are in proximity to potentially safety-related masonry walls are listed in Appendix A.

For purposes of identification, proximity is defined as within an arc length equal to a masonry wall height from the base of each face of the masonry wall extending to the floor. Furthermore, in plan view, proximity is defined by lines normal to the masonry wall extending from the ends of the masonry wall. Proximity does not extend beyond compartments.

The potentially safety-related masonry walls do not generally support a structurally significant amount of equipment.

A. WALL INSPECTION

Identification of potentially safety-related masonry walls started in May 1980. This included a review of design drawings, the plant Q list, and a walkdown of the plant.

A team started a detailed inspection of asonry walls on June 23, 1980. The team is collecting, verifying, and recording information regarding the as-built condition of existing masonry walls and structurally significant attachments. The presence of safety-related items in proximity to or attached to the masonry walls is also documented.

In some instances, ALARA considerations require that time spent near a masonry wall be minimized and that the inspection be limited to visual observations from some distance away from the masonry wall. These observations were compared with the design drawings. Confidence was established that the data obtained are adequate for masonry wall re-evaluation, and it is not intended that a further inspection be made of these masonry walls.

B. WALL PLANS WITH IDENTIFICATION NUMBERS

Plans have been prepared to locate and number masonry walls (Appendix A). Only the masonry walls which were designated as potentially safety related are further discussed and documented in this report.

3. PRIORITIZED PROGRAM

A. PRIORITIZED ORDER OF REVIEW

Safety-related masonry walls will be re-evaluated using the following order of priority:

- 1) Masonry Walls Supporting Safety-Related Equipment with Estimated Design Loadings Greater than 100 Pounds, or Safety-Related Piping 2-1/2 Inches in Diameter or Greater
- 2) Masonry Walls Supporting Other Safety-Related Items
- 3) Masonry Walls with Safety-Related Equipment in Proximity

B. COMPLETION SCHEDULE

It is anticipated that the re-evaluation of safetyrelated masonry walls to acceptance criteria prepared by Bechtel Power Corporation will be completed by November 4, 1980.

4. RE-EVALUATION CRITERIA

A. GENERAL

The Big Rock Point plant Final Hazards Summary Report (FHSR) does not specifically address masonry walls. Loadings will be defined from the FHSR and existing analyses for Seismic Category I structures. Load combinations will contain the applicable elements specified in the FHSR.

B. ANALYSIS

Analyses will be performed using standard calculation procedures to determine the structural adequacy of the safety-related masonry walls. Masonry walls are considered to be isotropic, elastic material. Plate or beam theory will be used to satisfy static equilibrium under all loading conditions. Cracked and/or uncracked section analyses will be performed, as applicable, to determine the stresses in the masonry and in the reinforcing steel. Highly stressed areas will be checked against the corresponding allowable stresses.

C. JUSTIFICATION OF RE-EVALUATION CRITERIA

Justification for the re-evaluation criteria will be submitted with the re-evaluation report within 180 days of the date of the bulletin received. Justifications will be based on reference to existing codes and established standards of practice related to concrete and masonry design.

It is anticipated that such justification will be considered appropriate, and that a test program will not be necessary, except as required to determine project unique structural properties and any other properties for which data are not available or cannot otherwise be determined.

5. REFERENCES

- A. U.S. NRC IE Bulletin 80-11, dated May 8, 1980
- B. Big Rock Point Nuclear Plant, Final Hazards Summary Report, Docket 50-155

APPENDIX A

WALL PLANS AND INFORMATION TABLES FOR

POTENTIALLY SAFFTY-RELATED MASONRY WALLS

The attached identifies safety-related equipment and systems associated with safety-related masonry walls. This listing is subject to revision.

The listing of systems associated with certain items is intended to reflect the primary system or systems associated with the particular item. For certain items, especially those associated with walls M100.14 and M100.18, a large list of systems would be required to completely define safety-related equipment in cabinets, conduits, and cable trays. For this report, the term "various" is used to include reactor cleanup, control rod drive, shutdown cooling, reactor coolant, core spray, emergency core cooling, and/or other systems which have circuitry combined in the conduits and cable trays noted in the attached tables.

These masonry walls do not generally support a structurally significant amount of nonsafety-related equipment. Therefore, attached nonsafety-related equipment and systems are not listed. Attached nonsafety-related equipment will be considered in the re-evaluation of these masonry walls.

The masonry wall number is the drawing number followed by a decimal, followed by the wall number indicated on the drawing.

Item System

Conduit Off-gas monitoring

Off-gas discharge monitor Off-gas monitoring

Off-gas monitoring Instrumentation

Item

System

Instrumentation

Off-gas monitoring

Item System

Conduit Reactor depressurization system

Uninterruptible power Reactor depressurization system supply (UPS) battery charger/inverter

UPS batteries Reactor depressurization system

<u>Item</u> System

Conduit Reactor depressurization system

UPS battery charger/ Reactor depressurization system

inverter

UPS batteries Reactor depressurization system

Item

System

Six-inch pipe

Fire system

Conduit

Reactor depressurization system

<u>Item</u> <u>System</u>

One- and 2-inch pipe Fire system

UPS battery charger/ Reactor depressurization system inverter

UPS batteries Reactor depressurization system

Conduit Reactor depressurization system

Item

UPS battery charger/

inverter

UPS batteries

Conduit

One- and 2-inch pipe

System

Reactor depressurization system

Reactor depressurization system

Reactor depressurization system

Fire system

Item System

UPS battery charger/ Reactor depressurization system inverter

UPS batteries Reactor depressurization system

Conduit Reactor depressurization system

<u>Item</u> <u>System</u>

UPS battery charger/ Reactor depressurization system

inverter

UPS batteries Reactor depressurization system

Conduit Reactor depressurization system

<u>Item</u> <u>System</u>

UPS battery charger/ Reactor depressurization system inverter

UPS batteries Reactor depressurization system

Conduit Reactor depressurization system

........ ..

<u>Item</u> System

UPS battery charger/ Reactor depressurization system

inverter

UPS batteries Reactor depressurization system

Conduit Reactor depressurization system

<u>Item</u> <u>System</u>

UPS battery charger/ Reactor depressurization system

inverter

UPS batteries Reactor depressurization system

Conduit . Reactor depressurization system

Item System

UPS battery charger/ Reactor depressurization system inverter

UPS batteries Reactor depressurization system

Conduit Reactor depressurization system

Fire system

One-, 2-, 3-, and 6-inch pipe

Item

System

Three- and 6-inch pipe Fire system

Four- and 6-inch pipe

Post-incident cooling

Batteries

Station power

Motor control center

125 V dc

Primary coolant system/ emergency condenser system

....

Conduit

Various

Cable tray

Various

Item

System

Two-, 3-, and 6-inch pipe

Fire system

Conduit

Reactor depressurization system

<u>Item</u> <u>System</u>

Rod position MG set Reactor protection system

Three-inch pipe Fire system

Four- and 6-inch pipe Post-incident cooling

Conduit Reactor depressurization system/

2,400 V cable

Batteries Station power

Cable tray Various

Battery chargers Station power

Ground detector Station power

Item System

Cable tray Reactor depressurization system,

2,400 V

Four- and 6-inch pipe Post-incident cooling

Conduit Reactor depressurization system

Switchgear Reactor feedwater and reactor

circulation systems and station

power transformers

Item

System

Load center, 480 V

Emergency conderser inlet

Motor control centers 1A, 2A, and 2B

Reactor cleanup, shutdown cooling,

and containment spray

Junction boxes JB42, JB43, and JB44

Emergency core cooling and containment isolation

Switchgear

Reactor feedwater and reactor circulation systems and station

power transformers

Conduit

Various

Cable tray

Various

Item

System

Four- and 6-inch pipe Post-incident cooling

Three-inch pipe Fire system

Cable tray

Various

Item

System

One-, 2-, 3-, 4-, and 6-inch pipe

Fire system

Four- and 6-inch pipe

Post-incident cooling

Cable tray

Various

Conduit

Systems (2,400 V)

Item

System

Two-, 4-, and 6-inch pipe and valves

Fire sys'.em

System (2,400 V)

Cable Tray

Conduit

Various

WALL M101.1

Item

System

Control panels

Reactor depressurization system

WALL MI01.3

Item

System

Downcomers

Primary coolant system


WALL M101.4


Item

System

Heat exchangers

Primary coolant system





ı