

INTERIM REPORT

Accession No. _____


Contract Program or Project Title: TRAC Assessment and Model Development

Subject of this Document: ~~May~~ ^{July} Monthly Highlight Letter

Type of Document: Monthly Highlights

Author(s): Pradip Saha
Department of Nuclear Energy, Brookhaven National Laboratory
Upton, NY 11973

Date of Document: July 1980



Responsible NRC Individual
and NRC Office or Division: Dr. Novak Zuber
Sr. Reactor Analyst
Analysis Development Branch
Division of Reactor Safety Research
Nuclear Regulatory Commission
Mail Stop G-158
Washington, DC 20555

This document was prepared primarily for preliminary or internal use. It has not received full review and approval. Since there may be substantive changes, this document should not be considered final.

Brookhaven National Laboratory
Upton, New York 11973
Associated Universities, Inc.
for the
U.S. Department of Energy

Prepared for
U.S. Nuclear Regulatory Commission
Washington, D.C. 20555
Under Interagency Agreement DE-AC02-76CH00016
FIN-3215

8101260850

NRC Research and Technical
Assistance Report

RES

Monthly Highlights

for

July 1980*

TRAC Assessment and Model Development

NRC FIN No. A-3215

Pradip Saha
Department of Nuclear Energy
Brookhaven National Laboratory
Upton, New York 11973

*Work carried out under the auspices of the United States Nuclear Regulatory Commission.

NRC Research and Technical
Assistance Report

TRAC Assessment and Model Development

1. University of Houston Flooding Tests (U. S. Rohatgi)

It was stated in the last quarterly that the TRAC-PIA one-dimensional formulation cannot simulate this countercurrent flow test due to an inadequate description of the relative velocity in the annular flow regime. Therefore, the two-fluid formulation of TRAC-PIA was investigated to see if it could predict the test. It was found from the preliminary analysis of the test data that the interfacial shear coefficient needed to calculate the experimental conditions is four to five times higher than the one in the code. This agrees with the conclusion reached by the LASL personnel when they simulated the countercurrent flow tests of Dartmouth College. These tests will be simulated with TRAC-PD2.

2. Super-CANON Experiments (P. Saha)

The sensitivity of TRAC-PIA predictions to the initial water temperature has been studied for the Super-CANON test with a full-open discharge end and an initial water temperature of 280° C. In order to achieve a good prediction of the short-term pressure history, the initial water temperature for the TRAC calculation was taken as 270° C. This temperature is 10° C lower than the average initial water temperature of the test, and 8° C lower than the minimum temperature recorded by any thermocouple at the start of the transient. With this hypothetical initial water temperature of 270° C, TRAC-PIA predicts the short-term ($t < 0.1$ sec) pressure history quite well. However, the pressure thereafter is underpredicted like the original TRAC-PIA prediction.

The value of the void distribution parameter, C_0 , was then changed from 1.1 (the original TRAC value) to 1.01 to reduce the relative velocity. The

initial water temperature was still kept at 270° C, 10° C lower than the experimental value. The resultant TRAC prediction was in close agreement with the data for the entire period of transient. However, it must be kept in mind that two input changes, one of which is highly artificial, were needed to produce the good agreement. This confirms our previous observation that further examination of the TRAC models for nonequilibrium phase change and relative velocity is required.

3. Battelle Institute (Frankfurt-Main) Vessel Top Blowdown Test (L. Neymotin)

A topical report on the simulation of this test with TRAC-PIA is being written.

4. RPI Phase Separation Test (U. S. Rohatgi)

The simulation of the remaining four high quality inlet flow tests with TRAC-PIA has been completed, and the conclusions drawn in the previous quarterlies still stand. All four of the tests failed to converge to a steady-state. The code still produced an asymmetric solution for the two tests with symmetric boundary conditions and two outlets. Furthermore, the code stopped computing due to overflow conditions for the remaining two tests with one outlet.

5. FRIGG-Loop Forced and Natural Circulation Tests (L. Neymotin)

Possible causes for TRAC's failure to reach a steady-state with the two-fluid formulation have been found using the results obtained recently for FRIGG Tests with one-dimensional "vessel" module. A BNL memo on this subject has been prepared. Complete 3-D calculations have not been performed due to the present shortage of funds for computer time.

A topical report on the FRIGG Test simulations with TRAC-PlA is currently being prepared.

6. TRAC-PD2 Implementation (G. Slevik)

The TRAC-PD2, as received from LASL, is being implemented at BNL.

Distribution TRAC Assessment and Model Development Program

BNL NSP Division Heads
BNL NSP Group Leaders
BNL RSE Personnel
BNL TAG Personnel

S. Fabric, NRC
Y. Y. Hsu, NRC
W. Y. Kato, BNL
H. J. C. Kouts, BNL
W. Lyon, NRC
F. Odar, NRC
R. M. Scroggins, NRC
L. M. Shotkin, NRC
L. S. Tong, NRC
N. Zuber, NRC

U. S. NRC Division of Technical Information and Control