UNITED STATES OF AMERICA NUCLEAR REGULATORY COMMISSION

In the Matter of:) Docket No. 40-3453 Source Material License
Atlas Minerals ATTN: Mr. R. Weaver	No. SUA-917 Amendment No. 5
P. C. Box 1207 Moab, Utah 84532	}

ORDER TO MODIFY LICENSE

POOR ORIGINAL

Atlas Minerals ("The Licensee") is the holder of Source Material License No. SUA-917 issued by the Nuclear Regulatory Commission ("The Commission"). The license authorizes the possession, use and processing of natural uranium and the production of 850 metric tons barreled of U_3O_8 (yellowcake) per year. The licensee converts natural uranium ore to U_3O_8 (yellowcake). The current license was issued April 23, 1979 and is the complex of April 30, 1984.

II

On January 13, 1977, the U.S. Environmental Protection Agency issued regulations setting forth environmental radiation protection standards for the uranium fuel cycle. These regulations are found in Title 40, Chapter 1, Subchapter F, Part 190, of the Code of Federal Regulations (40 CFR 190). The standard for uranium ore milling facilities became effective on December 1, 1980. The regulations in 40 CFR 190 require that planned discharges to the general environment of radioactive materials, radon and its daughters excepted, and

radiation from licensed milling operations shall be limited in such a manner as to provide reasonable assurance that no member of the public will receive an annual dose equivalent of more than 25 millirems to the whole body, 75 millirems to the thyroid, or 25 millirems to any other organ.

The Nuclear Regulatory Commission is responsible for assuring that uranium milling facilities licensed by the Commission meet the requirements of these new environmental radiation protection standards. To assure compliance with 40 CFR 190, the license is being modified to require the evaluation and periodic reporting of environmental monitoring data and other pertinent information. The attached NRC document, "Compliance Determination Procedures for Environmental Radiation Protection Standards for Uranium Recovery Facilities - 40 CFR 190," sets forth a standardized reporting format for the environmental monitoring data and the dose conversion factors to be used to calculate the dose commitments.

The NRC staff has reviewed the available environmental monitoring data and radiological assessments contained in the Final Environmental Statement (FES) for Atlas Minerals (NUREG-0453). On the basis of this information and its review, the staff concludes that implementation of the 40 CFR 190 scandard is practicable (see the NRC Report "40 CFR 190 Compliance Assessment for NRC Licensed Uranium Recovery Facilities as of December 1, 1980"). This report and the attached document describing NRC 40 CFR 190 compliance determination procedures form the technical basis for the conditions contained in this order.

Accordingly, in order to assure compliance with Title 40, Code of Federal Regulations, Part 190, pursuant to Sections 62, 63, 81, 83, 84, 161b, 161o, and 182 of The Atomic Energy Act of 1954, as amended, and the Commission's regulations in 10 CFR Parts 2 and 40, Source Material License No. SUA-917 is hereby amended to add the following conditions:

- For a period of four (4) calendar quarters beginning July 1, 1981, the sampling and analysis results of the Environmental Monitoring Program, as required by License Condition 37, shall be reported to the Uranium Recovery Licensing Branch, U.S. Nuclear Regulatory Commission, Washington, D.C. 20355, with a copy to the Director of Inspection and Enforcement, Region IV, U.S. Nuclear Regulatory Commission, 611 Ryan Plaza Drive, Arlington, Texas 76011, within 60 days of the end of each calendar quarter in accordance with the format in the attached Table, "Sample Format for Reporting Monitoring Data." Dose evaluations based on this actual environmental monitoring program data and the dose conversion factors as given in Attachment A of "Compliance Determination Procedures for Environmental Radiation Protection Standards for Uranium Recovery Facilities 40 CFR 190" shall be included in the report.
- The requirement in 10 CFR 20.405(c), when effective, for notification of levels of radiation or releases of radioactive materials in excess of the limits specified in 40 CFR 190 shall be suspended during the period that

the four quarterly environmental monitoring reports are being submitted as required in License Condition 47 above.

- The background air monitoring station required by License Condition 37 shall be operational by May 1, 1981. The location of this station shall be as indicated in the letter dated February 20, 1981 from G. Swanby to R. A. Scarano.
- The licensee shall submit the following information to the Uranium Recovery
 Licensing Branch, U.S. Nuclear Regulatory Commission, Washington, D.C. 20555,
 by June 1, 1981 for NRC review and approval prior to implementation:
 - A. Specifications for a quality assurance program. Regulatory

 Guide 4.15, "Quality Assurance for Radiological Monitoring Programs

 (Normal Operations) Effluent Streams and the Environment" may be followed by the licensee in submitting its specifications; or the licensee may provide specifications for an equivalent quality assurance program.
 - B. A detailed topographic map(s) showing all environmental sample collection locations and all of the following within 5 miles (8 km) of any portion of the restricted area boundary: private residences, grazing areas, private and public potable water and agricultural wells, milk cattle, nonresidential structures and uses, mining areas, and are storage pads.

The licensee shall follow the lower limits of detection (LLD) contained in the attached Table, "Lower Limits of Detection (LLD) for Sample Analysis" for the analysis of samples collected pursuant to the Environmental Monitoring Program of License Condition 37. If the licensee wishes to use other LLDs, such LLDs shall be submitted to the Uranium Recovery Licensing Branch, U.S. Nuclear Regulatory Commission, Washington, D.C. 20555, by June 1, 1981 for NRC review and approval prior to implementation.

IV

The licensee or any other person whose interest may be affected by this Order may request a hearing on this Order before May 1, 1981. A request for hearing shall be submitted to the Secretary, U.S. Nuclear Regulatory Commission, Washington, D.C. 20555. A copy of the request shall also be sent to the Executive Legal Director at the same address. If a hearing is requested by a person other than the licensee, that person shall describe, in accordance with 10 CFR 2.714(a)(2), the nature of the person's interest and the manner in which that interest is affected by this Order.

If a hearing is requested by the licensee or other person who has an interest affected by this Order, the Commission will issue an Order designating the time and place of any such hearing. If a hearing is held, the issue to be considered at such a hearing shall be:

Order, License Number SUA-917 should be modified as set forth in Section II of this III of this Order.

This amendment will become effective upon expiration of the period during which a hearing may be requested. In the event a hearing is requested, the amendment will become effective on a date specified in an Order made following the nearing.

The reporting requirements contained in this order to modify the license have been approved by the U.S. General Accounting Office under number B-180225 (20709).

FOR THE NUCLEAR REGULATORY COMMISSION

John B. Martin, Director
Division of Waste Management
Office of Nuclear Material Safety
and Safeguards

Dated at Silver Spring, Maryland this 26 day of March 1981.

Attachments:

- 1. "Compliance Determination Procedures for Environmental Radiation Protection Standards for Uranium Recovery Facilities - 40 CFR 190" (dated December 1980)
- Table "Sample Format for Reporting Monitoring Data"
- Table "Lower Limits of Detection (LLD) for Sample Analysis"

STACK SAMPLES

for each sample analyzed, report the following information:

- Date sample was collected
- b. location of sample collection
- c. Stack flow rate (m3/sec)

Radionuclide	Error Estimate(b) (µC1/ml)	Release Rate (C1/qr)	Error Estimate (C1/qr)	(hc1/m1)	X MPC(c)
U-nat					
Th-230					
Ra-226					
Pb-210					

AIR SAMPLES

Pb-210 Rn-222

For each sample analyzed, report the following information:

- Date sample was collected
- Location of sample collection

Radionuclide	Concentration (µCi/ml)	Error Estimate (µCi/ml)	(HC1/m1)	X MPC
U-nat				
1h-230				
Ra-226				

⁽a) This table illustrates format only. It is not a complete list of data to be reported.

⁽b) Error estimate should be calculated at 95% uncertainty level, based on all sources of random error, not merely counting error. Significant systematic error should be reported separately.

⁽c) All calculations of lower limits of detection (LLD) and percentages of maximum permissible concentration (MPC) should be included as supplemental information.

Eligato sametrs

for each sample analyzed, report the following information:

Date sample was complected tocation of sample follection

Type of sample (for example: surface, ground, drinking, stock, or irrigation)

Error Estimate (µCI/ml) Concentration (JIC1/m1) Radionuclide

(InC1/m1)

Po-210 (suspended)(d) Pb-210 (suspended)(d) Th-230 (suspended)(d) Ra-226 (suspended)(d) U-nat (suspended)(d) Po-210 (dissolved) Ra-226 (dissolved) Pb-210 (dissolved) Th-230 (dissolved) U-nat (dissolved)

for each sample analyzed, report the following information: VEGETATION, FOOD, AND FISH SAMPLES 4

4 3 3

Date sample was collected tocation of sample collection lype of sample and portion analyzed

Concentration (µC1/kg wet)

(pC1/kg)

Error Estimate (µCi/kg)

Radionuclide

U-nat

111-230 Ra-226 Pb-210

POOR ORIGINAL

Po-210

(d) Hot all samples must be analyzed for suspended radionuclides.

TABLE (Continued)

SAMPLE FORMAT FOR REPORTING MONITORING DATA

5. SOIL AND SEDIMENT SAMPLES

for each sample analyzed, report the following information:

- a. Date sample was collected
- b. Location of sample collection
- c. Type of sample and portion analyzed

Radionuclide	Concentration (μC1/g)	Error Estimate(µCi/g)	(pCi/g)	
U-nat				
16-230				
Ra-226				
Fb-210				
Po-210				

6. DIRECT RADIATION MEASUREMENTS

for each measurement, report the dates covered by the measurement and the following information:

Location Exposure Rate Error Estimate (mR/qr) (mR/qr)

7. RADON FLUX MEASUREMENTS

for each measurement, report the dates covered by the measurement and the following information:

Location

Flux (pC1/m2-sec) Error Estimate (pC1/m2-sec)

Lower Limits of Detection (LLD) for Sample Analysis

U-natural, Th-230, Ra-226 in air	-	1 x	10 ⁻¹⁶ µCi/ml
Pb-210 in air	-	2 x	10 ⁻¹⁵ μCi/ml
Rn-222		2 ×	10 ⁻¹⁰ µCi/ml
U-natural, Th-230, Ra-226 in water	-	2 x	10 ⁻¹⁰ µCi/ml
Po-210 in water		1 x	10 ⁻⁹ µCi/ml
Pb-210 in water		1 x	10 ⁻⁹ μCi/ml
U-natural, Th-230, Ra-226, Pb-210 in soil and sediment (dry)		2 x	10 ⁻⁷ µCi/g
U-natural, Th-230 in vegetation, food, and fish (wet)		2 x	10 ⁻⁷ μCi/kg
Ra-226 in vegetation, food, and fish (wet)		5 x	10 ⁻⁸ μCi/kg
Po-210, Pb-210 in vegetation, food, and fish (wet)		1 x	10 ⁻⁶ μCi/kg

SAMPLE TORMAT FOR REPORTING MONITORING DATA

STACK SAMPLES

for each sample analyzed, report the following information:

- Date sample was collected
- location of sample collection
- Stack flow rate (m3/sec)

Radionuclide	Concentration (µCi/ml)	Error Estimate(b) (pC1/ml)	Release Rate (Ci/qr)	Error Estimate (C1/gr)	(hc1/m1)	X HPC(c)
U-nat						
1h-230						
Ra-226						
Pb-210						

2. AIR SMIPLES

Pb-210 Rn-222

For each sample analyzed, report the following information:

- Date sample was collected
- b. Location of sample collection

Radionuclide	Concentration (µC1/m1)	(µC1/m1)	(hC1/w1)	X MPC
U-nat				:
Th-230				
Ra-226				

(a) Ihis table illustrates format only. It is not a complete list of data to be reported.

⁽b) Error estimate should be calculated at 95% uncertainty level, based on all sources of random error, not merely counting error. Significant systematic error should be reported separately.

⁽c) All calculations of lower limits of detection (LLD) and percentages of maximum permissible concentration (MPC) should be included as supplemental information.

SAMPLE FORMAT FOR REFORTING MONITORING DATA

LIQUID SAMPLES ď.

for each sample analyzed, report the following information:

Date sample was collected tocation of sample collection

Type of sample (for example: surface, ground, drinking, stock, or irrigation) . . .

Error Estimate (µC1/m1) Concentration (InC1/m1) Radionuclide

(InC1/m1)

U-nat (dissolved)

U-nat (suspended)(d) Th-230 (dissolved)

(P)(Panded)(q) Ra-226 (dissolved)

Ra-226 (suspended)(d)

Pb-210 (suspended)(d) Pb-210 (dissolved)

Po-210 (dissolved)

Po-210 (suspended)(d)

VEGETATION, FOOD, AND FISH SAMPLES

÷

for each sample analyzed, report the following information:

Date sample was collected to tocation of sample collection. Type of sample and portion analyzed

Concentration

(pC1/kg wet) Radionuc lide U-nat

14-230

RA-226

Po-210

Pb-210

(d) Hot all samples must be analyzed for suspended radionuclides.

POOR ORIGINAL

(pC1/kg)

Error Estimate (µC1/kg)

IABLE (Continued)

The second control and being the second control and control and the second and the second and the second

SAMPLE FOPMAT FOR REPORTING MONITORING DATA

SOIL AND SEDIMENT SAMPLES 5

for each sample analyzed, repor' the following information:

Date sample was collected tocation of sample collection Iype of sample and portion analyzed

Error Estimate (µCI/g) Concentration (pCI/g) Radionuclide

(6/13/1)

U-nat

111-230

Ra-226

Pb-210

Po-210

DIRECT RADIATION MEASUREMENTS 9 for each measurement, report the dates covered by the measurement and the following information:

Exposure Rate (mR/qr)

Location

Error Estimate (mR/qr)

RADON FLUX MEASUREMENTS 1. for each measurement, report the dates covered by the measurement and the following information:

Location

(pC1/m2-sec)

(pCI/m2-sec)

Lower Limits of Detection (LLD) for Sample Analysis

U-natural, Th-230, Ra-226 in air		1	x 10 ⁻¹⁶ µCi/ml
Pb-210 in air	-	2	x 10 ⁻¹⁵ µCi/ml
Rn-222		2	x 10 ⁻¹⁰ µCi/ml
U-natural, Th-230, Ra-226 in water		2	x 10 ⁻¹⁰ µCi/ml
Po-210 in water	-	1	x 10 ⁻⁹ µCi/ml
Pb-210 in water	-	1	x 10 ⁻⁹ µCi/ml
U-natural, Th-230, Ra-226, Pb-210 in soil and sediment (dry)		2	x 10 7 µCi/g
U-natural, Th-230 in vegetation, food, and fish (wet)		2	x 10 ⁻⁷ µCi/kg
Ra-226 in vegetation, food, and fish (wet)		5	x 10 ⁻⁸ μCi/kg
Po-210, Pb-210 in vegetation, food, and fish (wet)		1	x 10 ⁻⁶ µCi/kg

40 CFR 190 COMPLIANCE ASSESSMENT

FOR

NRC LICENSED URANIUM RECOVERY FACILITIES

AS OF

DECEMBER 1, 1980

U.S. Nuclear Regulatory Commission

Division of A Management

Uranium A Management icensing Branch

February 1981

8144424690 DUPLICATE
PAR