

LICENSEE EVENT REPORT

(PLEASE PRINT OR TYPE ALL REQUIRED INFORMATION)

CONTROL BLOCK

1 M I P A I U I 2 0001-100010101-100 3 41111111 4 1 5

LICENSE CODE 14 18 22 26 30 34 38 42 46 50 54 58

CON'T
 1 L 8 015100012515 7 07101618 11 08105811 9

REPORT SOURCE 20 24 28 32 36 40 44 48 52 56 60

DOCKET NUMBER 24 28 32 36 40 44 48 52 56 60

EVENT DATE 36 40 44 48 52 56 60

REPORT DATE 56 60 64 68 72 76 80

10 During reviring of a temperature switch on 1-1 diesel generator, a wire
 11 slipped, making contact with ground. As a result, the D/G control power
 12 supply breaker (72-301) tripped, thereby disabling the diesel generator.
 13 The condition was immediately detected, and the unit was restored to
 14 operable status by reclosing the breaker within four minutes. No threat
 15 to public health or safety existed.

11 E E 12 X 13 Z 14 E N G I N E E 15 Z 16 Z

SYSTEM CODE 11 15 19 23 27 31 35 39 43 47 51 55 59

CAUSE CODE 11 15 19 23 27 31 35 39 43 47 51 55 59

CAUSE SUBCODE 11 15 19 23 27 31 35 39 43 47 51 55 59

COMPONENT CODE 11 15 19 23 27 31 35 39 43 47 51 55 59

COMP SUBCODE 11 15 19 23 27 31 35 39 43 47 51 55 59

VALVE SUBCODE 11 15 19 23 27 31 35 39 43 47 51 55 59

17 1811 18 X 19 X 20 Z 21 Z 22 0000 23 N 24 N 25 A 26 A 1512

LER NO REPORT NUMBER 17 21 25 29 33 37 41 45 49 53 57 61 65 69

EVENT YEAR 21 25 29 33 37 41 45 49 53 57 61 65 69

SEQUENTIAL REPORT NO. 25 29 33 37 41 45 49 53 57 61 65 69

OCCURRENCE CODE 29 33 37 41 45 49 53 57 61 65 69

REPORT TYPE 33 37 41 45 49 53 57 61 65 69

REVISION NO. 37 41 45 49 53 57 61 65 69

ACTION TAKEN 33 37 41 45 49 53 57 61 65 69

EFFECT ON PLANT 37 41 45 49 53 57 61 65 69

SHUTDOWN METHOD 41 45 49 53 57 61 65 69

HOURS 45 49 53 57 61 65 69

ATTACHMENT 7 SUBMITTED 49 53 57 61 65 69

PRIME COMP SUPPLIER 53 57 61 65 69

COMPONENT MANUFACTURER 57 61 65 69

16 Work was being performed on a non-disabling function (temp alarm);
 17 however, the temp switch is powered from a ckt brkr which supplies
 18 functions critical to D/G operability. The feasibility of adding a power
 19 interrupt device to protect D/G safety related circuits in the event of
 20 ground faults in non-safety related circuits is being evaluated.

15 E 28 0000 29 NA 30 A 31 Annunciation 32

FACILITY STATUS 15 19 23 27 31 35 39 43 47 51 55 59

POWER 19 23 27 31 35 39 43 47 51 55 59

OTHER STATUS 23 27 31 35 39 43 47 51 55 59

METHOD OF DISCOVERY 27 31 35 39 43 47 51 55 59

DISCOVERY DESCRIPTION 31 35 39 43 47 51 55 59

16 Z 33 Z 34 NA 35 NA 36 NA

ACTIVITY CONTENT 16 20 24 28 32 36 40 44 48 52 56 60

RELEASED OF RELEASE 20 24 28 32 36 40 44 48 52 56 60

AMOUNT OF ACTIVITY 24 28 32 36 40 44 48 52 56 60

LOCATION OF RELEASE 28 32 36 40 44 48 52 56 60

17 0 37 0 38 NA 39

PERSONNEL EXPOSURES NUMBER 17 21 25 29 33 37 41 45 49 53 57 61 65 69

TYPE 21 25 29 33 37 41 45 49 53 57 61 65 69

DESCRIPTION 25 29 33 37 41 45 49 53 57 61 65 69

18 0 40 NA 41

PERSONNEL INJURIES NUMBER 18 22 26 30 34 38 42 46 50 54 58 62 66 70

DESCRIPTION 22 26 30 34 38 42 46 50 54 58 62 66 70

19 Z 42 NA 43

LOSS OF OR DAMAGE TO FACILITY TYPE 19 23 27 31 35 39 43 47 51 55 59

DESCRIPTION 23 27 31 35 39 43 47 51 55 59

20 N 44 NA 45

PUBLICITY ISSUED NUMBER 20 24 28 32 36 40 44 48 52 56 60

DESCRIPTION 24 28 32 36 40 44 48 52 56 60