

## PLANT SYSTEMS

### BASES

#### 3/4.7.5 STANDBY NUCLEAR SERVICE WATER POND

The limitations on the standby nuclear service water pond (SNSWP) level and temperature ensure that sufficient cooling capacity is available to either: (1) provide normal cooldown of the facility, or (2) mitigate the effects of accident conditions within acceptable limits.

The limitations on minimum water level and maximum temperature are based on providing a 30-day cooling water supply to safety-related equipment without exceeding its design basis temperature and is consistent with the recommendations of Regulatory Guide 1.27, "Ultimate Heat Sink for Nuclear Plants," March 1974.

The peak containment pressure analysis assumes that the Nuclear Service Water (RN) flow to the Containment Spray and Component Cooling heat exchangers has a temperature of 86.5°F. This temperature is important in that it, in part, determines the capacity for energy removal from containment. The peak containment pressure occurs when energy addition to containment (core decay heat) is balanced by energy removal from these heat exchangers. This balance is reached far out in time, after the transition from injection to cold leg recirculation and after ice melt. Because of the effectiveness of the ice bed in condensing the steam which passes through it, containment pressure is insensitive to small variations in containment spray temperature prior to ice meltout.

To ensure that the RN temperature assumptions are met, Lake Wylie temperature is monitored. During periods of time while Lake Wylie temperature is greater than 86.5°F, the emergency procedure for transfer of ECCS flow paths to cold leg recirculation directs the operator to align at least one train of containment spray to be cooled by a loop of Nuclear Service Water which is aligned to the SNSWP.

#### 3/4.7.6 CONTROL ROOM AREA VENTILATION SYSTEM

The OPERABILITY of the Control Room Area Ventilation System ensures that: (1) the ambient air temperature does not exceed the allowable temperature for continuous-duty rating for the equipment and instrumentation cooled by this system, and (2) the control room will remain habitable for operations personnel during and following all credible accident conditions. Operation of the system with the heaters operating to maintain low humidity using automatic control for at least 10 continuous hours in a 31-day period is sufficient to reduce the buildup of moisture on the adsorbers and HEPA filters. The OPERABILITY of this system in conjunction with control room design provisions is based on limiting the radiation exposure to personnel occupying the control room to 5 rems or less whole body, or its equivalent. This limitation is consistent with the requirements of General Design Criterion 19 of Appendix A, 10 CFR Part 50. ANSI N510-1980 will be used as a procedural guide for surveillance testing.

9006200099 900512  
PDR ADOCK 05000413  
P FDC

The 18 month surveillance to verify a positive pressure of greater than 1/8 inch water gauge, with less than or equal to 400 cfm of pressurization flow is to be conducted using only one intake from outside air open. By testing the capability to pressurize the control room using each intake individually, the design basis which assumes reopening of the two intakes following isolation of chlorine, smoke or radiation is tested.