

TABLE 3.3.2-1
 CRVICS INSTRUMENTATION

TRIP FUNCTION	ISOLATION SIGNAL ††	MINIMUM OPERABLE CHANNELS PER TRIP SYSTEM	APPLICABLE OPERATIONAL CONDITION	ACTION
1. PRIMARY AND SECONDARY CONTAINMENT ISOLATION				
a. Reactor Vessel Water Level-Low Low, Level 2	B ^{(b)(f)}	2 ^(a)	1, 2, 3 #	20 25
b. Reactor Vessel Water Level-Low Low, Level 2 (ECCS Div. I and II)	B	2 ^(a)	1, 2, 3	29
c. Reactor Vessel Water Level-Low, Low, Level 2 (HPCS-NSPS Div. III and IV)	B	2 ^{(a)(m)}	1, 2, 3	29
d. Drywell Pressure - High	L ^{(b)(f)}	2 ^(a)	1, 2, 3	20
e. Drywell Pressure - High (ECCS Div. I and II)	L	2 ^(a)	1, 2, 3	29
f. Drywell Pressure - High (HPCS-NSPS Div. III and IV)	L	2 ^{(a)(n)}	1, 2, 3	29
g. Containment Building Fuel Transfer Pool Ventilation Plenum Radiation - High	Z ^{(b)(f)}	2 ^(a)	##	25
h. Containment Building Exhaust Radiation - High				
1) Outboard (Div. I) Valve Isolation	M ^{(b)(f)}	2 ^{(a)(o)}	1, 2, 3 #	29 25
2) Inboard (Div. II) Valve Isolation	M ^{(b)(f)}	2 ^{(a)(o)}	1, 2, 3 #	29 25
i. Containment Building Continuous Containment Purge (CCP) Exhaust Radiation - High	5 ^{(b)(f)}	2 ^(a)	1, 2, 3 #	29 25
j. Reactor Vessel Water Level-Low Low Low, Level 1	U	2 ^(k)	1, 2, 3 #	29 25
k. Containment Pressure-High	P	1 ^{(k)(1)}	1, 2, 3 #	29 25

CLINTON - UNIT 1

3/4 3-13

Amendment No. #7, #8, 50

TABLE 3.3.2-1 (Continued)
CRVICS INSTRUMENTATION

TABLE NOTATIONS

- (m) Four reactor vessel water level trip channels are logically combined in a one-out-of-two-twice configuration. For the purposes of the associated ACTION, each one-out-of-two logic is defined as a separate trip system.
- (n) Four drywell pressure trip channels are logically combined in a one-out-of-two-twice configuration. For the purposes of the associated ACTION, each one-out-of-two logic is defined as a separate trip system.
- (o) One trip system is associated with the A and B monitors; the other trip system is associated with the C and D monitors.
- (p) Each channel consists of five temperature modules and their associated sensors. A channel is OPERABLE if and only if five temperature modules and their associated sensors are OPERABLE.