U. S. NUCLEAR REGULATORY COMMISSION
CONTROL BLOCK:
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $
CON'T
[0 2] [With the plant in Mode 3 and the monthly channel check surveillarce in accordance
O 3 [with S023-3-3.28 in progress, pressure indicator 2PI-8300 for steam generator E-088
0 4 [located on Remote Shutdown panel 2L-411 read more than 120 psia greater than a
o similar indicator located on Control Room panel CR-52 and was declared inoperable.
Image: Since the redundant indicator on Control Room Evacuation Shutdown panel 2L-042
Iremained operable and the inoperable indicator was returned to service within the
Image: Constraint of the state of the s
7 8 9 SYSTEM CODE CODE SUBCODE COMPONENT CODE COMPONENT CODE COMPONENT CODE SUBCODE 0 9 10 11 12 13 1 N STR SUBCODE SUBCODE VALVE SUBCODE 0 9 10 11 12 13 1 N STR 14 11 15 12 16 10 9 10 11 12 13 13 N STR 16 11 19 12 16 19 12 10 11 19 10 10 10 10 11 12 13 13 10
CAUSE DESCRIPTION AND CORRECTIVE ACTIONS (27)
[1]] [returned to service on November 29, 1982. A revised LER will be provided
[1] when our investigation is complete on or about January 31, 1983.
7 8 9 FACILITY STATUS * POWER OTHER STATUS 30 METHOD OF DISCOVERY DISCOVERY DESCRIPTION 32 1 5 B 28 0 0 0 29 N/A B 31 Surveillance Testing
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
I I <thi< th=""> I <thi< th=""> <thi< th=""></thi<></thi<></thi<>
NUMBER DESCRIPTION (41) 1 8 7 8 9 11 12 11 LOSS OF OR DAMAGE TO FACILITY (43) 8301170492 110 12 110 12 110 12 110 12 110 12 110 12 110 12 110 12 110 12 110 12 110 12 110 12 110 12
I I I I 7 8 9 10 PUBLICITY N/A NRC USE ONLY ISSUED DESCRIPTION (45) N/A I
NAME OF PREPARER H.B. Ray HBR. y/ Winnty PHONE 714-492-7700