UNITED STATES

#### NUCLEAR REGULATORY COMMISSION

REGIONIV

611 RYAN PLAZA DRIVE, SUITE 400 ARLINGTON TEXAS 76011-8064

MAR 29 1994

50-313 Dockets:

50-368

Licenses: DPR-51

NPF-6

Entergy Operations, Inc.

ATTN: J. W. Yelverton, Vice President Operations, Arkansas Nuclear One

Route 3, Box 137G

Russellville, Arkansas 72801

SUBJECT: PUBLIC MEETING OF MARCH 1, 1994

This refers to the public meeting conducted at Arkansas Nuclear One on March 1, 1994. The purpose of this meeting was to discuss plant activities associated with Refueling Outage 10, which is scheduled to begin on March 11, 1994. This meeting was attended by those personnel listed in Attachment 1.

We found that your presentation provided a comprehensive review of the preparations, scope, and outage risk assessments for Refueling Outage 10. We note that you have planned a 44-day outage. The specific topics you discussed at this meeting are listed in Attachment 2.

Your outage planning to ensure important material improvements are accomplished with the minimum dose appeared to be comprehensive. We note your plans to perform an early boration and hydrogen peroxide flush to reduce the source term and to increase the use of remote dose monitoring and video cameras to reduce dose. You also seem to have evaluated previous dose history and targeted high dose jobs for permanent hardware improvements. We note plans for extensive steam generator inspection, replacement of four high pressure safety injection valves, four containment electrical penetrations, and modifications to your secondary system to reduce causes of condenser tube failures.

Your use of a layered system to effectively control outage risk has worked well for you in the past and appears to have continued to improve. We note that you have scheduled three offsite power supplies and two onsite emergency diesel generators to be available during reduced inventory. As previously committed, we also note that you will notify us if power supply redundancy is degraded below the two emergency diesel generators and one offsite power supply condition that is planned during periods of reduced inventory.

Your plans to provide evolution specific simulator training to operators prior to the startup and shutdown, as well as providing extensive simulator training

9404050045 940329 ADOCK 05000313

in shutdown cooling operation and failure mitigation, demonstrates appropriate emphasis on safety.

In accordance with 10 CFR 2.790 of the NRC's "Rules of Practice," a copy of this letter and its enclosures will be placed in the NRC Public Document Room.

Should you have any questions concerning this matter, we will be pleased to discuss them with you.

Sincerely,

A. Bill Beach, Director Division of Reactor Projects

Attachments:

1. Attendance List

2. Licensee Presentation

cc w/attachments:

Entergy Operations, Inc.

ATTN: Harry W. Keiser, Executive

Vice President & Chief Operating Officer

P.O. Box 31995

Jackson, Mississippi 39286-1995

Entergy Operations, Inc.

ATTN: John R. McGaha, Vice President

Operations Support

P.O. Box 31995

Jackson, Mississippi 39286

Wise, Carter, Child & Caraway

ATTN: Robert B. McGehee, Esq.

P.O. Box 651

Jackson, Mississippi 39205

Honorable C. Doug Luningham County Judge of Pope County Pope County Courthouse

Russellville, Arkansas 72801

Winston & Strawn

ATTN: Nicholas S. Reynolds, Esq.

1400 L Street, N.W.

Washington, D.C. 20005-3502

Arkansas Department of Health
ATTN: Ms. Greta Dicus, Director
Division of Radiation Control and
Emergency Management
4815 West Markham Street
Little Rock, Arkansas 72201-3867

B&W Nuclear Technologies ATTN: Robert B. Borsum Licensing Representative 1700 Rockville Pike, Suite 525 Rockville, Maryland 20852

Admiral Kinnaird R. McKee, USN (Ret) 214 South Morris Street Oxford, Maryland 21654

ABB Combustion Engineering
Nuclear Power
ATTN: Charles B. Brinkman
Manager, Washington
Nuclear Operations
12300 Twinbrook Parkway, Suite 330
Rockville, Maryland 20352

bcc to DMB (IEO1)

bcc distrib. by RIV: L. J. Callan Branch Chief (DRP/D) MIS System RIV File Project Engineer (DRP/D)

Resident Inspector Lisa Shea, RM/ALF, MS: MNBB 4503 DRSS-FIPB Branch Chief (DRP\TSS)

C:DRP/D	D: DRP	
TFStetka;df	ABBeach	
3/22/94	3/29/94	

bcc to DMB (IEO1)

bcc distrib. by RIV: L. J. Callan Branch Chief (DRP/D) MIS System RIV File Project Engineer (DRP/D)

Resident Inspector Lisa Shea, RM/ALF, MS: MNBB 4503 DRSS-FIPB Branch Chief (DRP\TSS)

C:DRP/D	D: DRP	
TFStetka;df	ABBledch	
3/22/94	3/19/94	

#### ATTACHMENT 1

#### Licensee Personnel

- C. Anderson, Unit 2 Operations Manager
- S. Bennett, Licensing Supervisor
- D. Binkley, Reactor Building Lead Coordinator
- M. Bourgeois, Unit 2 Outage Manager
- S. Cecil, Unit 2 Shift Operations Superintendent, Shift Outage Coordinator
- R. Edington, Unit 2 Plant Manager
- R. Espolt, Unit 2 Technical Assistant to Plant Manager
- D. Gregory, Unit 2 Planning/Scheduling Coordinator
- M. Harris, Unit 2 Maintenance Manager
- D. Harrison, Steam Generator Engineer
- B. James, Outage Support Coordinator
- D. Mims, Licensing Director
- T. Mitchell, Unit 2 System Engineering
- S. Robinson, Station ALARA Supervisor
- J. Sutterfield, Unit 2 Operations
- P. Williams, Shutdown Safety Advisor/Nuclear Safety Analysis
- A. Wrape, III, Shift Outage Manager

#### NRC Personnel

- T. Alexion, NRC Project Manager
- L. Smith, NRC Senior Resident Inspector
- T. Stetka, Chief, Project Branch D

#### 2R10 PREVIEW TO THE NRC MARCH 01, 1994 GSB-107, 1300

#### **AGENDA**

. INTRODUCTION AND Dwight Mims
OPENING COMMENTS Randy Edington

II. PAST OUTAGE PERFORMANCE Mike Bourgeois

III. OPERATIONS & Craig Anderson/ SHUTDOWN SAFETY Sam Cecil

IV. 2R10 SCOPE AND SCHEDULE Mike Bourgeois

V. OUTAGE RISK ASSESSMENT & Patrick Williams
MANAGEMENT

VI. CONCLUDING REMARKS Randy Edington



#### Arkansas Nuclear One

Russellville, Arkansas



#### 2R10

ARKANSAS NUCLEAR ONE - UNIT 2 PRESENTATION TO NRC - 03/01/94



# Introduction & Opening Comments

- Dwight Mims
- Licensing Manager
- Randy Edington
- Plant Manager Unit 2

#### Past Outage Emphasis

Presented By:
Mike Bourgeois
Outage Manager - Unit 2

"We are what we repeatedly do.

Excellence, then, is not a act, but a habit."

Aristotle


# Underlying Outage Philosophy

- Outage Planning is a Continuous Process
- Outages are Repeatable
  - -80% Repeatable
  - -10% Predictable
  - -10% New
- Maximize Equipment Availability
- Outage Planning Supports the Safety Function Concept

#### Total Quality Objectives

- Ensure Personnel Safety
- Assure Shutdown Safety
- Reduce Personnel Radiation Exposure
- Improve Plant Availability
- Reduce Outage Cost
- Optimize Outage Duration


# Configuration Control Maintaining




# Planning

- Product of Process Management
  - ✓ Plan
  - ✓ Do
  - ✓ Check
  - ✓ Adjust

# Outage Planning Process




#### Outage Duration Comparison (Output Measure of the Process)





# Outage Job Orders (Output Measure of the Process)

- Improved Material Condition
- Efficiency Gains
  - -Work Processes
  - -Work Packages
- Technology Improvements



# Refueling Outage Exposure (Output Measure of the Process)





Defense Depth Technical Specifications, Safety Analysis Report Operating & Station Administration Procedures NUMARC 91-06, Commitments, Outage Plan Guidelines


## Operations Shutdown Safety

- Presented By:
- Craig Anderson
- Operations Manager Unit 2

### Safe Operating Environment

- Layered Protection
- Establishing Shutdown Safety Mindset
- Providing Operating Controls
  - -Reduce Probability of Shutdown Events
  - Protect Equipment needed for Safe Shutdown Operation
  - Protect Equipment needed for Mitigation of Shutdown Events

# Layered Protection



#### Training/Mindset

- Shift Superintendent Meetings
- Classroom Training
- Simulator Training
- Evolution Specific Training
- Outage Crew Meetings

# Operating Controls (Shutdown Cooling Control Procedure)

- Provides Physical Protection of Operating Shutdown Cooling Train & Associated Equipment
- Provides Routine Review of SDC & RCS Makeup Source Line
- Tracks Containment Closure Issues
- Specifies Requirements for RCS Monitoring Instruments

# Operating Controls (Shutdown Cooling Control Procedure)

- Specifies Additional Controls for Operation During Draindown
  - Pre-draindown Briefing
  - Dedicated Draindown Watch
  - Containment Breaches Approved by Ops Management
  - -Additional Level Instrumentation

# Shift Outage Manager & Score Cards

- Presented By:
- Sam Cecil
- Shift Operations Superintendent
- Shift Outage Manager for 2R10

Dynamic Static THE CASE OF THE COSE 語を表める。 Outsign Soft Reviewed **经过强的股份的股份** PSC Sub-committee formed for Independent Revie SOPP Dynamic Static VOPS Phil/Proc Verify to ORMG: V NUREG 1449

APPROVED OUTAGE PLAN

### Shift Outage Manager

Provides round the clock outage management for logistic, communications, coordination and interface support of the outage schedule.

- Major Communication Link with Control Room
- Management Oversight / Decision Making Authority
- Maintain Focus on Shutdown Safety
- Conduct Shift Outage Meetings
- Review Emergent Work



#### 2R10 SCORE Card 2A

- Condition Definition
- Equipment Requirements
  - A RCS Decay Heat Removal
  - B RCS & SFP Inventory Control
  - C Electrical Power Distribution
  - D Reactivity Control
  - E Containment Closure
  - F Miscellaneous

#### 6.2. CONDITION 2 REDUCED INVENTORY (RCS Level < 375' Elevation) DRAINED TO CENTERLINE OF HOT LEG

This condition begins with the draining of the RCS to reduced inventory. The opening of the S/G secondary side and the installation of the Nozzle Dams will occur during this condition but the longest activity requiring the reduced inventory window will be the replacement of "D" RCP seal.

This condition ends with closing the reduced inventory window.

- A. RCS Decay Heat Removal Equipment Requirements:
- \* As specified by 2R10 SCORE Cards 2A.
- \* I wo methods of heat removal
- B. RCS & SFP Inventory Control Requirements:
- \* As specified by 2R10 SCORE Cards 2A.
- \* One source and two (2) flow paths
- C. Electrical Power Distribution Requirements:
- \* As specified by 2R10 SCORE Cards 2A.
- \* Offsite and emergency power supplies:

3 of 5 (both EDG and an offsite)


4168 VAC load centers - both

480 VAC load centers - both

- D. Reactivity Control Requirements:
- \* As specified by 2R10 SCORE Cards 2A.
- Boric Acid Injection Paths 1 of 3
- \* Source Range Channels one
- Boron Dilution Tagout in place
- \* RICB open
- F. Containment Closure Requirements:
- \* Containment Closure Not Required
- F. Miscellaneous:
- A minimum of two independent Core Exit Thermocouples (CETs).
- " Two independent loop "A" hot leg level instruments (except during calibration.).
- Tygon tube level indication available and manned when changing RCS level.

#### 2R10 SYSTEMATIC CONTROL OF OUTAGE RISK EVOLUTIONS SCORE CARD 2A - SAFETY FUNCTION SYSTEMS AVAILABILITY

	MA	INTENANCE OF HEAT REMOVA	L: (FIG. 4.2.1.A)	A	В	С	D	E
elo co	STORYSTENIS	SPENT FUEL POOL COOLING	CONTRACTOR OF STREET	SFPCA	SFPCB	*sw		
	2.	REACTOR COOLANT SYSTEM	(MIN 2 OF 5)	S/G A	S/G B	SDCA	SDCB	> 390
	MA	INTENANCE OF INVENTORY: (F	(G. 4.2.2.A)	A	В	С	D	E
	1.	RCS MAKEUP SOURCE	(MIN 1 OF 3)	2T6A	2T6B	RWT		
	2.	RCS MAKEUP FLOW PATHS	(MIN 2 OF 4)	HPSIA	SPRAY	HPSIB	CHG	
	3,	SFP MAKEUP FLOW PATH	(MIN 1 OF 5)	2P39/ 2P109	2948	2986	*sW1	*sW:
	MA	INTENANCE OF VITAL AC: IFIG	. 4.2.3.A)					
	1.	POWER SOURCES	(MIN 3 OF 5)	2DG1	2DG2	2X02 (AUX)	2X03 (SU3)	X04 (SU2
	2.	4160 VAC LOAD CENTERS	(MIN 2 OF 2)	2A3	2A4			
	3.	480 VAC LOAD CENTERS	(MIN 2 OF 2)	285	286			
	4.	480 VAC MCCs	(MIN 4 OF 8)	2851	2852	2853	2854	
				2861	2862	2863	2864	
	5.	120 VAC BUSSES	(MIN 3 OF 4)	2RS1	2RS2	2RS3	2RS4	
	MA	MAINTENANCE OF VITAL DC: (FIG. 4.2.3.8)			C	D	8	
		VITAL (125V) DC BUS	AND DESCRIPTION OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON OF T	2D31 &2D01	2034 &2001	2D34 &2D02	2D32 &2D02	
E.	MA	MAINTENANCE OF REACTIVITY: (FIG. 4.2.4.A)			В	С	T	
			(MIN 1 OF 3)	2T6A	2768	RW:		
	2.	BORIC ACID FLOW PATH	(MIN 1 OF 3)	[ HPSIA ]	HPSIB	сна		
	3.	SOURCE RANGE CHANNELS	(MIN 1 OF 2)		8			
	4.	BORON DILUTION TAGOUT	IN PLACE			NOT IN PLACE		
	6	LOG CHANNELS (M	IN 3 OF 4 OR RTCB OPEN)	A	В	С	D	OPE



#### 2R10 SCORE Card 2A

- Expected Duration
- Special Precautions
- Major Activities
- Requirements for Advancing to Next Schedule Period

#### 2R10 SCORE Card 2A

Expected Period Duration: 72 hours

The duration for the 2R10 Schedule Period 2A is dependent on completing the RCP seal replacement work.

#### Special Precautions:

- \* Both SDC loops are available.
- \* Time to boil may be less than 30 minutes and time to uncovery is just over 2 hours (assuming no SDC or makeup available).
- \* Do not perform any maintenance or testing on any of the protected systems and avoid system alignment changes that could cause SDC flow or RCS level perturbations.

Major activities also in progress during thas Schedule Period include:

- \* The HPSI system is being prepared for the replacement of four (4) valves.
- \* "B" RCP motor replacement efforts are in progress.
- \* "D" RCP seal replacement efforts are in progress.

Required changes to safety function availability to progress into SCORE Card 3A:

\* The RCS is filled to the head removal level.

#### 2R10 Scope & Schedule

- Presented By:
- Mike Bourgeois
- Outage Manager

#### Previous Outage Good Practices

- Shutdown Protection Plan
- Shift Outage Managers
- Early Boration & Hydrogen Peroxide Flush
- Core Teams

# 2R10 Initiatives

- Early Integrated Leak Rate Testing
- Safety Injection Hydro Plug
- Shutdown Safety Enhancements
- Expansion of Core Teams
- Long Range Plan

#### 2R10 Initiatives

- Levelize Weekend Manpower
- New Outage Control Center & Expansion of Communications Network
- Work Package Enhancements
- Contingency Task Development

## 2R19 Scheduled Duration

• Start:

March 12, 1994

• End:

April 24, 1994

### 2R10 Major Projects

- Integrated Leak Rate Testing
- 'B' RCP Motor Replacement
- Replace Impellers on 'A' & 'B' Circ Water Pumps
- 'B' Circ Water Pump Motor Overhaul
- Major Inspection of LP 'A' Turbine Rotor
- Modification to MSR 'A'

### 2R10 Major Projects

- Replace Service Water Piping Train 'A'
- Replace 4 High Pressure Safety Injection Valves
- Replace 4 Containment Electrical Penetrations
- Steam Generator Inspection


### Steam Generator Work Scope


- 100% Bobbin Full Length
- 100% Hot Leg RPC at Top of Tubesheet
- 20% Cold Leg RPC at Top of Tubesheet
- 20% of Dented Tube Support Plates on Hot Leg Side with RPC
- Selected RPC of Bobbin Indications at Support Plates/Sludge Pile
- 100% Inspection of Existing Sleeves
- Secondary Side Inspection of "B" SG
- Sludge Lancing of both SG's

### 2R10 Work Load

• Repetitive Tasks (PM's):	1148
• Corrective/Enhancement:	1108
• Plant Changes:	41
• DCP's:	28

### Outage Manhours (Output Measure of the Process)





### MEN ORAM-TIP


Presented by:

# Risk Contribution Pie Chart


## ORAM-TIP Key Points

- ORAM-TIP is not a replace for solid program
- Model updatable during outage
- Check of Defense-in-Depth

# Safety Function Status Display



### ORAM-TIP Risk Profile



## Concluding Remarks

### Presented by:

Randy Edingham

Part Manager - Unit 2