

GPU Nuclear

100 Interpace Parkway Parsippany, New Jersey 07054 201 263-6500 TELEX 136-482 Writer's Direct Dial Number:

November 29, 1982

Mr. Dennis M. Crutchfield, Chief Operating Reactors Branch #5 Division of Licensing U. S. Nuclear Regulatory Commission Washington, DC 20555

Dear Mr. Crutchfield:

SUBJECT: Oyster Creek Nuclear Generating Station Docket No. 50-219 SEP Integrated Assessment

Our recent letter dated November 16, 1982, provided our schedules for equipment modifications and additions resulting from SEP integrated assessment. The letter also provided GPU Nuclear Corporation (GPUNC) positions concerning resolutions of some of the SEP topics proposed by the NRC staff with which we disagreed.

Subsequently, the NRC staff requested a meeting for further discussion of the schedules and topic resolutions in order to reach agreement between GPUNC and the NRC staff. That meeting was held on November 18, 1982 and we were able to reach agreement on all items.

ATTACHMENT I to this letter lists schedule and resolution agreed at our meeting for each of the topics.

A035

8212060247 821129 PDR ADDCK 05000219 P PDR Mr. D. M. Crutchfield Page 2 November 29, 1982

We are also transmitting the revised integrated assessment summary table (Table 4.1 of draft NUREG 0822) as ATTACHMENT II. The revised table reflects the agreements reached during our November 18, 1982, meeting with the NRC staff. The revised portions of the table are indicated by double asterisks (**).

Very truly yours,

P.R. Clark

P. R. Clark Executive Vice President

blf Attachments

cc: Ronald C. Haynes, Administrator Region 1 U. S. Nuclear Regulatory Commission 631 Park Avenue King of Prussia, NJ 19406

> NRC Resident Inspector Oyster Creek Nuclear Generating Station Forked River, NJ 08731

SEP TOPIC SCHEDULES AND RESOLUTIONS AGREED ON NOVEMBER 18,1982 BETWEEN GPUNC AND THE NRC STAFF

TOPIC NO. III-5E Pipe Break Outside Containment

As stated in our November 16, 1982 letter, GPUNC will prepare and transmit a report to the NRC by February 28, 1983, which predicts crack growth rate in the Oyser Creek isolation condenser lines. Based on our findings GPUNC will propose an appropriate leakage detection method with adequate sensitivity. Our preliminary evaluation indicates the extremely slow growth rate will allow the use of a crack with sufficiently large leak rate for visual and audio detection

TOPIC NO. V-5 Reactor Coolant Pressure Boundary Leakage Detection

GPUNC will perform a "leak before break" analysis for the most limiting piping to justify the sensitivity of the current leak detection systems available in the containment sump. Results of the analysis will be transmitted to the NRC by June 30, 1983. GPUNC will also propose Technical Specification change before Cycle 10 startup to include operability requirement of the leakage detection systems inside containment. GPUNC will prepare action statements in Technical Specifications.

TOPIC NO. VIII-3B DC Power System Bus Voltage Monitoring and Annunciation

Our November 16, 1982 letter stated that the battery status alarms will be installed during Cycle 11 refueling outage due to the number of modifications already planned in the control room during the forthcoming (Cycle 10) outage. However, the NRC staff requested an intermediate resolution of this issue since PRA performed by the NRC consultant rated this issue of high risk importance. GPUNC will provide an intermediate resolution which consists of periodic inspections of the safety related battery systems such as verification of battery breaker position, battery current, charger current, etc. Plant inspection procedure will be revised to include the periodic inspection of the battery systems before Cycle 10 starup. The intermediate resolution will be in effect until the installation of the battery status alarms during Cycle 11 outage.

TOPIC NO. V-12A Water Purity of BWR Primary Coolant

Our November 16 1982 letter to the NRC stated that GPUNC will revise Oyster Creek Technical Specifications after examining our Cycle 10 experience. However, during our meeting on November 18, 1982, the NRC staff requested GPUNC to revise Technical Specifications before Cycle 10 startup. GPUNC agreed to revise Technical Specifications prior to Cycle 10 startup incorporating Reg. Guide 1.56 limits for conductivity and chloride concentration. Action statements will be proposed by GPUNC. The NRC staff concluded in the meeting that an issuance of a special report rather than an LER by GPUNC would be acceptable following a violation of the Reg. Guide limit for conductivity. The existing limit for conductivity will still remain as an upper bound for the plant operation.

TOPIC NO. XV-16, XV-18 Radiological Consequences of Failure of Small Lines Carrying Primary Coolant and Main Steam Lines Outside Containment

GPUNC will revise Oyster Creek Technical Specification adopting General Electric Standard Technical Specifications for iodine limits before Cycle 10 startup. GPUNC will propose action statements.

TOPIC NO. III-4A Tornado Missiles

GPUNC will provide a portable pump and hoses for shutdown heat removal during a postulated tornado missile incident. The pump and hoses will be housed in the area of Reactor Building which is protected from the tornado missiles and flooding (the pump will also be used as a redundant pump to the existing condensate transfer pump during a postulated maximum hurricane flood -See SEP Topic II-3B in ATTACHMENT II). Since placing of the pump and hoses is not outage related, GPUNC will complete the project by the end of 1984. The project also include revising the plant emergency procedure for tornado incidents.

TOPIC NO. VI-7.A.3 Emergency Core Cooling System Actuation System TOPIC NO. VI-10A Testing of Reactor Trip System and ESF, Including Response Time Testing

Before Cycle 10 startup GPUNC will revise Technical Specifications to include the emergency condenser logic testing and the reactor trip system testing in accordance with the instruction provided in our current surveillance procedures for both systems.

Table 4.1 Integrated assessment summary

SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backfit requirements	Licensee agrees	Comple- tion date	PRA
11-3.8, 11-3.8.1,	4.1(1)	Condensate Transfer Pamp Power	No	See SEP Topic No. III-4A** Section No. 4.6.4	yes*	12/84**	•
I-3.C	4.1(2)	Flooding Level Procedures	No	None	100		
	4.1(3)	Canal Water Level Instrumentation	No	Install automatic water level instrumentation in the intake canal.	Yes	Cycle XI	•
	4.1(4)	Isolation Condenser Flooding	No	Demonstrate minimum quantity of water maintained in condensate storage tark sufficient for long-term cooling and include minimum inventory in plant procedures.	Yes	Cycle X	-
	4.1(5)	Low Water Level Shutdown	No	None	Sec. 22	40 m	1.0
	4.1(6)	Hurricane Flooding of Pumps	No	Revise emergency procedures to identify alternate water sources and flow paths should low elevation pumps be flooded.	Yes	Cycle X	•
	4.1(7)	Flooding Elevation	No	Evaluate consequences of offgas building flooding and confirm all other entrance levels above 23.5 ft.	Yes	2/83**	•

See footnotes at end of table.

Oyster Creek SEP

lable 4.1 (Continued)

1

SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backfit requirements	Licensee	Comple- tion	PRA
11-3.C	4.1(8)	Groundwater Elevation	No	See Item 4.4(2).	-		racing
	4.1(9)	Roof Drains	No	Install scuppers in the reactor building and turbine building parapets.	Yes	Cycle X +6 mo.	
III-1 '	4.2	Classification of Struc- tures, Components, and Systems	No	Evaluate design of specified components on a sampling basis, upgrade if necessary, and document classification in FSAR update.	Yes	10 CFR 50.71 (e)(3)(ii)	•
111-2	4.3.1	Reactor Building Steel Structure Above the Operating Floor	No	Analyze and identify any needed upgrading of reactor building upper steel structure for wind loads.	Yes	12/82**	•
	4.3.2	Ventilation Stack	No	Analyze and identify any needed upgrading of ventila- tion stack for wind loads.	Yes	12/82**	-
	4.3.3	Effects of Failure of Nonseismic Category I Structures	No	Analyze turbine building capacity for wind loads, evaluate consequences of failure and identify any needed upgrading.	Yes	6/83	•
	4.3.4	Components Not Enclosed in Qualified Structures	No	None			-
	4.3.5 .	Exterior Masonry Walls	No	Rone	1.44	8 - 7 T	

See footnotes at end of table.

Oyster Creek SEP

Table 4.1 (Continued)

SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backfit requirements	Licensee agrees	Comple- tion date	PRA rating
111-2	4.3.6	Roof Decks	No	Provide analysis of reactor building roof.	Yes	12/82**	-
				Analyze capacity of turbine building roof to withstand wind loads.	Yes	6783	-
	4.3.7	Intake Structure, Oil Tanks, and Diesel Gener- ator Building	No	Analyze capacity to with- stand wind and tornado loads and upgrade, if necessary.	Yes	12/82**	-
	4.3.8	Load Combinations	No	Submit analyses demon- strating wind loads were properly combined with other specified loads.	yes *	_ 6/83**	
	4.3.9	Soil and Foundation Capacities	No	None	- 1		-
11-3.A	4.4(1)	Hydrostatic Loads (Combination)	No	None	- 83		-
	4.4(2)	Hydrostatic Loads (Short-Duration)	No	Evaluate short-duration hydrostatic loads on and floatation potential of structures essential to safe shutdown in conjunction with flooding emergency procedures (Item 4.1(6)).	Yes	4./83	
	4.4(3)	Below-Grade Penetration	Nu	Hote			-

Oyster Creek SEP

111	ACHP	ENI	11	

lable 4.1 (Continued)

SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backfit requirements	Licensee	Comple- tion	PRA
111-3.C	4.5.1	Intake and Discharge Canals	No	None	-	-	- acing
	4.5.2	Intake Structure Trash Racks and Intake Screens	No	Formalize existing inspec- tion practice as part of shift turnover or inservice inspection (ISI) procedures until water level modifi- cation is complete (Item 4.1(3)).	Yes*	Cycle X**	
44	4.5.3	Roof Drains	No	See 11cm 4.1(2)	. 996		
	4.5.4	Inspection Program	No	Develop and implement a formal inspection program for water control structures.	Yes	Cycle X	-
II-4.A	4.6.1	Emergency Diesel Generators and Fuel Oil Day Tank	No	Analyze potential for and co sequences of tornado- missile damage of the diesel generator building.	Yes	3/83	•
4.6.2 Mechanical Equipment Access Area	Mechanical Equipment Access Area	No	Evaluate the potential for and consequences of tornado- missile impact in the reactor building access door region and identify any necessary corrective actions.	Yes	1/83	-	
	4.6.3	Control Room, Reactor Building, and Turbine Building Heating, Ventilating, and Air Conditioning (HVAC) Systems	No	None		-	-

See fuotnotes at end of table.

Oyster Creek SEP

	ATTACHMENT	II I	
	Table 4.1 (Continued)	
	lech. Spec. modifications required from	Backtit	
Title	SEP review	requirements	License

reek SE	SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backtit requirements	Licensee agrees	Comple- tion date	PRA
P	III-4.A	4.6.4	Condensate Storage Tank, Torus Water Storage Tank, and Service Water and Emergency Service Water Pumps	No	Provide protection for sufficient systems and components to ensure a safe shutdown in the event of damage from tornado missiles. 8	Yes**	12/84**	
	III-4.8	4.7	Turbine Missiles	No	Inspect turbine and propose inspection frequency based on results.	Yes	12/54	
4-					Justity monitoring program for main steam and reheat control valves.	Yes	2/83*	•
50	III-4.D	4.8.1	Truck Explosion	No	None			
		4.8.2	Aircraft Hazards	No	Evaluate potential for or consequences of aircraft impact.	Yes	3/83	-
	111-5.A	4.9(1)	Cascading Pipe Breaks	No	See Item 4.16.			
		4.9(2)	Jet Impingement Effects	No	None			_
		4.9(3)	Drywell Penetration	No	None			

See footnotes at end of table.

1.000	
0	
4	
ŝ	
et	
m	
-	
0	
-3	
0	
P	
T	
10	

Table 4.1 (Continued)

SEP Topic No.	Section No.	Title	lech. Spec. modifications required from SEP review	Backtit requirements	Licensee agrees	Comple- tion date	PRA
111-5.В	4.10(1)	LOCA Outside Containment	No	Evaluate and identify any needed upgrading of the main steam and reactor water cleanup (RWCU) piping outside containment to preclude an unisolatable break outside containment.	Yes	3/83	-
	4.10(2)	Emergency Condenser Isolation	No	Lvaluate and identify modi- fication to provide leakage detection to ensure flaws would be detected before pipe break occurs.	Ye.	Cycle X	-
11-6	4.11(1)	Piping Systems	No	Analyze on a sampling basis and verity adequacy of support designs for the seismic resistance of specified piping systems.	Yes	Cycle X	•
	4.11(2)	Mechanical Equipment	No	Demonstrate that the control rod drive system and vessel internals have sufficient capacity to resist a safe shutdown earthquake or take corrective action.	Ye.	12/82*	-
	4.11(3)	Electrical Equipment	No	Reevaluate 4160-V switch- gear panel anchorage and demonstrate, on a sampling basis, adequacy of electri- cal panel supports.	Yes	Cycle X start 18 mo.	•

1

See footnotes at end of table.

Oyster Creek SEP

Table 4.1 (Continued)

SEP Topic No.	Section No.	Title	fech. Spec modifications required from SEP review	Bastfil requirements	Licensee aurees	Comple- Lion	PRA
111-6	4.11(4)	Ability of Safety- Related Electrical Equipment to Function	No	Rone		*	-
	4.11(5)	Qualification of Cable Trays	No	Provide plan to implement results of SLP Owners Group Program on a plant- specific basis.	Yes	Cycle X	-
11I-7.B	4.12	Design Codes, Design Criteria, Load Combinations and Reactor Cavity Design Criteria	No	Evaluate adequacy of original design criteria on a sampling basis for specified structural elements.	Yes	6/83	•
III-8.A	4.13	Loose-Parts Monitoring and Core Barrel Vibration Monitoring	No	flone	•	•	Low
III-10.A	4.14(1)	Thermal Overload Bypass	No	Evaluate thermal-overload hypasses for engineered safety features (ESF) valves.	Yes	12/82**	Mediumi
	4.14(2)	Magnetic Trip Breakers	No	Hone			
IV-2	4.15	Reactivity Control Systems, Including Functional Design and Protection Against Single Failures	No	llone		-	Low

See footnotes at end of table.

Oyster Creek SEP

Table 4.1 (Continued)

SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backfit requirements	Licensee agrees	Comple- tion date	PRA rating
V-5	4.16.1	Airborne Particulate and Gaseous Radioactivity Monitoring	No	Make these monitors operational	Yes*	Cycle X**	Low
				Topic III-5.A analysis.			
	4.16.2	Operability Requirements	Yes	Include leakage detection system limiting conditions for operation in fechnical Specifications.	Yes**	12/82	-
	16.1	Intersystem Leakage	No	Rone			
	4.16.4	Reactor Coolant Inventory Balances	Ņo	None	- 12		-
V-6	4.17	Reactor Vessel Integrity	No	Submit a plan for the material surveillance capsules.	Yes	12/82**	
/-10.B	4.18	Residual Heat Removal System Reliability	Νσ	Review and upgrade, if necessary, shutdown procedures to specify alternate sources of water for primary and secondary makeup, with particular attention to external events	Yes	Before* Cycle 10 Startup	Low
/-11.A	4.19	Requirements for Isotation of Hign- and Low-Pressure Systems	No	Demonstrate relief capacity and acceptable consequences, or identify corrective action to protect Kact system	Yes	1/83	10.4*

See toolnotes at end of table.

Oyster Creek SEP

Table 4.1 (Continued)

.

SEP Topic No.	Section No.	Title	lech. Spec. modifications required from SEP review	Backfil requirements	Licensee dyrees	Comple- tion uale	PRA rating
V-12. A	4.20	Water Purity of BWR Primary Coolant	Yes	Implement proposed procedure and modify lechnical Specifi- cations to be consistent.	Yes*	Cycle X**	-
VI-1	4.21.1	Organic Materials	No	Inspect and repair, if necessary, drywell coatings and recoat the torus.	Yes	Cycle X 46 mo.	-
6. S	4.21.2	Postaccident Chemistry	No	Rome			-
VI-4	4.22.1	Locked-Closed Valves	No	Provide schedule to implement physical locking devices to ensure valves are not inadvertently opened.	Yes	11/82	Low
	4.22.2	Remote Manual Valves	No	Provide leakage detection and, if necessary, relocate the operating station for isolation valves in the containment spray and core spray systems.	Yes*	Cycle X**	•
	4.22.3	Valve Location	No	None			- /
	4.22.4	Instrument Lines	No	None		2	-
	4.22.5	Valve Location and Type	No	None	-		_
	4.22.6	Remote Manual Valves	No	None	_		1
VI-7.A.3	4.23 .	Emergency Core Cooling System Actuation System	Yes	Include emergency condenser logic testing in the lechnical specifications.	Yes**	Gycle X**	-

See footnotes at end of table.

Uyster Creek SEP

ATTACHMENT II Table 4.1 (Continued)							
SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backtii requirements	Licensee agrees	Comple- tion date	PRA
VI-7.A.4	4.24	Core Spray Nozzle Effectiveness	No	None	-	-	-
VI-7.C.1	4.25(1)	AC Automatic Bus Transfers	No	Evaluate the existing automatic bus transfers and identify corrective actions to ensure faulted loads would not be transferred.	Yes*	12/82	Medium
	4.25(2)	DC Automatic Bus Transfers	No	None			
VI-10.A	4.26.1	Response-Time Testing	No	None		-	Low
4.26	4.26.2	Instrumentation for Reactor Trip System (RTS) lesting	No	Verity all safety logic channels tied to the reactor mode switch are tested by procedure.	Yes	12/82	•
			Yes .	Include logic channel testing in fechnical Specifications.	Yes**	Cycle X**	•
	4.26.3	Dual-Channel Testing	No	None	-	-	1
VII-1.A	4.27(1)	Flux Monitoring Isolation	No	Perform failure mode and effect analysis to determine whether isolation devices are required and identify any needed upgrading.	Yes	12/82	Low
	4.27(2)	Reactor Protection System (RPS) Protective Trip	No	Lastall Cross if protection at the Responser supply and Reserventace	Yes	Cycle XI	- 7

See tootnotes at end of table.

Oyster Creek SEP

lable 4.1 (Continued)

SEP Topic No.	Section No.	litle	Tech. Spec. modifications required from SEP review	Backfit requirements	Licensee agrees	Comple- Lion date	PRA
VII-1.B	4.28	Trip Uncertainty and Setpoint Analysis Review of Operating Data Base	No	Install analog trip system	Yes	Cycle X1	Low
VII-2	4.29	Engineered Safety Features System Control Logic and Design	•	See Item 4.14(1).	-		Low
VI.I-3	4.30	Systems Required for Safe Shutdown	No	Provide minimum inventory for condensate storage tank as a water source for flood- ing events (Item 4.1(4)) and identify non-1SF equip- ment in cooldown procedures (Item 4.18).			Low
111-2	4.31	Onsite Emergency Power Systems (Diesel Generator)	No	Modify annunciators to conform to IEEE Std. 279-19/1 and bypass two trips (voltage-ampere reactive and reverse power) during accident conditions.	Yes	Cycle XI	Low
111-3.8	4.32	DC Power System Bus Voltage Monitoring and Annunciation	No	Schedule installation of specified battery status alarms.	Yes	12/82**	High
111-4	4.33	Electrical Penetrations of Reactor Containment	No	None	•		42.5

See footnotes at end of table.

Oyster Creek SEP

Table 4.1 (Continued)

SEP Topic No.	Section No.	Title	Tech. Spec. modifications required from SEP review	Backtin requirements	Licensee	Comple- tion	PRA
1x-5	4.34(1)	Restoration of Ventilation	No	Lvaluate and revise, if necessary, the loss-of- offsite-power procedures to ensure that restoration of ventilation systems will not overload the diesels.	· Yes	3/83	-
	4.34(2)	Reactor Building Ventilation	Nu	None	* - 2		
	4.34(3)	Core Spray and Containment Spray Pump Ventilation	No	Demonstrate subject pumps can operate with a loss of ventilation, or identify corrective action, as necessary.	Yes	3/83	·
	4.34(4)	Battery, Motor-Generator, and Switchgear ∀entilation	No	Evaluate effects of loss of ventilation to the subject rooms and identify any needed upgrading.	Yes	12/83	•
XV-1	4.35	Decrease in Feedwater Temperature, Increase in Feedwater Flow, and In- crease in Steam Flow and Inadvertent Opening of a Steam Generator Relief or Safety Valve	No	Rone		-	
XV-16	4.36	Radiological Consequences of Failure of Small Lines Carrying Primary Coolant Outside Containment	Yes	Implement BWR Standard lechnical Specification limit for primary coolant activity	Yes**	Cycle X**	-

Oyster Creek SEP

Lable 4.1 (Continued)

SEP Topic No.	Section No.	Title	<pre>fech. Spec. modifications required from SEP review</pre>	Backtit requirements	Licensee	Comple- tion	PRA
XV-18	4.37	Radiological Consequences of a Main Steam Line Failure Outside Containment	· · · · · · · · · · · · · · · · · · ·	See 11em 4.36.		-	-
XV-19 4.38 Lo Re of Wi	Loss-of-Coolant Accidents Resulting From Spectrum of Postulated Pipe Breaks Within the Reactor Coolant Pressure Boundary	No	Develop and implement a preventive maintenance program for the main steam isolation valves, or justify existing maintenance based on operating experience.	Yes	Cycle XI		
			Submit results of evalua- tion including testing experience.	Before* Cycle 10 Startup	Cycle X	•	

inght for other reasons as explained in the referenced section.

NOTES:

Later - the licensee has not yet responded.

.

Cycle - refers to the end of a specific refueling outage by core cycle.

Oyster Creek SEP