Docket file



NUCLEAR REGULATORY COMMISSION

WASHINGTON, D.C. 20555-0001

February 23, 1994

Docket Nos. 50-277 and 50-278

LICENSEE: Philadelphia Electric Company (PECO)

FACILITY: Peach Bottom Atomic Power Station (PBAPS), Units 2 and 3

SUBJECT: MEETING SUMMARY, PLANNED MODIFICATION TO INSTILL ADJUSTABLE SPEED DRIVES AT PBAPS (TAC NO. M88487)

On January 27, 1994, an open meeting was held in Rockville, M² yland, between PECO and the NRC staff (the staff). Enclosure 1 is the agenda used by the licensee, Enclosure 2 is the licensee's presentation slides, and Enclosure 3 is the list of meeting attendees.

The licensee began the meeting with a brief introduction and discussion of the purpose of the meeting. The licensee requested the meeting in order to inform the staff of PECO's planned modification regarding the power supplies of the recirculation pumps at PBAPS.

Currently the PBAPS recirculation pumps receive variable frequency power through motor-generator (MG) sets (the frequency is varied to change pump speed and thereby change reactor power). The planned modification would replace the MG sets with adjustable speed drives (ASDs). The ASDs use solid-state electronics along with microprocessor controls to provide the variable frequency power required. Since the use of ASDs for this application is relatively new, the licensee wanted to make a presentation to the staff to give the staff the opportunity to voice any concerns and ask questions.

The licensee continued the meeting with a discussion of the project's scope and anticipated benefits. The licensee plans to replace two complete MG sets (per unit) with ASDs. The modification will also incorporate a recirculation pump trip system. The licensee expects that the modification will result in reduced maintenance requirements and increased reliability. The licensee estimates that it will receive an annual savings of approximately 1.6 million dollars per unit after this modification is installed. The non-monetary benefits noted by the licensee included:

Improved recirculation pump speed control.

Reduced wear on the recirculation pump motors by providing a soft start.

Reduced fire hazard by removal of an oil system from inside the plant.

Provides additional critical power ratio margin.
 Increased flow capacity of recirculation pumps.

040053

NRC HLE CENTER COPY

(40)

The staff asked the licensee to address the potential for low power flow increases to reach a higher power level prior to mitigation, thus violating the safety limit MCPR.

The staff asked the licensee to include the effect of the ASD on power rerate and ARTS/MELLLA license amendments.

The staff asked the licensee to address the Emergency Operating Procedures, training, and human factors changes/considerations that are affected by this amendment.

The licensee agreed to address all of the staff's concerns and questions in their ASD license amendment submittal.

Stephen Dembek, Project Manager Project Directorate I-2 Division of Reactor Projects - I/II Office of Nuclear Reactor Regulation

Enclosures: As stated

cc w/enclosures: See next page

DISTRIBUTION: w/enclosures 1 and 3
TMurley/FMiraglia
Acting ADPR
SVarga
JCalvo

CMiller MO'Brien OGC EJordan PLoeser

RFrahm JWitter ACRS(10)

VMcCree, EDO

DISTRIBUTION: w/enclosures 1, 2 & 3
Docket File

NRC & Local PDRs PDI-2 Reading SDembek

CAnderson

OFFICE:	LA:PDI-2	PM;PDI-2	D:PDI-2	
NAME:	Mo'Brien for	SDembek: bp	CMiller 40	
DATE:	2123194	2/23/94	2/92/94	

OFFICIAL RECORD COPY

DOCUMENT NAME: B:MEETING.MIN

Mr. George A. Hunger, Jr. PECO Energy Company

Peach Bottom Atomic Power Station, Units 2 and 3

cc:

J. W. Durham, Sr., Esquire Sr. V.P. & General Counsel PECO Energy Company 2301 Market Street, S26-1 Philadelphia, Pennsylvania 19101

PECO Energy Company ATTN: Mr. G. R. Rainey, Vice President Peach Bottom Atomic Power Station Route 1, Box 208 Delta, Pennsylvania 17314

PECO Energy Company ATTN: Regulatory Engineer, A1-2S Peach Bottom Atomic Power Station Route 1, Box 208 Delta, Pennsylvania 17314

Resident Inspector U.S. Nuclear Regulatory Commission Peach Bottom Atomic Power Station P.O. Box 399 Delta, Pennsylvanía 17314

Regional Administrator, Region I U.S. Nuclear Regulatory Commission 475 Allendale Road King of Prussia, Pennsylvania 19406

Mr. Roland Fletcher Department of Environment 201 West Preston Street Baltimore, Maryland 21201

Carl D. Schaefer External Operations - Nuclear Delmarva Power & Light Company P.O. Box 231 Wilmington, DE 19899 Mr. William P. Dornsife, Director Bureau of Radiation Protection Pennsylvania Department of Environmental Resources P. O. Box 8469 Harrisburg, Pennsylvania 17105-8469

Board of Supervisors Peach Bottom Township R. D. #1 Delta, Pennsylvania 17314

Public Service Commission of Maryland Engineering Division Chief Engineer 6 St. Paul Centre Baltimore, MD 21202-6806

Mr. Richard McLean
Power Plant and Environmental
Review Division
Department of Natural Resources
B-3, Tawes State Office Building
Annapolis, Maryland 21401

Mr. John Doering, Chairman Nuclear Review Board PECO Energy Company 955 Chesterbrook Boulevard Mail Code 63C-5 Wayne, Pennsylvania 19087

AGENDA FOR NRC PRESENTATION MOD P00086 PEACH BOTTOM ATOMIC POWER STATION UNITS 2 AND 3

January 27, 1994

I.	INTRODUCTION/PURPOSE OF MEETING	Tom Loomis/Licensing
Π.	PROJECT SCOPE	Terry Nezter/PM
III.	DESIGN CHANGES	Giuseppe Termine/LRE
IV.	PLANT CHANGES	Todd Strayer/LSR
V.	LICENSING CHANGES	Tom Loomis
VI.	CONCLUSION	Tom Loomis

PECO ENERGY COMPANY ATTENDEES

George Beck

Senior Manager

Terry Nezter

Project Manager (PM)

Marilyn Kray

Licensing Manager

Tom Loomis

Licensing Engineer

Giuseppe Termine

Lead Representative Engineer (LRE)

Todd Strayer

Lead Station Representative (LSR)

Nelso Petroni

GE - Enginner

Kurt Schefer

GE - Licensing

LIST OF ATTENDEES MEETING BETWEEN NRC AND PECO ON ADJUSTABLE SPEED DRIVE MODIFICATION January 27, 1994

NAME	ORGANIZATION	
M. Lombard J. Witter S. Dembek P. Loeser R. Frahm G. Beck	MDM Engineering Corp. NRR/DSSA/SRXB NRR/DRPE/PDI-2 NRR/DRCH/HICB NRR/DSSA/SRXB PECO	
N. Petroni K. Schaefer T. Loomis M. Kray G. Termine T. Strayer T. Netzer	General Electric Co. General Electric Co. PECO PECO PECO PECO PECO PECO	

MODIFICATION P-0086 PEACH BOTTOM ATOMIC POWER STATION UNITS 2 AND 3

SCOPE

- Replace 2 complete Motor Generator (M-G) Sets per unit with Adjustable Speed Drives (ASD).
- Incorporate into the design a Nuclear Fuels Strategy Improvement to provide the Recirc Pump Trip (RPT) System.

REASONS

Reduce Maintenance

- M-G Set Bailey Scoop Tube Positioner, Scoop Tube Linkage and Knuckles are problematic.
- Generator Tachometer has caused numerous problems.
- Outage recovery has been impacted by the time to return the M-G Sets to service.

2. Increase Reliability

- Total full power hours (FPH) due to specific hardware causes average 53 FPH per year (60% derate).
- Reduced troubleshooting & repair required to keep units at power.
- M-G Set lockups can remove automatic operation of pump runbacks during plant transients.

TANGIBLE BENEFITS (ANNUAL)


- Estimated reduction of \$50K O&M Costs.
- 2. Reduction in plant derates due to M-G Set maintenance \$897K.
- 3. Reduction in house loads (2.7 MW/Unit) \$267K.
- Reduction in outage duration \$419K.

INTANGIBLE BENEFITS


- Give the operators improved speed control at all speed settings.
- 2. Operational Flexibility.
- Reduces wear on the recirc motors by providing soft start.
- Reduces System Manager and operator time and attention required to keep the current system operational.
- Reduces fire hazard by removal of an oil system from inside the plant.
- Reduces inventory on spare parts.
- Reduces heat loads on service water and building ventilation system.
- 8. Provide additional Critical Power Ratio (CPR) Margin.
- 9. Increased flow capability.

PLANT DESIGN CHANGES


M-G SET VS. ASD SYSTEM



PBAPS REACTOR RECIRCULATION SYSTEM WITH ADJUSTABLE SPEED DRIVE AND RPT SYSTEM



PBAPS REACTOR RECIRCULATION SYSTEM WITH M-G SET



ASD TECHNICAL ISSUES

- Effects of harmonics on pump motor and main power buses.
- 2. Effects of torque pulsations on RRS piping and valves.
- Effects on transient and accident analyses.
- 4. Analog vs. digital replacement
- 5. EMI/RFI Effects
- Effects of pressure pulsation frequency changes on vibration of vessel internals.
- 7. ASD failure modes.
- 8. Installation requirements.
- 9. Testing requirements.

RELIABILITY

- 1. 54 U.S. Utility Installations
 - Fan and Pump Applications
- 15% of Drive Population SurveyedSystem Drives


Unit Hrs = 1.4×10^6

Failures = 4

RPT SYSTEM DESIGN

- Utilizes ASD System with one output breaker.
- Two independent and redundant trip systems.
- 3. Utilizes RPS Logic for Trip initiation.
- Follows RPS electrical separation requirements (e.g. rigid steel conduits).

RPT SYSTEM DESIGN



PLANT CHANGES
REQUIRED

TO

IMPLEMENT ASDs

AND

RPT SYSTEM

OUTSIDE RADIOLOGICAL CONTROL AREA

- 1. Replace 13 Kv Transformers w/new dry type transformers.
- 2. Install harmonic filters.

CONTROL ROOM CHANGES RECIRC CONTROL PANEL

- 1. Remove existing RRS control equipment
 - M-G Sets lube oil pumps switches/lights
 - Analog indicators
 - Alarm windows
 - M-G Sets lube oil temperature recorder
- 2. Install new RPT System
 - Breakers control switches/lights
 - Breakers trip coil lights
 - RPT logic test switches w/reset
 - · Alarm windows
- Install new ASD System
 - Start/stop control switches/lights
 - Speed lock/reset switches
 - Video Display Unit (VDU) for status and alarms

M-G SET ROOM CHANGES

- 1. Removal of:
 - M-G Sets and pedestals
 - Service Water System and Lube Oil Piping/Tubing/Instrumentation
 - Control Panels
 - Fire Protection around M-G Sets
- 2. Modify HVAC System
- Installation of:
 - · ASD systems on skids
 - RPT breakers
 - · Sprinkler system for fire protection

TECHNICAL SPECIFICATION CHANGES

- Delete Fire Protection Requirements for M-G Sets (Tech Spec. Section 3.14.E)
- Add surveillance test requirements to Section 3.3 for RPT System

SCHEDULE

*	Submittal for Licensee Changes	3/94
	Unit 2	
	Ready to Work Date	6/10/94
	Outage Start Date	9/1/94
	Unit 3	
	Ready to Work Date	6/10/95
	Outage Start Date	9/1/95