

CONTROL BLOCK:

--	--	--	--	--	--

1

(PLEASE PRINT OR TYPE ALL REQUIRED INFORMATION)

0	1	C	A	S	O	S	3	2	0	0	-	0	0	0	0	0	-	0	0	3	4	1	1	1	1	4			5
7	8	14							25										30					57		CAT	58		
		LICENSEE CODE							LICENSE NUMBER										LICENSE TYPE										

CON'T

01 REPORT SOURCE L 6 0 5 0 0 0 3 6 2 7 0 9 1 7 8 3 8 1 0 1 7 8 3 9

EVENT DESCRIPTION AND PROBABLE CONSEQUENCES (10)

EVENT DESCRIPTION AND PROBABLE CONSEQUENCES	
02	On September 17, 1983, at 0450, with Unit 3 in Mode 3, Condenser Air

03	Ejector Wide Range Gas Monitor 3RI-3870 was declared inoperable. Redun-
----	-------------------------------------------------------------------------

04 | dant Monitor 3RI-7818 was also inoperable at this time. In accordance

05 | with LCO 3.3.3.1 and 3.3.3.6, grab samples were obtained every 8 hours,

06 | and action was initiated to restore the monitor to operable status with-

0 7 in 72 hours. Public health and safety were not affected.

7 8 9 10 11 12 13 14 15 16 17 18 19 20

SYSTEM CODE CAUSE CODE CAUSE SUBCODE COMPONENT CODE COMP. SUBCODE VALVE SUBCODE

0 9 M C X Z I N S T R U X Z

EVENT YEAR

17 LEN/RO
REPORT
NUMBER

8	3	—	0	6	9	/	0	3	L	—	0
---	---	---	---	---	---	---	---	---	---	---	---

ACTION TAKEN		FUTURE ACTION		EFFECT ON PLANT		SHUTDOWN METHOD		HOURS		ATTACHMENT SUBMITTED		NPRD-4 FORM SUB.		PRIME COMP. SUPPLIER		COMPONENT MANUFACTURER	
X	18	Z	19	Z	20	Z	21	0000	22	Y	23	N	24	N	25	G	1063
33		34		35		36		37	40	41		42		43		44	4

CAUSE DESCRIPTION AND CORRECTIVE ACTIONS (27)

CAUSE DESCRIPTION AND CORRECTIVE ACTIONS	
10	The inoperability of Monitor 3RI-7870 was due to a loss of communication

1 1 | between the RM80 microprocessor and the RM23 Control Room readout. The |

1 2 data base was reloaded, and Monitor 3RI-7870 was declared operable on

13 September 18 at 2200 in accordance with surveillance procedure

1	4	S023-II-4.36.
---	---	---------------

FACILITY STATUS		% POWER	OTHER STATUS	(30)	METHOD OF DISCOVERY	DISCOVERY DESCRIPTION	(32)					
1	5	B	(28)	0	0	0	(29)	NA	A	(31)	Operator Observation	

ACTIVITY CONTENT
RELEASED OF RELEASE

1 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50

AMOUNT OF ACTIVITY

NA

LOCATION OF RELEASE

NA

PERSONNEL EXPOSURES				
NUMBER	TYPE	DESCRIPTION	(39)	
17	000	(37) Z	(38)	NA

PERSONNEL INJURIES		DESCRIPTION		41	
NUMBER					
1	8	0	0	0	40
				NA	

[illegible]

7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60

PUBLICITY
ISSUED DESCRIPTION (45)

NA

16 Handed in NRC

NRC USE ONLY

NAME OF PREPARER

J. G. HAYNES

PHONE:

714/492-7700

8310270416 831017
PDR ADOCK 05000362
S PDR

Southern California Edison Company

SAN ONOFRE NUCLEAR GENERATING STATION

P.O. BOX 128

SAN CLEMENTE, CALIFORNIA 92672

October 17, 1983

SCE

RECEIVED
MTC

OCT 20 PM 2:35

U. S. Nuclear Regulatory Commission
Office of Inspection and Enforcement
Region V
1450 Maria Lane, Suite 210
Walnut Creek, California 94596-5368

Attention: Mr. J. B. Martin, Regional Administrator

Dear Sir:

Subject: Docket No. 50-362
30-Day Report
Licensee Event Report No. 83-069
San Onofre Nuclear Generating Station, Unit 3

Pursuant to Section 6.9.1.13.b of Appendix A, Technical Specifications to Facility Operating License NPF-15 for San Onofre Unit 3, this submittal provides the required 30-day written report and a copy of the Licensee Event Report (LER) form for an occurrence involving Limiting Conditions for Operation (LCO's) 3.3.3.1 and 3.3.3.6 associated with radiation monitoring instrumentation.

On September 17, 1983, at 0450 with Unit 3 in Mode 3, Condenser Air Ejector Wide Range Gas Monitor 3RI-7870 was observed to be in a failed condition and was declared inoperable. Redundant Monitor 3RI-7818 was also inoperable at this time. In accordance with the action statements of LCO's 3.3.3.1 and 3.3.3.6, grab samples were obtained every 8 hours and analyzed for gross activity every 24 hours, and action was initiated to restore the monitor to operable status within 72 hours.


The inoperability of Monitor 3RI-7870 was due to a loss of communication between the RM80 microprocessor and the RM23 control room readout. The data base was reloaded and the monitor was restarted and tested in accordance with I&C Procedure SO23-II-4.36. Monitor 3RI-7870 was declared operable at 2200 on September 18, 1983. Sampling required by LCO 3.3.3.1 was discontinued and LCO 3.3.3.6 was satisfied. There was no impact on the health and safety of plant personnel or the public associated with this event.

11
JLW

October 17, 1983

If you require any additional information, please so advise.

Sincerely,



J. G. HAYNES
STATION MANAGER

Enclosure: LER No. 83-069

cc: A. E. Chaffee (USNRC Resident Inspector, Units 1, 2 and 3)
J. P. Stewart (USNRC Resident Inspector, Units 2 and 3)

U. S. Nuclear Regulatory Commission
Office of Inspection and Enforcement

U. S. Nuclear Regulatory Commission
Division of Technical Information and Document Control

Institute of Nuclear Power Operations (INPO)