

PRAIRIE ISLAND NUCLEAR GENERATING PLANT

Red Wing, Minnesota
UNITS 1 AND 2



INSERVICE INSPECTION - EXAMINATION SUMMARY

PRAIRIE ISLAND NUCLEAR GENERATING PLANT - UNIT 1

MARCH 27, 1984 THRU MARCH 30, 1984

NORTHERN STATES POWER COMPANY MINNEAPOLIS, MINNESOTA

Report Date: May 9, 1984 Commercial Service Date: December 16, 1973

NORTHERN STATES POWER COMPANY

PRAIRIE ISLAND NUCLEAR GENERATING PLANT - UNIT 1

INSERVICE INSPECTION - EXAMINATION SUMMARY

PRAIRIE ISLAND NUCLEAR GENERATING PLANT - UNIT 1

MARCH 27, 1984 THRU MARCH 30, 1984

INSPECTION PERIOD 3

Report Date:

May 9, 1984

Prepared by: L.C. Dahlman M & SP Specialist

Reviewed by:

M.T. Anderson M & SP Engineer

Commercial Service Date: December 16, 1973

Approved by:

P.J. Krumpos Superintendent,

Materials and Special

Processes

Inservice Inspection - Examination Summary PRAIRIE ISLAND NUCLEAR GENERATING PLANT - UNIT 1

- INDEX -

- 1.0 INTRODUCTION
- 2.0 SUMMARY
- 3.0 DISCUSSION OF EXAMINATION
 - 3.1 Inspection Boundary
 - 3.2 Examination Methods
 - 3.3 Examination Procedures
 - 3.4 Equipment and Materials
 - 3.5 Personnel
 - 3.6 Evaluation
 - 3.7 Examination Reports and Documentation

APPENDIX A - ASME Class 2 Examinations

Inservice Inspection - Examination Summary Tables
Table S2.2.1 - Piping - Circumferential Butt Welds
Table II - Baseline Comparison Summary
Table III - Isometric Drawing Summary

APPENDIX B -

Table I - Personnel Listing

Table II - Ultrasonic Calibration Blocks

Table III - Procedure Listing

Table IV - Equipment and Materials

APPENDIX C - Form NIS-1, Owner's Data Report for Inservice Inspections

INSERVICE INSPECTION - EXAMINATION SUMMARY PRAIR ISLAND NUCLEAR GENERATING PLANT - UNIT 1 LARCH 27, 1984 to MARCH 30, 1983

1.0 INTRODUCTION

This report summarizes the inservice inspection examinations performed at Prairie Island Nuclear Generating Plant - Unit 1. This inspection was conducted during the period from March 27 to March 30, 1984 in response to the NRC Staff Evaluation Meeting documented April 18, 1983. Specifically, item 5 of Section 6 states that 10 welds will be examined every six months. The examinations were performed with the Unit in operation. Prairie Island - Unit 1 began commercial operation on December 16, 1973.

The examinations were performed on circumferential pipe welds in portions of the Safety Injection system that were identified as containing stagnant oxygenated borated water, and selection was based on those welds that are considered the most susceptable to trans-granular stress corrosion cracking.

Northern States Power Company contracted Lambert, MacGill, Thomas, Inc. to perform the examinations. Hartford Steam Boiler Inspection and Insurance Company, representing ANI, provided the Authorized Inspection.

2.0 INSPECTION SUMMARY

The evaluation of the results from the inservice examinations indicated that the integrity of the system has been maintained.

3.0 DISCUSSION OF EXAMINATION

3.1 Inspection Boundary

The examination plan focused on piping circumferential butt welds in portions of the Safety Injection system containing stagnant oxygenated borated water. This piping consists of 8" diameter, Schedule 10 (0.148" wall) and 12" diameter, Schedule 10 (0.180" wall) austenitic stainless steel. The components examined and the examination report numbers are summarized in the attached Appendix B - ASME Class 2 Examinations, Table S2.2.1.

3.2 Examination Methods

Ultrasonic examination methods and techniques were used to perform the volumetric examinations. The ultrasonic test system consisted of an ultrasonic digital/analog tester and a two-channel strip chart recorder. One channel of the recorder was calibrated to represent ultrasonic screen height (amplitude) and the second channel was calibrated to indicate metal path (range) to the reflector. This approach gives a permanent record of the examinations and allows further evaluation of any indications by the contractor's Level III and Northern States Power Company.

The ultrasonic techniques utilized miniature $(1/4" \times 1/4")$, 5.0 MHz transducers. These were mounted on high temperature wedges which provided refracted shear wave angles of 45 degrees and 52 degrees in the parts to be examined. A 2-1/2 V metal path was used for all examinations.

All visual examinations were aided, when necessary, with artificial lighting and verified for adquacy with an 18% neutral gray card containing a 1/32-inch black line.

3.3 Examination Procedures

The ultrasonic examination procedure for pipe welds complied with the requirements of Appendix III of ASME Section XI issued in the Winter 1975 Addenda. All other examination procedures complied with the requirements of the 1974 Edition through and including the Summer 1975 Addenda of ASME Section XI. A listing of the procedures used for the examinations is shown in Table III of Appendix B.

3.4 Equipment and Materials

All equipment and expendable materials used in the examinations are listed either by serial number or type along with their respective calibration date or batch number in Table IV of Appendix B.

The ultrasonic calibration standards used in the examination are listed in Table II of Appendix B. These standards are owned and maintained by NSP at the plant site.

3.5 Personnel

Northern States Power Company contracted Lambert, MacGill, Thomas, Inc. to perform the ultrasonic examinations. Hartford Steam Boiler Inspection and Insurance Company, representing ANI, provided the Authorized Inspection.

All personnel involved in the performance or evaluation of examinations are listed along with their title, organization, and ASNT Level of certification in Table I of Appendix B.

Certifications for examination personnel are maintained on file by Northern States Power Company.

3.6 Evaluation

Any indications disclosed in the examinations were evaluated by the examiner at that time in accordance with the rules of the procedure and ASME Section XI.

The ultrasonic examiner was aided in his evaluation by a calibration performed on a standard reference before each day's examination, checked before and after each individual examination, and at intervals not exceeding four (4) hours. In addition, the ultrasonic data was recorded on strip charts which were made a part of the inspection report, and permitted further evaluation.

3.7 Examination Reports and Documentation

All examination reports and documentation are maintained on file by Northern States Power Company. Table I of Appendix B identifies the examination report number(s) for each item examined. Many of the items identify more than one examination report because of the difference types of examinations performed on the item.

Table I of Appendix B summarizes all the examinations that have been performed to date and identifies the amount that will be examined in the future to complete the ten year examination requirements. For retrieval purposes, the prefix of the inspection report number corresponds with the year that the inspection was performed. The examination report numbers for this outage are prefixed with "84-".

Table II of Appendix B compares the baseline examination results with the results obtained during this examination. Table II of Appendix B identifies the isometric drawings that were used for the examinations. The personnel, ultrasonic calibration blocks, procedures, equipment and materials that were used for the inspection are identified in the tables of Appendix B. Appendix C contains the Form NIS-1, titled, "Owner's Data Report for Inservice Inspections".

APPENDIX A ASME CLASS 2 EXAMINATIONS PRAIRIE ISLAND UNIT 1

INSERVICE INSPECTION-EXAMINATION SUMMARY

PAGE 1 OF 8

SUB	CATE- GORY	COMPONENT OR SYSTEM AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D.	AMT. EXAM	ITEM IDENTIFICATION	INSPECTION REPORT NO.
2.1	C-G	CIRCUMFERENTIAL BUTT WELDS		114	THE PARTY IS		
		MAIN STEAM A					
		32-MS-1	1.	111-71			
		MAIN STEAM B					
		32-MS-2	-	-	-		
		MAIN STEAM A					
		30-MS-1	TWO	1	1	MS-7	79-125, 128
		MAIN STEAM B					
		30-MS-2	-	-	-		
		MAIN STEAM A					
		31-MS-1	ONE	1	1	MS-12	77-25, 30
	1	MAIN STEAM B					
		31-MS-2	1	-	-		
		MAIN STEAM A					
		RELIEF HDR, 30-MS-1	-	-	-		
		MAIN STEAM B RELIEF HDR, 30-MS-2	THREE	1	1	MS-186	81-162, 189
			HINEL		1	H3-100	01-102, 103
		MAIN STEAM A	T.10				
		6-MS-1	TWO	4	4	MS-147 MS-148	80A-1, 14 80A-3, 13
					F3 19	MS-149	80A-2, 12
						MS-150	80A-10, 34
		MAIN STEAM B		1, 131			
		6-MS-2	ONE	1	1	MS-136	77-22, 8
	4		TWO	4	4	MS-135	80A-4, 16
					ir.	MS-136	80A-7, 17
					13.00	MS-137	80A-5, 15
						MS-138	80A-6, 44

TABLE ____ \$2.2.1 PAGE __2 ___ OF __ 8

	GORY	AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D.	AMT. EXAM	IDENTIFICATION	INSPECTION REPORT NO.
2.1	C-G	(CONT'D)					
		FEEDWATER A					
		16-FW-12	THREE	1	2	FW-144, 164	81-144,179,90,75,87
		16-FW-13	TWO	18	19	FW-147	79-129
						FW-161, 162	79-SP-5,4
				E. Hill		FW-164	79-SP-2,1/80A-26, 78 81-104
						FW-164	82-029, 068, 087
						FW-164	83C-001, 001R, 003, 006, 117
						FW-148	79-SP2-1,72,74,105
						FW-149	79-SP2-1,9,60,106
						FW-150	79-SP2-1,10,61,107
						FW-227	79-SP2-6,6R,11,65, 108/80A-31, 50
						FW-151	79-SP2-1,12,64,109
						FW-152	79-SP2-1,13,69,110
						FW-153	79-SP2-5,14,68,111
						FW-154	79-SP2-1,15,67,112
						FW-155	79-SP2-1,16,71,113
						FW-156	79-SP2-1,17R,85,114
						FW-157	79-SP2-1,4,55,115
						FW-158	79-SP2-1,21,59,116
						FW-159	79-SP2-7,7R,22,52,
			100				117, 97, 98, 99
						FW-159 Baseline	79-SP2-103,104,118
					- 11	FW-159	80A-24, 48
					1	FW-160	79-SP2-8R,23,63,119,80A-25, 49
						FW-213	79-SP2-2,53,24,120
						FW-161	79-SP2,2,25,57,121
						FW-162	79-SP2-2,26,56,122
						FW-164	79-SP2-2,28,58,123

NORTHERN STATES POWER CO. PRAIRIE ISLAND UNIT

INSERVICE INSPECTION-EXAMINATION SUMMARY

TABLE \$2.2.1

SUB	CATE- GORY	COMPONENT OR SYSTEM AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D.	AMT. EXAM	ITEM IDENTIFICATION	INSPECTION REPORT NO.
2.1	C-G	(CONT'D)			13,24,19		
		FEEDWATER B					
		16-FW-15	ONE	1	1	FW-220	77-15, 9
		16-FW-16	TWO	4	4	FW-214, FW-216	79-SP-7, 8, 1
			10			FW-214	79-SP2-19, 32, 70
						FW-216	79-SP2-19,30,79,125
							80A-23, 51, 52, 105
			THREE	-	-	FW-216	81-89, 76, 76R, 88
				Maria I		FW-216	82-023, 030, 030R,
							067, 088
						FW-216	83C-002,002R,004,
							005,118
		FEEDWATER A					
	4	(8 IN) 3-AF-11	TWO	2	2	FW-165, AFW-202	79-SP-17, 18
						FW-165, AFW-202	79-SP2-127, 128
		FEEDWATER B	TUO		_	FU 107 AFU 100	La co 10 00
		(8 IN) 3-AF-12	TWO	2	2	FW-127, AFW-129	79-SP-19, 20
					1	FW-127, AFW-129	79-SP2-129, 130
		REFUELING WATER STORAGE					
		TANK DISCHARGE					
		14-SI-1	TWO	1	1	W-195	80-60
			THREE	1	1	W-178	81-198
		12-SI-3A	TWO	2	2	W-186, W-261	80-54, 55
			THREE	2	4	W-184,	83-82, 104, 40
						W-261, 186	83-67, 105, 68, 116
						W-187	83-69, 117
		12-SI-3B	TWO	1	1	W-194	80-56
			THREE	i	4	W-194, 258	83-74, 122, 73, 12
						W-191, 190	83-71, 120, 72, 119
					- In - I'		

TABLE \$2.2.1 PAGE 4 OF 8

SUB	CATE- GORY	COMPONENT OR SYSTEM AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D.	AMT. EXAM	ITEM IDENTIFICATION	INSPECTION REPORT NO.
2.1	C-G	(CONT'D)					
		12-SI-11	THREE	1	1 7	W-187 W-188, 189 W-100, 101 W-102, 103 W-104 W-104	81-30 83-070, 118, 83, 161 83-84, 129, 85, 123 83-86, 124, 90, 128 83-89, 125 838-002, 006
		12-SI-4	TWO THREE	1 1	1 1	W-196 W-202	30-57 82-076, 092
		10-SI-8 STREAM 1 STREAM 2	TWO THREE	1 -	1 1	W-206 W-213	80-50 82-089, 090
		CONTAINMENT SUMP B DISCHARGE LINES					
		14-SI-33A 14-SI-33B	-	-	:		
		12-SI-34A 12-SI-34B	TWO	ī	1	W-5	80-82
		ALTERNATE CONTAINMENT SPRAY PUMP SUCTION 6-RH-10A					
		BRANCH 1 BRANCH 2	TWO	1 2	1 2	W-269 W-5 W-7	80-53 80-65 80-67
		6-RH-10B BRANCH 1	TWO THREE	2 2	2 2	W-230, W-270 W-229, W-283	80-52, 51 81-66, 65

TABLE ____ \$2.2.1 PAGE _ 5 ___ OF _ 8 ___

SUB	CATE- GORY	AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D. AMT.	AMT. EXAM	ITEM	INSPECTION REPORT NO.	
2.1	C-G	(CONT'D)						
		BRANCH 2	TWO THREE	2	2	W-113, W-128 W-129	80-33, 66 81-64	
		RESIDUAL HEAT REMOVAL DISCHARGE 12-RH-6A 12-RH-6B	TWO TWO	1 1	1 1	W-17 W-6	80-81 80-83	
		8-RH-9A 8-RH-9B	TWO TWO THREE	1 2 1	1 2 1	W-112 W-195, W-193 W-243	80-46 80-21, 22 81-45	
		8-RH-7A 9-RH-7B	TWO TWO	1 3	2 3	W-88, 89 W-138,W-206,W-143	80-49, 47 80-19, 23, 20	
		SAFETY INJECTION PUMPS SUCTION						
		6-SI-13A 6-SI-13B	TWO TWO	1 2	1 2	W-17W W-134, 141W	80-3 80-58, 2	
		8-SI-17	TWO THREE	2	2 1 4	W-239, W-99 W-98 W-99, 239 W-98, 97 W-97	80-97, 95 81-32 83-55, 61, 54, 60 83-56, 59, 51, 58 84-001, 011	
		8-SI-18	TWO	7	7	W-243, 235, 236 W-74, 75, 80, 81	80-96, 99, 104 80-106,107,105,103	
			THREE	2	2 56	W-68/W-58 W-92, 91 W-238, 86W W-85, 243 W-94, 237	81-67/83-98, 42 83-52, 20, 48, 19 83-49, 18, 32, 17 83-34, 46, 53, 62 83-57, 63, 64, 141	

NORTHERN STATES POWER CO. PRAIRIE ISLAND UNIT

INSERVICE INSPECTION—EXAMINATION SUMMARY

TABLE ___ \$2.2.1 PAGE __6 __ OF __ 8

SUB	EXAM CATE- GORY	COMPONENT OR SYSTEM AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D.	AMT. EXAM	ITEM IDENTIFICATION	INSPECTION REPORT NO.
C2.1	C-G	(CONT'D)				W-88, 87 W-235, 83 W-234, 236 W-81, 80 W-79, 78 W-76, 77 W-75, 74 W-73, 72 W-71, 70 W-233, 69 W-68, 67 W-66, 64 W-63, 62 W-61, 60 W-59, 58 W-57, 242 W-52, 51 W-50, 53 W-277, 278 W-279, 280 W-281, 282 W-54, 46 W-47, 48 W-49, 55	83-65, 140, 66, 47 83-33, 50, 28, 26 83-24, 25, 23, 16 83-22, 15, 21, 14 83-12, 9, 11, 7 83-10, 3, 2, 4, 5 83-6, 8, 75, 142 83-87, 143, 88, 147 83-91, 149, 92, 150 83-93, 155, 94, 156 83-101, 152, 102, 153 83-103, 154, 97, 29 83-96, 27, 81, 30 83-80, 31, 79, 35 83-78, 36, 77, 37 83-41, 38, 76, 39 83-145, 139, 127, 138 83-115, 151, 126, 137 83-111, 136, 110, 135 83-109, 134, 108, 44 83-107, 133, 100, 132 83-99, 131, 148, 159 83-112, 157, 113, 158 83-114, 160, 45, 43
					9	W-282, 235 W-92, 59 W-66, 73 W-75, 77 W-78	83A-009,016,001,004 83A-003,005,007,014 83A-008,015,010,017 83A-011,018,012,019 83A-013, 020
					8	W-70, 81 W-83, 88 W-243, 52 W-54, 280	84-006, 016, 005, 015 84-004, 013, 003, 014 84-002, 012, 010, 020 84-008, 018, 009, 019

INSERVICE INSPECTION-EXAMINATION SUMMARY

TABLE S2.2.1
PAGE 7 OF 8
MAJOR ITEM: PIPING-CIRCUMFERENTIAL BUTT WELDS

SUB	CATE- GORY	COMPONENT OR SYSTEM AND DESCRIPTION OF ITEM TO BE EXAMINED	INSP. PER.	REQ'D. AMT.	AMT. EXAM	ITEM IDENTIFICATION	INSPECTION REPORT NO.
2.1	C-G	(CONT'D)					
		8-VC-71A	THREE		1	W-55	84-007, 017
		8-VC-71B	-	-	-	H-33	04-007, 017
		RESIDUAL HEAT REMOVAL					
		10-SI-9A					
		10-SI-9B	TWO	1	1	W-39W	80-10
		ACCUMULATOR DISCHARGE					
		LINES 12-SI-28A	ONE	1	1	SI-1317	77-35, 56
		12-SI-28B	- OINE	-	1	31-1317	77-35, 50
		12-SI-29A	-	-	-		
		12-SI-29B	TWO	1	1	SI-33	79-49, 47
		RESIDUAL HEAT REMOVAL					
	1 30 1	SUCTION					
	U 15 F	12-RH-5A	TWO	1	1	W-66	80-87
			THREE	2	2 2	W-72, W-63	81-40, 43
		12-RH-5B	TWO	2	2	W-37, W-42	80-11, 25
		8-RH-5A	TWO	1	1	W-64	80-92
			THREE	1	1	W-27	82-093, 094
		8-RH-5B	TWO	1	1	W-35	80-18
		8-RH-4A	TWO	.2	2	W-60, W-59	80-94, 93
		8-RH-4B	TWO	1	1	W-31	80-17
		10-RH-3	ONE	2	2	RH-1045R, RH-1048	77-76 77
	1	10-111-3	TWO	1	1	W-23	80-101
			THREE	2	2	W-27	82-93, 94
						W-1044	83C-091

NORTHERN STATES POWER CO.
PRAIRIE ISLAND UNIT

INSERVICE INSPECTION-EXAMINATION SUMMARY

TABLE ____ \$2.2.1

PAGE 8 OF 8

MAJOR ITEM: PIPING-CIRCUMFERENTIAL BUTT WELDS

EXAM COMPONENT OR SYSTEM SUB INSP. REO'D. AMT. ITEM INSPECTION CATE-AND DESCRIPTION OF ITEM PER. AMT. EXAM IDENTIFICATION REPORT NO. GORY ITEM TO BE EXAMINED C2.1 (CONT'D) C-G RESIDUAL HEAT REMOVAL DISCHARGE TWO 10-RH-11 3 3 RH-1, W-177 79-103/80-89, 88 W-176 THREE 2 2 W-170/ W-3 81-42/82-042 6-RH-12 THREE 82-101 1 W-8 8-RH-7A TWO 2 2 W-88, 89 80-49, 47 8-RH-7B TWO 3 3 W-138, 143, 206 80-19, 20, 23 W-112 8-RH-9A TWO 80-46 8-RH-9B TWO 2 W-195, 193 80-21, 22 SAFETY INJECTION 77-48, 57 6-SI-10B ONE SI-1290 TWO 6-SI-10A 3 3 W-128, 131, 126 80-72, 73, 71 REACTOR VESSEL SAFETY INJECTION TWO SI-1291 79-75 6-SI-25A 1 W-1292 82-099 THREE 1 6-SI-25B ONE 1 77-35, 58 SI-15

COMPONENT/SYSTEM	NSP ISO	NDE METHOD	W BASELINE IDENT.	REPORT NO.	BASELINE INDICATIONS	ISI INDICATIONS	EXAMINATION LIMITATIONS
C2.1 CIRCUMFERENTIAL BUTT WELDS							
BORIC ACID SUPPLY	84	UT	W-52	84-010	NONE	NONE	HEAT TRACE (H.T.) AT 3:00 & 9:00 S-2 LIMITED WELDED
		UT		84-020	S-2, 34% SPOTS@2:30, 4:00 &11:00	S-1, ID/OD GEO., 20%/30%, 360° S-2, ID/OD GEO., 20%/30%, 360°	LUGS AT 3:00 & 9:00 SAME AS ABOVE
	84	UT	W-54	84-008	NONE	S-2, SPOT, ID NOISE 20%	H.T. AT 3:00 &9:00 NO S-1 VALVE BEST EFFORT (B.E.) 2:00 TO 4:00 ELBOW INNER RADIUS
		UT		84-018	S-2,38%,S-3, 35%,S-4,48%, SPOT@1:00-	S-2, ID/OD GEO., 20%/30% 360°	(E.I.R.) SAME AS ABOVE
	84	UT	W-55	84-007	360° NONE	NONE	H.T. at 4:30 TO 6:00 & 9:00 NO S-2 VALVE NO S-1 AT 6:00 TO 6:30 SWEEP-O-LET
	84	UT		84-017	S-1, 65% SPOT @ 10:00	S-1, ID/OD GEO., 25%/30%, 360°	SAME AS ABOVE

	COMPONENT/SYSTEM	NSP ISO	NDE METHOD	W BASELINE IDENT.	REPORT NO.	BASELINE INDICATIONS	ISI INDICATIONS	EXAMINATION LIMITATIONS
		84	UT	W-280	84-009	NONE	NONE	H.T. AT 3:00 & 9:00 S-1 & S-2 B.E. 8:00
					84-019	S-1, 25% SPOT @ 2:00	S-1, ID/OD GEO. 25%/30%, 360° S-3, ID ROLL, 15%-20%, 360°	TO 10:00 E.I.R. SAME AS ABOVE
	SAFETY INJECTION	82	UT	W-70	84-006	NONE	NONE	H.T. AT 2:00, 5:00 8:00 & 10:30 B.E. S-2 4:00 TO 8:00 E.I.R. NO SCANS AT 6:00
			UT		84-016	S-1 & 3, 45% S-4,69% 3600 S-4 SPOT, 3600	S-1, ID/OD GEO., 25%/30%, 360° S-2 ID/OD GEO., 25%/30%, 360° S-3, ID ROLL, 20%-25%, 360° S-4, ID ROLL, 20%-25%, 360°	RESTRAINT. SAME AS ABOVE
l		82	UT	W-81	84-005	NONE	NONE	H.T. AT 3:00 & 10:00 B.E. S-2 4:00 TO
			UT		84-015	NONE	S-1, ID/OD GEO., 25%/30%, 360° S-2, ID/OD GEO., 25%/30%, 360° S-3, ID ROLL, 20%-25%, 360° S-4, ID ROLL 20%-25%, 360°	8:00 E.I.R. SAME AS ABOVE
							20%-25%, 360° S-4, ID ROLL	

TABLE II
PAGE 3 OF 3

COMPONENT/SYSTEM	NSP ISO	NDE METHOD	W BASELINE IDENT.	REPORT NO.	BASELINE INDICATIONS	ISI INDICATIONS	EXAMINATION LIMITATIONS
	82	UT	W-83	84-004	NONE	NONE	H.T. AT. 2:30 & 5:00 TO 6:00 NO SCANS 12:00 OBSTRUCTION B.E. S-1 2:00 TO
		UT		84-013	NONE	NONE	10:00 E.I.R. SAME AS ABOVE
	82	UT	W-88	84-003	NONE	NONE	H.T. AT. 6:00, 7:00 & 9:00 NO S-1 VALVE B.E. S-2 4:00 TO 8:00 E.I.R.
	82	UT		84-014	S-2, 25% SPOTS @ 9:00	NONE	SAME AS ABOVE
	82	UT	W-97	84-001	& 12:00 NONE	NONE	H.T. AT. 3:00 & 9:00 NO S-2 VALVE. B.E. S-1 8:30 TO 9:30 E.I.R. NO SCANS AT 6:00
		UT		84-011	NONE	NONE	SWEEP-O-LET SAME AS ABOVE
	82	UT	W-243	84-002	NONE	NONE	H.T. AT 4:00 & 9:00 B.E. S-1 8:00 TO 10:00 E.I.R. B.E. S-2 8:00 TO 10:00
		UT		84-012	S-1, 50% 0 4:00 & 7:00	NONE	'T' INNER RADIUS SAME AS ABOVE

PACE 1 OF 3

NORTHERN STATES POMER CO. PRAIRIE ISLAND UNIT 2 ISCHETRIC SUMMARY - CLASS 2

NSP ISO MARBER	REVISION	, COMPONENT OR SYSTEM	LOOP	SIZE	LINE MABER	UT - CAL STANDARD
2-151-37	0	STEAM GENERATORS	ALB	-		26
2-151-46	0	HAIN STEAM (GENERAL VIEW)	1 A	-		-
2-1SI-46A	0		A	32"	32-2MS-1	NO.
2-151-46B	0		A	31"	31-2HS-1	24
				30" 6"	30-2HS-1 6-2HS-1	23
		MATH CERTAL (CEMERAL WIEW)				
2-151-47	0	MAIN STEAM (GENERAL VIEW)	В	32"	32-2HS-2	NO.
2-151-47A	0		1 6	31"	31-2115-2	24
2-151-478	0			30"	30-2HS-2	23
				6"	6-2HS-2	7
2-151-48	0	FEEDWATER (GENERAL VIEW)	A	-	- 4	13/56
2-151-48A	0		A	16"	16-2FW-13	
2-151-488	0		A	16"	16-2FW-12	13
	1 3 3 3 3 3 3			16"	16-214-11	13
				8"	3-2AF-11	NO
2-151-49	0	FEEDWATER (GENERAL VIEW)	В	-		13736
2-151-49A	0		B	16"	16-2FW-16	
2-151-498	0		1 1	16"	16-2FW-15	13
				8"	3-2AF-12	NO
2-151-50	1	RIIR PUNP B SUCTION (WELDS)		10"	10-2RH-3	22
2-151-51	l i	RHR PUMP B SUCTION (HANGERS)	В	8"	8-2RH-4B	29
	1		B	8"	8-2RII-5B	29
				12"	12-2RH-5B	32 22
				10"	10-2SI-9B	1 22
		OUR RIDGE A CHICTION (UTLICE)	_ A	8"	8-2RH-4A	29
2-151-52	1	RHR PUMP A SUCTION (WELDS) RHR PUMP A SUCTION (HANGERS)	1 2	8"	8-2RH-5A	29
2-151-53	1	HIR PURE A SUCTION (HAMEENS)	1 %	12"	12-2RH-5A	32
			1 4	10"	10-251-9A	22

NORTHERN STATES POWER CO. PRAIRIE ISLAND UNIT 2 ISOMETRIC SUMMARY - CLASS 2 TABLE 3 PAGE 2 of 3

NSP ISO NUMBER	REVISION	COMPONENT OR SYSTEM	LOOP	LINE SIZE	LINE NUMBER	UT - CAL. STANDARD
2-151-54	1 .	RHR PUMP B DISCHARGE (WELDS)	В	8"	8-2RH-7B	29
2-ISI-55	0	RHR PUMP B DISCHARGE (HANGERS)	В	8"	8-2RH-9B	29
			В	6"	6-2SI-10B	27
2-151-56	1	RHR PUMP A DISCHARGE (WELDS)	A	8"	8-2RH-7A	29
2-ISI-57	0	RHR PUMP A DISCHARGE (HANGERS)	A	8"	8-2RH-9A	29
			A	10"	10-2RH-11	22
	Mark Addition		A	6"	6-2RH-12	27
2-151-58	1	CONTAINMENT SUMP B DISCHARGE	В	12"	12-2RH-6B	32
	A 200 (1)		В	14"	14-2SI-33B	NO.
			В	12"	12-251-348	NO
2-151-59	1	CONTAINMENT SIMP B DISCHARGE	A	12"	12-2RH-6A	12
			A	14"	14-2SI-33A	NO.
			A	12°	12-281-34A	;:0.
2-151-60	1	SAFETY INJECTION PUMPS SUCTION	A&B	6"	6-251-13A	28
					6-2S1-13B	28
2-151-61	1	BORIC ACID SUPPLY TO SAFETY INJECTION	-	12"	12-251-11	33
				8"	8-2SI-17	30
				8"	8-251-18	30
2-151-62	0	SAFETY INJECTION PUMP 22 SUCTION (WELDS)	В	6"	6-2RH-16B	27
2-151-63	0	SAFETY INJECTION PUMP 22 SUCTION (HANGERS				
2-151-64	0	SAFETY INJECTION PUMP 21 SUCTION (WELDS)	Λ	6"	6-28II-10A	27
2-151-65	0	SAFETY INJECTION PUMP 21 SUCTION (HANGERS) "		0-2811-108	
2-ISI-66	1	REFUELING WATER STORAGE (WELDS)		14"	14-251-1	NO.
		TANK DISCHARGE		12"	12-2SI-3A	33
2-151-67	0	REFUELING WATER STORAGE (HANGERS)		12"	12-251-3R	33
		TANK DISCHARGE		12"	12-251-4	33

NORTHERN STATES POWER CO. PRAIRIE ISLAND UNIT 2 ISOMETRIC SUMMARY - CLASS 2 TABLE 3 PAGE 3 OF 3

NSP ISO NUMBER	REVISION	ISION COMPONENT OR SYSTEM		LINE	LINE NUMBER	UT - CAL. STANDARD	
2-ISI-67 0 Continu		Continued		10" 12"	10-2SI-8 12-2SI-11		
2-ISI-68	1	BORIC ACID TANK 21	#21				
2-151-69	1	RESIDUAL HEAT EXCHANGERS	#21 & #23	-		NO	
2-1SI-70 2-ISI-71	0 0	REACTOR VESSEL SAFETY INJECTION (WELDS) REACTOR VESSEL SAFETY INJECTION (HANGERS	В	6"	6-2SI-25B	6	
2-151-72	0	REACTOR VESSEL SAFETY INJECTION (WELDS)	A	6"	6-2SI-25A	6	
2-ISI-73	0	REACTOR VESSEL SAFETY INJECTION (HANGERS					
2-151-74	1	BORIC ACID SUPPLY (WELDS)) - I	8"	8-251-18	30	
3-181-75	1	ACCUMULATOR DISCHARGE	A	12"	12-2SI-28A	11	
				12"	12-281-294	11	
			В	12"	12-251-258 12-251-298	11	
2-151-76	1	ACCUMULATOR TANKS	#21 6 22	-		NO	

APPENDIX B

TABLE I - PERSONNEL LISTING
TABLE II - ULTRASONIC CALIBRATION BLOCKS
TABLE III - PROCEDURE LISTING
TABLE IV - EQUIPMENT AND MATERIALS

TABLE I PAGE 1 of 1

	TITLE		ASNT LEVEL					
EXAMINER		ORGANIZATION	UT	PT	MT	VT	ET	RT
FETHERSTON,S.R.	TECHNICIAN	LMT(2)	I		I	-		
HALL, D.A.	TECHNICIAN	LMT	II			-		
HALL, K.L.	TECHNICIAN	LMT	I	-	-			
KIMBALL, T.	SUPERVISOR	LMT	II	II	II	II(1a	1) -	-
LOREDO, Q.	TECHNICIAN	LMT	I					-
DAHLMAN, L.C.	M & SP SPECIALIST	NSP	II	III	III	111(1	.a)_	III
BRUSSEAU, F.	ANII	HARTFORD STEAM BOILER INSURANCE COMPANY						
	1 1							

FOOTNOTES:

- (1a) Inspection experience and NDE qualifications were judged to be adequate to perform visual examinations in accordance with NSP-VT-1.
- (2) Organization: (LMT) Lambert, MacGill, Thomas, Inc. 515 Aldo Avenue Santa Clara, CA 95050

NORTHERN STATES POWER COMPANY
Prairie Island Unit I
ULTRASONIC CALIBRATION BLOCKS

APPENDIX B
TABLE II
PAGE 1 of 1

No. SIZE & D	SIZE & DIA. PIPE SCHEDULE MATERIA	L SERIAL OR CALIBRATION REPORTS	DATE
0 8"	& THICKNESS	HEAT NUMBER REPORTS	3-27-84 3-28-84 3-29-84 3-27-84 3-27-84 3-28-84 3-29-84

NORTHERN STATES POWER COMPANY
PRAIRIE ISLAND UNIT I
PROCEDURE LISTING

APPENDIX	В		
TABLE	III		
PAGE 1	0F 1		

PROCEDURE NUMBER AND REVISION	FIELD CHANGE	PROCEDURE TITLE	PLANT APPROVAL DATE	FIELD CHANGE REMARKS	CHANGE DESCRIPTION
NSP-UT-1, REV.1	1	ULTRASONIC EXAMINATION OF PIPE WELDS	6-9-82	NONE	COVER EXAMINATION VOLUME OF S/S PIPING WELDS LESS THAN .200 INCH WALL THICKNESS
NSP-UT-2, REV.1	N/A	AUTOMATIC DATA RECORDING	6-22-83	NONE	
NSP-VT-1, REV.2	N/A	VISUAL EXAMINATION	6-22-83	NONE	

MATERIAL OR EQUIPMENT	CALIDIALIUM		REMARKS
ULTRASONIC:			
NORTEC 131D NORTEC 131D NORTEC 131D	S/N 126 S/N 269 S/N 322	CAL. 03-13-84 CAL. 03-12-84 CAL. 01-26-84	
RECORDERS:			
BRUSH 220 BRUSH 220 BRUSH 220	S/N 15452 S/N 18940 S/N 19016	CAL. 12-01-83 CAL. 01-05-84 CAL. 03-05-84	
TEMPERATURE GAUGES:			
PTC SURFACE THERMOMETER	S/N 584 S/N 587	CAL. 11-15-83	CERTIFIED BY MANUFACTURER
ROMPAS BLOCKS:			
304 S/S 304 S/S	S/N LMT-008 S/N 021	CERT 9-8-77 CERT 1-3-79	ORLA'S MACHINE SHOP ORLA'S MACHINE SHOP
MATERIALS:			
ULTRASONIC COUPLANT	LMT - GEL	BATCH #12484	
ULTRASONIC TRANSDUCERS: AEROTECH HARISONIC HARISONIC HARISONIC	S/N F26143 T3206 W2124 W2166	SIZE 1/2" dia 1/4" dia 1/4" x 1/4" 1/4" x 1/4"	FREQUENCY 2.25 MHZ 5.0 MHZ 5.0 MHZ 5.0 MHZ

APPENDIX C

FORM NIS - 1
OWNERS DATA REPORT FOR INSERVICE INSPECTION

FORM NIS-1 OWNERS' DATA REPORT FOR INSERVICE INSPECTIONS (As Required by the Provisions of the ASME Code Rules)

1.)	Owner	NORTHERN ST	ATES POWER	COMPANY		
	Address	414 NICOLLE	T MALL, MIN	NNEAPOLIS, MINNESC	OTA 55401	
2.)	Plant	PRAIRIE ISL	AND NUCLEAR	GENERATING PLANT		
	Address _	WELSH, MINN	ESOTA			
3.)	Plant Uni	1		4.) Owner (Certi	ficate of Authoriza	tion)
5.1	Commercia	Service De	te12-16-	-73 6.) Nation	nal Board Number fo	r Unit
7.)	Components	Inspected				
	mponent or purtenance	Manufac or Inst		Manufacturer or Installer Serial No.	State or Province No.	National Board No.
ASME	CLASS II					
C2.0	PIPING PR	ESSURE BOUN	DARY			
C2.1	CIRCUMFER	ENTIAL BUTT	WELDS			
SI SA W- 28	PRIC ACID PPLY TO FETY INJEC 52, 54, 55 00, 70, 81, 1, 88, 97,	TION	vco			

FORM NIS-1 (back)

- 8.) Exertiation Dates 3-27-84 to 3-30-84 9.) Inspection Interval 12-16-73 to 12-16-83
- 10.) Abstract of Examinations. Include a list of examinations and a statement concerning status of work required for current interval.

This report summarizes the inservice inspection examination performed at Prairie Island Nuclear Generating Plant - Unit 1. This inspection was conducted during the period from March 27 to March 30, 1984 in response to the NRC Staff Evaluation Meeting documented April 18, 1983, specifically item 5 of Section 6 which states that 10 welds be examined every six months.

11.) Abstract of Conditions Noted.

The results from the inservice inspection examinations indicated that the integrity of the system has been maintained.

12.) Abstract of Corrective Measures Recommended and Taken.

No corrective measures were required.

19 84

Owner (//)
Certificate of Authorization No. (if applicable) Expiration Date
CERTIFICATE OF INSERVICE INSPECTION
I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and/or the Stace or Province of MINNESOTA and employed by HARTFORD STEAM BOILER INS. CO. OF HARTFORD, CONN. have inspected the components described in this Owner's Data Report during the period 3/27/84 to 3/30/84, and state that to the best of my knowledge and belief, the Owner has performed examinations and taken corrective measures described in this Owners' Data Report in accordance with the requirements of the ASME Code, Section XI.
By signing this certificate neither the Inspector nor his employer makes any warranty, expressed or implied, concerning the examinations and corrective measures described in this Owners' Data Report. Furthermore, neither the Inspector nor his employer shall be liable in any manner for any personal injury or property damage or loss of any kind arising from or connected with this inspection.
Date 5/9 1984 Commissions NO 8828 MN 238 Inspector's Signature National Board, State, Province & No.
The state of the s

We certify that the statements made in this report are correct and the examinations and

Signed Normery States Course Com

corrective measures taken conform to the rules of the ASME Code, Section XI.

Date May 9