EXERCISE MANUAL

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE
LIMERICK GENERATING STATION

July 25, 1984

Sections II and III are

CONFIDENTIAL
CONTENTS NOT TO BE DISCLOSED
TO EMERGENCY RESPONSE
EXERCISE PARTICIPANTS

1 5635

8408070336 840725 PDR ADDCK 05000352 F PDR

LIMERICK GENERATING STATION PRACTICE EMERGENCY RESPONSE EXERCISE

July, 1984

TABLE OF CONTENTS

SECTION I	GENERAL INT	FORMATION
	Part A Part B Part C Part D Part E	Exercise Schedule Controller and Evaluator Assignments Exercise Objectives Reference Documents
	Part F Part G Part H	Participating Emergency Centers Participating Agencies Exercise Guidelines Instructions for Controllers and Evaluators
SECTION II	EXERCISE SO	CENARIO
SECTION III	Part A Part B Part C	Summary of Exercise Scenario Detailed Exercise Scenario Significant Events Time Line
	Part A	 Plant Monitoring Data 1. Reactor Coolant Activity Concentration (μCi/gm) 2. Drywell and Suppression Chamber Air Space Concentrations (μCi/cc) 3. Suppression Pool Activity Concentration (μCi/gm) 4. Reactor Enclosure Concentrations (μCi/cc)
	Part B	Chemistry Sample Data Exposure Rate from Post Accident Sampling System Samples (mr/hr)
	Part C	North Vent Stack Sampling Data 1. North Vent Stack Release Data (Source Term) 2. North Vent Stack and Effluent Data A. Gaseous Effluent Monitor Readings B. Exposure Rate Increase from Iodine Collection on Charcoal Cartridge C. Exposure Rate from Stack Sample 3. Meteorological Conditions

TABLE OF CONTENTS (Cont)

Part D	Field Monitoring Data
	1. Whole Body Dose Rates
	2. SAM II Readings
	3. Anticipated Dose Assessment Group Results
Part E	Onsite Radiation Levels
	1. Site Map (Plot Plan) Divided Into Zones
	2. Dose Rate Vs Time for Each Zone
	3. Airborne SAM II Readings for Each Zone and Time
	4. Surface Contamination Levels
Part F	Inplant Area Radiation Levels
	1. Area Radiation Levels, Surface Contamination Levels, and Airborne Radioactivity Levels
	by Region
	2. Maps Showing Plant (Unit 1) Areas and Regions
	3. Area Radiation Monitoring System Data
Part G	Exercise Events
Part H	Control Room Messages
Part I	Headquarters Support Requests
Part J	Plant and Reactor System Values
Part K	Site and Field Monitoring Maps
Part L	Controller and Evaluator Checklist

EXERCISE SCHEDULE 1984 NRC/FEMA OBSERVED EMERGENCY RESPONSE LIMERICK GENERATING STATION

On-Site Controller/Evaluator Briefing

Date:

Tuesday, July 24, 1984

Time:

10:00 am

Location:

Limerick Energy Information Center Pre-Exercise Scenario Briefing

Purpose: Attendees:

PECo Controller/Evaluators

NRC Evaluators

Coordinator:

M. Gallagher

Exercise

Date:

Wednesday, July 25, 1984 Limerick Generating Station Radiological Emergency Response

Location: Purpose: Attendeed:

Site Personnel

Coordinator:

R. Kankus, M. Gallagher

Exercise Debriefing

Date:

Thursday, July 26, 1984

Time:

1:30 pm

Location:

Limerick Energy Information Center

Purpose:

Players and Controller/Evaluator Debriefing

Attendees:

PECo Players

NRC and PECo Controller/Evaluators

Coordinator:

M. Gallagher

Exercise Critique

Date:

Friday, July 27, 1984

Time:

10:00 am

Location:

Pottsgrove Junior High School, Pottstown, PA

Purpose:

FEMA/NRC Public Comment

Attendees:

PECo FEMA NRC

Coordinator:

R. Kankus, M. Gallagher

CONTROLLER AND EVALUATOR ASSIGNMENTS NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION JULY 25, 1984

CONTROL ROOM

Head Controller

Controller - Hand Outs

Controller - Controller -

*Controller - Accident Assessment *Controller - Accident Assessment

TECHNICAL SUPPORT CENTER

Lead Controller

Controller - Dose Assessment Evaluator - Dose Assessment

Evaluator - Person lel Safety Team Leader

Evaluator - Chemistry Team Leader
Evaluator - Security Team Leader
Evaluator - Tech Support Team Leader
Controller - Field Monitoring Team Red
Controller - Field Monitoring Team Blue
Controller - Field Monitoring Team Green
Controller - Field Monitoring Team Yellow

Controller - Chemistry Evaluator - Chemistry Lab Evaluator - Chemistry Team

Evaluator - PASS

Evaluator - Fire & Damage Team Leader

Controller - Assembly/Accountability/Evacuation

Controller - ERFDS Handouts Controller - Evacuation Offsite

OPERATIONS SUPPORT CENTER

Lead Controller -

Evaluator - Maintenance Supervisor

Controller - Damage/Repairs Controller - Damage/Repairs Controller - Fire Team Controller - First Aid Event Evaluator - OSC Coordinator

Evaluator - ARMS Handouts

Evaluator - In Plant Rad. Monitoring Teams

Controller - Damage/Repairs EMERGENCY OPERATIONS FACILITY

Head Controller (Offsite Activities)

Controller - Command & Control Controller - Dose Assessment

Evaluator - Communications/Status Boards

Evaluator - Dose Assessment

Controller - ERFDS Handouts/Engineering Support

NAME

M. Gallagher

R. Vanasse (SWEC)

C. Madsen

R. Gambone (PBAPS)

W. Mattiford

H. Carlberg (SWEC)

NAME

D. Graves (SWEC)

C. Mazzola (SWEC)

D. Burwell (SWEC)

H. Lipschitz (SWEC)

E. Michael (SWEL)

J. Basilio

F. Cross (PBAPS)

J. Dietrich (HP-NSS)

A. Bergey (HP-NSS)

M. Horvatinovic (HP-NSS)

R. Bernhardt (HP-NSS)

C. Doherty (SWEC)

W. Leinheiser (Chemistry-GP)

S. Blacklock (Chemistry-GP)

M. Clifton (Chemistry-GP)

M. Restaino (PBAPS)

D. Taylor

K. Serotkin (SWEC)

S. Gallagher (NSS-HP)

NAME

D. McDavitt (SWEC)

R. Hennessey

W. Stull

C. Wyler

S. MacAinsh

V. Affatato

(later)

R. Bettison (SWEC)

J. Richardo (NSS-HP)

J. McElwain

NAME

R. Kankus

E. Firth

E. Salomon (SWEC)

R. Smith (SWEC)

D. Leonard (SWEC)

V. Warren

HEADQUARTERS EMERGENCY SUPPORT CENTER Lead Controller Evaluator - Command & Controller Evaluator - Public Relations/C mmunications (Offsite Medical Facilities Controller K. Schlecker E. Doncarellis (SWEC)

OBJECTIVES FOR THE 1984 NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

In order to demonstrate the radiological emergency response preparedness of the Limerick Generating Station, the Philadelphia Electric Company (PECO), the Pennsylvania Emergency Management Agency (PEMA), and the surrounding risk counties, an integrated radiological emergency response exercise will be conducted.

The PECO objectives of the exercise are as follow:

A. Accident Assessment

- Demonstrate the ability of site personnel to recognize an emergency initiating event and properly characterize and classify the emergency according to the pre-established Emergency Action Levels.
- Demonstrate that PECO personnel can perform offsite dose projections and accident assessment, for both radioactive noble gases and radioiodine, quickly and accurately.
- 3. Demonstrate that onsite and offsite field monitoring teams can be dispatched and deployed in a timely manner; that field communications are adequate; that radiological monitoring equipment is functional; that simulated data are accurately obtained and transmitted to the appropriate location and individuals; that results for area radiation levels and air sampling and analysis for radioiodine and particulates can be effectively used in determining protective action recommendations.

B. Activation of Emergency Facilities

- Demonstrate the ability of station and corporate personnel to activate and staff the emergency response facilities as appropriate for the existing emergency class and to transfer functional responsibilities to the appropriate operations center when escalating or de-escalating to a different emergency class.
- Demonstrate that adequate security of facilities can be maintained.
- 3. Demonstrate functional capabilities of equipment in both EOF and TSC. (Functional capabilities may be simulated on real-time computer equipment.)

C. Notification and Communication

- Demonstrate that station and offsite notification of PECO staff and officials can be accomplished in a timely manner and that all initial notification and updating is verified and logged.
- 2. Demonstrate the ability to communicate with in-plant monitoring teams, rescue parties, and other station personnel as needed.
- 3. Demonstrate that the decision to notify the public officials can be accomplished in an effective and timely manner.
- 4. Demonstrate that messages are transmitted in an accurate and timely manner; that messages are properly logged; that status boards are accurately maintained and updated; that appropriate briefings are held and incoming EOF personnel are briefed and updated.
- 5. Demonstrate that public information is coordinated between PECO and offsite officials; that there are accurate and timely press releases and briefings; that designated public information personnel are implementing their procedures.

D. Station Health Physics and Security

- 1. Demonstrate the ability to account for all personnel within the protected area onsite.
- 2. Demonstrate the ability to provide adequate radiation protection services such as dosimetry and personnel monitoring (frisking).
- 3. Demonstrate the ability to perform area surveys under emergency conditions.
- 4. Demonstrate the ability to enter a highly contaminated area for the purpose of rescuing casualties.
- Demonstrate the ability to provide first aid and transportation to a suitably prepared medical facility for an injured individual who has been contaminated or has received a high radiation dose.
- 6. Demonstrate the ability to maintain plant security under emergency conditions.
- Demonstrate the ability to perform post-accident sampling and analysis of in-plane airborne radioactivity and surface contamination levels.

- 8. Demonstrate the ability to perform personnel and equipment decontamination.
- Demonstrate the use of post-accident sampling equipment to obtain transport, and analyze samples of reactor coolant and/or containment air samples under conditions involving fuel damage.

E. Direction and Control

- 1. Demonstrate that local offsite support agencies such as life squads and fire companies will provide timely support.
- 2. Demonstrate the ability of the directors to direct the emergency organizations in the implementation of the Emergency Plan and the Emergency Plant Implementation Procedures (EPIPs)
- Demonstrate the capability to technically evaluate the incident conditions and implement appropriate corrective actions.
- 4. Demonstrate that PECO has 24 hr capability. Demonstrate that all agency representatives who are assigned emergency reponsibilities can effectively operate from their planned location inside or outside the EOF. (May be done on a limited scale by designating two shifts.)

F. Protective Actions

- Demonstrate protective actions (including mock evacuation and sheltering) by preparing an exercise scenario which provides for a hypothetical total integrated whole body or thyroid dose exceeding the evacuation PAGs for at least the nearest residents.
- Demonstrate the ability of the site and the EOF to make recommendations on both the taking and relaxing of protective actions.

G. Parallel and Other Actions

 Demonstrate the ability to call on a designated hospital to treat a hypothetically contaminated injured patient and that the ambulance service can effectively transport hypothetically contaminated injured personnel to the hospital. Demonstrate that the ambulance and associated equipment can be decontaminated and that contaminated clothing and disposable materials are properly discarded. 2. Demonstrate the licensee's capability for self-critique and ability to identify areas needing improvement in order to make future appropriate procedural changes.

The PEMA objectives of the exercise are to test and evaluate the capabilities of state, counties and municipalities to interface and coordinate with each other in the following areas:

a. Notification of Officials and Staff

The adequacy of the nuclear incident notification and alert procedures from the fixed nuclear facility to PEMA, BRP, risk counties and municipalities, and support counties.

b. Public Alert/Notification and Information

The ability of state, county and municipal authorities to alert, notify and update the public of incidents within the plume exposure pathway emergency planning zone, to include actual use of sirens, EBS announcements, route alerting and other communications means available.

c. Communications

The adequacy of and/or the need for all planned internal and external communications systems among and between the participants to include backup communications system, EBS and RACES.

d. Emergency Operations Center

The adequacy of state, county and municipality emergency operation centers with respect to security, space, comfort, staffing and function for managing responses to nuclear facility incidents.

e. Direction and Control

The ability of key state, county and municipal emergency response personnel and elected officials' support for the initiation and coordination of timely and effective decisions and their ability to provide resource requirements for incidents.

f. Emergency Plans

The adequacy and capability of implementation of state, risk and support counties, and municipal emergency response plans.

g. Public Information

The adequacy of the interface of state, county and nuclear facility public information systems with the news media, to include news media briefing rooms, rumor control measures, etc.

h. Accident Assessment (Bureau of Madiation Protection)

The effectiveness of state BRP nuclear facility accident assessment system, to include adequacy of equipment, personnel staffing and competency skills with respect to reporting dose projection, field measurement, coordination and communications.

i. Protective Measures

The capability of the state, county and municipal emergency response systems to implement sheltering of evacuation and to take actions to activate such support functions as reception centers, mass care/decontamination centers, decontamination stations, risk school district procedures, ambulance services, bus operations, and pickup points.

j. Radiological Exposure Control

The capability of state, county and municipal emergency response personnel to implement access control points and traffic control points, the issuance of dosimetry and KI and the record keeping and decontamination procedures.

REFERENCE DOCUMENTS NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

- 1. Limerick Generating Station, Emergency Plan
- 2. Limerick Generating Station, Emergency Procedures
- 3. Limerick Generating Station, Final Safety Analysis Report
- 4. Title 10, Code of Federal Regulations, Part 50, Appendix E
- 5. NUREG-0654/FEMA-REP-1, Revision 1

PARTICIPATING EMERGENCY CENTERS NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Pennsylvania

Bureau of Radiation Protection Headquarters Assessment Center, Fulton Building, Harrisburg, PA

State of Pennsylvania Emergency Operations Center, Transportation Building, Commonwealth & Forrester Streets, Harrisburg, PA

Montgomery County Emergency Operations Center, 100 Wilson Blvd., Eagleville, PA 19408

Chester County Emergency Operations Center, 14 East Biddle St., West Chester, PA 19380


Berks County Emergency Operations Center, Leesport, PA 19533


Philadelphia Electric Company

Headquarters Emergency Support Center, 2301 Market St., Philadelphia, PA 19101

Limerick Generating Station Technical Support Center, Limerick, PA

Limerick Generating Station Emergency Operations Facility, Plymouth Service Building, Ridge Pike & Chemical Rd., Plymouth Meeting, PA 19462





PARTICIPATING AGENCIES NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

PENNSYLVANIA

State Agencies

Pennsylvania Emergency Management Agency (PEMA)

Bureau of Radiation Protection (BRP)

State Staff Sections

Department of Aging Department of Agriculture Banking Department of Commerce Department of Community Affairs Department of Education Governor's Energy Council Department of Environmental Resources Bureau of Radiation Protection Department of General Services Department of Health Insurance Labor and Industry Department of Military Affairs Public Utility Commission Department of Public Welfare Red Cross Pennsylvania State Police Department of Transportation Turnpike Commission Pennsylvania Game Commission

Risk Counties

Berks County Chester County Montgomery County

Support Counties

Philadelphia County Lehigh County

Federal Agencies

Nuclear Regulatory Commission (NRC)

GUIDELINES FOR CONDUCT OF THE JULY 1984 NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

I. PURPOSE AND SCOPE

This document provides guidance for conducting the July 1984 LGS emergency preparedness exercise. It provides methods for demonstrating emergency response capability, conducting the exercise, and evaluating results. Table 1.G-1 summarizes the degree of simulation to be employed by PECo in demonstrating emergency response capabilities.

II. CONCEPT OF OPERATIONS AND CONTROL OF THE EXERCISES

Philadelphia Electric Company (PECo) and Stone & Webster Engineering Corporation (SWEC) will supply official controllers and/or evaluators for each location where an emergency response is being demonstrated. Prior to the exercise, the controllers and evaluators will be provided with the appropriate locations, maps, time periods, guidelines, and an evaluator evaluation checklist corresponding to their assignments.

Controllers will hand out messages and cue cards and will make judgment decisions. If crisis situations arise, they will contact the Lead Controller in their assigned Emergency Response Facility (ERF) for advice or resolution of the problem. Lead Controllers are designated for the TSC, OSC, and EOF to keep these ERFs on track. If required, they will contact the Head Controller to force play of some events. The Head Controller, stationed in the Control Room, will be in overall charge of conducting the exercise. All requests for modifications or holding periods must be cleared through the Head Controller.

The exercise initiating events will be controlled by lead controllers. Hypothesized initiating events will consist of three types of information: (1) plant information and data provided to Control Room and Technical Support Center personnel; (2) release rates; (3) hypothesized environmental radiation levels. The Head Controller in conjunction with the Lead State Controller has the authority to determine the time sequence of these initiating events to ensure an orderly flow of exercise events. All other actions during the exercise will occur through a free-play response as the plant and corporate participants respond to the initiating events.

As the initiating events are provided to the plant staff, they will determine the nature of the emergency and the implementation of the appropriate emergency response procedures. These procedures are expected to include a determination of the emergency classification in accordance with NUREG-0654. FEMA-REP-1, Revision 1. Notifications will be made to the appropriate federal, state, and county authorities.

The hypothesized emergency will continue to develop based on data and information provided to the Control Room and TSC personnel. As the situation develops, information will be forwarded to appropriate plant and corporate personnel for the determination of actions to be taken in response to the hypothesized emergency. Where information would normally be confirmed via an independent source (such as National Weather Service for weather data), the confirmation data will be simulated. If a conflict exists between the hypothesized data and the actual data, the hypothesized data will be utilized.

Certain inconsistencies (such as plume width, release duration, technical reason for the simulated release, etc.) may be intentional and required to provide an exercise basis which tests the plant and corporate capabilities to the maximum extent feasible in a limited time frame. If an inconsistency is known or determined to be intentional, then the emergency response personnel will note the inconsistency and ignore it. The lead controllers will have the authority to resolve or explain any inconsistencies or problems that may occur during the exercise.

With the exception of the already cited and potential inconsistencies, the internal operations of the emergency response facilities will be identical with their intended operation in a real emergency.

III. GENERAL GUIDANCE FOR THE CONDUCT OF THE EXERCISE

1. Simulating Emergency Actions

Since exercises are intended to demonstrate actual capabilities as realistically as possible, participants should act as they would during a real emergency. Wherever possible, actions should be carried out. The actions that PECo will actually perform and those that will be realistically simulated are identified in Table 1.G-1. Only when it is not feasible to perform an action should it be simulated. Any orders given that for any reason cannot or should not actually be performed should begin with the word "Simulate." For example, the order to put out a fire that is being hypothesized would state: "Simulate discharging the fire extinguisher." Where such actions are being taken, it is suggested that participants inform any observers in the area of what action really would be taken had the emergency been real.

2. Avoiding Violation of Laws

Intentional violation of laws is not justifiable during any exercise. To implement this guideline, the following actions must be taken:

a. All evaluators and potential exercise participants must be specifically informed of the need to avoid intentional violation of all federal, state, and local laws, regulations, ordinances, statutes, and other legal restrictions. The orders of all police, sheriffs, or other authorities should be followed as would normally be the case.

- b. Exercise participants will not direct illegal actions being taken by other exercise participants or members of the general public.
- c. Exercise participants will not intentionally take illegal actions when being called out to participate in an exercise. Specifically, local traffic laws such as speed laws will be observed.

3. Avoiding Personnel and Property Endangerment

Participants and evaluators will be instructed to avoid endangering property (public or private), other personnel responding to the exercise, members of the general public, animals, and the environment.

4. Actions to Minimize Public Inconvenience

It is not the intent, nor is it desirable or feasible, to effectively train or test the public response during the conduct of radiological emergency exercises. Public inconvenience is to be minimized.

The actions of federal, state, and county agencies and nuclear power plant operators receive continuous public notice and scrutiny; therefore, the conduct of an exercise could arouse public concern that an actual emergency is occurring.

5. Maintaining Emergency Readiness

During the performance of an exercise the ability to recognize a real emergency, terminate the exercise, and respond to the new situation must be maintained. Therefore, the exercise scenario and actions of participants will not include any actions which seriously degrade the condition of systems, equipment or supplies, or affect the detection, assessment, or response capability to radiological or other emergencies.

Actions taken by the participants will also avoid actually reducing plant or public safety. The potential for creating real radiological or other emergencies will be specifically avoided.

If a real emergency occurs during the exercise, requiring the actions of plant and corporate personnel, then the exercise will be terminated. All messages about real events will be clearly identified as such. For example, precede a real message with: "This is NOT, repeat, NOT an exercise message."

IV. EMERGENCY RESPONSE IMPLEMENTATION AND OPERATIONS

1. Initial Notification

Initial notification will be made in accordance with the appropriate Emergency Plan Implementing Procedures (EPIPs).

2. Plant Operations

It should be emphasized that the exercise will in no way interrupt normal plant operations, production, and safety. The responses of Control Room personnel and plant operators will be simulated when taking action to combat the emergency. Instead, a controller will narrate the initiating events and the postulated plant response directly to the Shift Supervisor and other Control Room personnel who will then employ the appropriate emergency procedures.

3. Environmental Monitoring Teams

LGS will dispatch field environmental monitoring teams. The controllers will provide hypothesized field data which will be used to determine radiation readings at preselected locations. However, these teams will be equipped with the necessary equipment to enable them to determine actual area gamma dose rates and airborne radioiodine concentrations. The monitoring teams will not be suited up in anticontamination clothing, but will have such equipment at their disposal.

4. Public Notification

Actual emergency message transmissions via the Emergency Broadcast System will not occur.

5. Public Information

Press releases to the general public and news media will be simulated. The simulated press releases will contain all necessary information on the current status of the exercise but will not be transmitted.

6. Communications

Communications between the exercise participants will occur in accordance with the appropriate Emergency Plan Implementing Procedures. Should any primary communication path become inoperative or prove inadequate, backup means of communication will be utilized as appropriate.

V. CLOSEOUT OF THE EXERCISE

The exercise will be terminated by PECo and SWEC lead controllers, at their discretion, when the scenario is completed. This will occur after the plant has entered the recovery phase.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

TABLE 1G-1 SCOPE

IDENTIFICATION OF ACTUAL AND SIMULATED EVENTS

		A	CTUAL	SIMULATION		
1.	EME	RGENCY CLASSIFICATION AND DETECTION				
	0	Demonstrate the ability of site personnel to recognize an emergency initiating event and condition.	х			
	0	Demonstrate the ability of site personnel to properly classify events into an emergency class according to the pre-established Emergency Action Levels (EALs) which includes escalation and de-escalation of the classification.	X			
2.	EME	RGENCY RESPONSE ORGANIZATION				
	0	Demonstrate the response of the on-shift emergency organization.	Х			
	0	Demonstrate the timely augmentation of the on-shift emergency organization.	Х			
	0	Demonstrate that there are sufficient qualified personnel to respond to the postulated events.	Х			
	0	Demonstrate the timely augmentation of the plant staff emergency organization by corporate support personnel.	X			
	0	Demonstrate that emergency personnel understand and can implement their responsibilities	х			
3.	EMERGENCY RESPONSE SUPPORT RESOURCES					
	0	Demonstrate the ability of PECo corporate personnel to provide support.	х			
	0	Demonstrate the ability to procure assistance from outside contractors and private organizations.		Х		
	0	Demonstrate the ability to request assistance from Federal resources.		Х		

3. EMERGENCY RESPONSE SUPPORT RESOURCES

Demonstrate the ability to obtain assistance from nuclear and other facilities, organizations or individuals identified in the LGS Emergency Plan.

4. EMERGENCY FACILITIES ACTIVATION

- Demonstrate the ability of station and corporate personnel to activate and staff the following emergency facilities: Operations Support Center (OSC); Technical Support Center (TSC); Emergency Operations Facility (EOF); Headquarters Emergency Support Center (HESC) and Emergency News Center (ENC).
- X Demonstrate the ability to provide adequate supplies and equipment for use by emergency response personnel.
- Demonstrate functional capabilities of equipment in both EOF and TSC. (Functional capabilities may be similated on real-time computer equipment.)

NOTIFICATION AND COMMUNICATION 5.

Demonstrate the notification of state and local response organizations based on the emergency classification.

X

X

Demonstrate the effectiveness of notification messages and verification of these messages.

X

Demonstrate the ability to alert, notify, 0 and mobilize emergency response personnel.

X

Demonstrate the operation of the public 0 alerting system.

X

Demonstrate the adequacy of communications with state/local governments during the exercise.

X

Demonstrate the adequacy of communications 0 with federal emergency response organizations including the NRC Regional Office Emergency Operations Centers.

- o Demonstrate the adequacy of communications between the PECo emergency facilities and field survey groups.
- o Demonstrate the adequacy of communications X with offsite fire fighting company.

6. ACCIDENT ASSESSMENT

- o Demonstrate proficiency in the assessment X of plant conditions and radiological consequences in determining appropriate actions to response and recovery from an emergency.
- O Demonstrate that personnel can perform X radiological accident assessment and offsite dose projection techniques by using plant monitor readings, environmental data, and meteorological parameters.
- o Demonstrate the ability to effectively use X the Post Accident Sampling Station.
- o Demonstrate the ability to perform field X monitoring within the plume exposure Emergency Planning Zone.
- O Demonstrate the ability to estimate X integrated dose from projected and field monitored dose rates and compare these estimates with protective action guides.

7. RADIATION PROTECTION CONTROL

o Demonstrate the ability to provide X adequate radiation protection services, such as personnel dosimetry, respiratory protection, protective clothing, and personnel monitoring (frisking) to emergency response personnel during the exercise when required (donning of protective clothing, dosimetry, and respiratory protection equipment may be simulated in certain situations).

7. RADIATION PROTECTION CONTROL

 Demonstrate the ability to provide and monitor dosimeters for emergency workers. X

	0	Demonstrate the ability to evaluate the need for and provide the means for personnel decontamination.		X	
	0	Demonstrate the ability to provide contamination control measures such as areas access control.	х		
	0	Demonstrate the application of onsite exposure quidelines consistent with Emergency Exposure Guidelines.	Х		
	0	Demonstrate the ability for radiological monitoring of people evacuated from the site		X	
8.	CORR	ECTIVE ACTIONS			
	0	Demonstrate the ability to determine the cause of the emergency condition, terminate the condition with consideration of appropriate engineering safeguards, and place the plant in a safe condition.	X		
	0	Demonstrate the ability of PECo personnel to respond to and terminate a fire.		Х	
9.	PROT	ECTIVE ACTIONS			
	0	Demonstrate the ability to warn or advise personnel onsite of emergency conditions.	Х		
	0	Demonstrate the ability to evacuate nonessential personnel from the site. (A preselected group of onsite personnel will participate in this activity.)	х		
	0	Demonstrate the ability to provide timely and accurate protective action recommendations to the state and local authorities.	х		
10.	MEDI	MEDICAL ASSISTANCE			
	0	Demonstrate the ability to provide first aid and transportation for an injured individual who has been contaminated.		Х	
11.	PUBL	IC INFORMATION			
	0	Demonstrate the adequacy of facilities used for dissemination of information to the news media.	Х		

0	Demonstrate the ability of the PECo spokes- person to receive and disseminate necessary information.	X	
0	Demonstrate the ability for timely exchange of information among designated spokespersons.		Х
0	Demonstrate the ability to deal with rumors		Х
PAR	ALLEL AND OTHER ACTIONS		
0	Demonstrate proper procedures for emergency security measures, including control of access/egress and personnel accountability at the plant site.	X	
0	Demonstrate the establishment of a recovery organization		Х
0	Demonstrate the capability for self-critique and the ability to identify areas needing improvement in order to make future appro- priate plan and procedural changes.	X	

12.

INSTRUCTIONS FOR CONTROLLERS AND EVALUATORS NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

- Personnel are assigned as controllers or evaluators at all key function areas to monitor and control the exercise. In addition, they will accompany radiological monitoring teams, plant health physics personnel, and maintenance repair/rescue teams.
- 2. The inplant controllers will be coordinated by the Head Controller located at the Control Koom (ext. 2498). If unable to reach the Control Room, contact the Lead Controller in the TSC (ext. 2630). He will be responsible for the overall conduct of the exercise scenario. Field controllers should contact the Lead Controller in the EOF (ext. 2604) regarding coordination problems or questions. The Lead Controller at the EOF will be responsible for contacting the Lead State Controller to maintain schedules.
- 3. Message forms and simulated Control Room data will be used to initiate, modify, and complete the events comprising the overall scenario. Selected controllers will use the message forms to place the scenario events in effect and to trigger responses from the involved emergency response organizations. Each controller will have copies of the messages controlling the portion of the exercise scenario he/she is responsible for.

Two kinds of messages will be used:

Controlling

Messages used as a primary means of implementing scenario events by announcing or placing an event in effect by hypothesizing conditions resulting from previous actions.

Contingency

Messages used at the discretion of the controllers with the approval of the Head Controller in the Control Room in order to maintain the scenario plan continuity or schedule.

Controlling messages will be presented to the designated exercise participant at the time specified in the event schedule. The controller should follow up with an explanation of the message and answer questions to ensure that the participant understands the message.

Controllers will not initially provide information to the participants regarding scenario development or resolution of problem areas encountered. The participants are expected to obtain information through their own organization and exercise their own judgment in determining response actions and resolving problems. In the event of incorrect or incomplete responses, or if the participant indicates lack of knowledge of how to proceed, the controller will prompt the

participant with necessary instructions or contingency cards and will note the deficiency on his/her critique sheets.

- 4. Note that the scenario events are hypothetical. Any portions of the scenario depicting plant system operational transients are simulated events. No Control Room actions, or reactions involving operation of plant systems or affecting generation capability, will be initiated. All exercise scenario messages will be prefixed and suffixed with the words "THIS IS A DRILL." Controllers stationed at areas vital to maintaining generating capability should be especially aware and take extra precautions in issuing messages or giving instructions regarding the scenario events.
- 5. Required controllers will have the time-related plant and radiological parameters of the exercise scenario. This information should be issued upon request to the appropriate exercise participants by either the Control Room controller or controllers accompanying the radiological monitoring field teams.
- 6. Some exercise participants may insist that certain parts of the scenario are unrealistic. The controllers and evaluators have the authority, with the approval from the Lead controllers, to clarify any questions regarding scenario content. In some cases, it may be necessary to exercise "controller's prerogative" or "this is due to exercise requirements" to preserve the continuity and objectives of the exercise.
- Prior to commencement, all telecommunications should be tested to ensure satisfactory communications between the lead controllers and all other controllers.
- 8. All controllers and evaluators will synchronize their watches to ensure that messages are delivered at the proper time. Times on messages are set relative to the beginning of the exercise, with delivery of the first message of "T + 0:00".
- Controllers will commence their assignments at assembly locations for players that they are to observe or as directed by the Lead Controllers. (See Controller Assignment, Part B.)
- Scenario equipment problems not covered in the Exercise Events section of this manual will be handled by the controllers in the Control Room.
- 11. Players are not allowed to introduce items project free play into the exercise or its scenario.
- 12. Be sure to return all exercise books to the Lead Controller.
- 13. Lunches will be provided by PECO; however, there are no such lunch breaks in the exercise. Players and controllers shall be relieved for lunch as situation permits. Emergency team leaders should decide when team members may take a lunch break.
- 14. Be sure to have a hard hat with you when entering the plant.

CONTROLLER'S AND EVALUATOR'S RULES

DOs

- 1. Know the overall Controller's Organization (Part B).
- 2. Remember that there are two clocks: a scenario time and a clock time.
- 3. Identify the players by name and function
- Identify yourself at all times to all players. Wear T-shirts or tags as provided by PECO.
- Identify the phone (or radio for field teams) you will use to maintain communications with lead controllers.
- Position yourself in order to maximize your effectiveness in issuing messages and observing the players.
- Be sure you understand the player's scenario script and the master scenario.
- 8. Keep the play on schedule by checking your script.
- 9. Issue the message on time. Make sure the players understand it.
- 10. Remember to call the Lead Controller or Head Controller to report on status of players actions if off schedule or if in doubt about what to do. Call for advice if players depart signicantly from the scenario script which will create a major delay. If necessary, intervene with player action and put players back on scenario track.
- 11. Allow the players reasonable flexibility to do their functions and demonstrate their skill, knowledge, and initiative.
- 12. Identify the federal evaluators(s). Make sure they are reasonably aware of all your actions and those of the players.
- 13. Make notes on good and bad points of players' actions, the strongths and weaknesses, and areas for improvements. Use the Evaluators's Critique Sheets.
- 14. Attend the post-exercise critique session to provide your comments and recommendations to the Chief Controller on what happened.
- 15. Identify the players' leaders. Work with them as appropriate.
- 16. If a real emergency occurs and this affects the players, call off your portion of the exercise, and notify (later) immediately.
- 17. Be at your post at least 20 minutes prior to any player action commencement. Set yourself up.

- 18. The federal evaluators will not issue "surprise" messages or direct "surprise" actions at the players. They must work through the controller. This is essential for the success of the exercise.
- 19. Controllers and federal evaluators do not have to follow the radiation exposure control practices for the simulated radiation levels from the emergency exercise scenario. However, the players <u>must</u> follow the radiation protection rules Controllers and evaluators will be exempt from accountability and have access to all areas.

DON'Ts

- 1. Don't leave your post at key times.
- 2. Don't prompt the players to take action.
- 3. Don't coach the players.
- 4. Don't criticize the players' actions during the play.
- Don't forget to call the lead controllers to seek advice or help as necessary.
- 6. Don't allow the media/other external influences to distract the players. No interviews with players are allowed.
- 7. Don't allow free play to be interjected into the exercise scenario.
- 8. Don't allow simulation when equipment and facilities are available except for causing flow discharge of fire extinguishers, etc.

SUMMARY OF EXERCISE SCENARIO NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Unit 1 is operating at full power and has accumulated eight full power months of operation since the previous refueling. At that time, 15 fuel assemblies of a new design were installed so that they could be qualified under commercial operating conditions. The 15 fuel assemblies represent about 2 percent of the fuel in the core. All power generation equipment is operating, and all safety system equipment is operable.

At 1105, fire is reported at the instrument air compressor 1AK101. Offsite assistance is required since the fire is spreading and threatens the nearby lube oil storage tanks. The fire is reported extinguished at 1145.

*** UNUSUAL EVENT should be declared ***
Fire

A spurious "High Steam Flow" alarm causes isolation valves in two main steam lines to trip shut. The resulting transient causes isolation of the other main steam lines, due to high steam flow, and reactor scram. The spurious alarm occurs at 1315.

*** UNUSUAL EVENT should be declared ***
Unplanned reactor scram

The thermal/mechanical transient resulting from the unbalanced isolation of the main steam lines and reactor scram caused damage to the 15 new design fuel assemblies. Pins holding fuel rods in the upper and lower tie plates shattered, and fuel rod spacers became dislodged. The mechanical damage to the fuel is not an immediate cause of increased primary system activity, but it has resulted in significant loss of cooling flow paths at both lower and upper ends of the assemblies and the fuel begins heating up. The transient, with peak pressure of 1170 psig, also causes reactor vessel head seal leakage and cracks in the piping of several safety/relief valves (SRV) discharge lines at the point that they enter the drywell floor. The reactor vessel head seal leakage will cause pressurization of the drywell if reactor pressure is maintained, while the cracks in the SRV discharge piping will cause pressurization of the drywell if reactor pressure is reduced. At approximately 1345, reactor depressurization is begun.

By 1400, drywell pressure has reached 2.4 psig and radiation levels are 2.0 R/hr. Reactor coolant and drywell atmosphere samples indicate that nearly all the radioactivity is Xenon and Krypton. RHR A and B pumps are lined up for suppression pool cooling mode.

At 1430, the control room is notified that an assistant plant operator has been found unconscious and bleeding from a head laceration. He was on routine inspection of the radwaste enclosure and was found lying in a puddle that appears to be leakage from the fuel pool holding pump (00P340). Drywell radiation level has increased to 14 R/hr at 1500 and reaches 100 R/hr at 1600. Sample analysis continues to indicate primarily noble gases in the drywell atmosphere.

*** ALERT should be declared *** Containment radiation monitor reading exceeds 100 R/hr

At 1615, it is noted that the discharge flow of RHR pump B has started decreasing. Personnel are sent to investigate the cause. At 1630, airborne radiation levels in the secondary containment rise significantly due to leakage from the primary containment. Evacuation of the Unit 1 reactor building is ordered. Contact is lost with the personnel investigating the RHR pump problem, and a search is begun.

By 1700, reactor coolant activity indicates more than 300 μ Ci/gm of I-131 equivalent and drywell radiation level is 400 R/hr. Drywell pressure is leveling off at 4.5 psig. HPCI and RCIC have been secured, and the vessel is being filled with available LPCI and core spray pumps.

At 1715, the CO_2 portion of the fire protection system is declared inoperable due to decreasing tank pressure. A fire watch should be implemented until the system is restored. Alarms sound at 1730 indicating a fire in the East RHR heat exchanger room on el 177 ft-0 in. Reports are received that the fire has disabled both RHR B&D pump motors. Cause of the fire is unknown, but it is fueled by scaffolding material brought there in preparation for an inspection of the RHR heat exchangers. Station fire fighters are able to extinguish the fire.

At 1730, drywell radiation level has reached 1,000 R/hr.

*** SITE EMERGENCY should be declared ***

(Containment radiation monitor reading exceeds 1,000 R/hr.)

At 1800, the Standby Gas Treatment System (SGTS) effluent monitors detect radioactive releases. Subsequent analyses of SGTS exhaust samples indicate releases are approximately 0.1 Ci/second of noble gases. Meteorological conditions are not expected to change significantly for 12 to 24 hours. Wind is from the South Southeast (158°) at 3 mph.

Reactor pressure is near 30 psig at 1830. Containment radiation level is now 2,000 R/hr, and drywell pressure is approximately 4 psig. The control room is notified that the result of the 1830 sample of the cooling tower blowdown is 7N6 μ Ci/cc. Samples taken at 1815 and 1845 were both negative. At 1845, status lights on the control board indicate the containment purge isolation valve (HV-57-114) has backed off the fully-closed position. The valve does not respond to controls. At 1900, radioactive releases have increased to levels corresponding to site boundary-whole body dose rate of 2 mrem/hr and thyroid dose rate of 4 mrem/hr. Although there is as yet no confirming indication in the control room, the release is coming from leakage pass the closed isolation valve (HV-57-115) on the containment purge line. Drywell radiation level has increased to 4000 R/hr.

At 1915, status lights indicate that the containment purge line isolation valve (HV-57-115) is unseated and it also fails to respond to controls. Effluent releases increase rapidly, and ventilation exhaust monitors exceed the General Emergency Action Level by 1930 hours. Drywell radiation level reaches 10,000 R/hr.

*** GENERAL EMERGENCY should be declared ***

Potential or actual effluent releases correspond to 5 rem/hr thyroid or containment monitor reading exceeds 10,000 R/hr

Personnel in the reactor building report that it will require 10 hours to terminate the release from the containment purge line. At 1945, radioactive releases level off at values corresponding to offsite whole body and thyroid dose rates of 800 mrem/hr and 11,000 mrem/hr, respectively. Wind speed has increased to 4 mph but continues from the South Southeast.

At 2040, CS pump A trips. CS pumps B and D are manually initiated. CS pump C is tripped. Personnel are dispatched to diagnose the problem.

At 2145, the release is terminated by repair of the containment purge line valves. De-escalation of the emergency to SITE EMERGENCY and later to ALERT status is now feasible.

At 2145, the exercise will be terminated after the plant has demonstrated recovery.

DETAILED SCENARIO FOR UNIT 1 NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION July 25, 1984

Initial Conditions

Unit 1 is operating at full power and has accumulated 8 full power months of operation since the previous refueling. At that time, 15 fuel assemblies of a new design were installed so that they could be qualified under commercial operating conditions. The 15 fuel assemblies represent about 2 percent of the fuel in the core. On two occasions in the past three months, Unit 1 has experienced reactor trips caused by spurious main steam isolation valve (MSIV) closure signals. All power generation equipment is operating, and all safety system equipment is operable.

The initial plant and reactor system values are shown in Table 1.

The Meteorological conditions at 1100 are characterized by the influence of an almost stationary high pressure area centered over Greenwich, Connecticut. The clockwise flow around its center is evident by the following ground level Limerick Generating Station Met tower data:

Wind direction

Wind speed

Temperature

Delta Temperature

Southeast (137 degrees)

7.2 mph

71°F

-1.3°F

6.7 degrees azimuth

The National Weather Service indicates that the high is expected to slowly drift to the south during the next 12 to 24 hours. Skies will remain sunny with light winds gradually backing to the South Southeast.

- Reactor power is 100 percent, reactor pressure and water level are 1020 psig and +35 in., respectively. Drywell pressure and temperature are 0.6 psig and 130°F, respectively.
- 1105 Control room is notified of a fire in the turbine enclosure at el 217 ft-0 in. Instrument air compressor 1AK101 is on fire. Offsite assistance is required since the fire is spreading and threatens the nearby lube oil storage tank.

****UNUSUAL EVENT should be declared***

EP-101-5 Fire: Fire in protected area lasting 10 minutes or more after initial attempts to extinguish it as indicated by observation or fire alarm on OA(B)C850.

- The control room is notified that the fire in the turbine enclosure is extinguished.
- 1200 Reactor continues to operate at full power.
- 1315 A spurious high steam flow signal causes main steam isolation valves (MSIV) HV-41-1F028A and C to shut.

The remaining MSIVs close due to high steam flow.

The reactor scrams.

The reactor pressure increases to 1,170 psig.

Three groups of safety relief valves (SRVs) open.

The reactor water level decreases.

UNUSUAL EVENT should be declared

EP-101-12 Unusual Shutdown: Shutdown other than normal controlled shutdown and for the purpose of placing the plant in a safer condition.

The reactor pressure and water level decreased to 1,050 psig and -38 in., respectively. The SRVs have closed except for two SRVs which the operator has kept open in order to control pressure.

HPCI and RCIC systems are initiated on low-low water level. Standby gas treatment system (SGTS) is initiated.

1317 The reactor pressure has decreased to 1,040 psig.

Reactor water level has decreased to -40 in.

Drywell pressure and temperature begin to increase due to reactor vessel head seal leakage and cracks in SRV discharge lines. The reactor water level begins to increase due to HPCI and RCIC injection.

Reactor pressure and water level are 1,025 psig and +50 in., respectively. Drywell pressure has increased to 1.5 psig which results in a high drywell pressure alarm in the control room.

HPCI pump is manually operated for pressure level control.

1330 Drywell pressure has increased to 1.68 psig.

Containment group isolations occur.

HPCI is initiated in injection mode and trips at +54 in. Once the high level signal clears, HPCI is initiated and operated for pressure/level control.

1345 Reactor pressure and water level are 1,000 psig and +50 in., respectively.

Containment radiation level is 1 R/hr.

Depressurization of the reactor using SRVs is begun.

Reactor pressure and water level are 860 psig and +50 in., respectively.

Drywell pressure is 2.4 psig.

Containment radiation level is 2 R/hr.

Reactor coolant and drywell samples indicate that nearly all the radioactivity is Xenon and Krypton.

RHR A and B pumps are lined up for suppression pool cooling mode.

The wind speed has decreased to 4.8 mph. the wind direction is from the Southeast (145 degrees).

1430 Reactor pressure is 670 psig.

Reactor water level is being maintained at +50 in.

1430 The control room is notified of a contaminated injury in the radwaste enclosure.

1500 Cooldown and depressurization of the reactor continues.

Reactor pressure is 560 psig.

Drywell pressure is 4.0 psig.

Drywell radiation level has increased to 14 R/hr.

Reactor pressure is 440 psig. Core spray (CS) and RHR in the LPCI mode are initiated.

- 1548 RHR A and B pumps are returned to suppression pool cooling mode.
- Drywell radiation level has increased to 100 R/hr. Sample analysis reveal primarily noble gases in the drywell atmosphere.

ALERT should be declared

EP-101-8 Damage of Fuel: Containment post-LOCA radiation monitor greater than 100 R/hr.

- RHR pump B flow decreased to 500 grm. Personner are sent to investigate the cause. Reactor pressure and water level are 380 psig and +50 in., respectively.
- The control room is notified that the airborne radiation levels in the reactor enclosure have risen significantly and exceed 10 MPC. The high airborne radiation levels are due to small leakage from the primary containment.

Evacuation of the Unit 1 reactor enclosure is ordered.

The wind speed has decreased to 4.1 mph. The wind direction is from the South Southeast (151 degrees)

- The control room is notified that the person investigating RHR pump B is unaccounted for. A search is begun.
- 1700 Reactor pressure is 300 psig.

Drywell pressure is leveling off at 4.5 psig.

Drywell radiation level is 400 R/hr.

Reactor coolant activity sample results indicate more than 300 uCi/gm of I-131.

RCIC and HPCI pumps are manually tripped.

Reactor vessel is flooded with CS and LPCI.

- 1715 A low pressure alarm from the CO₂ storage unit 00S133 is received.
- 1730 The control room is notified that the CO₂ portion of the fire protection system is inoperable due to low tank pressure. A continuous fire watch is established for those areas in which redundant systems or components could be damaged.
- Annunciator alarm on the fire protection panel in the control room is received. The alarm indicates that the fire is located in the RHR heat exchanger and pump room at el 177 ft. RHR pump B trips.

Control room is notified that the fire has disabled the motors for both RHR pumps B and D. Cause of the fire is unknown, but it is fueled by scaffolding material brought there in preparation for an

inspection of the RHR heat exchangers. Offsite assistance is not required to extinguish the fire.

Drywell radiation level reaches 1,000 R/hr.

SITE EMERGENCY should be declared

EP-101-8 Damage of Fuel: Containment post-LOCA radiation monitors greater than 1,000 R/hr.

1745 LPCI is tripped once the reactor vessel is flooded.

Cooldown is continued by circulating reactor vessel inventory through the SRVs to the suppression pool using available CS pumps.

SGTS effluent monitor detects radioactive release concentration of 0.01 µCi/cc. Subsequent analyses of SGTS exhaust samples indicate releases are approximately 0.1 Ci/second of Noble gases. The wind is from the South Southeast (158 degrees) at 3 mph. Meteorological conditions are not expected to change significantly for 12 to 24 hours.

1830 Reactor pressure is 30 psig.

Containment drywell radiation level is 2,000 R/hr.

Drywell pressure is 4 psig.

1845 Status lights on the control board indicate the containment isolation valve HV-57-114 in the containment purge system has backed off the fully closed position. Repeated attempts to close the valve are unsuccessful.

1900 Drywell pressure is 3.8 psig. Reactor enclosure local radiation levels in the area of the containment purge system line are increasing.

The control room is notified that the result of the 1830 sample of the cooling tower blowdown is 7N6 μ Ci/cc. Samples taken at 1815 and 1845 were both negative.

Analysis of 1830 sample indicates that at least 60 percent of the activity is Technetium-99M.

Radioactive releases have increased to levels corresponding to site boundary-whole body dose rate of 2 mrem/hr and thyroid dose rate of 4 mrem/hr. The releases are due to leakage pass the closed isolation valve HV-57-115 in the containment purge line although there is no indication in the control room.

1915 Status lights on the control board indicate that the outboard containment purge line isolation valve HV-57-115 is unseated.

Repeated attempts to close the valve are unsuccessful. Effluent releases increase rapidly.

Personnel investigating the purge valves report that it will require 10 hours to terminate the release.

North stack effluent radiation monitor indicates 10 uCi/cc. Radiation releases correspond to offsite whole body and thyroid dose rates of 800 mrem/hr and 11,000 mrem/hr, respectively.

Drywell radiation level reaches 10,000 R/hr.

GENERAL EMERGENCY should be declared

EP-101-6 Radioactive Release: Projected thyroid dose greater than 5 rem at the site boundary or

EP-101-8 Damaged Fuel: Containment post-LOCA radiation monitor greater than 10,000 R/hr.

- The wind speed increased to 4.0 mph. The wind direction remains from the South Southeast.
- 2000 North stack effluent radiation monitor indicates 10 uCi/cc. Drywell pressure is 3.2 psig.
- 2040 CS pump A trips. CS pumps B and D are manually initiated. CS pump C is tripped.

Drywell radiation levels off at 1.8 x 104 R/hr.

- Drywell pressure is 2.5 psig. Drywell radiation level is 18,000 R/hr. Personnel investigating the seizure of CS pump A report that they have encountered high radiation fields and it will be some time before they can enter the area.
- Drywell pressure is 2.3 psig. Drywell radiation level is 17,000 R/hr. North stack effluent radiation monitor indicates 10 uCi/cc.
- The containment purge line valve HV-57-115 is repaired. Releases to the atmosphere are terminated.

Deescalation of emergency to SITE EMERGENCY and later to ALERT status is now feasible.

2230 Exercise is terminated after the plant has demonstrated recovery.

TABLE 1

Reactor Level	+35 inches	Drywell Press	_0.6_psig
Reactor Pressure	1020 psig	Drywell Atmos Temp	_130_ °F
Reactor Power	100 % Full Power	Supp Pool Press	0.6 psig
Core Plate DP	100 % Full Power	Supp Pool Temp	90 °F
Core Flow	100 lb/hr x 10 ⁶	Supp Pool Level	<u>22.1</u> feet
Total Steam Flow	_14_ lb/hr x 10 ⁶	Main Stm Line Rad Mon	1100 mR/hr
Total Feedwater Flow	_14_ lb/hr x 10 ⁶	Containment Rad Level	2 R/hr
Condenser Vacuum	_29_ inches Hg	Cond Stor Tank Level	38_ feet
Hotwell Level	_40_ inches	RCIC Flow	0_ gpm
CRD Charging Pressure	1300_ psig	HPCI Flow	O gpm
Inst. Gas to ADS Pressure		RHR A Flow	gpm
Equip. Drain Coll Tank Level	3 feet	RHR B Flow	gpm
Equip. Drain Surge Tank Level	3_ feet	RHR C Flow	o_gpm
Floor Drain Coll Tank Level	4_ feet	RHR D Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray A Flow	0 gpm
H ₂ Concentration	_ 0 %	Core Spray B Flow	O gpm
O ₂ Concentration	2.8 %	RHR Hx Outlet Temp	80 °F
SGTS Flow		RHR SW Inlet Temp	80 °F
North Vent Stack Concentration	5N6 µCi/cc	North Vent Stack Release Rate	7P2 µC1/sec

Limerick Generating Station Initial Plant and Reactor System Values

SIGNIFICANT EVENTS TIME LINE NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Emergency			
Classification	Time	Scenario Event	Expected Actions
None	1100	Initial Conditions • Unit I at Full Power • All power generation equipment operating • All safety systems operable • Meteorological conditions • Stable • Wind velocity 5.2 mph from 137° (Southeast)	
None	1100	Exercise Starts	
UNUSUAL EVENT	1105	Fire is discovered at instrument air compressor 1AK101 which threatens Lube Oil Storage Tank	 Fire Fighting Group responds to fire Offsite fire assistance is required Local fire company responds Unusual Event should be declared Internal Notification Offsite Agencies Notified
UNUSUAL EVENT	1145	Fire is reported extinguished	

SIGNIFICANT E	VENTS	E LI	NE (Cont)
---------------	-------	------	------	-------

Emergency Classification	Time	Scenario Event	Expected Actions
UNUSUAL EVENT	1315	Reactor scrams on spurious Main Steam Isolation Valve (MSIV) closure signal • Safety Relief Valves (SRVs) open • Reactor level decreases • Standby Gas Treatment System (SGTS) initated	 Reactor operators follow standard operating procedures and emergency procedures Unusual Event Declared Internal notification Offsite agencies notified
UNUSUAL EVENT	1330	Drywell "Hi-Pressure" setpoint of 1.68 psig is exceeded	
		Containment group isolation occur	 Isolation valves on instrument nitrogen lines opened to reestablish manual control of SRVs. HPCI placed on manual control Operators attempt to stop leakage by backseating of valves
UNUSUAL EVENT	1345	Drywell pressure increase continues	Depressurization of reactor using SRVs is begun
UNUSUAL EVENT	1400	Reactor coolant and drywell samples indicate that nearly all radio-activity is Xenon and Krypton	
UNUSUAL EVENT	1430	Worker is injured and radioactively contaminated in the Radwaste Enclosure	 Search and Rescue/First Aid Group dispatched Emergency medical First Aid administered Personnel contamination survey performed Personnel decontamination performed Offsite medical assistance

SIGNIFICANT EVENTS E LINE (Cont)

Emergency			
Classification	Time	Scenario Event	Expected Actions
ALERT	1600	Drywell Radiation Level has increased to 100 R/hr	 Alert should be declared Offsite notification Internal notification Technical Support Center activated Operations Support Center activated Offsite emergency teams placed on standby State and County EOCs partially activated
ALERT	1615	RHR pump B flow decreases to 500 gpm	 Personnel dispatched to investigate cause of reduced flow
ALERT	1630	Control room is notified that significant airborne activity levels are detected in the reactor enclosure	• Local evacuation of reactor enclosure ordered
ALERT	1650	Contact is lost with personnel investigating RHR pump B	 Search and Rescue/First Aid Group dispatched to find missing person.
ALERT	1700	Reactor coolant sample indicates activity of more than 300μCi/gm of I-131 equivalent	 The Search and Rescue/First Aid Group finds the person and escorts the individual out of the affected area. The individual is not injured or contaminated.
ALERT	1715	Low pressure alarm from CO_2 storage tank of the Fire Protection System	 Personnel are sent to investigate CO₂ portion of fire protection system

SIGNIFICANT EVENTS E LINE (Cont)

Emergency Classification	Time	Scenario Event	Expected Actions
ALERT	1730	Alarm indicates that there is a fire in the RHR heat exchanger and pump room	Fire Fighting Group responds to fire and extinguishes it
SITE EMERGENCY	1730	Drywell radiation level has increased to 1000 R/hr	 Site Emergency should be declared Notification of offsite
			agencies Emergency Operations Facility activated Headquarters Emergency Support Center activated News Media Center activated Field survey groups deployed State and Local EOCs fully activated
SITE EMERGENCY	1800	North Stack effluent monitors detect radioactive concentrations of 0.01 µCi/cc	Dose assessment team should conclude that no protective action required
SITE EMERGENCY	1845	Status lights on control board indicate 1 of 2 isolation valves on containment purge line has backed off fully-closed position	• Plant personnel will attempt to get the valve closed
SITE EMERGENCY	1900	Local radiation levels near the containment purge line are increasing	

SIGNIFICANT EVENTS TE LINE (Cont)

Emergency			
Classification	Time	Scenario Event	Expected Actions
SITE EMERGENCY	1900	High radioactivity in cooling tower blowdown reported	 Dose assessment per EP-318 and EP-319 Continue sampling of blowdown Perform notification in accordance with EP-312
SITE EMERGENCY	1915	Status lights indicate that 2nd isolation valve on containment purge line is unseated	 Personnel checking isolation valves estimate 10 hours to repair
GENERAL EMERGENCY	1930	Drywell radiation level reaches 10,000 R/hr North stack effluent radiation monitor indicates 10 µCi/cc	 General Emergency should be declared Offsite notification of agencies Dose projections should continue Field surveys continue and confirm that site boundary doses are 200 mrem/hr whole body and 4,000 mrem/hr thyroid
GENERAL EMERGENCY	1945	Radioactive releases continue	 PECo recommends evacuation of nearby residents
GENERAL EMERGENCY	2000	Radioactive releases continue	 State recommends protective action of evacuation
GENERAL EMERGENCY	2015	Radioactive releases continue	 Public alert sirens are sounded
GENERAL EMERGENCY	2040	Core Spray pump A trips	 Personnel are sent to investigate Core Spray pump manually tripped Core Spray pumps B and D started



Emergency Classification

Time

2230

GENERAL EMERGENCY 2145

Scenario Event

Containment purge line isolation valves are repaired

Radioactive releases ended

Exercise Terminated

Expected Actions

 Field survey groups to confirm that releases have stopped

 Deescalation to Site Emergency and later to Alert is considered

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Reactor Coolant Activity Concentrations (µCi/gm)

	Kr-85	Kr-85M	Kr-87	Kr-88	Xe-133	Xe-135	Total Noble Gas	I-131	I-133	Total Iodine	Gross Beta	
1100-1330	*4.N2	8.N1	6.N4	2.	4.	4. *	*1.P2	5.N3	1.N1	8.N1	1.6P2	
1330-1400	1.5	3.P1	2.P1	6.P1	2.P2	1.2P2	8.P2	2.N2	3.N1	1.5	1.P3	
1400-1430	3.	6.P1	3.P1	1.2P2	2.5P2	2.P2	2.P3	6.N2	5.N1	2.	2.P3	
1430-1500	1.P1	2.P2	1.2P2	5.P2	1.P3	1.P3	6.P3	2.N1	1.0	4.	6.P3	
1500-1530	2.P1	4.P2	2.P2	9.P2	2.P3	2.P3	1.P4	8.N1	3.5	10.	8.P3	
1530-1600	2.8P1	6.P2	3.P2	1.4P3	3.P3	3.P3	1.4P4	2.2	9.	3.P1	1.P4	
1600-1630	4.P1	8.P2	4.P2	1.8P3	4.P3	4.P3	1.8P4	2.5P1	1.P2	2.5P2	1.P4	
1630-1700	4.P1	8.P2	4.P2	1.9P3	4.P3	4.P3	1.8P4	9.P1	3.5P2	8.P2	1.P4	
1700-1715	4.P1	8.P2	4.P2	2.P3	4.P3	4.P3	1.8P4	2.5P2	1.P3	2.P3	9.P3	
1715-1730	4.P1	9.P2	3.7P2	2.P3	4.P3	4.P3	1.6P4	6.P2	2.5P3	5.P3	8.P3	
1730-1745	4.P1	9.P2	3.P2	2.P3	4.P3	4.P3	1.6P4	8.P2	3.P3	6.P3	8.P3	
1745-1800	4.2P1	9.P2	2.7P2	2.P3	4.2P3	4.P3	1.5P4	9.P2	3.5P3	7.P3	7.P3	
1800-1830	4.5P1	9.P2	2.5P2	2.P3	4.2P3	4.P3	1.5P4	9.P2	3.5P3	7.P3	7.P3	
1830-1900	4.8P1	1.P3	2.P2	2.P3	4.5P3	4.P3	1.5P4	9.P2	3.6P3	7.P3	6.P3	
1900-1915	5.P1	1.P3	2.P2	1.8P3	4.5P3	4.P3	1.4P4	9.P2	3.6P3	6.P3	6.P3	
1915-1930	5.P1	1.P3	2.P2	1.8P3	4.5P3	4.2P3	1.4P4	9.P2	3.5P3	6.P3	5.P3	
1930-2000	5.P1	1.P3	1.8P2	1.7P3	4.5P3	4.2P3	1.4P4	8.P2	3.P3	5.P3	5.P3	
2000-2030	5.P1	1.P3	1.7P2	1.5P3	5.P3	4.2P3	1.2P4	8.P2	3.P3	5.P3	5.P3	
2030-2045	5.P1	9.P2	1.6P2	1.5P3	5.P3	4.2P3	1.2P4	8.P2	3.P3	5.P3	5.P3	
2045-2100	5.P1	9.P2	1.5P2	1.3P3	5.P3	4.5P3	1.2P4	8.P2	3.P3	5.P3	5.P3	
2100-2145	5.P1	8.P2	1.3P2	1.2P3	5.P3	4.5P3	1.2P4	7.P2	3.P3	5.P3	4.P3	
*4 N2 = 4	× 10-2											

 $*4.N2 = 4 \times 10^{-2}$

 $**1.P2 = 1 \times 10^2$

NRC/FEMA OBSERVED EMERGENCY RESPONSE FXERCISE LIMERICK GENERATING STATION

Drywell and Suppression Chambers Air Concentrations (µCi/gm)

	Kr-85	Kr-85M	Kr-87	Kr-88	Xe-133	Xe-135	Total Noble Gas	I-131	I-133	Total Iodine	Gross Beta
1100-1330	*1.N6	2.N5	2.N5	5.N5	1.N4	1.N4	2.N3	2.N8	3.N9	2.N7	4.N3
1330-1400	2.N4	4.N3	3.N6	1.N2	2.N2	2.N2	5.N1	6.N8	1.5N7	8.N7	8.N1
1400-1430	8.N4	1.5N2	1.N2	3.N2	1.N1	6.N2	4.N1	1.5N7	6.N7	3.N6	5.N1
1430-1500	1.5N3	3.N2	1.5N2	6.N2	1.5N1	1.2N1	1.	5.N7	2.N6	7.N6	1.
1500-1530	5.N3	1.N1	6.N2	2.5N1	5.N1	5.N1	3.	5.N7	2.N6	6.N6	3.
1530-1600	1.N2	2.N1	1.N1	4.5N1	1.	1.	5.	3.N6	1.N5	3.N5	4.
1600-1630	1.4N2	3.N1	1.5N1	7.N1	3.	1.5	7.	7.N6	3.N5	8.N5	5.
1630-1700	4.N2	8.N1	4.N1	2.	8.	4.	2.P1	1.N4	4.N4	8.N4	**1.P1
1700-1715	1.N1	2.	1.	5.	2.P1	6.	3.P1	3.N4	1.2N3	2.N3	2.P1
1715-1730	1.N1	2.	1.	5.	2.P1	1.P1	5.P1	7.N3	3.N2	6.N2	2.P1
1730-1745	2.N1	4.	1.6	1.P1	3.P1	2.P1	8.P1	1.5N2	6.N2	1.2N1	4.P1
745-1800	2.N1	4.	1.5	1.P1	2.P1	2.P1	7.P1	2.5N2	1.N1	2.N1	3.P1
1800-1830	2.1N1	4.2	4.	1.P1	2.P1	2.P1	2.P2	6.N2	2.5N1	5.N1	1.5P2
1830-1900	5.N1	4.5	4.	2.P1	4.P1	4.P1	2.P2	8.N2	3.N1	6.N1	2.P2
1900-1915	5.N1	1.P1	6.	2.5P1	5.P1	5.P1	3.P2	4.N1	1.6	2.5	3.P2
1915-1930	1.	2.P1	1.P1	4.5P1	1.P2	1.P2	5.P2	1.	4.	7.	4.P2
1930-2000	2.5.	5.P1	1.P1	9.P1	1.8P2	1.8P2	5.P2	4.	1.6P1	3.P1	2.P2
2000-2030	2.5	5.P1	1.P1	8.P1	2.P2	2.P2	6.P2	1.P1	4.P1	7.P1	2.P2
2030-2045	2.5	5.P1	1.P1	8.P1	2.5P2	2.2P2	6.P2	9.	3.5P1	6.P1	2.P2
2045-2100	2.5	4.5P1	8.	7.P1	2.5P2	2.2P2	6.P2	9.	3.5P1	6.P1	2.P2
2100-2145	2.5	4.5P1	6.	6.P1	2.5P2	2.2P2	6.P2	9.	3.5P1	6.P1	2.P2

 $*1.86 = 1 \times 10^{-6}$ $**1.P1 = 1 \times 10^{1}$

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENRATING STATION Suppression Pool Activity Concentrations (µCi/gm)

1100-1330 *5.N7 3.N8 7.N7 2.N5 1330-1400 2.N6 4.N6 2.N5 3.N5 1400-1430 1.5N5 5.N5 7.N5 7.N5 1430-1500 8.N5 3.N4 6.N4 6.N4 1500-1530 4.N4 1.6N3 3.N3 2.5N3 1530-1600 2.N3 8.N3 1.4N2 1.N2 1600-1630 6.N3 2.5N2 4.N2 3.N2 1630-1700 1.N1 4.N1 6.N1 3.N1
1400-1430 1.5N5 5.N5 7.N5 7.N5 1430-1500 8.N5 3.N4 6.N4 6.N4 1500-1530 4.N4 1.6N3 3.N3 2.5N3 1530-1600 2.N3 8.N3 1.4N2 1.N2 1600-1630 6.N3 2.5N2 4.N2 3.N2 1630-1700 1.N1 4.N1 6.N1 3.N1
1430-1500 8.N5 3.N4 6.N4 6.N4 1500-1530 4.N4 1.6N3 3.N3 2.5N3 1530-1600 2.N3 8.N3 1.4N2 1.N2 1600-1630 6.N3 2.5N2 4.N2 3.N2 1630-1700 1.N1 4.N1 6.N1 3.N1
1500-1530 4.N4 1.6N3 3.N3 2.5N3 1530-1600 2.N3 8.N3 1.4N2 1.N2 1600-1630 6.N3 2.5N2 4.N2 3.N2 1630-1700 1.N1 4.N1 6.N1 3.N1
1530-1600 2.N3 8.N3 1.4N2 1.N2 1600-1630 6.N3 2.5N2 4.N2 3.N2 1630-1700 1.N1 4.N1 6.N1 3.N1
1600-1630 6.N3 2.5N2 4.N2 3.N2 1630-1700 1.N1 4.N1 6.N1 3.N1
1630-1700 1.N1 4.N1 6.N1 3.N1
[2] (1) [1] [1] [1] [1] [1] [1] [1] [1] [1] [1]
1700-1715 5.N1 2. 3. 2.
1715-1730 1.5 6. 1.P1 8.
1730-1745 5. 1.8P1 3.P1 2.P1
1745-1800 **1.3P1 5.P1 8.P1 6.P1
1800-1830 1.7P1 7.P1 1.P2 7.P1
1830-1900 2.0P1 8.P1 1.2P2 9.P1
1900-1915 2.3P1 1.P2 1.4P2 1.P2
1915-1930 2.5P1 1.P2 1.5P2 1.P2
1930-2000 2.7P1 1.1P2 1.6P2 1.1P2
2000-2030 2.9P1 1.1P2 1.6P2 1.2P2
2030-2045 3.1P1 1.2P2 1.7P2 1.2P2
2045-2100 3.3P1 1.3P2 1.8P2 1.3P2
2100-2145 3.5P1 1.4P2 1.9P2 1.3P2

 $*5.N7 = 5 \times 10^{-7}$ $**1.3P1 = 1.3 \times 10^{1}$

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Reactor Enclosure Atmosphere PASS Sample Concentrations (µCi/cc)

	Kr-85	Kr-85R	Kr-87	Kr-88	Xe-133	Xe-135	Total Noble Gas	I-131	I-133	Total Iodine	Gross Beta
1100-1315	*2.0N8	1.3N7	2.4N7	3.6N7	9.2BN7	1.8N7	2.0N6	**	**	**	4.0N6
1315-1800	1.7N8	3.6N7	1.0N7	7.9N7	1.5N6	1.5N6	4.3N6	1.8N10	7.2N10	9.0N10	6.N6
1800-1900	1.2N8	2.4N7	6.8N8	4.3N7	8.5N7	8.5N7	2.4N6	1.8N9	7.2N9	9.0N9	3.N6
1900-1915	5.0N9	9.8N8	2.8N8	1.8N7	3.5N7	3.5N7	1.0N6	2.0N9	8.0N9	1.0N8	1.0N6
1915-1945	7.0N10	1.4N8	3.9N9	2.5N8	4.9N8	4.9N8	1.4N7	2.0N9	8.0N9	1.0N8	1.047
1945-2145	4.0N10	8.4N9	2.4N9	1.5N8	3.0N8	3.0N8	8.5N8	2.0N9	8.0N9	6.0N8	7.N8

 $*2.088 = 2 \times 10^{-8}$

**less than detectable

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Post Accident Sampling System Readings (mR/hr)

			From To	$\frac{1100}{1330}$	$\frac{1330}{1400}$	$\frac{1400}{1430}$	- Company Constitution	$\frac{1500}{1530}$	$\frac{1530}{1600}$	$\frac{1600}{1630}$	$\frac{1630}{1700}$	$\frac{1700}{1715}$	$\frac{1715}{1730}$	$\frac{1730}{1745}$
System	Sample Size	Distance	Shield											
Drywell	15.ml	1 inch	none		0.3.	1.5	3.	13.	23.	50.	90.	150.	250.	400.
Atmosphere		1 ft	none	-		0.02	0.03	0.15	0.25	0.5	0.9	1.5	2.5	4.
		1 inch	2" lead		-	0.01	0.02	0.1	0.2	0.4	0.7	1.2	2.	3.
		1 ft	2" lead	-		-			0.01	0.01	0.02	0.03	0.06	0.1
Reactor	10.ml	1 inch	none	2.P3	1.6P4	4 4.P4	1.2P5	2.P5	3.P5	3.6P5	3.7P5	4.P5	4.2P5	4.4P5
Coolant		1 ft	none	20.	160.	400.	1.2P3		3.P3	3.6P3	3.7P3		4.2P3	
		1 ft	2" lead	0.4	3.	8.	25.	40.	60.	70.	75.	80.	85.	90.
		1 ft	4" lead	0.01	0.06	0.16	0.5	0.8	1.2	1.4	1.5	1.6	1.7	1.8
Gas Stripped	15 ml	1 inch	none	1.5P3	1.2P	3.P4	9.P4	1.5P5	2.2P5	2.7P5	3.P5	3.P5	3.P5	3.P5
From Reactor		1 ft	none	15.	120.	300.	900.	1.5P3	2.2P3	2.7P3	3.P3	3.P3	3.P3	3.P3
Coolant		1 ft	2" lead	0.3	2.5	6.0	18.	30.	44.	55.	60.	60.	60.	60.
		1 ft	4" lead	-	0.05	0.1	0.4	0.6	1.	1.1	1.2	1.2	1.2	1.2
Suppression	10 ml	1 inch	none					0.15	0.7	2.0	30.	90.	500.	1.5P3
Pool Liquid		1 ft	none	-	-		-	-	0.01	0.02	0.3	0.9	5.	15.
		1 inch	2" lead						3	0.01	0.2	0.7	4.	12.
Ambient Radia	tion Level			0.2	0.2	0.7	2.	3.	3.	5.	5:	8.	10.	15.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Post Accident Sampling System Readings (mR/hr)

			From To	$\frac{1745}{1800}$	$\frac{1800}{1830}$	$\frac{1830}{1900}$	$\frac{1900}{1915}$	$\frac{1915}{1930}$	$\frac{1930}{2000}$	2000 2030	2030 2045	$\frac{2045}{2100}$	2100 2145
System	Sample Size	Distance	Shield										
Drywell Atmosphere	15.ml	1 inch 1 ft 1 inch 1 ft	none none 2" lead 2" lead	600. 6. 4. 0.15	800. 8. 6. 0.2	1.5P3 10. 4. 0.3	1.P3 15. 13. 0.4	2.5P3 25. 20. 0.7	4.5P3 45. 35. 1.2	4.P3 40. 35. 1.1	4.P3 40. 35. 1.1	3.5P3 35. 30. 1.0	3.P3 30. 25. 0.8
Reactor Coolant	10.ml	1 inch 1 ft 1 ft 1 ft	none none 2" lead 4" lead	4.4P5 4.4P3 90. 1.8		4.4P5 4.4P3 90. 1.8		4.P5 4.P3 80. 1.6	3.8P5 3.8P3 80. 1.6	3.4P5 3.4P3 70. 1.4	3.4P5 3.4P3 70. 1.4	3.4P5 3.4P3 70. 1.4	3.4P5 3.4P3 70. 1.4
Gas Stripped From Reactor Coolant	15 ml	1 inch 1 ft 1 ft 1 ft	none none 2" lead 4" lead	3.P5 3.P3 60. 1.2	3.P5 3.P3 60. 1.2	3.P5 3.P3 60.	2.7P5 2.7P3 55. 1.1	2.7P5 2.7P3 55. 1.1	2.5P5 2.5P3 50. 1.0	2.3P5 2.3P3 45. 1.0	2.3P5 2.3P3 45. 0.9	2.0P5 2.0P3 40. 0.8	1.8P5 1.8P3 40. 0.8
Suppression Pool Liquid	10 m1	1 inch 1 ft 1 inch	none none 2" lead	4.P3 40. 30.	5.P3 50. 40.	6.P3 60. 50.	7.P3 70. 55.	7.5P3 75. 60.	8.P3 80. 65.	8.P3 80. 65.	8.5P3 85. 70.	8.5P3 85. 70.	8.5P3 85. 70.
Ambient Radia	tion Level			15.	20.	20.	20.	20.	25.	25.	25.	25.	25.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION North Vent Release Data (Source Term)

Time Interval	1315- 1800	1800- 1900	1900- 1915	1915- 1945	1945- 2145
North Vent Stack Flow(cfm)	3000.	3000.	3000.	3000.	3000.
Stack Concentrations (µCi/CC) of release					
Kr-85	2.0N8	*3.N5	1.N4	2.N2	6.N2
-85M	4.2N7	7.N4	2.N3	4.N1	1.2N1
-87	1.2N7	2.N4	6.N4	9.N2	2.N1
-88	9.0N7	1.5N3	4.N3	7.N1	2.
Xe-133	1.8N6	3.N3	1.N2	2.	6.
-135	1.8N6	3.N3	9.N3	1.8	5.5
I-131	2.0N11	5.N7	5.N5	7.N3	3.26N2
-133	8.0N11	2.N6	2.N4	3.N2	1.3N1
North Vent Stack Release Rate (µ	Ci/sec)				
Kr-85	2.8N2	43.	**1.4P2	3.P4	9.P4
-85M	6.N1	1.P3	3.P3	6.P5	1.8P6
-87	1.7N1	3.P2	8.P2	1.3P5	3.P5
-88	1.3	2.P3	6.P3	1.P6	2.8P6
Xe-133	2.5	4.3P3	1.4P4	3.P6	8.5P6
-135	2.5	4.3P3	1.3P4	2.6P6	7.P6
I-131	2.8N5	0.7	70.	1.P4	4.7P4
-133	1.N4	3.	3.0P2	4.3P4	2.0P5
Exposure Rate from 100 ml					
3 Sample at 1." (mR/hr)		3.	10.	1.9P3	4.P3
*3.N5 = 3 x 10 * **1.4P2 = 1.4 x 10 ²					

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION North Vent Stack Effluent and Sample Data

	1315- 1800	1800- 1900	1900- 1915	1915- 1945	1945- 2145
Gaseous Effluent Monitor Readings (µCi/CC)					
Low Range 2LE-076 Mid Range 1ME-076 High Range 3HE-076 Composite Channel (µCi/sec) 4TE-076	5.0N6 - - 7.0	*8.5N3 9.N3 - 1.2P4	2.6N2 3.N2 **4.P4	Off-Scale 5. 5. 7.P6	Off-Scale 15. 15. 2.P7
Increase in Readings from Iodine Collection Cartridge					
Normal Range Detector 2/5 IE-075 (µCi/cc)	1.0N10	2.5N6	Off-Scale	Off-Scale	Off-Scale
Dose Rate from Unshielded Cartridge (mR/hr/minute)			1.	120.	240.
Dose Rate from 2" Lead Shielded Cartridge (mR/hr/minute)				2.4	5.
Dose Rate from Unshielded Stack Sample (mR/hr)					
15 ml sample		0.4	1.6	300.	600.
100 ml sample	-	3.	10.	1.9P3	4.P3
750 ml sample		22.	80.	1.5P4	3.P4
Dose Rate from 2" Lead Shielded Stack Sample (mR/hr)					
15 ml sample		-	.03	6.	10.
100 ml sample		0.05	0.2	40.	80.
750 ml sample		0.4	1.6	300.	600.
$*8.5N3 = 8.5 \times 10^{-3}$ $**4.P4 = 4 \times 10^{4}$					

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Meteorological Parameters

	1100- 1400	1400- 1600	1630 - 1800	1800- 1945	1945- 2400
Wind Speed - mph					
Ground Elevated	5.2 7.1	4.8 6.3	4.1 5.1	3.0 3.1	4.0
Wind Direction - deg azm					
Ground Elevated					
Sigma Theta - deg azm	137 144	145 152	151 157	158 158	158 158
Ground Elevated	6.7 8.0	5.9 6.9	11.0 13.6	10.6 12.9	10.2 12.4
Delta T - deg F					
Ground Elevated	-1.3 -1.1	-1.7 -1.3	-2.3 -2.3	-2.1 -2.1	-2.1 -2.1
Temperature - deg F					
Elevated	71	75	82	79	16

NRC/FEMA Observed Emergency Response Exercise Limerick Generating Station Whole Body Bose Rate Along Centerline of Plume (mR/hr)

Distance (Miles)	0.5	1	2	3	4	5	6	7	8	9	10
Release 1 Arrival Time Reading	1810 0.14	1820 0.05	1840 0.02	1900 0.01	1920	1940	1956	2011	2026	2041	2052
Release 2 Arrival Time Reading	1910 0.38	1920 0.13	1940 0.05	1956 0.02	2011 0.01	2026	2041	2056	2111	2126	2141
Release 3 Arrival Time Reading	1925 68.	1935 24.	1952 6.	2007 3.6	2022 2.2	2037 1.5	2052 1.0	2107 0.8	2122 0.6	2137 0.5	2152 0.4
Release 4 Arrival Time Reading	1952 150.	2000 55.	2015 19.	2030 8.	2045 5.0	2100 3.5	2115 2.6	2130 2.0	2145 1.6	2200 1.2	2215 1.0
End of Releases	2152	2200	2215	2230	2245	2300	2315	2330	2345	2400	2415

Note: Use these values for areas shaded red;

0.5 of these values for areas shadded blue;

^{0.3} of these values for areas shaded or nge;

^{0.1} of these values for areas shaded yellow;

^{0.01} of these values for areas shaded green

NRC/FEMA Observed Emergency Response Exercise Limerick Generating Station SAM-II Readings Along Centerline of Plume (cpm above background)

Distance (Miles)	0.5	1.	2.	3.	4.	5.	6.	7.	8.	9.	10.
Release 1 Arrival Time Reading	1810	1820	1840	1900	1920	1940	1956	2011	2026	2041	2056
Release 2 Arrival Time Reading	1910 140.	1920 50.	1940 19.	1956 9.	2011	2026	2041	2056	2111	2126	2141
Release 3 Arrival Time Reading	1925 2.P4	1935 *8.5P3	1952 2.8P3	2007 1.1P3	2022 710.	2037 510.	2052 390.	2107 310.	2122 250.	$\frac{2137}{200}$.	2152 150.
Release 4 Arrival Time Reading	1952 8.P4	2030 3.3P4	2015 1.P4	2030 4.P3	2045 2.5P3	2100 1.8P3	2115 1.3P3	2130 1.1P3	2145 850.	2200 700.	$\frac{2215}{600}$.
End of Releases	2152	2200	2215	2230	2245	2300	2315	2330	2345	2400	2415

Note: Use these values for areas shaded red;

^{0.5} of these values for areas shadded blue;

^{0.3} of these values for areas shaded orange;

^{0.1} of these values for areas shaded yellow;

^{0.01} of these values for areas shaded green

 $^{*8.5}P3 = 8.5x10^3$

NRC/FEMA Observed Emergency Response Sxorcise Limerick Generating Station I-131 Concentestion Centerline of Plume (µCi/cc)

Distance (Miles)	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	0.8	5.0	10.
Release 1 Arrival Time Reading	1810	1820	1840	1900	1920	1943	1956	2011	2026	2041	2055
Release 2 Arrival Time* Reading	1910 1.4N9	1920 5.N/G	1940 1.7N/O	1956 7.N11	2011	2026	2041	2056	2111	2126	2161
Release 3 Arrival Time Reading	1925 2.3N7	1935 8.N8	1952 2.8NS	2007 1.3NE	2022 7.N9	2037 5.1N9	2052 4.N9	2107 3.N9	2122 2.5N9	2137 2.89	2152 1.5N9
Release 4 Arrival Time Reading	1952 7.N7	2000 2.5N7	2015 9.N8	2030 3.9N8	2045 2.5N8	2100 1.8NS	2115 1.3N8	2130 1.N8	2145 3 N9	2200 7.89	2213 6.N9
End of Releases	2152	2200	2215	2230	2245	2300	2315	2330	2345	2400	2415

 $^{*1.4}N9 = 1.4x10^{-9}$

NRC/FEMA Observed Emergency Response Exercise Limerick Generating Station Inhalation Thyroid Dose Rate Along Centerline of Plume

Distance (Miles)	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.
Release 1 Arrival Time Reading	1810	1820	1840	1900	1920	1940	1956	2011	2026	2041	2056
Release 2 Arrival Time* Reading	$\frac{1910}{6.2}$	$\frac{1920}{2.2}$	1940 0.8	$\frac{1956}{0.3}$	2011	2026	2041	2056	2111	2126	2141
Release 3 Arrival Time Reading	$\frac{1925}{890}$.	1935 320.	1952 110.	2007 50.	$\frac{2022}{30}$.	2037 22.	2052 16.	2107 12.	$\frac{2122}{10}$.	2137 8.2	$\frac{2152}{6.9}$
Release 4 Arrival Time Reading	$\frac{1952}{3000}$.	2000 1060.	2015 380.	$\frac{2030}{160}$.	$\frac{2045}{100}$.	2100 70.	2115 55.	2130 40.	$\frac{2145}{33}$.	2200 27.	2215 23.
End of Releases	2152	2200	2215	2230	2245	2300	2315	2330	2345	2400	2415

NRC/FEMA Observed Emergency Response Exercise
Limerick Generating Station
Whole Body Does Rate at Various Field Monitoring Location (mR/hr)
with Plume Front Arrival Times

Field Monitoring Location	NNW-0	<u>NW-1</u>	NNW-1	<u>N-1</u>	<u>N-2</u>	NW-2.1	NNW-2.1	NNW-2.2	NW-2.2
Arrival Time WB Dose Rate	1816 0.06	1826	$\frac{1832}{0.03}$	1830	1840	1840	1842	1852	1852
Arrival Time WB Dose Rate	1916 0.14	1926	1932 0.09	1930	1940	1940	$\frac{1942}{0.02}$	$\frac{1950}{0.02}$	1950
Arrival Time WB Dose Rate	1931 27.	$\frac{1941}{0.7}$	1946 16.	1945	$\frac{1953}{0.04}$	1953 0.06	$\frac{1954}{2.7}$	<u>2002</u> 4.0	2002 0.4
Arrival Time WB Dose Rate	1957 60.	$\frac{2005}{1.5}$	2009 37.	2007	2015 0.09	2015 0.15	2017 6.1	$\frac{2024}{9.1}$	2024 0.91
Field Monitoring Location	N-3.1	NNW-3	<u>NW-3</u>	NNW-4	<u>N-4</u>	<u>N-5.1</u>	NNW-5.1	NNW-5.2	
Arrival Time WB Dose Rate	1900	1910 0.02	1914	1932	1924	1942	1944	1950	
Arrival Time WB Dose Rate	1956	2004 0.02	2007	2020	2014	2028	2029 0.01	2035	
Arrival Time WB Dose Rate	2008	$\frac{2015}{2.7}$	2018 0.01	2032 1.2	2026	2039	$\frac{2041}{1.4}$	$\frac{2047}{0.6}$	
Arrival Time WB Dose Rate	2030	2038 6.1	$\frac{2041}{0.03}$	2054 2.7	2048	2102	$\frac{2104}{3.0}$	2109 1.5	

Field Monitoring Location	NNW-6.1	NNW-6.2	N-6.2	N-7.1	NNW-7.2	NNW-7.1	NNW-8.3
Arrival Time	2002	2004	2001	2016	2016	2019	2031
WB Dose Rate							
Arrival Time	2047	2049	2046	2101	2101	2104	2116
WB Dose Rate							
Arrival Time	2059	2100	2058	2112	2112 0.85	2115	2127
WB Dose Rate	0.09	0.92	0.09		0.85	0.27	0.54
Arrival Time	2121	2122	2120	2135	2135	2138	$\frac{2150}{1.2}$
WB Dose Rate	0.2	2.1	0.2		2.0	0.6	1.2

NRC/FEMA Observed Emergency Response Exercise
Limerick Generating Station
SAM-II Readings at Various Field Monitoring Locations (cpm above background) with Plume Front Arrival Times

Field Monitoring Location	NNW-0	<u>NW-1</u>	NNW-1	<u>N-1</u>	<u>N-2</u>	NW-2.1	NNW-2.1	NNW-2.2
Arrival Time SAM-II	1816	1826	1832	1830	1840	1840	1842	1852
Arrival Time SAM-II	1916 65.	1926	$\frac{1932}{29}$.	1930	1940	1940	1942 6.	1950 9.
Arrival Time SAM-II	1931 9.1P3	$\frac{1941}{260}$.	1946 5.5P3	1945	$\frac{1953}{13}$.	$\frac{1953}{26}$.	1954 910.	2002 1.3P3
Arrival Time SAM-II	1957 3.0P4	2005 730.	2009 1.8P4	2007	2015 47.	2015 83.	2017 3.1P3	2024 4.7P3
Field Monitoring Location	NW-2.2	<u>N-3.1</u>	NNW-3	NW-3	NNW-4	<u>N-4</u>	N-5.1	NNW-5.1
Arrival Time SAM-II	1852	1900	1910	1914	1932	1924	1942	1944
Arrival Time SAM-II	1950	1956	<u>2004</u>	2007	2020	2014	2028	2029
Arrival Time SAM-II	$\frac{2002}{140}$.	2008	2015 910.	2018 5.	$\frac{2032}{420}$.	2026	2039	2041 440.
Arrival Time SAN-II	$\frac{2024}{470}$.	2030	2038 3.1P3	$\frac{2041}{16}$.	2054 1.4P3	2048	2102	2104 1.5P3

Field Monitoring Location	NNW-5.2	NNW-6.1	NNW-6.2	N-6.2	<u>N-7.1</u>	NNW-7.2	NNW-7.1	NNW-8.3
Arrival Time SAM-II	1950	2002	2004	2001	2016	2016	2019	2031
Arrival Time SAM-II	2035	2047	2049	2046	2101	2101	2104	2116
Arrival Time SAM-II	$\frac{2047}{250}$.	$\frac{2059}{34}$.	$\frac{2100}{340}$.	2058 34.	2112	$\frac{2112}{310}$.	2115 90.	$\frac{2127}{180}$.
Arrival Time SAM-II	2109 730.	$\frac{2121}{100}$.	2122 1.0P3	$\frac{2120}{100}$.	$\frac{2135}{13}$.	$\frac{2135}{940}$.	$\frac{2138}{310}$.	$\frac{2150}{600}$.

NRC/FEMA Observed Emergency Response Exercise
Limerick Generating Station

I-131 Concentration at Various Field Monitoring Locations
(μCi/cc) with Plume Front Arrival Times

Field Monitoring Location	NNW-0	<u>NW-1</u>	NNW-1	<u>N-1</u>	<u>N-2</u>	NW-2.1	NNW-2.1	NNW-2.2
Arrival Time I-131 Conc.	1816	1826	1832	1830	1840	1840	1842	1852
Arrival Time I-131 Conc.	1916 5.6N10	1926	1932 3.4N10	1930	1940	1940	1942 5.4N11	1950 8.1N11
Arrival Time I-131 Conc.	1931 7.9N8	1941 2.3N9	1946 4.7N8	1945 4.5N12	1953 1.1N10	1953 1.9N10	1954 7.9N9	2002 1.1N8
Arrival Time I-131 Conc.	1957 2.0N7	2005 6.3N9	2009 1.0N7	2007 1.3N11	2015 4.1N10	2015 7.2N10	2017 2.7N8	2024 4.1N8
Field Monitoring Location	NW-2.2	N-3.1	NNW-3	<u>NW-3</u>	NNW-4	<u>N-4</u>	<u>N-5.1</u>	NNW-5.1
Arrival Time I-131 Conc.	1852	1900	1910	1914	1932	1924	1942	1944
Arrival Time I-131 Conc.	1950 9.0N12	1956	2004 5.4N11	2007	2020	2014	2028	2029 2.7N11
Arrival Time I-131 Conc.	2002 1.2N9	2008 2.2N12	2015 7.9N9	2018 4.1N11	2032 3.6N9	2026 2.2N12	2039	2041 3.8N9
Arrival Time I-131 Conc.	2024 4.1N9	2030 1.3N11	2038 2.7N8	2041 1.4N10	2054 1.2N8	2048 6.8N12	2102 2.2N12	2104 1.3N8

Field Monitoring Location	NNW-5.2	NNW-6.1	NNW-6.2	<u>N-62</u>	<u>N-7.1</u>	NNW-7.2	NNW-7.1	NNW-8.3
Arrival Time I-131 Conc.	1950	2002	2004	2001	2016	2016	2019	2031
Arrival Time I-131 Conc.	2035 1.6N11	2047	2049 1.6N11	2046	2101	2101 1.6N11	2104 9.0N12	2116 9.0N12
Arrival Time I-131 Conc.	2047 2.2N9	2059 2.9N10	2100 2.9N9	2058 2.9N10	2112 2.3N11	2112 2.7N9	2115 7.9N10	2127 1.6N9
Arrival Time I-131 Conc.	2109 6.3N9	2121 8.8N10	2122 8.8N9	2120 8.8N10	2135 1.1N10	2135 8.1N9	2138 2.7N9	2150 5.2N9

NRC/FEMA Observed Emergency Response Exercise
Limerick Generating Station
Inhalation Thyroid Dose at Various Field Monitoring Locations (mR/hr)
with Plume Front Arrival Times

Field Monitoring Location	NNW-0	<u>NW-1</u>	NNW-1	<u>N-1</u>	<u>N-2</u>	NW-2.1	NNW-2.1	NNW-2.2
Arrival Time Thyroid Dose Rate	1816	1826	1832	1830	1840	1840	1842	1852
Arrival Time Thyroid Dose Rate	$\frac{1916}{2.5}$	1926	$\frac{1932}{1.5}$	1930	1940	1940	$\frac{1942}{0.24}$	1950 0.36
Arrival Time Thyroid Dose Rate	1931 350	1941 10	1946 210	1945 0.02	$\frac{1953}{0.50}$	1953 0.85	1954 35	2002 50
Arrival Time Thyroid Dose Rate	1957 1170	2005 28	2009 710	2007 0.06	2015 1.8	2015 3.2	2017 120	2024 180
Field Monitoring Location	NW-2.2	N-3.1	NNW-3	NW-3	NNW-4	<u>N-4</u>	<u>N-5.1</u>	NNW-5.1
Arrival Time Thyroid Dose Rate	1852	1900	1910	1914	1932	1924	1942	1944
Arrival Time Thyroid Dose Rate	1950 0.04	1956	2004 0.24	2007	2020	2014	2028	2029 0.12
Arrival Time Thyroid Dose Rate	2002 5.3	$\frac{2008}{0.01}$	2015 35	2018 0.18	2032 16	2026 0.01	2039	2041 17
Arrival Time Thyroid Dose Rate	2024 18.	2030 0.06	2038 120	2041 0.60	2054 53	2048 0.03	2102 0.01	2104 59

Field Monitoring Location	NNW-5.2	NNW-6.1	NNW-6.2	N-6.2	N-7.1	NNW-7.2	NNW-7.1	NNW-8.3
Arrival Time Thyroid Dose Rate	1950	2002	2004	2001	2016	2016	2019	2031
Arrival Time Thyroid Dose Rate	2035 0.07	2047	2049 0.07	2046	2101	$\frac{2101}{0.07}$	2104 0.04	2116 0.04
Arrival Time Thyroid Dose Rate	2047 9.6	2059 1.3	2100 13.	2058 1.3	2112 0.1	$\frac{2112}{12}$	2115 3.5	2127 7.1
Arrival Time Thyroid Dose Rate	2109 28.	2121 2.9	$\frac{2122}{39}$.	$\frac{2120}{3.9}$	$\frac{2135}{0.5}$	$\frac{2135}{36}$.	2138 12.	$\frac{2150}{23}$.

NRC/FEMA Observed Emergency Response Exercise Limerick Generating Station I-131 Concentration on Downwind Pastures (µCi/m²)

Distance (miles)	0.5	1.	2.	3.	4.	5.	6.	7.	8.	9.	10.
1815-1830	2.5N4										
1830-1845	5.0N4	1.N4									
1845-1900	7.5N4	2.N4	3.5N5								
1900-1915	4.N2	3.N4	6.7N5	1.4N5							
1915-1930	8.N2	1.6N2	1.0N4	2.9N5							
1930-1945	2.N1	6.7N2	5.6N3	4.2N5							
1945-2000	3.4N1	1.2N1	1.8N2	2.6N3							
2000-2015	4.8N1	1.6N1	3.5N2	1.0N2	1.4N3						
2015-2030	6.2N1	2.N1	5.3N2	1.8N2	6.4N3	1.0N3					
2030-2045	7.6N1	2.6N1	7.0N2	2.6N2	1.1N2	4.6N3	6.9N4				
2045-2100	9.0N1	3.N1	8.8N2	3.4N2	1.6N2	8.3N3	3.2N3	6.N4 .			
2100-2115	1.0	3.5N1	1.1N1	4.2N2	2.1N2	1.2N2	5.8N3	2.7N3	4.8N4		
2115-2130	1.2	4.N1	1.2N1	5.N2	2.6N2	1.6N2	8.3N3	4.8N3	2.1N3	4.N4	
2130-2145	1.3	4.5N1	1.4N1	5.8N2	3.N2	1.9N2	1.1N2	6.9N3	3.7N3	1.6N3	3.N4
2145-2400	1.5	4.9N1	1.6N1	6.6N2	3.5N2	2.2N2	1.3N2	9.0N3	5.3N3	3.0N3	1.2N3

NRC/FEMA Observed Emergency Response Exercise Limerick Generating Station I-131 Concentration in Milk Produced by Cows Grazing on Downwind Pastures (µCi/liter)

Distance (miles)	0.5	1.	2.	3.	4.	5.	6.	7.	8.	9.	10.
1815-1830	1.8N4										
1830-1845	3.6N4	6.3N5									
1845-1960	5.4N4	1.3N4	2.1N5								
1900-1915	2.9N2	1.9N4	4.2N5	8.8N6							
1915-1930	5.8N2	1.N2	6.3N 5	1.8N5							
1930-1945	1.4N1	4.2N2	3.5N3	2.6N5							
1945-2000	2.2N1	7.4N2	1.1N2	1.6N3							
2000-2015	3.1N1	1.0N1	2.2N2	6.5N3	8.8N4						
2015-2030	4.0N1	1.3N1	3.3N2	1.1N2	4.N3	6.4N4					
2030-2045	4.9N1	1.6N1	4.2N2	1.6N2	7.N3	2.9N3	4.3N4				
2045-2100	5.8N1	1.9N1	5.5N2	2.1N2	1.N2	5.2N3	2.0N3	3.8N4			
2100-2115	6.7N1	2.2N1	6.6N2	2.6N2	1.3N2	7.5N3	3.6N3	1.7N3	3.N4		
2115-2130	7.6N1	2.5N1	7.7N2	3.1N2	1.6N2	9.8N3	5.2N3	3.N3	1.3N3	2.5N4	
2130-2145	8.4N1	2.8N1	8.8N2	3.6N2	1.9N2	1.2N2	6.8N3	4.3N3	2.3N3	1.N3	1.9N4
2145-2400	9.3N1	3.1N1	9.9N2	4.1N2	2.2N2	1.4N2	8.4N3	5.6N3	3.3N3	1.9N3	7.5N4

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION ONSITE RADIOLOGICAL SURVEY DATA

1800-1900 1900-1915 1915-1945 1945-2145

Whole Body Dose Rate (mR/hr)				
Upwind of Line A-A	1.6	5.	850	*1.8P3
Between A-A and B-B	.6	1.9	340	700
Downwind of Line B-B	.14	.38	68	150
SAM-II Count Rate (cpm)				
Upwind of Line A-A	150	1.7P3	2.2P5	9.P5
Between A-A and B-B	60	680	9.4P4	3.8P5
Downwind of Line B-B	<.0	150	2.1P4	8.1P4
Iodine-131 Concentration (uCi/co)			
Upwind of Line A-A	**1.4N9	1.6N8	2.5N6	8.No
Between A-A and B-B	5.7N10	6.8N9	1.N6	3.3N6
Downwind of Line B-B		1.5N9	2 4N7	7.2N7
Inhalation Dose Rate (mrem/hr)				
Upwind of Line A-A	6.2	70	1P4	3.3P4
Between A-A and B-B	2.4	28	4.1P3	1.4P4
Downwind of Line B-B		6.2	890	3.P3
Contamination Survey (dpm/100 cm	12)			
Upwind of Line A-A	<10	<10	3.P3	1.2P4
Between A-A and B-B	<10	<10	1.3P3	5.P3
Downwind of Line B-B	<10	<10	250	1.5P3

 $*1.8P3 = 1.8 \times 10^{3}$ $**1.4N9 = 1.4 \times 10^{-9}$

Note:

Use these values for areas shaded red; one half of these values for areas shaded blue; one tenth of these values for areas shaded yellow; and one hundredth of these values for areas shaded green.

Note:

Survey meter readings of swipes in cpm are 1/10 of contamination values in $dpm/100 \ cm^2$.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 177 Ft

		$\frac{1100}{1400}$	1400 1500	1500 1600	$\frac{1600}{1630}$	1630 1715	1715 1730
Ambient Rad	iation Lev	el (mR/hr)					
Core Spray	1,	1.	1.	3.	10.	150.	1500.
	2 ^A	1.	1.	1.	4.	60.	600.
	34	1.	1.	1.	1.	15.	150.
	44	1.	1.	1.		6.	60.
	1A 2A 3A 4A 5A	1.	1.	1.	1.	3.	30.
RCIC	1.	50.	400.	700.	1.2P3	2.P3	600.
	¹ C ² C	12.	100.	175.	300.	500.	150.
Core Spray	1	1.	1.	3.	10.	150.	1.5P3
core spray	2D	1.	1.	1.	4.	40.	400.
	3D	1.	1.	1.	1.	15.	150.
	4D	1.	1.	1.	1.	4.	40.
	5D	1.	1.	1.	1.	1.5	15.
	1 _D 2 _D 3 _D 4 _D 5 _D	1.	1.0	1.	1.	0.1	8.
HPCI	1,,	50.	200.	200.	200.	200.	200.
	1 _H 2 _H	12.	50.	50.	50.	50.	50.
RHR	1,	10.	10.	30.	100.	300.	1500.
	2.	2.	2.	5.	20.	60.	300.
	3 ^L	0.5	0.5	1.	5.	15.	75.
	4 ^L	0.5	0.5	0.5	2.5	8.	40.
	5 t	0.5	0.5	0.5	1.	4.	20.
	1 L 2 L 3 L 4 L 5 L	0.5	0.5	0.5	0.5	1.5	8.
All Other A	reas	0.5	0.5	0.5	0.5	1.5	5.
ARM	-01	100.	800.	1.4P3	2.5P3	4.P3	1.3P3
	-02	80.	300.	320.	320.	320.	320.
	-03	1.	1.	1.	1.	2.	20.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 177 Ft (Cont)

		$\frac{1730}{1800}$	1800 1900	$\frac{1900}{1930}$	1930 2045	2045 2145
Ambient Radi	iation Level	(mR/hr)				
Core Spray	1A 2A 3A 4A 5A	2.4P3 600. 250.	1.5P4 6.P3 1.5P3 600.	8.P3 2.P3	1.P4 2.5P3 1.3P3	8.P3 2.P3
RCIC	1 _C 2 _C		600. 150.		600. 150.	600. 150.
Core Spray	1 _D 2 _D 3 _D 4 _D 5 _D 6 _D	1.6P3 600. 160.	4.P3	7.P3 2.4P3 700. 240.	250.	6.P3
HPCI	1 _H 2 _H	200. 50.		200. 50.	200. 50.	200. 50.
RHR	1 L 2 L 3 L 4 L 5 L 6 L		6.P3 1.2P3 300. 150. 80. 30.			6.P3 1.2P3 300. 150. 80. 30.
All Other A	reas	3.	2.	5.	15.	20.
ARM	-01	1.2P3	1.2P3	1.2P3	1.2P3	1.2P3
	-02	320.	320.	320.	320.	320.
	-03	80.	200.	300.	350.	280.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 177 Ft (Cont)

1100	1400	1500	1600	1630	1715
1400	1500	1600	1630	1715	1730

Contamination Survey (dpm/100 cm2)

-Inside-	<100.	<100.	<100.	500.	1.4P3	5.P3
'Inside'	200.	400.	700.	1.P3	1.5P3	4.P3
//////////////////////////////////////	100.	200.	300.	600.	4.P4	1.P5

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

Airborne Radioactivity Level

-Inside-	cpm/100 ft ³ cpm/6 ft ³ % I-131 % I-133	140. <20 15. 70.	240. <20 20. 80.	300. <20 20. 80.	400. 24 20. 80.	1.8P4 1.1P5 20. 80.	4.P4 2.4P3 20. 80.	1
'Inside'	cpm/100 ft ³ cpm/6 ft ³ % I-131 % I-133	600. 40. 5. 15.	1.P3 60. 10. 50.	1.2P3 72. 15. 85.	1.4P3 80. 20.	1.2P4 720. 20. 80.	1.8P4 1.1P3 20.	1
///////////Inside/	cpm/100 ft ³ cpm/6 ft ³ % I-131 % I-133	100. <20 15. 80.	140. <20 20. 80.	200. <20 20. 80.	300. <20 20. 80.	6.P4 4.P3 20.	1.4P5 8.P3 20.	J

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 177 Ft (Cont)

1730	1800	1900	1930	2045
1800	1900	1930	2045	2145

Contamination Survey (dpm/100 cm2)

	1.P4	3.P4	5.P4	7.P4	9.P4
'Inside'	9.P3	2.P4	5.P4	6.P4	8.P4
//////////////////////////////////////	2.P5	1.9P5	1.7P5	1.7P5	1.5P5

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm2.

	cpm/100 ft ³	3.P4	3.2P4	3.2P4	3.2P4	3.2P4
	cpm/6 ft ³	1.8P3	2.P3	2.P3	2.P3	2.P3
	% I-131	20.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.
'Inside'	cpm/100 ft ³	2.P4	1.P4	1.P4	8.P3	6.P3
	cpm/6 ft ³	1.2P3	600.	600.	400.	400.
	% I-131	15.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.
///////////Inside/	cpm/6 ft ³ cpm/6 ft ³ % I-131 % I-133	4.P4 2.4P3 20. 80.	1.8P4 1.2P3 20.	1.8P4 1.2P3 20.	1.4P4 8.P2 20.	1.P4 600. 15. 85.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 201 Ft

		1100 1400	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730
Ambient Rad	iation Level (
	,	2.	2.	6.	20.	60.	300.
	2L	1.	1.	2.	7.	20.	100.
	1 2 1 3 L	0.5	0.5	0.5	2.	6.	30.
	1 2 3 3 8	0.5	0.5	1.	2.	2.	5.
	25	0.5	0.5	0.5	1.	2.	5.
	3°S	0.5	0.5	0.5	1.	2.	5.
All Other A	reas	0.5	0.5	0.5	1.	2.	5.
RM	-06	0.5	8.	50.	80.	120.	160.
	-08	8.	8.	25.	80.	240.	1.2P3
	-09	8.	8.	25.	80.	240.	1.2P3
Contaminatio	on Survey (dpm	/100 cm ²))				
		200	222	202	400	500	2 02
-Inside-		300.	300.	300.	400.	500.	2.P3
'Inside'		100.	200.	500.	800.	1.3P3	5.P3
NOTE:	Survey meter	readings	s of swip	es in cpm	are 1/10	of	
irborne Rad	dioactivity Le	vel					
	cpm/100 ft3	80.	80.	180.	300.	1.4P3	1.6P3
-Inside-	cpm/ó ft ³	<20.	<20	<20	0	84.	100.
	% I-131	10.	20.	20.	15.	20.	20.
	% I-133	60.	80.	80.	75.	80.	80.
	cpm/100 ft ³	160.	200.	600.	800.	5000.	6.P3
1 Tanidal	16 Ex3	120	20	40	50	300	360

20.

20.

75.

<20

15.

70.

'Inside'

.

cpm/6 ft3

% I-131

% I-133

40.

20.

30.

300.

20.

80.

50.

15.

80.

360.

20.

80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 201 Ft (Cont)

Ambient Radiation Level (mR/hr)

Ambient Radia	ation Level (m	R/hr)				
	1 L 2 L 3 L		1.2P3 400. 120.	400.	1.2P3 400. 120.	1.2P3 400. 120.
	1 S 2 S S S S S	8. 5. 5.	16. 10. 10.	16.	100. 40. 20.	120. 50. 30.
All Other Are	eas	10.	10.	10.	15.	20.
ARM	-06	160.	160.	160.	200.	240.
	-08	5.P3	5.P3	5.P3	5.P3	5.P3
	-09	5.P3	5.P3	5.P3	5.P3	5.P3
Contamination	n Survey (dpm/	100 cm²)				

7/4-	/ no	6 na	7 00	1 0/	1 D/
-Inside-	4.P3	6.P3	7.P3	1.P4	1.P4
1 1 1 1 1 1					
'Inside'	9.P3	1.2P4	1.3P4	1.6P4	1.8P4
11111					

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm 2 .

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 201 Ft (Cont)

-Inside-	cpm/100 ft ³	3.P3	4.P3	6.P3	8.P3	6.P3
	cpm/6 ft ³	180	240.	400.	500.	400
	% I-131	20.	20.	20.	15.	20.
	% I-133 cpm/100 ft ³	80. 8.P3	80. 1.2P4	80. 1.6P4	80.	75.
'Inside'	cpm/6 ft ³	480.	700.	1.P3	800.	600.
	% I-131	20.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 217 Ft

		Reactor	Enclosure	e El. 217	Ft		
		$\frac{1100}{1400}$	1400 1500	1500 1600	1600 1630	1630 1715	$\frac{1715}{1730}$
Ambient Radi	lation Level (mR/hr)					
	A	0.5	0.5	3.	5.	8.	25.
	B ^S	0.5	0.5	1.	2.	5.	10.
	c ^S	0.5	0.5	0.5	1.	4.	5.
	DS	0.5	0.5	0.5	0.5	4.	3.
	ES	0.5	0.5	0.5	0.5	4.	3.
	AS BS CS DS ES FS	0.5	0.5	0.5	0.5	4.	3.
	1,	9.5	0.5	0.5	0.5	3.	3.
	¹ ₂ _D	0.5	0.5	0.5	0.5	3.	3.
All Other Ar	reas	0.5	0.5	0.5	0.5	3.	3.
ARM	-10	0.5	0.5	2.	8.	15.	20.
Contaminatio	on Survey (dpm	/100 cm ²)					
-Inside-		200.	200.	200.	300.	1.P3	4.P3
			400	100	600	1 202	/ P2
'Inside'		400.	400.	400.	600.	1.2P3	4.P3
NOTE:	Survey meter contamination	readings n values	s of swip	es in cpm 00 cm².	are 1/10	of	
Airborne Rac	dioactivity Le	vel					
	cpm/100 ft3	160.	340	600	1.P3	3.2P3	4.P3
-Inside-	cpc/6 ft3	<20	20.	40.	60.	200.	240.
	% I-131	15.	20.	20.	20.	20.	20.
	% 1-133	80.	80.	80.	75.	80.	80.
	cpm/100 ft#	100	180	400.	600.	1.6P3	2.P3
! Took do!	com/6 f+3	<20	<20	24.	40.	100.	120

<20

20.

80.

<20

15.

60.

24.

20.

80.

cpm/6 ft3

% I-131

% I-133

'Inside'

40.

20.

80.

100.

20.

80.

120

20.

80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 217 Ft (Cont)

	1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
Ambient Radiation Level	(mR/hr)				
As BS CS LS ES FS	60. 20. 10. 6. 3. 1.5	90. 45. 20. 8. 4. 2.	110. 50. 25. 8. 4.	130. 55. 32. 13. 7.	150. 60. 30. 15. 8.
¹ ₂ _η	6. 3.	10. 5.	20. 10.	60. 30.	60. 30.
All Other Areas	1.5	1.5	1.0	1.0	1.0
ARM -10	20.	20.	20.	20.	20.
Contamination Survey (dp	m/100 cm ²)				
Inside-	6.P3	7.P3	1.P4	1.2F′	1.2P4
'Inside'	6.5P3	7.524	1.1P4	1.2P4	1.3P4

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

-Inside-	 cpm/100 ft ³ cpm/6 ft ³ % I-131 % I-133	6.P3 400. 10. 70.	6.P3 409. 15. 80.	7.P3 500. 20. 80.	7.P3 500. 20. 80.	8.P3 500. 20. 80.
'Inside'	cpm/100 ft ³	2.6P3	3.P3	3.6P3	4.P3	4.P3
inside	% I-131	160.	180.	215.	240.	240
	% I-133	70.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 253 Ft

		$\frac{1100}{1400}$	$\frac{1400}{1500}$	$\frac{1500}{1600}$	$\frac{1600}{1630}$	$\frac{1630}{1715}$	$\frac{1715}{1730}$
Ambient Ra	diation Leve	1 (mR/hr)					
	¹ ₂ D	0.5 0.5	0.5	0.5 0.5	1.	4.	3. 3.
All Other	Areas	0.5	0.5	0.5	1.	4.	3.
ARM	-15	0.5	0.5	0.5	1.	4.	3.
	-16	0.5	0.5	0.5	1.	4.	3.
	-17	0.5	0.5	0.5	1.	4.	3.
	-18	0.5	0.8	4.	8.	10.	15.
Contaminat	ion Survey (dpm/100 cm ²)					
General		400.	500.	700.	900.	1.5P3	3.P3
NOTE: Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm ² .							
Airborne Ra	adioactivity	Level					

160.

<20

20.

80.

160.

<20

15.

80.

600.

40.

20.

80.

1.P3

60.

20.

80.

240.

<20

20.

80.

80.

<20

15.

80.

General cpm/100 ft3

cpm/6 ft3

% 1-131

% I-133

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure E1. 253 Ft (Cont)

		1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
Ambient Rac	diation Level	(mR/hr)				
	¹ ₂ _D	4. 3.	6. 2.	20. 8.	35. 12.	35. 12.
All Other	Areas	3.	2.	2.	2.	2.
ARM	-15	3.	2.	2.	2.	2.
	-16	3.	2.	2.	2.	2.
	-17	3.	2.	2.	2.	2.
	-18	20.	20.	20.	20.	20.
Contaminat	ion Survey (d	pm/100 cm ²)				
General		5.P3	6.P3	7.P3	9.P3	1.P4

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm 2 .

General	cpm/100 ft3	1.2P3	1.2P3	1.4P3	1.8P3	2.P3
	cpm/ 6 ft3	70.	70.	80.	110.	120.
	% I-131	20.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 283 Ft

		$\frac{1100}{1400}$	1400 1500	$\frac{1500}{1600}$	$\frac{1600}{1630}$	1630 1715	1715 1730	1
Ambient Radi	ation Level	(mR/hr)						
Injecti	on A	5.	5.	5.	10.	250.	2.P3	
Valve	BC	5.	5.	5.	5.	120.	1.P3	
Area	CC	3.	5.	5.	5.	60.	500.	
	BC CC DC	0.5	5.	5.	5.	30.	250.	
Recombi	ner Ap	1.	1.	1.	2.	4.	9.	
	P.	1.	1.	1.	1.	2.	5.	
	C _P	1.	1.	1.	1.	1.	2.	
	CP DP	1.	1.	1.	1.	1.	1.	
All Other Ar	eas	0.5	1.	1.	2.	3.	7.	
ARM	-21	0.5	1.	1.	2.	3.	7.	
	-22	0.5	1.	1.	2.	3.	7.	
	-23	0.5	1.	1.	2.	3.	7.	
	-24	1.	1.	1.	2.	4.	9.	
Contaminatio	n Survey (dp	m/100 cm ²	500.	500.	700.	800.	2.P3	
'Inside'		600.	800.	1.P3	1.7P3	1.9P3	4.P3	
NOTE:	Survey meter				are 1/10	of		
Airborne Rad	ioactivity L	evel						
	cpm/100 ft3	240.	340.	400.	600.	1.4P3	1.4P3	1
-Inside-	cpm/6 ft3	<20	20.	24.	24.	78.	78.	1
	% 1-131	20.	20.	20.	20.	20.	20.	
	% I-133	80.	80.	80.	80.	80.	80.	
		140.	180.	340.	380.	800.	1.P3	1
	cpm/100 ft ³		180. <20	340. 22.	380. 22.	800. 48.	1.P3 60.	1
'Inside'		140. <20 20.						1

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure E1. 283 Ft (Cont)

		1730 1800	$\frac{1800}{1900}$	1900 1930	1930 2045	2045 2145
Ambient Radi	ation Level	(mR/hr)				
Injecti Valve Area	on AC BC CC DC	1.P4 5.P3 3.P3 1.5P3	3.P4 1.5P4 8.P3 4.P3	3.P4 2.P4 1.P4 5.P3	4.P4 2.P4 1.P4 5.P3	4.P4 2.P4 1.P4 5.P3
Recombiner	APBPCPDP	70. 35. 20. 10.	100. 50. 25. 13.	500. 250. 120. 60.	4.P4 2.P4 1.P4 5.P3	7.P4 3.5P4 1.8P4 9.P3
All Other Ar	eas	7.	6.	5.	5.	5.
ARM	-21 -22 -23 -24	7. 7. 7. 70.	6. 6. 100.	5. 5. 5. 500.	5. 5. 5. >1.P4	5. 5. 5. >1.P4
Contaminatio	n Survey (d	pm/100 cm	4)			
-Inside-		3.P3	3.P3	4.P3	4.P3	6.P3
'Inside'		6.P3	6.P3	6.P3	7.P3	7.P3
NOTE:	Survey met				m are 1/10) of
Airborne Rad	lioactivity	Level				
	pm/100 ft ³ pm/6 ft ³ % I-131 % I-133	100. 20.	1.6P3 100. 20. 80.	1.6P3 100. 20. 80.	1.6P3 100. 20. 80.	2.P3 100. 20. 80.
'Inside' c	pm/6 ft3		1.2P3 74. 20. 80.	1.4P3 80. 20. 80.	1.4P3 80. 20. 80.	1.4P3 90. 20. 80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 313 and 331 Ft

		$\frac{1100}{1400}$	1400 1500	1500 1600	1600 1630	1630 1715	$\frac{1715}{1730}$
Ambient	Radiation Leve	1 (mR/hr)					
	A _P B _P C _P C _P	1. 1.	1. 1. 1.	1. 1.	2. 1. 1.	4. 2. 1.	9. 5. 2.
		1.	2.	2.	5.	60.	800.
	2 F 3 F 6 F	1 1 1 1	1. 1. 1.	1. 1.	2.5 2. 2.	6. 3.5 3.	80. 20. 5.
All orac	r Areas	0.5	1.	1.	2.	3.	7.
ARM	-27	1.	4.	1.	1.	1.5	3.0
Contumin	ation Survey (dpm/100 cm2)				
Gen	eral	۵00.	200.	200.	200.	200.	200.
NOTE:	The state of the s	ter reading tion values		The state of the s	are 1/10	of	
Airborne	Radioactivity	Level					
	cpm/100 ft3	80.	100.	140.	200.	400.	500.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Reactor Enclosure El. 313 and 331 Ft (Cont)

	1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
Ambient Radiation Level	(mR/hr)				
AP BP CP DP	70. 35. 20. 10.	100. 50. 25. 13.	500. 250. 120. 60.	4.P4 2.P4 1.P4 5.P3	7.P4 3.5P4 1.8P4 9.P3
1 2 F 3 F 4 F	1.1P3 110. 30. 10	1.4P3 140. 35. 15.	1.6P3 160. 40. 20.	1.7P3 170. 40. 20.	1.7P3 170. 40. 20.
All Other Areas	7.0	6.	5.	5.	5.
ARM -27	25.	35.	150.	>1.P4	>1.P4
Contamination Survey (dp	m/100 cm ²)				
General	200.	300.	500.	600.	700.
NOTE: Survey mete contaminati				are 1/10	of
Airborne Radioactivity L	evel				
General cpm/100 ft ³ cpm/6 ft ³ % I-131 % I-133	600. 40. 20. 80.	800. 48. 20. 80.	800. 50. 20. 80.	800. 60. 20. 80.	1.P3 60. 20. 80.

NRC/FEMA CESERVED EMERGENCY RESPONSE EXERCISE I IMERICK GENERATING STATION Turbine Enclosure E1. 200 Ft

		1100 1400	1400 1500	$\frac{1500}{1600}$	1600 1630	1630 1715	$\frac{1715}{1730}$
Ambient Rad	iation Level	(mR/hr)					
	1,	80.	30.	15.	15.	15.	15.
	24	40.	15.	8.	8.	8.	8.
	1 2 A 3 A	10.	4.	2.	2.	2.	2.
All Other A	reac	0.2	0.2	0.2	0.7	1.1	2.
ARM	-04	0.2	0.2	0.2	0.7	1.1	2.
	-05	0.2	0.2	0.2	0.7	1.1	2.
	-07	90.	35.	20.	20.	15.	15.
	-34	6.2	0.2	0.2	0.7	1.1	2.
Contaminatio	on Survey (dp	m/100 cm ²))				
-Inside-		250.	400	700.	750.	900.	900.
'Inside'		200.	350.	550.	600.	600.	600.
111111							
/Inside/		500.	800.	1.P3	1.1P3	1.1P3	1.3P3
11111							
	Survey mete				are 1/10	of	
NOTE:		on values			are 1/10	of	
NOTE:	contaminati	evel	in apm/1		are 1/10	of 240	340
NOTE: Airborne Rac	contaminati dioactivity L cpm/100 ft ³ cpm/6 ft ³	evel 40.	in apm/1	00 cm ² .			340 20
NOTE: Airborne Rac	contaminati dioactivity L cpm/100 ft ³ cpm/6 ft ³ % 1-131	evel 40. <20 20.	in dpm/1 60. 220 20.	00 cm ² .	150. <20 15.	240 <20 20.	20 20.
NOTE: Airborne Rac	contaminati dioactivity L cpm/100 ft ³ cpm/6 ft ³	evel 40.	in dpm/1 60.	00 cm ² .	160. <20	240 <20	20
NOTE:	contaminati dioactivity L cpm/200 ft ³ % 1-131 % 1-133	evel 40. <20 20. 80. 60.	60. 20. 20. 80.	00 cm ² . 40. <20 20. 80.	150. <20 15. 70.	240 <20 20. 80.	20 20. 80.
NOTE: Airborne Race -Inside- ce 'Inside' ce	contaminati dioactivity L cpm/100 ft ³ % 1-131 % I-133 cpm/100 ft ³	40. <20 20. 80. 60. <20	60. 29 20. 80.	40. <20 20. 80. <20	150. <20 15. 70.	240 <20 20. 80.	20 20. 80.
NOTE: Airborne Race -Inside- ce 'Inside' ce	contaminati dioactivity L cpm/100 ft ³ % 1-131 % I-133 cpm/100 ft ³ cpm/6 ft ³ % 1-131	40. <20 20. 80. <20 10.	60. <29 20. 80. <20 15.	00 cm ² . 40. <20 20. 80. <20 20.	160. <20 15. 70. 120. <20 20.	240 <20 20. 80. 120. <20 20.	20 20. 80. 120. <20 20.
Airborne Rad	contaminati dioactivity L cpm/100 ft ³ % 1-131 % I-133 cpm/100 ft ³	40. <20 20. 80. 60. <20	60. 29 20. 80.	40. <20 20. 80. <20	150. <20 15. 70.	240 <20 20. 80.	20 20. 80.
NOTE: Airborne Rac -Inside- c 'Inside' c	contaminati dioactivity L cpm/100 ft ³ % 1-131 % I-133 cpm/100 ft ³ % I-131 % I-133	40. <20 20. 80. <20 10.	60. <29 20. 80. <20 15.	00 cm ² . 40. <20 20. 80. <20 20.	160. <20 15. 70. 120. <20 20.	240 <20 20. 80. 120. <20 20.	20 20. 80. 120. <20 20. 80.
NOTE: Airborne Rac -Inside- c 'Inside' c	contaminati dioactivity L cpm/100 ft ³ % 1-131 % I-133 cpm/100 ft ³ % I-131 % I-133	evel 40. 20. 20. 80. 60. 20. 10. 40.	60. <20 20. 80. <20 15. 60.	00 cm ² . 40. <20 20. 80. <20 20. 80.	160. <20 15. 70. 120. <20 20. 86.	240 <20 20. 80. 120. <20 20. 80.	20 20. 80. 120. <20 20. 80.
	contaminati dioactivity L cpm/200 ft ³ % 1-131 % I-133 cpm/100 ft ³ % I-131 % I-133 cpm/6 ft ³ % I-133	evel 40. 20. 20. 80. 60. 20. 10. 40.	60. 20. 20. 80. 60. 20. 5. 60.	00 cm ² . 40. <20 20. 80. <20 20. 80.	160. <20 15. 70. 120. <20 20. 80.	240 <20 20. 80. 120. <20 20. 80.	20 20. 80. 120. <20 20. 80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 200 Ft (Cont)

		1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
Ambient R	adiation Leve	el (mR/hr)				
	1 2 A 3 A	15. 8. 2.	15. 8. 2.	15. 8. 2.	15. 8. 2.	15. 8. 2.
All Other	Areas	3.	3.	3.	3.	3.
ARM	-04 -05 -07 -34 tion Survey (3. 3. 20. 3. dpm/100 cm ²)	3. 3. 20. 3.	3. 3. 20. 3.	3. 3. 20. 3.	3. 3. 20. 3.
-Inside-		1.P3	1.P3	1.23	1.1P3	1.1P3
'Inside'		800.	800.	800.	900.	1.P3
	1	1.7P3	1.7P3	1.7P3	2.P3	2.P3

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

cpm/100 ft ³	500.	700.	1.P3	1.6P3	3.P3
-Inside- cpm/6 ft?	30.	44.	60.	100.	180.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.
''' cpm/100 ft ³	140.	180.	180.	200.	200.
'Inside' cpm/6 ft3	<20	<20	<20	<20	<20
' ' ' ' % I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.
/////cpm/100 ft ³	3.2P3	5.P3	8.P3	1.2P4	1.8P4
/Inside/ cpm/6 ft3	200.	300.	500.	600.	1.P3
///// % I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 217 Ft

			e El. 217			
	$\frac{1100}{1400}$	$\frac{1400}{1500}$	1500 1600	$\frac{1600}{1630}$	$\frac{1630}{1715}$	1715 1730
ation Level	(mR/hr)					
1 2 7 3 T	120. 60. 20.	50. 25. 10.	20. 10. 3.	20. 10. 3.	20. 10. 3.	20. 10. 3.
eas	0.7	0.7	1.	1.	1.	1.5
-12	0.7	0.7	1.	1.	1.	1.5
-13	50.	20.	7.	7.	7.	7.
Survey (d	pm/100 cm ²)				
	400.	400.	400.	500.	600.	600.
	900.	900.	900.	900.	900.	900.
				are 1/10	of	
oactivity 1	Level					
	400. 24. 20. 80.	400. 24. 20. 80.	400. 24. 20. 80.	400. 24. 20. 70.	600. 40. 20. 80.	800. 50. 20. 80.
	Survey meter contaminate conta	1400 Ation Level (mR/hr) 1	1400 1500 Ation Level (mR/hr) 1 120. 50. 60. 25. 3T 20. 10. 2T 60. 25. 3T 20. 10. 2as 0.7 0.7 -12 0.7 0.7 -13 50. 20. Survey (dpm/100 cm²) 400. 400. 900. 906. Survey meter readings of swip contamination values in dpm/100 cm² (mm/6 ft³ 24. 24. % 1-131 20. 20.	1400 1500 1600 ation Level (mR/hr) 1T 120. 50. 20. 2T 60. 25. 10. 3T 20. 10. 3. eas 0.7 0.7 1. -12 0.7 0.7 1. -13 50. 20. 7. a Survey (dpm/100 cm²) 400. 400. 900. 900. 900. Survey meter readings of swipes in cpm contamination values in dpm/100 cm². coactivity Level 50. 400. 400. 6 ft³ 24. 24. 24. % I-131 20. 20. 20.	Ition Level (mR/hr) 1T 120. 50. 20. 20. 2T 60. 25. 10. 10. 3T 20. 10. 3. 3. eas 0.7 0.7 1. 1. -12 0.7 0.7 1. 1. -13 50. 20. 7. 7. a Survey (dpm/100 cm²) 400. 400. 400. 500. 900. 900. 900. 900. Survey meter readings of swipes in cpm are 1/10 contamination values in dpm/100 cm². coactivity Level mm/100 ft³ 400. 400. 400. 400. mm/6 ft³ 24. 24. 24. 24. % I-131 20. 20. 20. 20. 20.	1400 1500 1600 1630 1715 ation Level (mR/hr) 1

1.2P3

70.

20.

80.

1.2P3

70.

20.

80.

1.2P3

70.

20.

80.

1.4P3

80.

20.

80.

' ' ' ' cpm/100 ft³

'Inside' cpm/6 ft³

% I-133

300.

<20

10.

60.

600.

36.

20.

80.

NRC/FEMA	OBSERVED	EMERGENCY	RESPONSE	EXERCISE
	LIMERICK	GENERATING	STATION	
	Turbine E	closure El	. 217 Ft	(Cont)

		1730 1800	1800 1900	1900 1930	1930 2045	$\frac{2045}{2145}$
Ambient	Radiation Leve	1 (mr/hr)				
	1 _T 2 _T 3 _T	20. 10. 3.	20. 10. 3.	20. 10. 3.	20. 10. 3.	20. 10. 3.
All Oth	er Areas	1.5	1.5	2.	2.	2.
ARM	-12	1.5	1.5	2.	2.	2.
	-13	7.	7.	7.	7.	7.

Contamination Survey (dpm/100 cm2)

-Inside-	600.	600.	700.	700.	700.
'Inside'	900.	900.	900.	900.	900.

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

/100 6+3	800.	800.	1.P3	1.2P3	1.4P3
cpm/100 ft3					
-Inside- cpm/6 ft3	50.	50.	60.	70.	80.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	70.	80.
''' cpm/100 ft ³	1.4P3	1.4P3	1.4P3	1.4P3	200.
'Inside' cpm/6 ft3	80.	80.	80.	80.	80.
'''' % I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 239 Ft

		lurbine	e Enclosui	e E1. 23	, ,,		
		$\frac{1100}{1400}$	1400 1500	1500 1600	$\frac{1600}{1630}$	1630 1715	$\frac{1715}{1730}$
Ambient Radia	tion Level	(mR/hr)					
	1.	100.	40.	20.	20	15.	15.
	25	100.	40.	20.	20.	15.	15.
	35	20.	8.	4.	4.	3.	3.
	1 2 3 3 4 5	5.	2.	1.	1.	1.	1.
	1_	0.5	0.5	0.5	0.5	1.	1.
	2P	0.5	0.5	0.5	0.5	1.	1.
	3.P	0.5	0.5	0.5	0.5	1.	1.
	1 _P 2 _P 3 _P 4 _P	0.5	0.5	0.5	0.5	1.	1.
All Other Are	eas	0.5	0.5	0.5	0.5	1.	1.
ARM	-19	100.	40.	20.	20.	15.	15.
	-20	100.	40.	20.	20.	15.	15.
-Inside-		300.	300.	300.	400.	500.	600.
'Inside'		<100.	<100.	<100.	<100.	170.	170.
//////////Inside/		<100.	<200.	700.	700.	700.	700.
NOTE:	Survey met contaminat				m are 1/10	of	
Airborne Rad	ioactivity	Level					
c	om/100 ft3	320.	400.	400.	400.	400.	600.
-Inside- c		<20	26.	36.	26.	26.	40
	% I-131	5.	15.	20.	20.	20.	20.
	% I-133	50.	70.	70.	80.	80.	80.
	pm/100 ft ³	40.	100.	120	140.	140.	340.
	pm/ 6 ft3	<20	<20	<20	<20	<20	<20
THOTUE C	hm) o re.				00	00	20

20.

80.

10.

70.

% I-131

% I-133

20.

80.

20.

80.

20.

80.

20.

80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 239 Ft (Cont)

	$\frac{1100}{1400}$	1400 1500	$\frac{1500}{1600}$	$\frac{1600}{1630}$	$\frac{1630}{1715}$	1715 1730
/////cpm/100 ft ³	120.	320	400.	400.	400.	400.
/Inside/ cpm/6 ft3	<20	<20	24.	24.	24.	24.
///// % I-131	15.	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 239 Ft (Cont)

		$\frac{1730}{1800}$	$\frac{1800}{1900}$	1900 1930	$\frac{1930}{2045}$	2045 2145
Ambient F	Radiation Level	(mR/hr)			
	1-	20.	15.	15.	15.	15.
	1s 2s 3s 4s	20.	15.	15.	15.	15.
	3S	4.	3.	3.	3.	3.
	,S	1.	1.	1.	1.	1.
	S	•				
	1,	1.	1.	1.	1.	1.
	1 _P 2 _P 3 _P 4 _P	1.	1.	1.	1.	1.
	3 ^P	1.	1.	1.	1.	1.
	4P	1.	1.	1.	1.	1.
	P					
All Other	r Areas	1.	1.	1.	1.	1.
ARM	-19	20.	15.	15.	15.	15.
	-20	20.	15.	15.	15.	15.
-Inside-	· · · · · · · · · · · · · · · · · · ·	600. 170. 400.	600. 170. 400.	600. 170. 500.	700. 200. 700.	700. 200. 700.
NOTE:	Survey met contaminat Radioactivity	ion val				0 of
	cpm/100 ft ³	800	800	800	1.P3	1.2P3
	- cpm/6 ft ³		50.	50.	60.	70.
	% I-131		20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.
	' 'cpm/100 ft ³	400.	400.	400.	400.	600.
'Inside	cpm/6 ft3	24.	24.	24.	24.	38.
1 1 1 1	' ' % I-131	20.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.

80.

% I-133

30.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 239 Ft (Cont)

	1730	1730 1800		1930	2045	
	1800	1900	1930	2045	2145	
''' 'cpm/100 ft3	600.	800.	800.	800.	1.P3	
'Inside cpm/6 ft3	34.	48.	50.	48.	60.	
''' % I-131	20.	20.	20.	20.	20.	
% I-133	80.	80.	80.	80.	80.	

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 269 Ft

	$\frac{1100}{1400}$	1400 1500	1500 1600	$\frac{1600}{1630}$	$\frac{1630}{1715}$	1715 1730
Ambient Radiation Leve	1 (mR/hr)					
1 ₂ G 3 _G	100. 50. 10.	40. 20. 4.	20. 10. 2.	20. 10. 2.	20. 10. 2.	15. 7. 1.5
All Other Areas	0.5	0.5	0.5	0.5	1.	1.
ARM -25	0.5	0.5	0.5	0.5	1.	1.
-57	0.5	0.5	0.5	0.5	1.	1.
Contamination Survey (dpm/100 cm ²)				
General	500.	600.	600.	600.	600.	

Airborne Radioactivity Level

NOTE:

General cpm/100 ft3 120. 120. 120. 140. 340. 340. cpm/6 ft3 <20 <20 <20 <20 20. 20. % I-131 20. 15. 20. 20. 20. 20. 70. 75. 80. 80. 80. 80. % I-133

Survey meter readings of swipes in cpm are 1/10 of

contamination values in dpm/100 cm2.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 269 Ft (Cont)

1730	1800	1900	1930	2045
1800	1900	1930	2045	2145

Ambient Radiation Level (mR/hr)

	1 2 3 3 6	15. 7. 1.5	15. 7. 1.5	15. 7. 2.	15. 7. 2.	15. 7. 2.
All Othe	er Areas	1.	1.	1.	1.	1.
ARM	-25	1.	1.	1.	1.	1.
	-57	1.	1.	1.	1.	1.

Contamination Survey (dpm/100 cm2)

General 600. 700. 700. 700. 770.

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General	cpm/100 ft3	400.	400.	600.	600.	600.
	cpm/6 ft3	24.	24.	40.	40.	40
	% I-131	15.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Turbine Enclosure El. 302 Ft

	1100 1400	1400 1500	1500 1600	$\frac{1600}{1630}$	1630 1715	1715 1730
Ambient Radiation Level	(mR/hr)					
1,	1.	1.	1.	1.	1.	1.
2 ^F	0.5	0.5	1.	1.	1.5	1. 1.5
1 2 3 3 F	0.5	1. 0.5 0.5	1.	1.	2.	2.
All Other Areas	0.5	0.5	1.	1.	2.	2.
ARM -28	0.5	0.5	1.	1.	2.	2.
Contamination Survey (dpr	m/100 cm ²)				
General General	500.	600.	600.	600.	600.	700.
NOTE: Survey meter contamination				are 1/10	of	

General cpm/100 ft3	200.	400.	640.	400.	800.	800.
cpm/6 ft ³	<20	24.	24.	24.	50.	50.
% I-131	20.	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Turbiae Enclosure El. 302 Ft (Cont)

		$\frac{1730}{1800}$	$\frac{1800}{1900}$	$\frac{1900}{1930}$	1930 2045	2045 2145	
Ambient Radiation Leve	1 (mR/hr)						
	¹ ₂ _F ³ _F	1. 1.5 2.	1. 1.5 2.	1. 1.5 2.	1. 1.5 2.	1. 1.5 2.	
All Other Areas	2.	2.	2.	2.	2.		
ARM	-28	2.	2.	2.	2.	2.	
Contamination Survey (dpm/100 cm ²)							
General		700.	700.	700.	700.	700.	

NOTE: Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General-cpm/100	ft ³	800.	1.2P3	1.4P3	1.4P3	2.P3
	cpm/6 ft3	50.	50.	80.	80.	120.
	% I-131	20.	20.	20.	20.	20.
	% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Turbine Enclosure El. 321, 332, and 350 Ft

		1100 1400	1400 1500	1500 1600	1600 1630	$\frac{1630}{1715}$	1715 1730
Ambient Radiation	Level	(mR/hr)					
1 2 3 3 4 4 1 1 N 2 N		0.5 0.5 0.5 0.5 1.	0.5 0.5 0.5 0.5 1.	0.5 0.5 0.5. 0.5 1.	0.5 0.5. 0.5 0.5 1.	1.5 1. 1. 1. 1. 0.5	5. 1. 1. 1. 1. 0.5
General-Elevation -Elevation -Elevation	332	0.5 0.3 0.5	0.5 0.5 0.5	0.5 0.5 0.5	0.5 0.5 0.5	0.5 1. 0.5	0.5 1. 0.5
ARM -58		0.5	0.5	0.5	0.5	1.2	2.
Contamination Sur	vey (dp	m/100 cm ²	4)				
General-Elevation -Elevation -Elevation	332	600. 700. 1.P3	700. 800. 1.P3	1.P3 1.2P3 1.4P3	1.2P3 1.3P3 2.P3	1.2P3 1.4P3 2.P3	1.5P3 1.6P3 2.5P3

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm2.

General-						
Elevation 321						
cpm/100 ft ³	120.	140.	200.	260.	340.	400.
cpm/6 ft3	<20	<20	<20	<20	20	24.
% I-131	20.	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.	80.
Elevation 332						
cpm/100 ft ³	140	180	260	320	400	600.
cpm/6 ft3	<20	<20	<20	<20	24.	40.
% I-131	20.	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Turbine Enclosure El. 321, 332, and 350 Ft (Cont)

	1100 1400	1400 1500	1500 1600	$\frac{1600}{1630}$	1630 1715	$\frac{1715}{1730}$
Elevation 350 cpm/100 ft ³	120.	160	200	240	280	380
cpm/6 ft ³	72.	<20	<20	<20	20.	22.
% I-131	10.	20.	20.	20.	20.	20.
% I-133	70.	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Turbine Enclosure El. 321, 332, and 350 Ft (Cont)

Ambient Radiation	Level (1730 1800 mR/hr)	1800 1900	1900 1930	1930 2045	2045 2145
1,		8.	15.	25.	7.P3	2.6P4
2 ^F		1.7	3.5	5.	1.7P3	6.P3
3 ^F		1.	2.	2.	600.	2.P3
4 ^F		1.	2.	2.	170.	600.
1,		2.	4.	12.	700.	3.P3
1F 2F 3F 4F 1N 2N		1.	2.	6.	350.	1.5P3
General-Elevation	321	1.	1.	2.	2.	2.
-Elevation	332	1.	2.	2.	3.	4.
-Elevation	350	1.	1.	2.	2.	3.
ARM -58		4.	7.	10.	3.5P3	1.2P4
Contamination Surv	vey (dpm	/100 cm ²)				
General-Elevation	321	1.7P3	3.P3	4.P3	6.P3	7.P3
-Elevation	332	2.5P3	4.P3	7.P3	9.P3	1.P4
-Elevation	350	2.5P3	3.P3	4.P3	6.P3	6.P3

NOTE: Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General-					
Elevation 321 cpm/100 ft ³	800.	1.2P3	1.4P3	2.P3	3.4P3
cpm/6 ft ³	50.	70.	80.	120	200.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.
Elevation 332					
cpm/100 ft ³	1.2P3	1.4P3	2.8P3	3.2P3	4.P3
cpm/6 ft ³	72.	84.	170.	190.	240.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.
Elevation 350					
cpm/100 ft ³	700.	900.	1.6P3	1.8P3	2000.
cpm/6 523	44.	56.	100	110	120.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Radwaste Enclosure El. 162 Ft

		1100 1400	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730
Ambient	Radiation Level	(mR/hr)					
	1 2 3 7 3	0.5 0.5 0.5	0.5 0.5 0.5	1. 1. 0.5.	2. 1. 1.	3. 1. 1.	5. 1.5 1.
All Othe	r Areas	0.2	0.3	0.4	0.8	0.8	0.8
ARM	-41	0.2	0.3	0.4	0.6	0.8	0.8
	-42	0.2	0.3	0.4	0.6	0.8	0.8
Contamin	ation Survey (dp						
	General	300.	600.	1.P3	1.5P3	2.2P3	3.P3

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General-cpm/100 ft3	400.	5.4P	2 800.	1.4P3	2.6P3	5.P3
cpm/6 ft ³	24.	32.	50.	80.	160	300
% I-131	10.	10.	15.	20.	20.	20.
% I-133	50.	60.	70.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Radwaste Enclosure El. 162 Ft (Cont)

		1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
Ambient	Radiation Leve	el (mR/hr)				
	1 2 7 3 T	10. 3. 1.	20. 7. 2.	40. 13. 4.	60. 20. 7.	110. 35. 10.
All Othe	r Areas	0.8	0.8	2.5	5.	8.
ARM	-41	3.0	0.8	2.5	5.	8.
	-42	0.8	0.8	2.5	5.	8.
Contamin	ation Survey	(dpm/100 cm ²)			
Gen	eral	4.P3	6.P3	9.P3	1.4P4	2.P4

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm2.

Ceneral-cpm/100	ft ³ 1.P4	1.6P4	1.6P4	1.6P4	1.6P4
cpm/6 ft	3 6.P2	1.P3	1.P3	1.P3	1.P3
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Radwaste Enclosure El. 191 Ft (Cont)

		1100 1400	1400 1500	1500 1600	$\frac{1600}{1630}$	$\frac{1630}{1715}$	1715 1730	
Ambient	Radiation Level	(mR/hr)						
	1 <u>L</u> 2 <u>L</u> 3 <u>L</u>	1. 0.5 0.5	1. 0.5 0.5	2. 0.5 0.5.	5. 1.5 1.	10. 3. 1.	10. 3. 1.	
All Other	r Areas	0.5	0.5	0.5	1.	1.	1.	
ARM	-43	0.5	0.5	0.5	1.	1.	1.	
	-46	0.5	0.5	0.5	1.	1.	1.	
	-47	0.5	0.5	0.5	1.	1.	1.	
Contamina	ation Survey (dr	om/100 cm ²)						
	General	400.	700.	900.	1.P3	1.2P3	1.5P3	

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General-cpm/100 ft3	340	400	500	540	800	1.2P3
cpm/6 ft ³	20.	24.	30.	32.	50.	70.
% I-131	20.	20.	20.	20.	20.	20.
% I-133	40.	50.	60.	70.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Radwaste Enclosure El. 191 Ft (Cont)

		1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
Ambien	nt Radiation Level	(mR/hr)				
	1 2 1 3 L	15. 5. 1.5	15. 5. 1.5	15. 5. 1.5	20. 7. 2.	20. 7. 2.
A11 Ot	her Areas	1.	1.	1.	1.	2.
ARM	-43	1.	1.	1.	1.	2.
	-46	1.	1.	1.	1.	2.
	-47	1.	1.	1.	1.	2.
Contam	ination Survey (dp	om/100 cm ²)			
G	eneral	2.P3	3.P3	4.P3	5.P3	7.P3

NOTE:

Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General-cpm/100 ft3	1.5P3	2.P3	2.6P3	3.P3	3.6P3
cpm/6 ft ³	80.	120.	160.	180.	2.2P2
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Radwaste / oclosure El. 217 Ft

	Radwaste	Inclosu	re El. 21	7 Ft		
	1100 1400	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730
Ambient Radiation Level	(mR/hr)					
All Areas	0.2	0.2	0.4	0.5	0.5	0.8
ARM -51	0.2	0.2	0.4	0.5	0.5	0.8
Contamination Survey (dp	m/100 cm ²))				
 -Inside-	100.	200.	250.	300.	350.	600.
'Inside'	300.	400.	500.	600.	700.	1.2P3
NOTE: Survey mete				are 1/10	of	
Airborne Radioactivity I	evel					
cpm/100 ft ³ -Inside- cpm/6 ft ³	80. <20	120. <20	160. <20	220. <20	280. <20 20.	360. 22.

180

<20

20.

50.

'Inside' cpm/6 ft³
'Inside' topm/6 ft³
'Inside' topm/6 ft³

% I-133

120

<20

20.

30.

2.8P2 400.

<20

15.

75.

24.

20.

80.

6.P2

40.

20.

80.

5.P2

30.

20.

80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION Radwaste Enclosure El. 217 Ft (Cont)

Radwaste Enclosure El. 217 Ft (Cont)								
		1730 1800	1800 1900	1900 1930	1930 2045	$\frac{2045}{2145}$		
Ambient Radiation Level	(mR/hr)							
All Areas		1.	1.	1.	1.	1.		
ARM	-51	1.	1.	1.	1.	1.		
Contamination Survey (d	pm/100 cm ²)	,						
	800.	800.	800.	800.	800.			
'Inside'	1.5P3	2.P3	2.5P3	3.P3	4.P3			
NOTE: Survey meter contamination values in			es in cpm	are 1/10	of			
Airborne Radioactivity	Level							
	500. 30. 20. 80.	700. 42. 20. 80.	800. 48. 20. 80.	900. 54. 20. 80.	1.P3 60. 20.			

1.P3

60.

20.

80.

1.4P2 1.6P3

100.

20.

80.

80.

20.

80.

2.P3

120.

20.

80.

800.

50.

20.

80.

'!Inside' cpm/6 ft³
'Inside' cpm/6 ft³
'! '''' % I-131
% I-133

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Radwaste Enclosure El. 237 and 257 Ft

	1100 1400	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730
Ambient Radiation Level	(mR/hr)					
1 _D 2 _D	0.1	0.1	0.2	0.3	0.5 0.5	0.5 0.5
1 _W 2 _W	0.2	0.2	0.4	0.6	1.0	1.0
General-Elevation 237	0.2	0.2	0.4	0.6	1.0	1.0
-Elevation 257	0.1	0.1	0.2	0.3	0.5	0.5
ARM -55	0.1	0.1	0.2	0.3	0.5	0.5
Contamination Survey (dp	m/100 cm ²)					
General-Elevation 237	200.	300.	400.	500.	600.	1.P3
-Elevation 257	100.	200.	300.	350.	400.	700.

NOTE: Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm2.

General-						
Elevation 237						
cpm/100 ft ³	80.	100.	120	180.	360.	300.
cpm/6 ft3	<20	<20	<20	<20	<20	<20
% I-131	20.	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Radwaste Enclosure El. 237 and 257 Ft (Cont)

	$\frac{1100}{1400}$	1400 1500	1500 1600	$\frac{1600}{1630}$	$\frac{1630}{1715}$	1715 1730	1
Elevation 257 cpm/100 ft ³	60.	80.	100.	140.	180.	200.	1
cpm/6 ft ³ % I-131 % I-133	<20 20. 80.	<20 20. 80.	<20 20. 80.	<20 20. 80.	<20 20. 80.	<20 20. 80.	

NRC/FEMA OBSERVED EMERGENCY RESPONSE EXERCISE LIMERICK GENERATING STATION

Radwaste Enclosure El. 237 and 257 Ft (Cont)

	1730 1800	1800 1900	1900 1930	1930 2045	2045 2145			
Ambient Radiation Level (mR	(hr)							
	1 _D	0.7	0.8	0.8	0.8	1.0		
	1 2 W	1.4	1.5	1.5	1.5	1.5 1.5		
General-Elevation 237	1.4	1.5	1.5	1.5	1.5			
-Elevation 2	257 0.7	0.8	0.8	0.8	1.0			
ARM	-55	0.7	0.8	0.8	0.8	1.0		
Contamination Survey (dpm/100 cm ²)								
General-Elevation 237	1.2P3	1.5P3	1.6P3	1.7P3	2.P3			
-Elevation 257	800.	1.P3	1.P3	1.1P3	1.1P3			

NOTE: Survey meter readings of swipes in cpm are 1/10 of contamination values in dpm/100 cm².

General-					
Elevation 237					
cpm/100 ft ³	400.	500.	600.	700.	700.
cpm/6 ft ³	24.	30.	36.	44.	46.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.
Elevation 257					
cpm/100 ft ³	260.	320.	360.	400.	500.
cpm/6 ft ³	<20	20.	22.	24.	30.
% I-131	20.	20.	20.	20.	20.
% I-133	80.	80.	80.	80.	80.

NRC/FEMA OBSERVED EMERGENCY REPONSE EXERCISE LIMERICK GENERATING STATION Area Monitor Readings (mR/hr)


ARM No.	Location	Full Scale Reading	1200 1400	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730	1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
RE-01	RCIC Pump Compartment	1.P4	100.	800.	1.4P3	2.5P3	4.P3	1.3P3	1.2P3	1.2P3	1.2P3	1.2P3	3 1.2P3
-02	HPCI Pump Compartment	1.P4	80.	300.	320.	320.	320.	320.	320.	320.	320.	320.	320.
-03	Sump Compart- ment	1.P4	1.	1.	1.	1.	2.	20.	80.	200.	300.	350.	280.
-04	CRD Pumps Area	1.P4	0.2	0.2	0.2	0.7	1.1	2.	3.	3.	3.	3.	3.
-05	Turb.Aux.Bay Hallway	1.P4	0.2	0.2	0.2	0.7	1.1	2.	3.	3.	3.	3.	3.
-06	Isolation Valve Compartment	1.P4	0.5	8.	50.	80.	120.	160.	160.	160.	160.	200.	240.
-07	Concensate Pump Compartment	1.P4	90.	35.	20.	20.	15.	15.	20.	20.	20.	20.	20.
	RHR Div.I Compartment	1.P4	8.	8.	25.	80.	240.	1.2P3	5.P3	5.P3	5.P3	5.P3	5.P3
-09	RHR Div.II Compartment	1.P4	8.	8.	25.	80.	240.	1.2P3	5.P3	5.P3	5.P3	5.P3	5.P3
-10	Steam Vent Area Stairwell	1.P4	0.5	0.5	2.	8.	15.	20.	20.	20.	20.	20.	20.
-12	Hallway, Cond. Filt Demin.	. 1.P4	0.7	0.7	1.	1.	1.	1.5	1.5	1.5	2.	2.	2.
-13	Condensate Area	1.P6	50.	20.	7.	7.	7.	7.	7.	7.	7.	7.	7.
-15	CRD HCU Area East	1.P4	0.5	0.5	0.5	1.	4.	3.	3.	2.	2.	2.	2.
-16	CRD HCU Area West	1.P4	0.5	0.5	0.5	1.	4.	3.	3.	2.	2.	2.	2.
-17	Neutron Mon. System Area	1.P4	0.5	0.5	0.5	1.	4.	3.	3.	2.	2.	2.	2.
-18	Neutron Mon. Driv Mech.	e 1.P4	0.5	0.8	4.	8.	10.	15.	20.	20.	20.	20.	20.

NRC/FEMA OBSERVED EMERGENCY REPONSE EXERCISE LIMERICK GENERATING STATION Area Monitor Readings (mR/hr) (Cont)

ARM No.	Location	Full Scale Reading	1200 1400	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730	1730 1800	1800 1900	1900 1930	1930 2045	2045 2145
RE-19	Turb.Aux.Bay Hallway East	1.96	100.	40.	20.	20.	15.	15.	15.	15.	15.	15.	15.
-20	Turb.Aux.Bay Hallway West	1.P6	100	40.	20.	20.	15.	15.	15.	15.	15.	15.	15.
-21	RWCU Heat Exchanger Area	1.P4	0.5	1.	1.	2.	3.	7.	7.	6.	5.	5.	5.
-22	RWCU Pump Area	1.P4	0.5	1.	1.	2.	5.	7.	7.	6.	5.	5.	5.
-23	SLC System Area	1.P4	0.5	1.	1.	2.	3.	7.	7.	6.	5.	5.	5.
	RWCU Instr. Rack Area	1.P4	1.	1.	1.	2.	4.	9.	70.	100.	500.	>1.P4	
-25	Turb. Aux. Bay	1.P4	0.5	0.5	0.5	0.5	1.	1.	1.	1.	1.	1.	1.
-27	RWCU Filter Area	1.P4	1.	1.	1.	1.	1.5	30.	25.	35.	150.	>1.P4	>1.P4
-28	Eq.Comp. Ex. Filter Area	1.P4	0.5	0.5	1.	1.	2.	2.	2.	2.	2.	2.	2.
-34	H ₂ /O ₂ Analyzer Area	1.P4	0.2	0.2	0.2	0.7	1.1	2.	3.	3.	3.	3.	3.
-36	OSC Area	1.P4	0.5	0.5	0.5	0.5	1.	1.	1.	1.	1.	1.	1.
-41	Sludge Disch. Mixing Pump Room	1.P4	0.2	0.3	0.4	0.6	0.8	0.8	0.8	0.8	2.5	5.	8.
-42	Radwaste Enclosur Hallway		0.2	0.3	0.4	0.6	0.8	0.8	0.8	0.8	2.5	5.	8.
-43	Conc. Storage Disch Pump Room	1.P4	0.5	0.5	0.5	1.	1.	1.	1.	1.	1.	1.	2.
-46	Fuel Pool Holding Pump Room	1.P4	0.5	0.5	0.5	1.	1.	1.	1.	1.	1.	1.	2.
-47	Precoat Tank and Pump Room	1.P4	0.5	0.5	0.5	1.	1.	1.	1.	1.	1.	1.	2.
-51	Radwaste Enclosur Hallway	re 1.P4	0.2	0.2	0.4	0.5	0.5	0.8	1.	1.	1.	1.	1.

NRC/FEMA OBSERVED EMERGENCY REPONSE EXERCISE LIMERICK GENERATING STATION Area Monitor Readings (mR/hr) (Cont)

No.	Location	Scale Reading	1200 1406	1400 1500	1500 1600	1600 1630	1630 1715	1715 1730	1730 1800	1800	1900 1930	1930 2045	2045 2145
E~-55	Radwaste Ex. Fan Area	1.P4	¢.1	0.1	0.2	0.3	0.5	0.5	0.7	0.8	8.0	0.8	1.
-56	Control Room	1.P4	0.1	0.1	C. 1	0.1	9.1	0.1	0.1	0.1	0.1	0.1	0.1
57	Turb. Area Operating Floor	1.P4	0.5	0.5	0.5	0.5	1.	1.	1.	1.	1.	1.	1.
	SGTS Filter Room North Stack Sampl	1.P4 e	0.5	0.5	0.5	0.5	1.2	2.	4.	7.	10.	3.5P	3 >1.P4
	Roam	1.P4	.5	.5	.5	.5	.5	.5	-5	.5	1.5	100.	430.



REACTOR ENCLOSURE EL. 177' LIMERICK GENERATING STATION


REACTOR ENCLOSURE EL. 2011 LIMERICK GENERATING STATION


REACTOR ENCLOSURE EL. 217' LIMERICK GENERATING STATION


REACTOR ENCLOSURE EL. 253' LIMERICK GENERATING STATION


REACTOR ENCLOSURE EL. 283' LIMERICK GENERATING STATION


REACTOR ENCLOSURE EL. 313' LIMERICK GENERATING STATION













PLANS AT EL 321-0", 332'-0" E 350'-0" LIMERICK GENERATING STATION

RADWASTE ENCLOSURE PLAN AT EL. 162'-0" LIMERICK GENERATING STATION





RADWASTE ENCLOSURE PLAN AT EL. 217'-0" LIMERICK GENERATING STATION

RADWASTE ENCLOSURE PLAN AT EL. 237'-0" E. EL. 257'-0" LIMERICK GENERATING STATION

EVENT SUMMARY

Event No.	Time	Location	Description	Initiation	Page Number
1	1105	Turbine Enclosure	Fire Instrument Air Compressor	Control Room Message	3G-1
2	1430	Radwaste Enclosure	Contaminated Injury	Control Room Message	3G-4
3	1600	North Parking Lot	Construction Workers Site Evacuation	After Alert Declared	36-17
4	1615	Reactor Enclosure	RHR Pump B Flow Decreases	Control Room Message	3G-18
5	1650	Reactor Enclosure	Search & Rescue	Control Room Message	3G-21
6	1715	Turbine Enclosure	Co ₂ Storage Tank Low Press.	Control Room Message	3G-23
7	1730	Reactor Enclosure	Fire in RHR Hx Room	Control Room Message	3G-25
8	1845	Reactor Enclosure	Purge Exhaust Line Leakage	Control Room Message	3G-28
9	1900	Chemistry Lab.	High Activity Cooling Tower Sample	Chemistry Controller Message	3G-33
10	2040	Reactor Enclosure	Core Spray Pump A Trips	Control Room Message	3G-35

EVENT NO. 1

Fire at The Instrument Air Compressor (1AK101)

Approximate Time

of Event:

1105

Location:

Instrument air compressor (IAK101) area in turbine

enclosure el 217 ft-0 in.

Problem:

Fire has broken out at the instrument air compressor (1AK101) and is spreading. The sprinkler system in the area is inoperable and the fire threatens the nearby lube oil storage tanks.

Response:

Dispatch Fire Fighting Group members to the scene. They will determine that assistance will be necessary from Linfield/Limerick Fire Department.

The fire is extinguished at 1145.

Controller Locations:

One in the area.

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 1

CUE CARD NO. 1-1

FOR: FIRE FIGHTING GROUP MEMBERS

TIME: 1105

LOCATION: TURBINE ENCLOSURE

217 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

teletekeletekeletekeletekeletekekeletekekeletekekeletekekeletekekeletekekeletekekeletekekeletekekeletekekelete

Instrument air compressor lAK101 is on fire. The sprinkler system in the area is inoperable and the fire is spreading rapidly to nearby lube oil storage tanks.

interestation in interestation interestation interestation interestation interestation interestation in inte

THIS IS A DRILL

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 1

CUE CARD NO. 1-2

FOR: FIRE FIGHTING GROUP MEMBERS

TIME: 1145

LOCATION: TURBINE ENCLOSURE

217 FT-0 IN., EL

in described and the describ

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

FIRE IS OUT.

the trade to the test de to the test de test d

THIS IS A DRILL

EVENT NO. 2

Contaminated Injured Individual

Approximate Time of Event:

1430

Location:

Fuel pool holding pump 00P340 in radwaste enclosure el 191 ft-0 in, Rm 236B.

Problem:

An assistant plant operator who was dispatched for routine inspection in the radwaste enclosure is found unconscious lying in a puddle that appears to be leakage from the fuel pool holding pump (00P340). He is bleeding from a head laceration.

Response:

The Search and Rescue/First Aid group should be Remove the man's dispatched to the area. in clothing. him contamirated put anticontamination clothing, and escort the man out the radwaste enclosure to the personnel decontamination room where he should be externally decontaminated and be prepared for transfer to the Pottstown Memorial Medical Center. In the medical center, he should be treated for his bleeding from the head laceration and then released to the RMC for treatment of possible internal contamination.

Controller Locations:

One initially in the radwaste enclosure and then in the ambulance going to the Hospital.

One at Hospital.

TABLE 3G-4A

CONTAMINATED OPERATOR'S VITAL SIGNS

	Right After Injury (Unconscious)	Ambulance Arrives (Conscious But Disoriented)		Ambulance Improper Care	After Hospital Treatment
Pupils	Dilated & Responsive	Dilated & Responsive	Dilated & Responsive	Dilated & Responsive	Dilated & Responsive
Blood Pressure	106/76	90/60	110/78	80/60	120/80
Pulse	100	116	116	120	88
Skin	Pale, Cool & Clammy	Pale, Cool & Clammy	Pale, Cool & Clammy	Pale, Cool & Clammy	Normal, Warm & Dry
Respiration	12	16-18	16-18	18	12-25

EMERGENCY PREPAREDNESS DRILL

CUE CARD NO. 2-1 DRILL TYPE/EVENT NO. 2 FOR: OPERATOR INSPECTING RADWASTE ENCLOSURE TIME: 1430 LOCATION: RADWASTE ENCLOSURE 191 FT-0 IN., EL; RM 236B THIS IS A DRILL DO NOT initiate actions affecting normal plant operations. YOU SLIP AND FALL IN A PUDDLE NEAR FUEL POOL HOLDING PUMP (00P340). YOU GO UNCONSCIOUS. THIS IS A DRILL *************************************

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2

CUE CARD NO. 2-2

FOR: PERSON FINDING THE INJURED OPERATOR

TIME: 1430

LOCATION: RADWASTE ENCLOSURE

191 FT-0 IN., EL; RM 236B

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

THE MAN IS UNCONSCIOUS LYING IN A PUDDLE THAT COULD BE LEAKAGE FROM FUEL POOL HOLDING PUMP (00P340). HE IS BLEEDING FROM A HEAD LACERATION.

THIS IS A DRILL

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2

CUE CARD NO. 2-3

FOR: SEARCH AND RESCUE/FIRST AID GROUP LEADER TIME: 1430+

LOCATION: RADWASTE ENCLOSURE

191 FT-0 IN., EL; RM 236B

to to the total to the total to the total total to the total total total total to the total tota

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

THE MAN IS LYING UNCONSCIOUS WITH HIS HANDS AND FACE IN A PUDDLE THAT LOOKS LIKE LEAKAGE FROM FUEL POOL HOLDING PUMP (00P340). HE IS BLEEDING FROM A HEAD LACERATION.

1.0 MR/HR GENERAL AREA RADIATION INJURED EXTERNAL CONTAMINATION LEVELS UP TO 20,000 CPM (SURVEY INSTRUMENT).

interpolation interpolation in the interpolation in

THIS IS A DRILL

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2

CUE CARD NO. 2-4

FOR: SEARCH AND RESCUE/FIRST AID GROUP LEADER TIME: 1430+

PERSONNEL

LOCATION: DECONTAMINATION AREA

to be to be

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

CONTAMINATION LEVELS AFTER REMOVAL OF SHIRT (SURVEY INSTRUMENT): RIGHT ARM - FRONT FROM SHOULDER TO WRIST 2,000 CPM RIGHT SIDE OF FACE, JAW, AND LIPS 10,000 CPM LEFT HAND, WRIST, AND FOREARM 6,000 CPM

THIS IS A DRILL




Figure 3G-2-1 Contaminated Areas of Body

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2

CUE CARD NO. 2-5

FOR: SEARCH AND RESCUE/FIRST AID GROUP LEADER TIME: 1430+

LOCATION: DECOMTAMINATION AREA

independent der bestehen bestehe bestehen bestehe bestehen bestehen bestehe

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

determination of the state of t

CONTAMINATION LEVELS AFTER INITIAL CLEANING OF CONTAMINATED AREAS ARE (SURVEY INSTRUMENT): RIGHT ARM - FRONT FROM SHOULDER TO WRIST <100 CPM 3,000 CPM RIGHT SIDE OF FACE, JAW, AND LIPS 2,500 CPM LEFT HAND, WRIST, AND FOREARM

THIS IS A DRILL

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2

CUE CARD NO. 2-6

FOR: SEARCH AND RESCUE/FIRST AID GROUP LEADER TIME: 1430+

LOCATION: DECONTAMINATION AREA

THIS IS A DRILL

to the state of th

DO NOT initiate actions affecting normal plant operations.

CONTAMINATION LEVELS AFTER 2ND CLEANING OF CONTAMINATED AREAS ARE (SURVEY INSTRUMENT): CONTAMINATED AREAS ARE
CONTAMINATED AREAS AREAS
CONTAMINATED AREAS AREAS AREAS
CONTAMINATED AREAS AREAS AREAS
CONTAMINATED AREAS ARE LEFT HAND, WRIST, AND FOREARM

THIS IS A DRILL

determined in the second of th

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2	CUE CARD NO. 2-7
FOR: SEARCH AND RESCUE/FIRST AID G	ROUP LEADER TIME: 1430+
*********************************	riekki kileleiriki kikileiriki kilekileiriki kikileirikikileiri, keleirikileiri
THIS	S IS A DRILL
DO NOT initiate actions affect	ting normal plant operations.
******	**************************************
CONTAMINATION LEVELS AFTER 3RD CONTAMINATED AREAS ARE (SURVEY LEFT HAND, WRIST, AND FOREARM	INSTRUMENT):
*******************************	eteleketerteketeketeketeketeketeketeketekete
THIS	S IS A DRILL
	etalalalalalalalalalalalalalalalalalalal

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2

CUE CARD NO. 2-8

FOR: HOSPITAL STAFF

TIME: 1430+

LOCATION: POTTSTOWN MEMORIAL MEDICAL CENTER

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MAN'S CONTAMINATED TO (20,000/1,000) CPM ALONG WITH INJURY.

*DEPENDING ON WHETHER HE WAS DECONTAMINATED AT LGS.

THIS IS A DRILL

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2	CUE CARD NO. 2-9
FOR: LGS HEALTH PHYSICS TECHNICAN	TIME: 1430+
LOCATION: AMBULANCE GOING TO POTTSTOWN MEMORIAL MEDICAL CENTER	
****************	**************
THIS IS A DR	ILL
DO NOT initiate actions affecting nor	mal plant operations.
*********	deletek kele le bele le le kele te te te le kele le le le le le le kele le te le ke
CONTAMINATION LEVELS INSIDE THE AMBULAL LIMITED TO THE STRETCHER (400 CPM > BK	

THIS IS A DR	ILL
teleleleteleteleleteleleteleteleteletel	iki lehehekekekekekehekehekehekehekehekeheke

EMERGENCY PREPAREDNESS DRILL

in the total to the total to the total to the total to

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 2	CUE CARD NO. 2-11
FOR: WHOLE BODY COUNTER OPERATOR	TIME: 1430+
LOCATION: WHOLE BODY COUNTER* (LGS, RMC)	
************************************	.
THIS IS A DRII	LL
DO NOT initiate actions affecting norma	al plant operations.
***********	kalekakakakakakakakakakak irisisisisisisisisis
SCAN INDICATES NEGATIVE FOR POSSIBLE INCOF RADIONUCLIDES.	GESTION
*SIMULATE THE EVENT IF WHOLE BODY COUNTY	ER IS NOT ACCESSIBLE.
kitele kekitekekitele kekitekekekitekitekekitekitekitekitekite	i ch letekekek kiris kekek kiris is is kelekele letek kiris is is is
THIS IS A DRII	LL

PreSelected Construction Workers Site Evacuation

Approximate Time

of Event:

1600

Location:

North parking lot.

Problem:

After an "Alert" has been declared by the control room, preselected Unit 2 construction personnel should evacuate.

Response:

All preselected construction workers should report to North parking lot for personnel accountability.

Controller

Locations:

One at North parking lot.

FOR CONTROLLER USE ONLY

RHR Pump (1BP202) Discharge Flow Drop

Approximate Time

of Event:

1615

Location:

RHR discharge valve (HV-51-1F047B) in reactor

enclosure el 217 ft-0 in.

Problem:

Discharge flow on RHR pump (1BP202) starts decreasing to 500 gpm. There are no apparent

problem indications in the control room.

Response:

An operator is sent to investigate the problem locally. An extremely loud noise is heard at the RHR discharge valve (HV-51-1F047B). The valve has partially closed and the operator's attempts to manually open the valve are unsuccessful. Due to the noise, the operator does not hear the announcement to evacuate the reactor enclosure at 1630, nor can he clearly communicate with the control room. Finally, a Search and Rescue/First Aid Group finds him and asks him to evacuate the

reactor building.

Controller Locations:

One accompanying the operator from the control

room.

FOR CONTROLLER USE ONLY

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 4	CUE CARD NO. 4-1
FOR: CONTROL ROOM OPERATOR	TIME: 1615
LOCATION: CONTROL ROOM	
*********	************
THIS IS	A DRILL
DO NOT initiate actions affecting	normal plant operations.

THERE ARE NO PROBLEM INDICATIONS IN	N THE CONTROL ROOM.
************************	*******
THIS IS	A DRILL
**********	*********************

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 4

CUE CARD NO. 4-2

FOR: OPERATOR INVESTIGATING RHR PUMP B TIME: 1615+

LOCATION: REACTOR ENCLOSURE

217 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

AN EXTREMELY LOUD NOISE IS HEARD AT RHR DISCHARGE VALVE HV-51-1F047B. THE VALVE HAS PARTIALLY CLOSED AND ATTEMPTS TO MANUALLY OPEN IT ARE UNSUCCESSFUL. YOU CANNOT CLEARLY COMMUNICATE WITH THE CONTROL ROOM DUE TO HIGH BACKGROUND NOISE.

to be the best of the best of

THIS IS A DRILL

Search and Rescue/First Aid Group

Approximate Time

of Event:

1650

Location:

RHR discharge valve (HV-51-1F047B) in reactor

enclosure el 217 ft-0 in.

Problem:

An operator was dispatched to investigate the cause for RHR pump B discharge flow drop at 1615. Communication with the dispatched operator becomes very difficult due to extreme background noise. Due to high radiation levels, evacuation of the reactor building is ordered at 1630. The operator

is still unaccounted for at 1650.

Response:

A Search and Rescue/First Aid Group is dispatched to find the operator. They find the operator and

evacuate the reactor building.

Controller Locations:

One accompanying the Search Group from the OSC.

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 5

CUE CARD NO. 5-1

FOR: SEARCH AND RESCUE/FIRST AID GROUP TIME: 1650+

LOCATION: DECONTAMINATION AREA

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

RESULTS OF PERSONNEL CONTAMINATION SURVEY WITH INSTRUMENT ARE <100 cpm.

THIS IS A DRILL

Low Pressure Alarm at The CO2 Storage Unit (00S133)

Approximate Time

of Event:

1715

Location:

CO2 Storage Unit 00S133, in turbine enclosure el

239 ft-0 in.

Problem:

A low pressure alarm from the CO2 storage unit

(00S133) is received at 1715.

Response:

A Damage Repair Group is dispatched to investigate the problem. The control room is notified that the pressure relief valve PSV-22-065 is leaking and the ${\rm CO}_2$ portion of the Fire Protection System is inoperable due to low tank (00S133) pressure at

1730.

A continuous fire watch is established for those areas in which redundant systems or components could be damaged. For other areas, establish an

hourly fire watch patrol.

Controller Locations:

One in the control room. One accompanying the

dispatched Damage Repair Group.

FOR CONTROLLER USE ONLY

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 6

CUE CARD NO. 6-1

FOR: DAMAGE REPAIR GROUP LEADER INVESTIGATING TIME: 1715+

STORAGE UNIT 00S133 LOW PRESSURE ALARM

LOCATION: TURBINE ENCLOSURE

239 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

A WHISTLING NOISE CAN BE HEARD AT PRESSURE RELIEF VALVE PSV-22-065. LOW TANK (00S133) PRESSURE ALARM.

to the body to be to be the transfer of the transfer to the tr

THIS IS A DRILL

Fire at The East RHR Heat Exchanger Room (103)

Approximate Time

of Event:

1730

Location:

East RHR heat exchanger room (103) in reactor

enclosure el 177 ft-0 in.

Problem:

Alarms sound at 1730 indicating a fire in the east RHR heat exchanger room on reactor enclosure el 177 ft-0 in. Cause of the fire is unknown, but it is fueled by scaffolding material brought there in preparation for an inspection of the RHR heat exchanger. The fire has disabled both RHR pump

B & D motors.

Response:

Fire Fighting Group members are dispatched to the

scene and they are able to extinguish the fire at

1800.

Controller Locations:

One in the area.

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 7

CUE CARD NO. 7-1

FOR: FIRE FIGHTING GROUP MEMBERS

TIME: 1730+

LOCATION: REACTOR ENCLOSURE

117 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

EAST RHR HEAT EXCHANGER ROOM (103) IS ON FIRE. THE FIRE IS FUELED BY SCAFFOLDING MATERIAL LEFT NEAR THE RHR HEAT EXCHANGER. OFFSITE ASSISTANCE IS NOT NEEDED. MOTORS FOR BOTH RHR PUMPS B AND D HAVE BEEN DISABLED.

THIS IS A DRILL

in led eleterate lederate le

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/E/ENT NO. 7

CUE CARD NO. 7-2

FOR: FIRE FIGHTING GROUP MEMBERS

TIME: 1800

LOCATION: REACTOR ENCLOSURE

117 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

FIRE IS OUT.

THIS IS A DRILL

Mickle Kickele Kickel

Containment Purge Exhaust Line Leakage

Approximate Time

of Event:

1845

Location:

Containment purge exhaust line isolation valves (HV-57-113), (HV-57-114) and (HV-57-115) in reactor

enclosure el 283.

Problems:

Status lights on the control board indicate the containment isolation valve (HV-57-114) in the containment purge system has backed off the fully closed position at 1845. Reactor enclosure local radiation levels in the area of the containment purge system line are increasing. The releases are due to leakage pass the closed isolation valve (HV-57-115) in the containment purge line. Status lights on the control board indicate that the containment purge line isolation valve (HV-57-115)

is unseated at 1915.

Response:

Damage Repair Group is sent to investigate and try to shut the valves locally. Dispatched personnel estimate that it will take 10 hours to terminate the release. The containment purge line valve (HV-57-115) is repaired at 2145 and releases to the

atmosphere are terminated.

Controller Locations:

One accompanying the dispatched team.

FOR CONTROLLER USE ONLY

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 8

CUE CARD NO. 8-1

FOR: GROUP INVESTIGATING CONTAINMENT PURGE

TIME: 1845+

EXHAUST VALVES.

LOCATION: REACTOR ENCLOSURE

283 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

CONTAINMENT PURGE EXHAUST VALVE HV-57-114
HAS BACKED OFF CLOSED-POSITION. EFFORTS
TO MANUALLY SHUT VALVES HV-57-113 OR
HV-57-114 ARE UNSUCCESSFUL.

THIS IS A DRILL

inicicled where the lateral electric inicicles in inicial electric inici

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 8

CUE CARD NO. 8-2

FOR: GROUP INVESTIGATING CONTAINMENT PURGE TIME: 1915+

EXHAUST VALVES.

LOCATION: REACTOR ENCLOSURE 283 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

CONTAINMENT PURGE EXHAUST VALVE HV-57-115 HAS ALSO BACKED OFF CLOSED-POSITION AND IS OPEN. THE MANUAL HANDWHEEL DOES NOT TURN. REPAIR ESTIMATES ARE 10 HOURS TO SHUT THIS VALVE.

THIS IS A DRILL

to the transfer of the transfe

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 8	CUE CARD NO. 8-3
FOR: GROUP INVESTIGATING CONTAINMENT PURGE EXHAUST VALVES.	TIME: 2145
LOCATION: REACTOR ENCLOSURE 283 FT-0 IN., EL	
***********	. *************
THIS IS A DRILL	
DO NOT initiate actions affecting normal	plant operations.
******************	.
CONTAINMENT PURGE EXHAUST VALVE HV-57-115	IS REPAIRED.
*******************************	ekkkkkkkikkk kkkkkkickickickk
THIS IS A DRILL	
in the invitation in the invit	ek kekeke le le le kekele kele le le le kele le kele le

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 8	CUE CARD NO. 8-4
FOR: GROUP INVESTIGATING CONTAINMENT PURGE EXHAUST VALVES.	TIME: 2200
LOCATION: REACTOR ENCLOSURE 283 FT-0 IN., EL	
******	kkkkiikkkkkkkkkkkkkkk
THIS IS A DRILL	
DO NOT initiate actions affecting normal	plant operations.
***********	kakakakakakakakakakakakakakakak
CONTAINMENT PURGE EXHAUST VALVE HV-57-114	IS REPAIRED.
**************************************	ininkrinink in in inininkrinink in inininkrinink in inininkri
THIS IS A DRILL	

in the first in th

Cooling Tower Blowdown Sample Analysis

Approximate Time

of Event:

1900

Location:

Chemistry laboratory, radwaste enclosure el 217

ft-0 in.

Problem:

The result of the 1830 sample of the cooling tower

blowdown is 7N6 µci/cc. Samples taken at 1815 and

1845 were both negative.

Response:

The control room and city authorities are informed

for possible Schuulkill River contamination.

Controller

Locations:

One in chemistry laboratory.

FOR CONTROLLER USE ONLY

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 9

CUE CARD NO. 9-1

FOR: CHEMISTRY TECHNICIAN

TIME: 1900

LOCATION: CHEMISTRY LAB., RADWASTE ENCLOSURE

217 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

COOLING TOWER BLOWDOWN SAMPLE TAKEN AT 1830 INDICATES 7N6 µCi/cc, FROM WHICH AT LEAST 60 PERCENT OF THE ACTIVITIY IS DUE TO TECHNETIUM - 99M.

SAMPLES TAKEN AT 1815 AND 1845 ARE BOTH NEGATIVE.

THIS IS A DRILL

Core Spray Pump A Trip

Approximate Time

of Event:

2040

Location:

Core Spray Pump 1AP206 in reactor enclosure el 177

ft-0 in.

Problem:

Core Spray Pump 1AP206 trips at 2040. Core Spray

Pump C is not affected and continues to operate.

Response:

After all attempts from the control room fail, a Damage Repair Group is dispatched to determine cause/solution for the pump trip. Due to high area radiation levels, the Group has to evacuate the reactor building without sufficient time to diagnose the problem. Core Spray Pumps B and D are manually initiated and Core Spray Pump C is

tripped.

Controller Locat ons:

One accompanying the dispatched team from OSC.

FOR CONTROLLER USE ONLY

EMERGENCY PREPAREDNESS DRILL

DRILL TYPE/EVENT NO. 10

CUE CARD NO. 10-1

FOR: GROUP INVESTIGATING CORE SPRAY PUMP 1AP206 TIME: 2040+

LOCATION: REACTOR ENCLOSURE 177 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

CORE SPRAY PUMP A IS SHUT OFF.

THE PUMP MOTOR IS SMOKING AND FEELS VERY HOT.

CORE SPRAY PUMP C IS RUNNING.

THIS IS A DRILL

EMERGENCY PREPAREDNESS DRILL

DRILL TYPS/EVENT NO. 10

CUE CARD NO. 10-2

FOR: GROUP INVESTIGATING COKE SPRAY PUMP 1AP206 TIME: 2040+

LOCATION: REACTOR ENCLOSURE

177 FT-0 IN., EL

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

DUE TO HIGH AREA RADIATION LEVELS, YOU HAVE TO LEAVE AND RETURN IN ABOUT 2 HOURS.

ARKETERIER KARIER CICRICK X MICKICKICK CICRICK KICKICK CICRICK KICKICK KICKICK

THIS IS A DRILL

to lock to be to b

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Full Power

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Initial Conditions:

Unit 1 has accumulated 8 full power months of operation since the previous refueling. At that time, 15 fuel assemblies of a new design were installed so that they could be qualified under commercial operating conditions. The 15 fuel assemblies represent about 2 percent of the fuel in the core. On two occasions in the past three months, Unit 1 has experienced reactor trips caused by spurious main steam isolation valve (MSIV) closure signal. All power generation equipment is operating, and all safety system equipment is operable. The initial plant and reactor system values are shown in the attached table.

The meteorological conditions at 1100 are characterized by the influence of an almost stationary high pressure area centered over Greenwich, Connecticut. The clockwise flow around its center is evident by the following ground level Limerick generating station met tower data:

Wind Direction Southeast (137 degrees)
Wind Speed 5.2 mph
Temperature 71°F
Delta Temperature -1.3°F
Sigma Theta 6.7 degrees azimuth

The National Weather Service indicates that the high is expected to slowly drift to the South during the next 12 to 24 hours. Skies will remain sunny with light winds gradually backing to the South-Southeast.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Initial Conditions:

Unit 1 has accumulated 8 full power months of operation since the previous refueling. At that time, 15 fuel assemblies of a new design were installed so that they could be qualified under commercial operating conditions. The 15 fuel assemblies represent about 2 percent of the fuel in the core. On two occasions in the past three months, Unit 1 has experienced reactor trips caused by spurious main steam isolation valve (MSIV) closure signal. All power generation equipment is operating, and all safety system equipment is operable. The initial plant and reactor system values are shown in the attached table.

The meteorological conditions at 1100 are characterized by the influence of an almost stationary high pressure area centered over Greenwich, Connecticut. The clockwise flow around its center is evident by the following ground level limerick generating station met tower data:

Wind Direction
Wind Speed
Southeast (137 degrees)

5.2 mpc

71°F
Delta Temperature
Sigma Theta
6.7 degrees

Southeast (137 degrees)

6.7 degrees

The National Weather Service and actes that the high is expected to slowly drift to the such during the next 12 to 24 hours. Skies will remain sunny with light winds gradually backing to the South-Southeast.



Limerick Generating Station Initial ant and Reactor System Values

Reactor Level	+35 inches	Drywell Press	_0.6_ psig
Reactor Pressure	1020 psig .	Drywell Atmos Temp	_130_ °F
Reactor Power	100 % Full Power	Supp Pool Press	0.6 psig
Core Plate DP	100 % Full Power	Supp Pool Temp	90 °F
Core Flow	100 lb/hr x 106	Supp Pool Level	22.1 feet
Total Steam Flow	_14_ lb/hr x 10 ⁶	Main Stm Line Rad Mon	1100 mR/hr
Total Feedwater Flow	_14_ lb/hr x 10 ⁶	Containment Rad Level	2 R/hr
Condenser Vacuum	inches Hg	Cond Stor Tank Level	
Hotwell Level	io_ inches	RCIC Flow	0_ gpm
CRD Charging Pressure	1300_ psig	HPCI Flow	0 gpm
Inst. Gas to ADS Pressure	110 psig	RHR A Flow	0 gpm
Equip. Drain Coll Tank Level	3 feet	RHR B Flow	0_ gpm
Equip. Drain Surge Tank Level	3_ feet	RHR C Flow	gpm
Floor Drain Coll Tank Level	4_ feet	RHR D Flow	0 gpm
Floor Drain Surge Tank Level	3_ feet	Core Spray A Flow	0 gpm
H ₂ Concentration	_ 0 %	Core Spray B Flow	0 gpm
0 ₂ Concentration	2.8 %	RHR Hx Outlet Temp	80 °F
SGTS Flow		RHR SW Inlet Temp	_80 °F
North Vent Stack Concentration	5N6 µC1/cc	North Vent Stack Release Rate	7P2 µC1/sec

TABLE (con't)

Limerick Generat... Station Area Radiation Monitor Readings (mR/hr)

Area Radiation Monitor Readings (mR/hr) Time: 1100 Date: 7-25-8				7-25-84
AICH No	. Location	Reading	ARM No. Location	Reading
KE-01	RCIC Pump Compartment	100.	RE-22 RWCU Pump Area	0.5
RE-02	HPC1 Pump Compartment	80.	RE-23 Standby Liquid Control Sys. Area	0.5
RE-03	Sump Compartment	1	RE-24 RWCU Instrument Rack Area	1.
RE-04	CRD Pumps Area	0.2	RE-25 Turbine Auxiliary Bay	0.5
RE-05	Turbine Aux. Bay Hallway	0.2	RE-27 RWCU Filter Area	1.
RE-06	Isolation Valve Compartment	0.5	RE-28 Equip. Compt. Exh. Filters Area	0.5
RE-07	Condensate Pump Compartment	90.	RE-34 Hydrogen/Oxygen Analyzers Area	0.2
RE-08	RITR Division I Compartment	8	RE-36 OSC Area	0.5
RE-09	RHR Division II Compartment	8	RE-41 Sludge Discharge Mixing Pump Room	0.2
RE-10	Steam Vent Area Stairwell	0.5_	RE-42 Radwaste Enclosure Hallway	0.2
KE-12	Hallway, Condensate Filter Demins.	0.7_	RE-43 Concentrate Stor. Disch. Pump Room	0.5
RE-13	Condensate Area	_50	RE-46 Fuel Pool Holding Pump Room	0.5
RE-15	CRD HCU Area East	0.5	RE-47 Precoat Tank & Pump Room	0.5
RE-16	CRD HCY Area West	0.5	RE-51 Radwaste Enclosure Hallway	0.2
RE-17	Neutron Monitoring System Area	0.5	RE-55 Radwaste Exhaust Fan Area	0.1
RE-18	Neutron Monitoring Drive Mechanism	0.5	RE-56 Control Room	0.1
RE-19	Turbine Auxiliary Bay Hallway East	100.	RE-57 Turbine Area Operating Floor	0.5
RE-20	Turbine Auxiliary Bay Hallway West	100.	RE-58 Standby Gas Treatment Filter Room	0.5
RE-21	RWCU Heat Exchanger Area	0.5	RE-60 North Vent Stack Sample	0.5

TABLE 1 (cont) LIMERICK GENERATING STATION

TIME: 1100 DATE: 7-25-84

	Reactor Coolant Activity Concentration (µCi/gm)	Drywell and Suppression Chamber Air Concentration (µCi/gm)
Kr-85	4.N2	1.N6
Kr-85M	8.N1	2.N5
Kr-87	6.N4	2.N5
Kr-88	2.	5.N5
Xe-133	4.	1.N4
Xe-135	4.	1.N4
Total Noble Gas	1.P2	2.N3
I-131	5.N3	2.N8
I-133	1.N1	3.N9
Total Iodine	8.N1	2.N7
Gross Beta	1.6P2	4.N3

TABLE 1 (cont)

LIMERICK GENERATING STATION

SUPPRESSION POOL ACTIVITY CONCENTRATIONS (µC1/gm)

TIME: 1100 DATE: 7-25-84

I-131 5.N7
I-133 3.N8
Total Noble Gas 7.N7
Gross Beta 2.N5

TABLE 1 (cont) LIMERICK GENERATING STATION ISOTOPIC STACK CONCENTRATIONS

TIME: 1100 DATE: 7-25-84

	North Vent ¹ (µCi/cc)	South Vent ² (µC1/cc)
Kr-85	2.0N8	2.0N8
Kr-85M	4.2N7	1.3N7
Kr-87	1.2N7	2.4N7
Kr-88	9.0N7	3.6N7
Xe-133	1.8N6	9.2N7
Xe-135	1.8N6	1.8N7

¹ Assume North Vent Stack Flow Rate of 300,000 cfm.

² Assume South Vent Stack Flow Rate of 120,000 ~fm.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Alarm is received in the control room due to a fire in

the turbine enclosure at elevation 217 ft-0 in. Offsite

assistance is required.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Fire ALARM at instrument air compressor 1AK101 in

turbine enclosure. (Event No. 1)

ACTION EXPECTED: "Unusual Event" should be declared. Fire Fighting Group

should be dispatched to the scene.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Fire ALARM at instrument air compressor 1AK101 in

turbine enclosure.

ACTION EXPECTED:

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Spurious MSIV's closure which causes Reactor Scram.

Reactor vessel pressure increases to 1170 psig. Reactor

water level decreases.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

MSIVs close.

Reactor scrams.

SRVs open.

ACTION EXPECTED:

"Unusual Event" should be declared.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

MSIVs close.

Reactor scrams.

SRVs open.

ACTION EXPECTED:

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: The reactor pressure and water level have decreased to

1050 psig and -38 in., respectively.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

HPCI and RCIC systems are initiated.

Standby gas treatment system (SGTS) is initiated.

ACTION EXPECTED:

Two SRVs are kept open to control pressure.

Date _____7/25 ___Time 1316

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

HPCI and RCIC systems are initiated.

Standby gas treatment system (SGTS) is initiated.

ACTION EXPECTED:

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor pressure and water level are 1025 psig and

+50 in., respectively.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

teletekikkikkikieletekikkikieletekiki */ckielekikieletekikielekikieletekieletekieletekikieletekieletekieleteki

MESSAGE: High drywell pressure ALARM

ACTION EXPECTED: HPCI pump is manually operated for pressure/level

control.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

High drywell pressure ALARM

Date _____7/25 ____Time 1330

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Drywell pressure has increased to 1.68 psig.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Containment group isolations occur on high drywell

pressure. HPCI is initiated in injection mode and trips

at +54 in.

ACTION EXPECTED: HPCI is initiated and operated for pressure/level

control when the high reactor water level signal clears.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL '

DO NOT initiate actions affecting normal plant operations.

wiekieleinie

MESSAGE:

Containment group isolations occur on high drywell pressure. HPCI is initiated in injection mode and trips at +54 in.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor pressure and water level are 860 psig and

+50 in, respectively. Suppression pool temperature is

110°F.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: RHR A and B pumps are lined up for suppression pool

cooling mode.

ACTION EXPECTED: Depressurization of the reactor using SRVs has begun

since 1345.

Date ____7/25 ___Time 1400

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

in keleber in the langer is the langer in the langer in

MESSAGE:

RHR A and B pumps are lined up for suppression pool cooling mode.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor vessel cooldown is continued.

in the interpretation of the interpretation in the interpretation

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

deletekirkik kikirkik kikirkik kikirkik kikirki kikirkirki kikirkirkirkirkirkirkirkirkiri kikiriri kiriri kiri

An assistant operator has been found unconscious lying MESSAGE:

in a puddle that appears to be leakage from the fuel pool holding pump (00P340). He is bleeding from a head

laceration. (Event No. 2)

Search and rescue/first aid group should be dispatched ACTION EXPECTED:

to the area. "Unusual Event" should be declared.

Date ___7/25 __Time 1430

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

in least the l

MESSAGE: An assistant operator has been found unconscious lying

in a puddle that appears to be leakage from the fuel pool holding pump (00P340). He is bleeding from a head

laceration.

Date ____7/25 ___Time 1545

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Teactor pressure and water level are 440 psig and

+50 in., respectively.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Core Spray (CS) and RHR in the LPCI mode are initiated.

ACTION EXPECTED: RHR A and B pumps are returned to suppression pool

cooling mode.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Core Spray (CS) and RNR in the LPCI mode are initiated.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Sample analyses reveal primarily noble gases in the

drywell atmosphere.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Drywell radiation level has increased to 100 R/hr.

ACTION EXPECTED: "Alert" should be declared.

Date ____7/25 ___Time 1600

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Drywell radiation level has increased to 100 R/hr.

Date ____7/25 ___Time 1615

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor pressure and water level are 380 psig and

+50 in., respectively.

tekekekekekekekekeinin keleinin keleini

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: RHR pump B flow has decreased to 500 gpm. (Event No. 4)

ACTION EXPECTED: An operator is dispatched to investigate the problem

with the RHR pump B.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

in the last the las

MESSAGE:

RHR pump B flow has decreased to 500 gpm.

CONTINGENCY MESSACE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Airborne radiation levels in the reactor enclosure start

rising significantly due to small leakage from the

primary containment.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Due to high airborne radiation levels, evacuation of the

Unit 1 reactor enclosure is required.

ACTION EXPECTED: Reactor enclosure personnel accounting and investigation

for high airborne radiation source.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

with initial classical with the initial classical clas

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

which in the lateral elements in the lateral element

MESSAGE:

Due to high airborne radiation levels, evacuation of the

Unit 1 reactor enclosure is required.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Airborne radiation levels in the reactor enclosure still

rising.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: The person investigating RHR pump B is unaccounted for.

(Event No. 5)

ACTION EXPECTED: A Search and Rescue/First Aid Group is dispatched to

find the person investigating the RMR pump B and to ask

him to evacuate reactor enclosure.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

the late the late that the late the late that the late that the late that the late the late the late the late that the late the late the late that the late the late that the late that the late th

TILS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: The person investigating RHR pump B is unaccounted for.

Date ____7/25 ___Time 1700

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor pressure is 300 psig. Drywell pressure is

leveling off at 4.5 psig.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: RCIC and HPCI pumps are manually tripped.

ACTION EXPECTED: Reactor vessel is flooded with CS and LPCI.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

RCIC and HPCI pumps are manually tripped.

Date ____7/25 ___Time 1715

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: LPCI is manually tripped once the reactor vessel is

flooded. Cooldown is continued by circulating reactor vessel inventory through the SRVs to the suppression

pool using available CS pumps.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: CO2 storage unit 00S133 low pressure ALARM. (Event

No. 6)

ACTION EXPECTED: Investigation for the cause of the ALARM.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

in the kind the kin

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

which is in the interpolation of the interpolation is in the interpolation of the interpola

MESSAGE: CO2 storage unit 00S133 low pressure ALARM.

Date _____7/25 ____Time 1730

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor vessel cooldown is continued.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: CO2 portion of the fire protection system is inoperable

due to low tank pressure. (Event No. 6)

ACTION EXPECTED: A continuous fire watch should be established for those

areas in which redundant systems or components could be damaged. For other areas, an hourly fire watch patrol

is established.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

CO2 portion of the fire protection system is inoperable

due to low tank pressure.

Date _____7/25 ___Time 1730

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Reactor vessel cooldown is continued.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

East RHR heat exchanger room (103) fire ALARM.

RHR pump B trips. (Event No. 7)

ACTION EXPECTED: Fire Fighting Group is dispatched to the scene.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

East RHR heat exchanger room (103) fire ALARM.

RHR pump B trips.

Date ____7/25 ___Time 1730+

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Cause of the fire is unknown, but it is fueled by

scaffolding material brought there in preparation for an inspection of the RHR heat exchangers. Fire has

disabled both RHR pump B and D motors.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Drywell radiation level 1000 R/hr.

ACTION EXPECTED: "Site Emergency" should be declared.

Date 7/25 Time 1730+

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Drywell radiation level 1000 R/hr.

Date ____7/25 ___Time 1845

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Containment purge exhaust isolation valve HV-57-114

indicates open position.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Status lights on the control board indicate the con-

tainment isolation valve HV-57-114 in the containment purge system has backed off the fully closed position.

(Event No. 8)

ACTION EXPECTED: Repeated attempts from the control room to close the

valve.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

in location which is the description of the descr

MESSAGE:

Status lights on the control board indicate the containment isolation valve HV-57-114 in the containment purge system has backed off the fully closed position.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Repeated attempts from the control room to close the

containment purge exhaust isolation valves are

unsuccessful.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Containment purge exhaust isolation valve HV-57-115

indicates open position. (Event No. 8)

ACTION EXPECTED: Personnel will be dispatched to try to shut the valves

locally.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Containment purge exhaust isolation valve HV-57-115

indicates open position.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: The radiation release path to the atmosphere is still

open. It is estimated that it will take about 9 hours

to terminate the release.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: CS pump A trips.

CS pump C is not affected and continues to operate.

(Event No. 10)

ACTION EXPECTED: Personnel will be dispatched to investigate the problem.

CS B and D pumps are manually initiated.

CS pump C is tripped.

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

telephological elements to the telephological elements telephological elements to the telep

MESSAGE:

CS pump A trips.

CS pump C is not affected and continues to operate.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Releases to the atmosphere are terminated.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Containment purge exhaust isolation valve HV-57-115 is

repaired. (Event No. 8)

ACTION EXPECTED: Deescalation of emergency to "Site Emergency" and later

to "Alert" status is considered.

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Containment purge exhaust isolation valve HV-57-115 is

repaired.

Date __ 7/25 Time 2200

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS: Releases to the atmosphere are terminated.

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE: Containment purge exhaust isolation valve HV-57-114 is

repaired. (Event No. 8)

ACTION EXPECTED: Deescalation of emergency to "Site Emergency" and later

to "Alert" status is considered.

Date 7/25 Time 2200

CONTINGENCY MESSAGE

MESSAGE FOR: Control Room

SIMULATED

PLANT CONDITIONS:

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Containment purge exhaust isolation valve HV-57-114 is

repaired.

HEADQUARTERS SUPPORT MESSAGE

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 1830

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Headquarters engineering support is needed to devise supplementary radwaste processing methods. Temporary system and storage tanks should be sent to LGS as soon as possible.

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

DATE: 7/25/84 TIME: 1830

MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Headquarters engineering support is needed to devise supplementary radwaste processing methods. Temporary system and storage tanks should be sent to LGS as soon as possible.

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 1850

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Headquarters support is needed to expedite the following purchasing requirements:

300 Anticontamination Suits and Hoods

500 Pairs of Rubber Gloves

1,000 Rolls of 2 in. Masking Tape

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

DATE: 7/25/84 TIME: 1850

MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Headquarters support is needed to expedite the following purchasing requirements:

300 Anticontamination Suits and Hoods

500 Pairs of Rubber Gloves

1,000 Rolls of 2 in. Masking Tape

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

DATE: 7/25/84 TIME: 1910

MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Investigate arrangements for feeding emergency center and plant personnel on an extended basis.

HEADER SUPPORT MESSAGE

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 1925

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

The Lieutenant Governor is requesting a visit to the TSC and a briefing of the plant status. State House press representatives will accompany him. A PECO representative should be assigned to contact him.

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

HEADER SUPPORT MESSAGE

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 1925

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

The Lieutenant Governor is requesting a visit to the TSC and a briefing of the plant status. State House press representatives will accompany him. A PECO representative should be assigned to contact him.

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 2030

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

There is an immediate need for 20 RM-14 Friskers at LGS. Units should be purchased or borrowed from supporting organizations.

ACTIONS EXPECTED:

Submit request o Site Emergency Coordinator.

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 2030

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

There is an immediate need for 20 RM-14 Friskers at LGS. Units should be purchased or borrowed from supporting organizations.

HEADQUARTERS SUPPORT MESSAGE

MESSAGE FOR: EMERGENCY DIRECTOR

DATE 7/25/84 TIME: 2050

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

A call has been received from a Lieutenant of the Pennsylvania State Police. He would like to coordinate road blocking status with a PECO representative in Philadelphia.

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

DATE 7/25/84 TIME: 2050

MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

A call has been received from a Lieutenant of the Pennsylvania State Police. He would like to coordinate road blocking status with a PECO representative in Philadelphia.

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 2110

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

A call has been received from a panicked nearby resident requesting help. A family member who was outside when the public alert sirens came on, has started vomiting and there is fear for high radiation dose exposure.

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 2110

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

A call has been received from a panicked nearby resident requesting help. A family member who was outside when the public alert sirens came on, has started vomiting and there is fear for high radiation dose exposure.

HEADQUARTERS SUPPORT MESSAGE DATE: 7/25/84 TIME: 2130
MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

I&C support is requested from headquarters to analyze the effects of steam and radiation in containment on instrumentation. Need to know from environmental qualification data if any instruments are susceptible to continue reading on scale after failure.

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

DATE: 7/25/84 TIME: 2130

MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

I&C support is requested from headquarters to analyze the effects of steam and radiation in containment on instrumentation. Need to know from environmental qualification data if any instruments are susceptible to continue reading on scale after failure.

HEADQUARTERS SUPPORT MESSAGE

DATE: 7/25/84 TIME: 2150

MESSAGE FOR: EMERGENCY DIRECTOR

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Construction personnel are required to erect a temporary wooden storage building, with 200,000 cu ft storage capacity. Building will be used to store emergency equipment enroute to LGS and is to be erected near the information center parking lot area.

ACTIONS EXPECTED:

Submit request to Site Emergency Coordinator.

MESSAGE FOR: EMERGENCY DIRECTOR

DATE: 7/25/84 TIME: 2150

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Construction personnel are required to erect a temporary wooden storage building, with 200,000 cu ft storage capacity. Building will be used to store emergency equipment enroute to LGS and is to be erected near the information center parking lot area.

HEADQUARTERS SUPPORT MESSAGE DATE: 7/25/84 TIME: 2210 MESSAGE FOR: EMERGENCY DIRECTOR THIS IS A DRILL DO NOT initiate actions affecting normal plant operations. MESSAGE: Headquarters QA/QC support is needed to inspect emergency repair methods and approve welding in process. ACTIONS EXPECTED: Submit request to Site Emergency Coordinator.

MESSAGE FOR: EMFRGENCY DIRECTOR

DATE: 7/25/84 TIME: 2210

THIS IS A DRILL

DO NOT initiate actions affecting normal plant operations.

MESSAGE:

Headquarters QA/QC support is needed to inspect emergency repair methods and approve welding in process.

Time 1100 Hours	. 1		LGS 7/25
Reactor Level	+35 inches	Drywell Press	0.6 psig
Reactor Pressure	1020 psig	SGTS Flow	O cfm
Reactor Power	100 % Full Power	Drywell Atmos Temp	130 °F
Core Plate DP	100 % Full Power	Supp Pool Press	0.6 psig
Core Flow	100 lb/hr x 106	Supp Pool Temp	90 °F
Total Steam Flow	14 lb/hr x 106	Supp Pool Level	22./ feet
Total Feedwater Flow	14 lb/hr x 106	Main Stm Line Rad Mon	//00 mR/hr
Condenser Vacuum	29 inches Hg	Containment Rad Level	2 R/hr
Hotwell Level	40 inches	Cond Stor Tank Level	38 feet
CRD Charging Pressure	1300 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	110 paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	O gpm
Equip. Drain Surge Tank Level	3 feet	RIER B Flow	_ O gpm
Floor Drain Coll Tank Level	# feet	Core Spray A Flow	_ O gpm
Floor Drain Surge Tank Level	3. feet	Core Spray B Flow	O gpm
H ₂ Concentration	0 1	RHR Hx Outlet Temp	80 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time	1130	Hours		•
Reactor Leve	:1		+35 inches	Drywell Press
Reactor Pres	sure		1020 psig	SGTS Flow

100 % Full Power

100 % Full Power

100 lb/hr x 106

14 lb/hr x 106

14 lb/hr x 106

29 inches Hg

40 inches

1300 psig

//O psig

3 feet

3 feet

4 feet

3 feet

0 %

2.8 %

Drywell Press	0.6 psig
SGTS Flow	
Drywell Atmos Temp	130 °F
Supp Pool Press	0.6 psig
Supp Pool Temp	90 °F
Supp Pool Level	22./ feet
Main Stm Line Rad Mon	//00 mR/hr
Containment Rad Level	_2 R/hr
Cond Stor Tank Level	38 feet
RCIC Flow	_ O gpm
HPCI Flow	O gpm
RHR A Flow	
RHR B Flow	O gpm
Core Spray A Flow	O gpm
Core Spray B Flow	O gpm
RHR Hx Outlet Temp	80 °F
RHR SW Inlet Temp	80 °F
RHR C Flow	O 8bm
RHR D Flow	_O_gpm

LGS

7/25

Reactor Power

Core Plate DP

Total Steam Flow

Condenser Vacuum

H2 Concentration

02 Concentration

Notwell Level

Total Feedwater Flow

CRD Charging Pressure

Inst. Gas to ADS Pressure

Equip. Drain Coll Tank Level

Equip. Drain Surge Tank Level

Floor Drain Coll Tank Level

Floor Drain Surge Tank Level

Core Flow

Time 1200 Hours	1		LGS	7/25
Reactor Level	+35 inches	Drywell Press	0.6	psig
Reactor Pressure	1020 psig	SGTS Flow	0	cfm
Reactor Power	100 % Full Power	Drywell Atmos Temp	130	oř
Core Plate DP	100 % Full Power	Supp Pool Press	0.6	psig
Core Flow	100 lb/hr x 106	Supp Pool Temp	90	oF.
Total Steam Flow	14 1b/hr x 106	Supp Pool Level	22.1	feet
Total Feedwater Flow	14 lb/hr x 106	Main Stm Line Rad Mon	1100	mR/hr
Condenser Vacuum	29 inches Hg	Containment Rad Level	2	R/hr
Hotwell Level	40 inches	Cond Stor Tank Level	38	feet
CRD Charging Pressure	1300 psig	RCIC Flow	0	gpm
Inst. Gas to ADS Pressure	//0 psig	HPCI Flow	0	gpm
Equip. Drain Coll Tank Level	_3_ feet	RIIR A Flow	0	gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	0	gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	_0_	gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	0	gpm
H ₂ Concentration	1 2	RHR Hx Outlet Temp	80	°F
0 ₂ Concentration	2.8 2	RHR SW Inlet Temp	80	oF.
		RHR C Flow	0	gpm
		RHR D Flow	0	gpm

		- 4		
-1		-1		8
		17		,
	ь.		,	r

Time 1230

Hours

-		
	ce	
-	-	

7/25

Reactor Level	+35 inches	Drywell Press	0.6 psig
Reactor Pressure	1020 psig	SGTS Flow	<u>0</u> cfs
Reactor Power	100 % Full Power	Drywell Atmos Temp	_130 °F
Core Plate DP	100 % Full Power	Supp Pool Press	O.6 psig
Core Flow	100 lb/hr x 106	Supp Pool Temp	90 °F
Total Steam Flow	14 lb/hr x 106	Supp Pool Level	22.1 feet
Total Feedwater Flow	/4 lb/hr x 106	Main Stm Line Rad Mon	//00 mR/hr
Condenser Vacuum	29 inches Hg	Containment Rad Level	2 R/hr
Hotwell Level	40 inches	Cond Stor Tank Level	38 feet
CRD Charging Pressure	/300 psig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O psig	HPCI Flow	O gpm
Equip'. Drain Coll Tank Level	3 feet	RHR A Flow	O gpm
Equip. Drain Surge Tank Level	7 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	
H ₂ Concentration	01	RHR Hx Outlet Temp	80 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	_O_ gpm

	-	-	-	-

Reactor Level	+35 inches	Drywell Press	0.6 psig
Reactor Pressure	1020 psig	SGTS Flow	
Reactor Power	100 % Full Power	Drywell Atmos Temp	130 °F
Core Plate DP	100 % Full Power	Supp Pool Press	0.6 psig
Core Flow	100 lb/hr x 106	Supp Pool Temp	90 °F
Total Steam Flow	14 lb/hr x 106	Supp Pool Level	22.1 feet
Total Feedwater Flow	// lb/hr x 106	Main Stm Line Rad Mon	1100 mR/hr
Condenser Vacuum	29 inches Hg	Containment Rad Level	2 R/hr
Hotwell Level	40 inches	Cond Stor Tank Level	38 feet
CRD Charging Pressure	1300 psig	RCIC Flow	gpm
Inst. Gas to ADS Pressure	//o paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level		RHR A Flow	O gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	_O_ 8pm
H ₂ Concentration	0 1	RHR Hx Outlet Temp	80 °F
0 ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 13.15 Hours			LGS	7/25
Reactor Level	+35 inches	Drywell Press	0.6	psig
Reactor Pressure	1000 psig	SGTS Flow	0	cfm
Reactor Power	100 % Full Power	Drywell Atmos Temp	130	oF.
Core Plate DP	100 % Full Power	Supp Pool Press	0.6	psig
Core Flow	/00 lb/hr x 106	Supp Pool Temp	90	oF.
Total Steam Flow	/4 lb/hr x 106	Supp Pool Level	22.	feet
Total Feedwater Flow	_/4 lb/hr x 106	Main Stm Line Rad Mon	1100	mR/hr
Condenser Vacuum	29 inches Hg	Containment Rad Level	2	R/hr
Hotwell Level	40 inches	Cond Stor Tank Level	38	feet
CRD Charging Pressure	<u>1300</u> psig	RCIC Flow	0	gpm
Inst. Gas to ADS Pressure		HPCI Flow	0	gpm
Equip. Brain Coll Tank Level	_3_ feet	RHR A Flow	0	_ gpm
Equip. Drain Surge Tank Level	_3_ feet	RHR B Flow	0	_ gpm
Floor Drain Coll Tank Level	_4_ feet	Core Spray A Flow	0	_ gpm
Floor Drain Surge Tank Level		Core Spray B Flow	0	gpm
H ₂ Concentration	0 %	RHR Hx Outlet Temp	80	°F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80	°F
		RHR C Flow	0	_ gpm
		RHR D Flow) gpm

Reactor Level	O inches	Drywell Press	0,6 psig
Reactor Pressure	//00 psig	SGTS Flow	
Reactor Power	O % Full Power	Drywell Atmos Temp	
Core Plate DP	20 % Full Power	Supp Pool Press	0.6 psig
Core Flow	20 lb/hr x 106	Supp Pool Temp	90 °F
Total Steam Flow	O 1b/hr x 106	Supp Pool Level	22.2 feet
Total Feedwater Flow	2 lb/hr x 106	Main Stm Line Rad Mon	150 mR/hr
Condenser Vacuum	25 inches Hg	Containment Rad Level	/_ R/hr
Hotwell Level	40 inches	Cond Stor Tank Level	38 feet
CRD Charging Pressure	1300 paig	RCIC Flow	
Inst. Gas to ADS Pressure	//O psig	HPCI Flow	
Equip. Drain Coll Tank Level		RIIR A Flow	
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	
Floor Drain Coll Tank Level		Core Spray A Flow	_O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	0 1	RHR Hx Outlet Temp	80 °F
0 ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time /3/7 Hours			I.GS 7/25
Reactor Level	-40 inches	Drywell Press	0.8 psig
Reactor Pressure	1040 psig	SGTS Flow	3000 cfe
Reactor Power	O % Full Power	Drywell Atmos Temp	130 °F
Core Plate DP	20 % Full Power	Supp Pool Press	O.b psig
Core Flow	20 lb/hr x 106	Supp Pool Temp	90 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.6 feet
Total Feedwater Flow	O 1b/hr x 106	Main Stm Line Rad Mon	120 mR/hr
Condenser Vacuum	_O_inches Hg	Containment Rad Level	_/_ R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	36.6 feet
CRD Charging Pressure	1300 psig	RCIC Flow	<i>630</i> 8₽m
Inst. Gas to ADS Pressure		HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	8Pm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	_ O gpm
H ₂ Concentration	0 1	RHR Hx Outlet Temp	80 °F
0 ₂ Concentration	2.3 %	RHR SW Inlet Temp	_80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 1325 Hours			LGS 7/25
Reactor Level	+50 inches	Drywell Press	
Reactor Pressure	1025 psig	SGTS Flow	7000 cfm
Reactor Power	O % Fuil Power	Drywell Atmos Temp	144 °F
Core Plate DP	20 % Full Power	Supp Pool Press	O.8 psig
Core Flow	20 lb/hr x 106	Supp Pool Temp	9/ °F
Total Steam Flow	_ 0 lb/hr x 106	Supp Pool Level	22.7 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	85 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	_/_ R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	26.6 feet
CRD Charging Pressure	1300 psig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure	110 psig	HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	O gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	0 1	RHR Hx Outlet Temp	_80 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time	1350	Hours

Reactor Level

+50 inches

O % Full Power

20 % Full Power

20 lh/hr x 106

O 1b/hr x 106

O 1b/hr x 106

O inches Hg

39 inches

1300 psig

110 psig

3 feet

3 feet

4 feet

3 feet

0 %

2.8 %

1020 psig

	LGS
Drywell Press	
SGTS Flow	
Drywell Atmos Temp	
Supp Pool Press	
Supp Pool Temp	
Supp Pool Level	

1.68 psig
3000 cf
150 °F
1.0 psig
93 of
22.7 feet
70 mR/hr
/ R/hr
26. feet
630 gpm
5600 gpm
O gpm
O gpm
O gpm
O gpm
80 °F
80 °F
O gpm

O gpm

7/25

SGTS Flow
Drywell Atmos Temp
Supp Pool Press
Supp Pool Temp
Supp Pool Level
Main Stm Line Rad Mon
Containment Rad Level
Cond Stor Tank Level
RCIC Flow
HPCI Flow
RHR A Flow
RHR B Flow
Core Spray A Flow
Core Spray B Flow
RHR Hx Outlet Temp
RHR SW Inlet Temp
RHR C Flow

Reactor Level	+50 inches	Drywell Press	2.2 psig
Reactor Pressure	/000 psig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	
Core Plate DP	15 % Full Power	Supp Pool Press	_/./ psig
Core Flow	15 lb/hr x 106	Supp Pool Temp	99 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Tota' Feedwater Flow	_ 0 lb/hr x 106	Hain Stm Line Rad Mon	_35 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	_/_ R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	24.2 feet
CRD Charging Pressure	1300 psig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure		HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	_O gpm
Equip. Drain Surge Tank Level	3 feet	RHP B Flow	_O_ gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	0 1	RHR Hx Outlet Temp	80 °F
O ₂ Concentration	2.8 %	RIIR SW Inlet Temp	80 °F
		RHR C Plow	O gpm
		RHR D Flow	_O gpm

7/25

2.4 psig

3000 cfm

168 °F

110 °F

22.9 feet

25 mR/hr

2 R/hr

22.4 feet

630 gpm

5600 gpm

10,000 gpm

10,000 SPE

_O gpm

_ O gpm

95 of

80 °F

O gpm

O gpm

1.2 psig

T	7	ъ,	o	
в.	л	n	5	Ł
-	*	-	**	

**				_
н	വ	u	r	s
••	•	-	-	-

1400

Time

Reactor Level	+50 inches	Drywell Press	
Reactor Pressure	860 paig	SGTS Flow	
Reactor Power	O % Full Power	Drywell Atmos Temp	
Core Plate DP	10 % Full Power	Supp Pool Press	
Core Flow	/O lb/hr x 106	Supp Pool Temp	
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	
Condenser Vacuum	O inches Hg	Containment Rad Level	
Hotwell Level	39 inches	Cond Stor Tank Level	
CRD Charging Pressure	1160 paig	RCIC Flow	
Inst. Gas to ADS Pressure	110 psig	HPCI Flow	
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	
Equip. Drain Surge Tank Level	3 feet	RIIR B Flow	
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	
H ₂ Concentration	./ 1	RHR Hx Outlet Temp	
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	
		RHR C Flow	

RHR D Flow

Time 1415 Hours	1		LGS		1/25
Reactor Level	+50 inches	Drywell Press		2.8	
Reactor Pressure	.750 paig	SGTS Flow		3000	cfm
Reactor Power	O % Full Power	Drywell Atmos Temp		190	o _F
Core Plate DP	5 % Full Power	Supp Pool Press		1.2	psig
Core Flow	5 1b/hr x 103	Supp Pool Temp		116	o _F
Total Steam Flow	0 lb/hr x 108	Supp Pool Level		23.0	feet
Total Feedwater Flow	O 1b/hr x 106	Main Stm Line Rad Mon		25	mR/hr
Condénser Vacuum	O inches Hg	Containment Rad Level		4	R/hr
Hotwell Level	39 inches	Cond Stor Tank Level		20.6	feet
CRD Charging Pressure	1050 paig	RCIC Flow		630	gpm
Inst. Gas to ADS Pressure	110 paig	HPCI Flow		5600	gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow		10,000	gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow		10000	gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow		0	gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow		0	gpm
H ₂ Concentration	./ 1	RHR Hx Outlet Temp		95	°F
O ₂ Concentration	2.8 1	RIIR SW Inlet Temp		80	°F
		RHR C Flow		0	gpm

RHR D Flow

O gpm

			1/2
Reactor Level	+50 inches	Drywell Press	3.3 psig
Reactor Pressure	670 psig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Temp	208 of
Core Plate DP	/ % Full Power	Supp Pool Press	1.3 psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	120 °F
Total Steam Flow	_ 0 lb/hr x 106	Supp Pool Level	23./ feet
Total Feedwater Flow	O 1b/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	6 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	18.4 feet
CRD Charging Pressure	1000 psig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure		HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level		RHR A Flow	10000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	/00008Pm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ 1	RHR Hx Outlet Temp	95 °F
0 ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

7.6 psig

7/25

Time	1145	Nours
ctor Level		

Reactor Level	+50 inches
Reactor Pressure	620 psig
Reactor Power	O % Full Power
Core Plate DP	_/ % Full Power
Core Flor	
Total Steam Flow	O 1b/hr x 106
Total Feedwater Flow	O 1b/hr x 106
Condenser Vacuum	o iaches Hg
Hotwell Level	39 inches
CRD Charging Pressure	950 psis
Inst. Gas to ADS Pressure	110 psig
Equip. Drain Coll Tank Level	3 feet
Equip. Drain Surge Tank Level	3 feet
Floor Drain Coll Tank Level	4 feet
Floor Drain Surge Tank Level	3 feet
H ₂ Concentration	./ 1
0 ₂ Concentration	2.8 %

Drywell Press
SGTS Flow
Drywell Atmos Temp
Supp Pool Press
Supp Pool Temp
Supp Pool Level
Hain Stm Line Rad Mon
Containment Rad Level
Cond Stor Tank Level
NCIC Flow
HPCI Flow
RMR A Flow
RHR B Flow
Core Spray A Flow
Core Spray B Flow
RHR Hx Outlet Temp
RHR SW Inlet Temp
RHR C Flow

RHR D Flow

Reactor Level	+50 inches	Drywell Press	4.0 psig
Reactor Pressure	560 psig	SGTS Flow	3000 cfm
Reactor Power	_O % Full Power	Drywell Atmos Temp	235 °F
Core Plate DP	_/ % Full Power	Supp Pool Press	1.6 psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	126 °F
Total Steam Flow	O 1b/hr x 106	Supp Pool Level	23.3 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	// R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	15.2 feet
CRD Charging Pressure	900 paig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure	110 psig	HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10,000 gpm
Equip. Drain Surge Tank Level		RHR B Flow	10,000 gpm
Floor Drain Coll Tank Level	4 feet	Co: Spray & Flow	O gpm
Floor Drain Surge Tank Level	_3_feet	Core Spray B Flow	O gpm
H ₂ Concentration	/_%	RHR Mx Outlet Temp	96 °F
O ₂ Concentration	2.8 %	RIIR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 1515 Hours			LGS 7/25
Reactor Level	+50 inches	Drywell Press	<u>4.2</u> psig
Reactor Pressure	520 psig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	240 °F
Core Plate DP	_/ % Full Power	Supo Pool Press	1.6 psig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	127 °F
Total Steam Flow	O 1b/hr x 106	Supp Pool Level	23.4 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches lig	Containment Rad Level	40 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	13.4 feet
CRD Charging Pressure	850 psig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure		HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RITR A Flow	10,000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	10,000 8Pm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O_ gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O_ gpm
H ₂ Concentration	/ 1	RHR Mx Outlet Temp	97 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	_80 °F
		RHR C Flow	_O gpm
		RHR D Flow	gp ■

7/25

LGS

Hours

15=0

Time

Reactor Level	+50 inches	Drywell Press	<u>4.3</u> psig
Reactor Pressure	480 psig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	244 °F
Core Plate DP	/ % Full Power	Supp Pool Press	
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	128 °F
Total Steam Flow	0 lb/hr x 10 ⁶	Supp Pool Level	23.5 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	_O inches Hg	Containment Rad Level	60 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	12.4 feet
CRD Charging Pressure	800 paig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure	//o psig	HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10,000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	10,000 8Pm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O spen
H ₂ Concentration	/_ 1	RHR Hx Outlet Temp	98 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	<u>o</u> 9pm
		RHR D Flow	O gpm

Time 1545 Hours			LGS 7/25
Reactor Level	+50 inches	Drywell Press	4.4 psig
Reactor Pressure	440 psig	SGTS Flow	3000 cfm
Reactor Power	_O % Full Power	Drywell Atmos Temp	247 °F
Core Plate DP	_/ % Full Power	Supp Pool Press	<u>1,8</u> psig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	130 °F
Total Steam Flow		Supp Pool Level	23.6 feet
Total Feedwater Flow	O lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	80 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	11.2 feet
CRD Charging Pressure	750 psig	RCIC Flow	_630 gpm
Inst. Gas to ADS Pressure	110 psig	HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	10,000 8PM
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	
H ₂ Concentration	/ %	RIIR Hx Outlet Temp	_100 °F
0 ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		CHR C Flow	O gpm
		CHR D Flow	O gpm

			경기장 무료에 있는 가장 맛요. 나는 가장 십 보고 있으면 가득하였다.
Reactor Level	+50 inches	Drywell Press	4.4 psig
Reactor Pressure	4/0 psig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Temp	250 °F
Core Plate DP	_/ % Full Power	Supp Pool Press	_1.8_ psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	<u>130</u> °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	23.7 feet
Total Feedwater Flow	_O lb/hr x 10 ⁶	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	
Hotwell Level	39 inches	Cond Stor Tank Level	10.2 feet
CRD Charging Pressure	730 psig	RCIC Flow	630 gpm
Inst, Gas to ADS Pressure	/10 psig	HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	10,000 8Pm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	_O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	/ 1	RHR Hx Outlet Temp	100 °F
0 ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	
		RHR D Flow	D gpm

Time 1615 Hours			LGS 7/25
Reactor Level	+50 inches	Drywell Press	4.5 psig
Reactor Pressure	380 psig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	252 °F
Core Plate DP	/ % Full Power	Supp Pool Press	18 psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	130 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	23.8 feet
Total Feedwater Flow	_ 0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	150 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	9.2 feet
CRD Charging Pressure	700 psig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure	//0 psig	HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10,000 8Pm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	500 gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	_O gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	
H ₂ Concentration	/ 1	RHR Hx Outlet Temp	/00 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 1630 Hours			LGS 7/25
Reactor Level	+50 inches	Drywell Press	4.5 psig
Reactor Pressure	350 psig	SGTS Flow	3000 cf
Reactor Power	% Full Power	Drywell Atmos Temp	<u>253</u> ⁰F
Core Plate DP	/ % Full Power	Supp Pool Press	_/.8 psig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	130 °F
Total Steam Flow		Supp Pool Level	23.9 feet
Total Feedwater Flow	_O_ lb/hr x 106	Main Stm Line Rad Mon	
Condenser Vacuum	_O inches Hg	Containment Rad Level	200 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	82 feet
CRD Charging Pressure	650 psig	RCIC Flow	630 gpm
Inst. Gas to ADS Pressure		HPCI Flow	5600 gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10000 8Pm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	_500 gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	_O_ 8pm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O_ 8pm
H ₂ Concentration	/ 1	RHR Hx Outlet Temp	_100 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	_80 °F
		RHR C Flow	. <u>D</u> gpm
		RHR D Flow	O gpm

Time		45	-	

Reactor Level

Reactor Power

Core Plate DP

Total Steam Flow

Condenser Vacuum

Hotwell Level

Total Feedwater Flow

CRD Charging Pressure

Inst. Gas to ADS Pressure

Equip. Drain Coll Tank Level

Equip. Drain Surge Tank Level

Floor Drain Coll Tank Level

Floor Drain Surge Tank Level

Core Flow

Reactor Pressure

lours

+50 inches

O % Full Power

/ % Full Power

/ lb/hr x 106

0 lb/hr x 106

O 1b/hr x 106

O inches Hg

39 inches

625 psig

110 psig

3 feet

3 feet

4 feet

7 feet

.1 %

2.8 %

325 psig

LGS 4.5 psig Drywell Press SGTS Flow 3000 cfm

Supp Pool Temp

Cond Stor Tank Level

254 oF Drysell Atmos Temp 1.9 psig Supp Pool Press

7/25

130 °F

7.2 feet

O gpm

24 feet Supp Pool Level 25 mR/hr Main Stm Line Rad Mon

Containment Rad Level 300 R/hr

RCIC Flow 630 gpm

HPCI Flow 5600 gpm

RIR A Flow 10,000 gpm

RHR B Flow 500 gpm Core Spray A Flow

O gpm Core Spray B Flow

RHR Hx Outlet Temp 100 °F

RHR SW Inlet Temp 80 °F

O gpm RHR C Flow

O gpm RHR D Flow

B2-1471200-15

H2 Concentration

02 Concentration

Reactor Level	+50 inches	Drywell Press	4.5 psig
Reactor Pressure	300 psig	SGTS Flow	3000 cf■
Reactor Power		Drywell Atmos Temp	255 °F
Core Plate DP	/ % Full Power	Supp Pool Press	2.0 psig
Core Flow		Supp Pool Temp	130 °F
Total Steam Flow	_ 0 lb/hr x 106	Supp Pool Level	24.1 feet
Total Feedwater Flow	_ 0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	400 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	600 paig	RCIC Flow	
Inst. Gas to ADS Pressure	//O psig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10,000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	500 gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	5000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ 1	RHR Hx Outlet Temp	100 °F
O ₂ Concentration	2.8 %	RIFR SW Inlet Temp	80 °F
		RHR C Flow	5000 gpm
		RHR D Flow	O gpm

Time 17.15 Hour	s		LGS 7/2
Reactor Level	+ 135 inches	Drywell Press	4.4 psig
Reactor Presamre	30 paig	SGTS Flow	3000 cfm
Reactor Power	_O % Full Power	Drywell Atmos Temp	225 °F
Core Plate DP	_/ % Full Power	Supp Pool Press	_1.9_ psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	129 °F
Total Steam Flow	0 lb/hr x 10 ⁶	Supp Pool Level	3.6' feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	_O_ inches Hg	Containment Rad Level	500 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 psig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure		HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	10,000 8Pm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	500 gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	5000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	_,/ 1	RIIR Hx Outlet Temp	99 °F
0 ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	5000 gpm

RHR D Flow

7/25

Reactor Level	+275 inches	Drywell Press	4.4 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	225 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1:9 psig
Core Flow	_/ lb/hr x 10 ⁶	Supp Pool Temp	129 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	23,2' feet
Total Feedwater Flow	O 1b/hr x 106	Main Stm Line Rad Mon	<u>25</u> mR/hr
Condenser Vacuum	_O inches Hg	Containment Rad Level	1000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 psig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O psig	HPCI Flow	O 8ba
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/8,000 8Pm
Equip. Drain Surge Tank Level	3 feet	RIIR B Flow	500 gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	5000 gpm
Floor Drain Surge Tank Level	J feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ 1	RIM Hx Outlet Temp	99 °F
0 ₂ Concentration	28 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	5000 gpm
		RHR D Flow	O gpm

Time 1745 Hours	1		LGS 7/2
Reactor Level	+325 inches	Drywell Press	<u>4.3</u> psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	225 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.9 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	128 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	_O_inches Hg	Containment Rad Level	1200 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O psig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 SPm
Equip. Drain Surge Tank Level	3 feet	RIER B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 spm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	_O gpm
H ₂ Concentration	./ %	RHR Mx Outlet Temp	98 °F
O ₂ Concentration	2.8 %	RIFR SW Inlet Temp	80 °F
		RHR C Flow	O gpm

RHR D Flow

Time Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	4.2 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	204 °F
Core Plate DP	/ % Full Power	Supp Pool Press	
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	127 °F
Total Steam Flow	0 1b/hr x 10 ⁶	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 10 ⁶	Main Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	1400 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	62 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 8Pm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ 1	RHR Hx Outlet Temp	97 °F
02 Concentration	2.8 %	RIIR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 18/5 Hours			LGS	7/25
Reactor Level	+325 inches	Drywell Press .	4.3	2 psig
Reactor Pressure	30 psig	SGTS Flow	3000	2 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	221	√ °F
Core Plate DP	/ % Full Power	Supp Pool Press	_1.9	psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	126	•F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.1	8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Mon	25	mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	150	O R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	_6.5	2 feet
CRD Charging Pressure	350 psig	RCIC Flow	0	gpm
Inst. Gas to ADS Pressure	//O psig	HPCI Flow	_0	_ gpm
Equip. Drain Coll Tank Level	3 feet	RIGR A Flow	10,00	2 gpm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	_0	. gpm
Floor Drain Coll Tank Level	1 feet	Core Spray A Flow	2000	2 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	_0	_ gpm
H ₂ Concentration	./ 1	RIFR Hx Outlet Temp	90	6 °F
02 Concentration	2.8 %	RHR SW Inlet Temp	_80) °F
		RHR C Flow		gpm
		RHR D Flow		gpm

Time 1830 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	4.0 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	204 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.9 psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	125 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	2000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RIR A Flow	10,000 SPm
Equip. Drain Surge Tank Level	3 feet	RIIR B Flow	O spe
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	/ 1	RHR Hx Outlet Temp	95 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O spm

*	
-	
	175
- 61	-

-		

1845	Hours

Time

+325 inches
30 paig
O % Full Power
/ % Full Power
/ lb/hr x 104
0 1b/hr x 106
0 lb/hr x 106
O inches Mg
39 inches
350 paig
//O paig
3 feet
3 feet
4 feet
3 feet
./ 1
2.8 %

Dr	ywell Press
SG	7S Flow
Dr	ywell Atmos Temp
Su	pp Pool Press
Su	pp Pool Temp
Su	pp Pool Level
Ha	in Stm Line Rad Mon
Co	ntainment Rad Level
Co	nd Stor Tank Level
RC	IC Flow
нР	CI Flow
RH	R A Flow
RII	R B Flow
Co	re Spray A Flow
Co	re Spray B Flow
RII	R Kx Outlet Temp
RH	R SW Inlet Temp
RH	R C Flow
RH	R D Flow

20		1/23
	3.8	psig
	3000	cfm
	224	o _F
	1.9	psig
	124	•F
	22.8	feet
	25	mR/hr
	4000	R/hr
	6.2	feet
	0	gpm
	0	gpm
	10,000	gpm
	0	gpm
	2000	gpm
	0	gpm
	95	

80 °F

O gpm

_Ø gpm

Time 1900 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	3.8 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	203 of
Core Plate DP	_/ % Full Power	Supp Pool Press	1.9 psig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	122 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	6000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RIR A Flow	/0,000 spm
Equip. Drain Surge Tank Level	3 feet	RIFR 3 Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ %	RITR Hx Outlet Temp	95 °F
02 Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	. O gpm
		RHR D Flow	O gpm

Time 1915 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	<u>7.7</u> paig
Reactor Pressure	30 paig	SGTS Flow	3000 cf
Reactor Power	O % Full Power	Drywell Atmos Temp	222 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.8 paig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	120 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	8000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 SP®
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O spm
H ₂ Concentration	./ 1	RIFR Hx Outlet Temp	94 °F
02 Concentration	2.8 %	RIR SW Inlet Temp	80 °F
		RHR C Flc	O gpm

RHR D Flow

Time 1930 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	3.5 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	222 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.8 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	119 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	10,000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 8Pm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 spm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O spe
H ₂ Concentration	/_1	RIFR Hx Outlet Temp	94 °F
02 Concentration	2.8 %	RIR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 1945 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	3.4 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	222 °F
Core Plate DP	/ % Full Fower	Supp Pool Press	1.8 psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	
Total Steam Flow	0 1b/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Mg	Containment Rad Level	:13,000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O spm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O apm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 BPm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
N2 Concentration	./ 1	RHR Hx Outlet Temp	94 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	_O_ gpm
		RI/R D Flow	O gpm

Time 2000 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	3.3 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	221 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.7 psig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	115 °F
Total Steam Flow	0 lb/hr x 10 ⁶	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 10 ⁶	Hain Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	15000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	_O spm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RIR A Flow	/0,000 spm
Equip. Drain Surge Tank Level	3 feet	RIIR B Flow	O apm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	2000 spm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
W2 Concentration	./ 1	RHR Mx Outlet Temp	94 °F
0 ₂ Concentration	2.8 %	RIIR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

Time 2015 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	3.1 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	221 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.7 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	18000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 SPm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	(2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ 1	RIFR Mx Outlet Temp	94 °F
O ₂ Concentration	2.8 %	HIR SW Inlet Temp	80 °F

RHR C Flow

RHR D Flow

_O_8pm

Time 2030 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	2.9 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	220 °F
Core Plate DP	% Full Power	Supp Pool Press	1.7 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	//2 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	18000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O spm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 8Pm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration	./ 1	RIFR Hx Outlet Temp	94 08
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	gpm
		RHR D Flow	O gpm

Time 2045 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	2,8 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	220 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.6 paig
Core Flow	_/_ lb/hr x 104	Supp Pool Temp	
Total Steam Flow	0 lb/hr x 104	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 1b/hr x 104	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	_ C inches Hg	Containment Rad Level	18000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	110 pais	HPCI Flow	O gpm
Equip. Drain Coll Yank Level	3 feet	RHR A Flow	/0,000 RPm
Equip. Drain Surge Tank Level	3 feet	RIIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 spm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O spm
M ₂ Concentration	/ 1	RHR Mx Outlet Temp	94 °F
02 Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	_O gpm
		RHR D Flow	Ø gpm

Time 2100 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	2.7 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	0 % Fall Power	Drywell Atmos Temp	220 °F
Core Plate DP	/ % Full Power	Supp Pool Press	/.6 paig
Core Flow	_/_ 1b/hr x 10 ⁶	Supp Pool Temp	108 °F
Total Steam Flow	0 1b/hr x 10 ⁶	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 104	Main Stm Line Red Mon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	18000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	_3_ feet	RHR A Flow	A).000 SP=
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O spe
Floor Drain Coll Tank Level	/ feet	Core Spray & Flow	20001 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O spe
H ₂ Concentration	/ 1	RIIR Nx Outlet Temp	93 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	<u> </u>

Time 2115 Hours	1		LGS 7,725
Reactor Level	+325 inches	Drywell Press	2.5 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Yeap	29 °¥
Core Plate DP	/ % Full Power	Supp Pool Press	1.6 paig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Poel Temp	_/06 °F
Total Steam Flow	0 1b/hr x 10 ⁶	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	1 <u>2,000</u> R/hr
Hotwell Level	39 taches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	_O_ gpa
Inst. Gas to ADS Pressure	110 pais	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 spm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O gpm
H ₂ Concentration .	./ 1	RIIR Mx Outlet Temp	93 °F
02 Concentration	2.8 %	RIIR SW Inlet Temp	80 °F
		RHR C Flow	<u>O</u> 8Pm
		RHR D Flow	O gpm

Time 2130 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	2.4 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Temp	218 •
Core Plate DP	/ % Full Power	Supp Pool Press	1.5 paig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	104 °F
Total Steam Flow	0 lb/hr x 104	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 10 ⁴	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	18000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O ape
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RIR A Flow	/0,000 apm
Equip. Drain Surge Tank Level	3 feet	RIER B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	2000 apm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O apm
M ₂ Concentration	./ 1	RIR Mx Outlet Temp	93 .
O ₂ Concentration	2.8 %	RIIR SW Inlet Temp	80 °F
		RHR C Flow	8pm
		RIR D Flow	O gpm

2145 LGS 7/25 Time Hours 2. 7 paig Dryvell Press +325 inches Reactor Level 3000 cfm 30 paig SGTS Flow Reactor Pressure 218 °F Reactor Power O % Full Power Drywell Atmos Temp 1.5 paig / % Yull Power Core Plate DP Supp Pool Press / 1b/hr x 100 102 °F Core Flow Supp Pool Temp 0 1b/kr x 100 22.8 feet Total Steam Flew Supp Fool Level 25 m2/hr 0 1b/br x 106 Total Feedwater Flow Mais Sum Line Rad Mon Condenser Vacuum O inches Hg Containment and Level 15,000 R/hr 6.2 feet Hotwell Level 39 inches Cond Stor Tank Level O gpm CRD Charging Pressure 350 pais RCIC Flow Inst. Gas to ADS Pressure //O paig HPCI Flow O spe Equip. Drain Coll Tank Level 3 feet RHR A Flow 16.000 spm Equip. Drain Surge Tank Level 3 feet RHR B Flow O ston y feet Floor Drain Coll Tank Level Core Spray A From 2000 gpm 3 feet Floor Drain Surge Tank Level Core Spray B Flow O gpm 1 % M2 Concentration EIR Mx Outlet Temp 90 °F 02 Concentration 2.8 % 80 °F RHR SW Inlet Temp O gpm RHR C Flow O gpm RHR D Flow

Time 2200 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	2.0 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfs
Reactor Power	0 % Full Power	Drywell Atmos Temp	218 °F
Core Plate DP	% Full Power	Supp Pool Press	_/.4 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	100 °F
Total Steam Flow	0 lb/hr x 104	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Ng	Containment Rad Level	10,000 R/hr
Notwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O goa
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O spe
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 SP®
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O apm
Floor Drain Coll Tank Level	/ feet	Core Spray & Flow	2000 gpm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	O ape
N2 Concentration	/ 1	RIIR Hx Outlet Temp	90 %
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	_O_gpm
			O gpm
		RHR D Flow	

Time 2215 Hours	1		LGS 7/25
Reactor Level	+325 inches	Drywell Press	
Reactor Pressure	30 pais	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	218 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.4 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	100 °¥
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedweter Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Ng	Containment Rad Level	9000 R/hr
Motwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	_O_ gpm
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	O apm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 spm
Equip. Drain Surge Tank Level	3 feet	RIFR B Flow	O gpm
Floor Drain Coll Tank Level	1 feet	Core Spray A Flow	1. 0 : spe
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 spe
N2 Concentration	./ 1	RIP Mx Outlet Temp	90 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	
		RHR D Flow	O gpm

Time 2230 Hours			LGS 7/2
Reactor Level	+325 inches	Drysell Press	1.8 peis
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Temp	217 °¥
Core Plate DP	/ % Full Power	Supp Pool Press	1.4 paig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	100 %
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 10 ⁶	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	_O_ inches Ng	Containment Rad Level	8000 R/hr
Notwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	
Inst. Gas to ADS Pressure	//O paig	HPCI Flow	0 spm
Equip. Drain Coll Tank Level	3 feet	RIIR A Flow	/0.000 spm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	LQ- apo
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 spm
H ₂ Concentration	./ 1	RHR Mx Outlet Temp	90 °F
02 Concentration	2.8 %	RIFR SW Inlet Temp	80 °F
		RHR C Flow	gpm
		RHR D Flow	O gpm

Time 2245 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	1.8 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	218 °F
Core Plate DP	/ % Full . wer	Supp Pool Press	1.4 paig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	100 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	_O inches Hg	Containment Rad Level	7500 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	_6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	
Inst. Gas to ADS Pressure	//O paig	NPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 EPM
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	O spm
Floor Brain Surge Tank Level	3 feet	Core Spray B Flow	2000 spm
N ₂ Concentration	/ 1	RHR Hx Outlet Temp	90 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	_80 °F
		RHR C Flow	O gpm
		RHR D Flow	O gpm

2300 7/25 Time Hours LGS +325 inches 1.7 paig Reactor Level Dryvell Press Reactor Pressure 30 pais SGTS Flow 3000 cfm O % Full Power 217 of Reactor Power Drywell Atmos Temp 1.4 paig Core Plate DP / % Full Power Supp Pool Press _/_ lb/hr x 106 Core Flow 100 °F Supp Pool Temp O 1b/hr x 106 Total Steam Flow Supp Pool Level 22.8 feet 0 lb/hr x 106 Total Feedwater Flow 25 mR/hr Main Stm Line Rad Hon O inches Hg 7000 R/hr Condenser Vacuum Containment Rad Level 6.2 feet Hotwell Level 39 inches Cond Stor Tank Level 350 paig CRD Charging Pressure RCIC Flow O spe Inst. Gas to ADS Pressure //O paig MPCI Flow O gpm 3 feet Equip. Drain Coll Tank Level RHR A Flow 10,000 SPm 3 feet Equip. Drain Surge Tank Level RHR B Flow O spm 1 feet Floor Drain Coll Tank Level Core Spray A Flow O'spe 3 feet Floor Drain Surge Tank Level 2000 spm Core Spray & Flow ./ % 90 °F H2 Concentration RHR Mx Outlet Temp 2.8 % 02 Concentration 80 °F RHR SW Inlet Temp 0 3pm RHR C Flow O gpm RHR D Plow

Tile 23/5 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	_1.7 paig
Reactor Pressure	70 paig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Temp	216 %
Core Plate DP	_/ % Full Power	Supp Pool Press	
Core Flow	_/_ lb/hr x 10 ⁴	Supp Pool Temp	100 %
Total Steam Flow	0 lb/hr x 100	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 15/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	6000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O psig	RPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 RPm
Equip. Drain Surge Tank Level	3 feet	RIGR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	epm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 spm
N2 Concentration	/ 1	RHR Mx Outlet Temp	90 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	<u>Ø</u> 8₽■
		RHR D Flow	O gpm

Time 2330 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	1.6 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	216 °F
Core Plate DP	/ % Full Power	Supp Pool Press	
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	100 °F
Total Steam Flow	0 1b/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Mon	25 mR/hr
Condenser Vacuum	_O_inches Hg	Containment Rad Level	5500 R/br
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressuce	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O poig	HPCI Flow	
Equip. Drain Coll Tank Level	3 feet	RIR A Flow	10,000 apm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O spen
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	<u>O</u> spe
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 apm
H ₂ Concentration	/ 1	RHR Mx Outlet Temp	90 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	_80 °F
		RHR C Flow	O gpm

RHR D Flow


2345 LGS 7/25 Hours Time +325 inches 1.6 paig Reactor Level Drywell Press 30 paig 3000 cfm Reactor Pressure SGTS Flow O % Full Power 216 °F Reactor Power Drywell Atmos Temp 1.3 paig / % Full Power Supp Pool Press Core Plate DP / 1b/hr x 106 100 °F Core Flow Supp Pool Temp O 1b/hr x 106 22.8 feet Total Steam Flow Supp Pool Level 0 lb/hr x 108 25 mR/hr Total Feedwater Flow Main Stm Line Rad Mon Condenser Vacuum O inches Mg 5000 R/hr Containment Rad Level Motwell Level 39 inches Cond Stor Tank Level 6.2 feet 350 paig CRD Charging Pressure RCIC Flow _O gpm 110 paig Inst. Gas to ADS Pressure HPCI Flow O gpm 3 feet Equip. Drain Coll Tank Level RHR A Flow 10,000 SPB 7 feet Equip. Drain Surge Tank Level RHR & Flow O gpm / feet Floor Drain Coll Tank Level O'spe Core Spray A Flow 3 feet Floor Drain Surge Tank Level 2000 spm Core Spray B Flow ./ % 90 °F #2 Concentration RHR Mx Outlet Temp 02 Concentration 2.8 % 80 °F RIR SW Inlet Temp O gpm RHR C Flow O gpm RHR D Flow


Time 2400 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	1.5 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	0 % Full Power	Drywell Atmos Yemp	216 °F
Core Plate DP	_/ % Full Power	Supp Pool Press	
Core Flow	_/ lb/hr x 106	Supp Pool Temp	_100 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	_O_inches Ng	Containment Rad Level	5000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O apa
Inst. Gas to ADS Pressure	_//O paig	MPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RIR A Flow	/0,000 RPm
Equip. Drain Surge Tank Level	3 feet	RIR B Flow	O apm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	O spe
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 spm
N2 Concentration	_/ 1	RMR Mx Outlet Temp	90 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	
		RHR D Flow	


Time 00/5 Hours			LGS 7/25
Reactor Level	<u>+325</u> inches	Drywell Press	1.4 psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	212 °F
Core Plate DP	/ % Full Power	Supp Pool Press	1.3 paig
Core Flow	_/_ lb/hr x 106	Erop Pool Temp	99 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	_ 0 lb/hr x 106	Main Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	_O inches Mg	Containment Rad Level	5000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	O gpm
Inst. Gas to ADS Pressure	//O peig	MPCI Flow	O gpm
Equip. Drain Coll Tank Level	_3_ feet	RHR A Flow	/0,000 spm
Equip. Drain Surge Tank Level	3 feet	RMR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	0 8pm
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 gpm
N ₂ Concentration	/ 1	RHR Hx Outlet Temp	89 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	<u>Ø</u> 8₽®


Time 0000 Hours			LGS · 7/25
Reactor Level	+325 inches	Drywell Press	1.3 paig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O T Full Power	Drywell Atmos Temp	217 °F
Core Plate DP	/ % Full Power	Supp Pool Press	_/./ paig
Core Flow	_/_ lb/hr x 10 ⁶	Supp Pool Temp	98 •1
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Main Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Ng	Containment Rad Level	5000 R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	Q gpm
Inst. Gas to ADS Pressure		HPCI Flow	O gpm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 spm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	4 feet	Core Spray A Flow	_O spe
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 spm
N ₂ Concentration	./ 1	RHR Hx Outlet Temp	28 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	80 °F
		RHR C Flow	O gpm
		RHR D Flow	<u>O</u> 8Pm


Time 0045 Hours			LGS 7/25
Reactor Level	+325 inches	Drywell Press	/, / psig
Reactor Pressure	30 paig	SGTS Flow	3000 cfm
Reactor Power	O % Full Power	Drywell Atmos Temp	212 °F
Core Plate DP	_/ % Full Power	Supp Pool Press	1.0 paig
Core Flow	_/_ lb/hr x 106	Supp Pool Temp	96 °F
Total Steam Flow	0 lb/hr x 106	Supp Pool Level	22.8 feet
Total Feedwater Flow	0 lb/hr x 106	Hain Stm Line Rad Hon	25 mR/hr
Condenser Vacuum	O inches Hg	Containment Rad Level	. <u>5000</u> R/hr
Hotwell Level	39 inches	Cond Stor Tank Level	6.2 feet
CRD Charging Pressure	350 paig	RCIC Flow	
Inst. Gas to ADS Pressure	HO paig	MPCI Flow	O spm
Equip. Drain Coll Tank Level	3 feet	RHR A Flow	/0,000 gpm
Equip. Drain Surge Tank Level	3 feet	RHR B Flow	O gpm
Floor Drain Coll Tank Level	/ feet	Core Spray A Flow	(0 · spe
Floor Drain Surge Tank Level	3 feet	Core Spray B Flow	2000 apm
M ₂ Concentration	./ 1	RHR Hx Outlet Temp	86 °F
O ₂ Concentration	2.8 %	RHR SW Inlet Temp	_80 °F
		RHR C Flow	8P=
		RHR D Flow	_O_8pa



















31-61








































3.1-74
























33-82





31-8


































35-94











































INDEX FOR PLANT AND REACTOR SYSTEM PARAMETERS VS TIME GRAPHS

	Parameter	Units	Graph No.	Parameter	Units	Graph No.
	Reactor Level	inches	1,1A,1B	Drywell Press	psig	20,20A
	Reactor Pressure	psig	2,2A	SGTS Flow	cfm	21
	Reactor Power	% Full Power	3	Drywell Atmos Temp	°F	22
	Core Plate DP	% Full Power	4	Supp Pool Press	psig	23
	Core Flow	1b/hr x 10 ⁶	5	Supp Pool Temp	°F	24
	Total Steam Flow	1b/hr x 10 ⁶	8	Supp Pool Level	feet	25
	Total Feedwater Flow	1b/hr x 10 ⁶	7	Main Stm Line Rad Mcn	mR/hr	26
	Condenser Vacuum	inches Hg	8	Containment Rad Level	R/hr	27
	Hotwell Level	inches	9	Cond Stor Tank Level	feet	28
	CRD Charging Pressure	psig	10	RCIC Flow	gpm	29
3J-110	Inst. Gas to ADS Pressure	psig	11	HPCI Flow	gpm	30
	Equip. Drain Coll Tank Level	feet	12	RHR A Flow	gpm	31
	Equip. Diain Surge Tank Level	feet	13	RHR B Flow	gpm	32
	Floor Drain Coll Tank Level	feet	14	Core Spray A Flow	gpm	33
	Floor Drain Surge Tank Level	feet	15	Core Spray B Flow	gpm	34
	H ₂ Concentration	×	16	RHR Hx Outlet Temp	°F	35
,	O ₂ Concentration	%	17	RHR SW Inlet Temp	°F	36
	North Vent Stack Concentra-	μCi/cc	18	RHR C Flow	gpm	37
	tion			RHR D Flow	gpm	38
	North Vent Stack Release Rate	μCi/sec	19			






GRAPH-IA


Reactor Level(WR)


(inches)

Reactor Level Shutdown (inches)



Reactor Pressure (NR)
(psig)







GRAPH-2A

Reactor, Pressure (WR)
.
(psig)

Reactor Power
(% Full Rower)







Core Plate DP (% Full Power)


2400 20008 1800

GRAPH-5


Core Flow








Total Feedwater Flow (16/hrx104)



Condenser Vacumm
(inches Hg)



DOSS 2000 1900

GRAPH-9


Hotwell Level (inches)

GRAPH-10

CRD Charging Pressure
(psig)


	2400	
	2300	
	2200	
GRA.PH-II	2/00	
	2000	
	1900	
Inst. Gas To ADS Pressure	/800	
(pizq)	1700	
	1600	
	1500	
	1400	
	/300	
	1200	
	1100	50 75 100 125 150 P514

2400 2300 GRAPH- 12 2/00 000S · 8 1900 Equip Drain Coll Tank Level 1800 (feet) 1200 1300.



GRAPH-14

Floor Drain Coll Tank Level
(feet)



Ha Concentration (%)


2500					
2200	3	PER CEN	r HA	25	10
2000					
1700	10	15	1 20	25	10 20 20 20 20 20 20 20 20 20 20 20 20 20
1500					
1200	10	PERCENT	20	25	36


2400 PER CEUI O2 2300 2200-2100 GRAPH-17 PER CENT C2 2000 -1900 1800 Oa Concentration PER CENT O (%) 1700 1600 1500++ PER CENT O

GRAPH-18


North Vent Stack Concentration

(µCi/cc)






Drywell Press (NR)
(psig)




GRAPH-20A

Drywell Press (WR)
(psig)


SGTS Flow (cfm)





GRAPH-23

Supp Pool. Press (psig)



Supp Pool Temp


GRAPH-25

Supp Pool Level (feet)

2400 2300 UNITS mr/M 2200 2/00 2000 UNITS 1900 1800 1700 UNITS M-/M 1600 1500 UNITS mr/m /300 \$1200

GRAPH- 26

Main Stm Line Rad Mon




1900 GPM

GRAPH-29

(gpm)

HPCI Flow (gpm)



GPM

RHR A Flow

RHR B Flow (gpm)


				4 4	
2400					
2300					
		The Object			
		property.		1.	
	- 80		1		
2200					
	11.11				
2100					
11.					
the F					
2000				111	
-	14 Hart			- ja-barjan	
				1.15	
1900					
	110				
1800		11 1 11 11			100
			The same	101	
700					
	1111				
	1111111				
1600				1	
	- I - while it is		10000		
1111	11111				
HTTE				Tir	
500				100	
PITT		HARRY.			
				17.23	
1400					
3919		11111			
		11111			
300	Li-bi-		بالسدار	لناراز	
	1-1-11				
				H	
200					
Sec. or					
	A COURT MANUAL		15.5		
2111	uged		B000 /	0.00	12560

2.400 1800


GRAPH-33

Core Spray A Flow (gpm)


Core Spray B Flow (gpm)



RHR Hx Outlet Temp (°F)



RHR SW Inlet Temp.




RHRC Flow


2400	2 1年にからは後で
2300	
2200	
2/00	
2000	
1900	
	1
/70g	
1400	
1500	Martin State
	1
7500	
1200	
0 PM	

2300

GRAPH-38

RHR DF10W (gpm)





OBSERVER CHECKLIST

OBSER	VER
BSERVED: CONTROL ROOM	DATE
corresponds to the evalu	ation made by the
S = Satisfact	ory
U = Unsatisfa	ctory
NO = Not Obser	ved
ed, so note in Comments c	olumn.
ERIA RATING	SCALE COMMENTS
	BSERVED: CONTROL ROOM Circle the number on the corresponds to the evalu observer. The Rating Sc

I. ACTIVATION AND RESPONSE

Control room personnel rapidly and correctly interpreted the problem.

Control Room personnel knew when to refer to the Emergency Operating procedures, Emergency Plan and which Emergency Implementing procedures to use.

Plant process information was available when required.

CR personnel obtained timely meteorological data.

CR personnel got timely release information from radiological and effluent monitor systems.

CR personnel responded quickly to personal injury incident.

CR personnel responded quickly to fire alarm.

CR operators responded properly to simulated operational events.

HP assistance was requested as needed.

Event classifications were timely, accurate and clear.

The (I) E. Director took action to determine what other conditions might exist which would verify the accuracy of the initial indication.

Control Room personnel took appropriate actions to mitigate the effects of the accident.

Technical advise was reqested and/or received from the proper people.

The emergency was upgraded or downgraded when appropriate.

The (I) E. D. made the correct response to implement on-site and off-site assessment and protective measures.

II. COMMUNICATIONS/DISSEMINATION OF INFORMATION

Notifications were timely and porperly completed.

Communication networks were operational and utilized efficiently.

Communication flow was adequate to ensure that information was timely, effective, and efficient.

Phone listings were available, complete and up-to-date.

General status announcements were made and updated periodically throughout the drill. Proper data flow was maintained between TSC and Control Room.

Logs were maintained.

The ambient noise level in the Control Room was not a problem.

Transfer of information within the Control Room was clearly and completely understood.

III. PROCEDURES

Emergency Operating Procedures and Emergency Plan Implementing Procedures were clearly marked and readily available in Control Room.

Procedures used were current and controlled.

IV. DIRECTION AND CONTROL

The (I) E.D. promptly assumed control and authority.

Action was taken to initiate activation of the Emergency Facilities when plant conditions and procedures indicated they should be activated.

The proper management chain of command in the Control Room was followed when making decisions.

Emergency control and authority was properly transferred to the designated Emergency

The transfer of control and authority was announced and logged.

V. MATERIAL AND EQUIPMENT

Plant Monitoring System functioned correctly.

Radiation Meteorological Monitoring System (RMMS) functioned correctly.

ERFDS functioned correctly.

Met data available independent of RMMS.

Public Address System functioned correctly.

Paging/Callout System functioned correctly.

Message recorders functioned correctly.

PABX and dedicated Hotlines functioned correctly.

Station Alarm/Fire Alarm System functioned correctly.

Radios functioned correctly.

VI. PROTECTIVE MEASURES

Personnel in the control room adequately protected from radiological and chemical hazards.

Supplies such as respirators, protective clothing and KI for control room personnel were available.

HP personnel were available as needed.

VII. ACCESS CONTROL

Access to Control Room was limited to personnel assigned to the control room, or participating in the drill exercise.

		OBSERVER	
LOCATION/GROUP O	BSERVED: I	DOSE ASSESSMENT - CR DATE	
DIRECTIONS:	correspond	e number on the rating scale is to the evaluation made by The Rating Scale is define	the
		S = Satisfactory	
		U = Unsatisfactory	
		NO = Not Observed	
* If not observ	ed, so note	e in Comments column.	
EVENT/CRIT	ERIA	RATING SCALE	COMMENTS

The need to perform dose measurements was promptly identified.

The correct procedures were used for making dose calculations.

Shift Technical Advisor (STA) assigned to perform dose calculations were familiar with the procedures.

Dose calculations were performed efficiently and accurately.

Some means were available to verify that the dose calculations were correct.

* If not observe	d, so note	in Com	ments co	lumn.	
		NO = No	t Observ	ed	
		U = Un	satisfac	tory	
		S = Sa	tisfacto	ry	
	Circle the correspond observer. follows:	s to th	e evalua	tion made	by the
LOCATION/GROUP OB					DATE
			OBSERV	ER	
			OBSERVI	ER	

I. ACTIVATION AND RESPONSE

The TSC was activated and manned in a timely manner at the Alert Action Level.

Command and control authority was transferred from the control room according to procedure.

The transfer of command and control was formal, was announced, and was logged.

Pollow-on activities to manage injured persons.

Follow-on activities to manage fire.

Field survey group dispatched, if appropriate.

II. COMMUNICATIONS/DISSEMINATION OF INFORMATION

Plant status and/or radiation parameters needed to determine the existing conditions were

available in the TSC including portable radiological monitoring, chemistry and meteorological data.

Communication with State, Counties and NRC officials was quickly established.

Initial (if appropriate) and Follow-Up Notifications were made in timely (usually 15 minutes) fashion.

Major changes in plant or radiation release status was made known to all parties quickly.

Off-site protective action recommendations were made quickly and clearly.

All responsible persons in the TSC kept abreast of current conditions.

Communications between TSC and CR, EOF, OSC and HESC were established and used.

Comminication with field survey group was adequate.

Discussions were held concerning trends, prognosis, courses of action.

III. PROCEDURES

Current and controlled copies of the Emergency Plan and Implementing Procedure s were available.

Personnel using procedures were trained and familiar with them.

Communication with off-site groups were made in accordance

with procedures.

IV. DIRECTION AND CONTROL

Transfer of command from Control Room was clear and understood by all persons in TSC.

Transfer of command from TSC to EOF was clear and understood by all persons in TSC.

Appropriate TSC personnel made prompt recommendations.

Logs were kept.

Recommendations were passed on to Emergency Director for decisions.

Proper classification upgrading and downgrading was done.

V. MATERIAL AND EQUIPMENT

ERFDS was operational.

Blueprints as-built drawings, maps, etc. were available.

PABX sound powered, and dedicated Hotlines functioned correctly.

Public Address System functioned correctly.

Radios functioned correctly.

Facsimile machine functioned correctly.

PABX and dedicated Hotlines functioned correctly.

Status boards in place and used.

VI. PROTECTIVE MEASURES

EVENT/CRITERIA

HP coverage available in TSC (air sampling, dose rate instruments).

Protective equipment and supplies for TSC personnel.

Plant evacuation decisions logical and clear.

Plant evacuation directives included travel routes, special precautions, etc.

Continuing accountability information given to Security.

In-plant radiological monitoring reported to TSC.

VII. ACCESS CONTROL

Only those people with assigned responsibilities were in TSC.

Sign-in system was employed.

	0	BSERVER	
LOCATION/GROUP OF	SERVED: HEALTH PHYS	ICS DATE	
DIRECTIONS:	Circle the number on corresponds to the e observer. The Ratin follows:	valuation made by	the
	S = Satis	factory	
	U = Unsat	isfactory	
	NO = Not 0	bserved	
* If not observe	d, so note in Commen	ts column.	

RATING SCALE

COMMENTS

Adequate trained personnel were available to furnish HP coverage for the emergency situation and First Aid teams, Chemistry, Search and Rescue teams, Fire teams, Repair teams, EOF, OSC and evacuees.

EVENT/CRITERIA

Onsite monitoring equipment was easily accessible and properly distributed.

Equipment was checked for proper operability prior to its use.

Standard HP practices were employed for entry into actual or potential radiation areas.

Proper survey records, dosimetry, stay time, etc. were maintained during entry.

Survey results were reported to the appropriate personnel.

Follow-up actions were taken on survey results.

	.====
LOCATION/GROUP OBSERVED: SEARCH AND RESCUE TEAM DATE	
DIRECTIONS: Circle the number on the rating scale that corresponds to the evaluation made by the observer. The Rating Scale is defined as follows:	
S = Satisfactory	
U = Unsatisfactory	
NO = Not Observed	
* If not observed, so note in Comments column.	

RATING SCALE

COMMENTS

OSC Supervisor selected three or more volunteers to serve as team.

EVENT/CRITERIA

If radiological hazards are involved, one team member is a HP Technician.

Team members have current first aid training.

Team members briefed in accordance with procedure

At least one team member has required formal access permit to area being entered.

Radio check performed.

Safety and first aid equipment available as needed.

Communications maintained with OSC during search and rescue.

Log of activities kept.

Pocket dosimeters were frequently checked and properly logged.

The TSC, OSC & CR habitability was frequently monitored.

Team members had adequate understanding of proper utilization of equipment (survey instruments, radios, SCBA's, etc.).

Inplant Survey results were systematically collected by the Plant Survey Group Leader

The correct procedure was used to establish emergency dose limits, if needed.

Authorization to exceed 10CFR20 Exposure Limits were documented.

Debriefing conducted, records and logs collected.

Personal dosimetry used, if needed.

TSC informed of results of search and rescue.

		OBSERVER	
OCATION/GROUP OF	SERVED:	DOSE ASSESSMENT - TS	C DATE
DIRECTIONS:	correspon	ne number on the ration nds to the evaluation The Rating Scale i	made by the
		S = Satisfactory	
		U = Unsatisfactory	
		NO = Not Observed	
If not observe	d, so not	e in Comments column	
EVENT/CRITE	RIA	RATING SCALE	COMMENTS

Initial and subsequent dose calculations were performed in a timely manner.

Computerized equipment was properly utilized (RMMS).

Plume was defined and tracked.

Teams were contacted, briefed, and dispatched expeditiously.

Communications were maintained with all teams.

Personnel was efficiently utilized.

Dose Assessment Team Leader initiated and provided periodic updates to the Emegency Director on Protective Actions.

Status was maintained on team exposure levels.

Comparisons were made between projected and actual field measurements.

RATING SCALE

EVENT/CRITERIA

COMMENTS

Field Survey Group were provided with adequate information to perform their duties.

	OBSERVER
LOCATION/GROUP OBSERVED:	OFFSITE MONITORING TEAMS DATE
correspo	the number on the rating scale that onds to the evaluation made by the observer. ing Scale is defined as follows:
	S = Satisfactory
	U = Unsatisfactory
	NO = Not Observed
* If not observed, so n	ote in Comments column.
EVENT/CRITERIA	RATING SCALE COMMENTS

Initial team briefings were held.

Team assembled with field kits, vehicles and communications equipment in a timely manner.

Field Monitoring kits were checked for contents before leaving site.

Instruments checked for proper operability and current calibration.

Teams received explicit instructions of where to go and what to sample.

Procedures for conducting offsite monitoring were consulted and followed.

Vehicles were readily available.

Vehicle checked for contamination after mission completed.

Sampling locations were readily located.

Samples were properly packaged, identified and labeled.

Pocket dosimeters were periodically checked.

Pocket dosimeter readings were logged in upon return to LGS.

Communications were maintained with the TSC and/or EOF throughout sampling activity.

	OBSERV	ER
LOCATION/GROUP O	BSERVED: FIRE TEAM	DATE
DIRECTIONS:	Circle the number on the corresponds to the evalua observer. The Rating Sca follows:	tion made by the

S = Satisfactory

U = Unsatisfactory

NO = Not Observed

* If not observed, so note in Comments column.

EVENT/CRITERIA

RATING SCALE

COMMENTS

Reaction time between fire alarm and fire team activation is timely.

Fire fighting personnel response time to the scene of the fire was timely.

Fire team members report to scene of fire with appropriate fire fighting gear and equipment.

Initial assessment of fire situation is adequately performed.

When it is apparent team cannot control the fire, offsite support is requested and obtained in a timely manner.

Communications are maintained between the fire team leader and the CR (Control Room).

Adequate information is provided by the fire team to the Control Room for their assessment. Smooth transition and coordination is made between plant fire team and local fire department.

Arrival of local fire department to fire scene is timely.

Patient was made ready for transport by the First Aid team.

Dosimeter was left with the patient.

Adequate HP's coverage was provided at the hospital.

Patient's radiation doses are monitored by HP personnel.

HP performed radiation survey of ambulance at hospital before vehicle was released.

Consideration/measures were taken to prevent spread of contamination.

Periodic status reports are provided to the Shift Supervisor as to the injured individual's status.

EVENT/CRIT	ERIA	RATING SCALE	COMMENTS
* If not observe	ed, so note in (Comments column	1.
	NO =	Not Observed	
	u =	Unsatisfactory	
	S =	Satisfactory	
DIRECTIONS:	Circle the number corresponds to observer. The follows:	the evaluation	made by the
LOCATION/GROUP OF	SSERVED: FIRST	AID TEAM	DATE
		OBSERVER _	

First Aid Team assembly was timely following notification.

First Aid team assebled with the proper first aid equipment.

Accident/injury assessment made by the First Aid team.

First Aid assistance was rendered in a timely manner.

Appropriate decontamination measures were taken.

Maintained communications linkage with Control Room.

The HP escort reacted properly to the simulated event.

The request for and notification of ambulance was in accordance to procedures.

Patient was made ready for transport by the First Aid team.

Dosimeter was left with the patient.

Adequate HP's coverage was provided at the hospital.

Patient's radiation doses are monitored by HP personnel.

HP performed radiation survey of ambulance at hospital before vehicle was released.

Consideration/measures were taken to prevent spread of contamination.

Periodic status reports are provided to the Shift Supervisor as to the injured individual's status.

OBSERVER

LOCATION/GROUP OBSERVED: OPERATIONAL SUPPORT CENTER DATE

DIRECTIONS: Circle the number on the rating scale that corresponds to the evaluation made by the observer. The Rating Scale is defined as

follows:

S = Satisfactory

U = Unsatisfactory

NO = Not Observed

* If not observed, so note in Comments column.

EVENT/CRITERIA

RATING SCALE

COMMENTS

I. ACTIVATION AND RESPONSE

The OSC was activated in a timely fashion.

All support personnel listed in the Emergency Plan were available in the OSC.

The personnel stationed in the OSC understood their emergency response functions.

There were enough specialists available to fill all demands for HP, Fire Brigades, Search and Rescue teams, Repair teams, and Field Monitoring teams.

II. COMMUNICATIONS/DISSEMINATION OF INFORMATION

Communications with the Control Room and TSC were adequate.

Communication with HP AND ASSISTANCE were adequate.

Comminications with specialty teams was adequate.

There was adequate information flow from the TSC concerning plant conditions and hazardous areas.

There was adequate information flow from the OSC to specialty teams.

III. PROCEDURES

The Emergency Plan and Implementing Procedures were available and current and controlled copies.

Appropriate procedures were available, as needed, for the specialty teams.

IV. DIRECTION AND CONTROL

The OSC was supervised (coordinated) adequately.

A chain-of-command was established.

Team formation and briefings were done quickly and accurately.

Information for continuing accountability was supplied to Security.

V. MATERIAL AND EQUIPMENT

The office and communication equipment necessary to activate the OSC were available.

Specialized tools were obtainable.

VI. PROTECTIVE MEASURES

Protective equipment, clothing and decontamination facilities were available.

The OSC was monitored for radiation.

VII. ACCESS CONTROL

Only OSC assigned personnel were in the prescribed areas.

			OBSE	RVER		
OCATION/GROUP	BSERVED:	EMERGE	NCY CHEM	ISTRY	DATE	
DIRECTIONS:	Circle to corresponding	nds to	the eval	uation m	nade by	the
		S =	Satisfac	tory		
		U =	Unsatisf	actory		
		NO =	Not Obse	rved		
If not observ	red, so no	te in C	omments	column.		
EVENT/CRIT	CERIA		RATING	SCALE	C	COMMENTS

I. ACTIVATION AND RESPONSE

The Chemistry Engineer reported promptly to the Technical Assessment area of the TSC.

The Chemistry Supervisor reported promptly to the RAE Laboratory.

An adequate number of technicians were available or were called in.

Analytical results were available within the specified times.

II. COMMUNICATIONS/DISSEMINATION OF INFORMATION

Communications with the Control Room and/or TSC were adequate.

Directions given to technicians were clear.

Plant status information was available to laboratory personnel.

III. PROCEDURES

The following procedures were available and followed:

IV. DIRECTION AND CONTROL

Samples were collected and analyzed as requested by Control Room or TSC.

Chemistry Supervisor (or alternate) was clearly in command.

Analytical results were verified.

Logs of actions were kept.

V. MATERIAL AND EQUIPMENT

Analytical equipment functioned properly.

Sample points were accessible and open (valves correctly aligned by Control Room and/or technicians).

VI. PROTECTIVE MEASURES

Health Physics covereage was requested as needed.

Protective equipment was available to lab personnel.

COMMENTS

VII. ACCESS CONTROL

Only personnel with emergency responsibilities were present during exercise.

Access to PASS, etc. was made according to procedure.

OBSERVER	

LOCATION/GROUP OBSERVED: EMERGENCY OPERATIONS FACILITY DATE
DIRECTIONS: Circle the number on the rating scale that
corresponds to the evaluation made by the observer.
The Rating Scale is defined as follows:

S = Satisfactory

U = Unsatisfactory

NO = Not Observed

* If not observed, so note in Comments column.

EVENT/CRITERIA

RATING SCALE

COMMENTS

I. ACTIVATION AND RESPONSE

EOF was activated and manned within a reasonable time after declaration of Site Emergency or at the discretion of the Site Emergency Coordinator or Emergency Director.

Site Emergency Coordinator received briefing from Emergency Director prior to assuming command and control.

EOF personnel informed of assumption of specific responsibilities.

Sign-in system used to assume full staffing.

II. COMMUNICATIONS/DISSEMINATION OF INFORMATION

Communications were checked and established with Control Room, TSC, HESC and required offsite Federal, State, County, and local agencies.

Technical Support Center notified of assumption of command and control of EOF designated responsibilities.

Needed data was available from TSC and CR

EOF received prompt information on radiological status, both on and off-site.

Pertinent information quickly (15 minutes) transmitted to offsite groups.

Up-to-date meteorological data was available.

Plant status information was promptly available.

Communication with off-site monitoring teams was adequate.

General status announcements and updates were made to EOF personnel throughout exercise.

EOF coordinated the supply of information to Hqtrs ESC Public Information Services

Status boards used and kept current.

III. PROCEDURES

Emergency Plan and Implementing Procedures were available in current and controlled copies.

EOF participants were familiar with procedures.

Correct procedures were used.

IV. DIRECTION AND CONTROL

The organizational structure and chain of command in EOF was clear.

Appropriate people made prompt decisions and recommendations.

EOF Staff took appropriate follow-up actions to care for injured personnel, if any.

Status boards kept current.

Plume pathway tracked and visible.

Emergency classifications and action level notifications transmitted to proper authorities as required.

Protective action recommendations were made clearly and timely.

Continuing accountability data forwarded to Security.

V. MATERIAL AND EQUIPMENT

ERFDS was available.

Facsimile machine functioned.

Status boards available.

Reference materials, procedures, prints, etc., available.

VI. ACCESS CONTROL

Only assigned EOF people were present.

Security Control Established

			OBSERV	/EF		
				==		
LOCATION/GROUP	OBSERVED:	DOSE	ASSESSMENT	-	EOF	DATE
LOCATION/GROUP OBSER	OBSERVED:	DOSE	ADDEDDINENT	-	201	

DIRECTIONS: Circle the number on the rating scale that corresponds to the evaluation made by the observer. The Rating Scale is defined as follows:

S = Satisfactory

U = Unsatisfactory

NO = Not Observed

* If not observed, so note in Comments column.

EVENT/CRITERIA

RATING SCALE

COMMENTS

Initial and subsequent dose calculations were performed in a timely manner.

Computerized equipment was properly utilized (RMMS).

Plume was defined and tracked.

Teams were contacted, briefed, and dispatched expeditiously.

Communications were maintained with all teams.

Personnel was efficiently utilized.

Dose Assessment Team
Leader will initiated and
provided periodical updates to
the Site Emergency Coordinator on PAG's

Status was maintained on team exposure levels.

Offsite monitoring data were coordinated with State.

EVENT/CRITERIA

RATING SCALE

COMMENTS

Comparisons were made between projected and actual field measurements.

Field Survey Group were provided with adequate information to perform their duties.

	OBSERVER
OCATION/GROUP OBS	ERVED: Hqtrs Emergency Support CenterDATE
C	ircle the number on the rating scale that orresponds to the evaluation made by the bserver. The Rating Scale is defined as ollows:
	S = Satisfactory
	U = Unsatisfactory
	NO = Not Observed
If not observed	, so note in Comments column.
EVENT/CRITER	IA RATING SCALE COMMENTS

I. ACTIVATION AND RESPONSE

The Hatrs Emergency Support Center was fully staffed in a timely fashion.

The Emergency Support Officer was clearly in command.

Information was received quickly from Emergency Support Center (ESC)

II. COMMUNICATIONS/DISSEMINATION OF INFORMATION

Emergency News were coordinated prior release as required by EP-C with functions.

Emergency News Releases were made in a accordance with prescribed procedure.

Spokespersons were clearly identified.

Rumor control methods were used.

III. PROCEDURES

Controlled and current copies of the Emergency Plan and Implementing Procedures were available.

IV. DIRECTION AND CONTROL

Emergency Support Officer was clearly in control of the ESC.

Major decisions were made by Emergency Support Officer in consulation with his staff.

News releases were reviewed and issued smoothly and quickly.

Logistical Support and manpower requests were acted on in an expeditous manner by staff

Liaison with off-site law enforcement was provided, as appropriate.

Spokespersons were knowledgeable about technical aspects of plant problems.

V. MATERIAL AND EQUIPMENT

Space for staff was adequate.

Space for news media representatives were adequate.

Adequate telephones to handle traffic were available.

Facsimile machine operable.

VI. PROTECTIVE MEASURES

(Not applicable) .

VII. ACCESS CONTROL

Only persons with assigned emergency responsibilities were present.