

SERIAL: NLS-92-017

ENCLOSURE 4

SHEARON HARRIS NUCLEAR POWER PLANT
NRC DOCKET NO. 50-400/LICENSE NO. NPF-63
REQUEST FOR LICENSE AMENDMENT
STEAM GENERATOR F* TUBE PLUGGING CRITERIA

TECHNICAL SPECIFICATION PAGES

REACTOR COOLANT SYSTEM

STEAM GENERATORS

SURVEILLANCE REQUIREMENTS (Continued)

4.4.5.2 (Continued)

3. A tube inspection (pursuant to Specification 4.4.5.4a.8) shall be performed on each selected tube. If any selected tube does not permit the passage of the eddy current probe for a tube inspection, this shall be recorded and an adjacent tube shall be selected and subjected to a tube inspection.
- c. The tubes selected as the second and third samples (if required by Tables 4.4-2 A and B) during each inservice inspection may be subjected to a partial tube inspection provided:
 1. The tubes selected for these samples include the tubes from those areas of the tube sheet array where tubes with imperfections were previously found, and
 2. The inspections include those portions of the tubes where imperfections were previously found.
- d. Each inspection shall include a sample of those tubes expanded in the preheater section of the steam generator. The first sample size, second sample size and subsequent inspection shall follow Table 4.4-2B.

The results of each sample inspection shall be classified into one of the following three categories:

<u>Category</u>	<u>Inspection Results</u>
C-1	Less than 5% of the total tubes inspected are degraded tubes and none of the inspected tubes are defective.
C-2	One or more tubes, but not more than 1% of the total tubes inspected are defective, or between 5% and 10% of the total tubes inspected are degraded tubes.
C-3	More than 10% of the total tubes inspected are degraded tubes or more than 1% of the inspected tubes are defective.

Note: In all inspections, previously degraded tubes must exhibit significant (greater than 10%) further wall penetrations to be included in the above percentage calculations.

- e. In addition to the 3% sample, all tubes for which the alternate plugging criteria (F*) has been previously applied shall be inspected in the tubesheet region.

REACTOR COOLANT SYSTEM

STEAM GENERATOR

SURVEILLANCE REQUIREMENTS (Continued)

4.4.5.4 Acceptance Criteria

a. As used in this specification:

1. Imperfection means an exception to the dimensions, finish, or contour of a tube from that required by fabrication drawings or specifications. Eddy-current testing indications below 20% of the nominal tube wall thickness, if detectable, may be considered as imperfections;
2. Degradation means a service-induced cracking, wastage, wear, or general corrosion occurring on either inside or outside of a tube;
3. Degraded Tube means a tube containing imperfections greater than or equal to 20% of the nominal wall thickness caused by degradation;
4. % Degradation means the percentage of the tube wall thickness affected or removed by degradation;
5. Defect means an imperfection of such severity that it exceeds the plugging limit. A tube containing a defect is defective;
6. Plugging Limit means the imperfection depth at or beyond which the tube shall be removed from service and is equal to 40% of the nominal tube wall thickness. *(Insert From Next Page).*
7. Unserviceable describes the condition of a tube if it leaks or contains a defect large enough to affect its structural integrity in the event of an Operating Basis Earthquake, a loss-of-coolant accident, or a steam line or feedwater line break as specified in Specification 4.4.5.3c., above;
8. Tube Inspection means an inspection of the steam generator tube from the point of entry (hot leg side) completely around the U-bend to the top support of the cold leg; and
9. Preservice Inspection means an inspection of the full length of each tube in each steam generator performed by eddy current techniques prior to service to establish a baseline condition of the tubing. This inspection shall be performed prior to initial POWER OPERATION using the equipment and techniques expected to be used during subsequent inservice inspections.

10. *(Insert from Next Page)*

11. *(Insert from Next Page)*

4.4.5.4.a. inserts:

6. . . . This definition does not apply to the area of the tubesheet region below the F* Distance provided the tube is not degraded (i.e., no indications of cracking) within the F* Distance.

10. F* Distance is the distance into the tubesheet from the face of the tubesheet or the top of the last hardroll, whichever is lower (further into the tubesheet) that has been conservatively chosen to be 1.6 inches.

11. Alternate Tube Plugging Criteria does not require the tube to be removed from service or repaired when the tube degradation exceeds the plugging limit so long as the degradation is in that portion of the tube from F* to the bottom of the tubesheet. This definition does not apply to tubes with degradation (i.e., indications of cracking) in the F* Distance.

REACTOR COOLANT SYSTEM

STEAM GENERATOR

SURVEILLANCE REQUIREMENTS (Continued)

4.4.5.4 Acceptance Criteria (Continued)

- b. The steam generator shall be determined OPERABLE after completing the corresponding actions (plug all tubes exceeding the plugging limit and all tubes containing through-wall cracks) required by Tables 4.4-2A and B.

4.4.5.5 Reports

- a. Within 15 days following the completion of each inservice inspection of steam generator tubes, the number of tubes plugged in each steam generator shall be reported to the Commission in a Special Report pursuant to Specification 6.9.2;
- b. The complete results of the steam generator tube inservice inspection shall be submitted to the Commission in a Special Report pursuant to Specification 6.9.2 within 12 months following the completion of the inspection. This Special Report shall include:
 - 1. Number and extent of tubes inspected,
 - 2. Location and percent of wall-thickness penetration for each indication of an imperfection, and
 - 3. Identification of tubes plugged.
- c. Results of steam generator tube inspections which fall into Category C-3 shall be reported in a Special Report pursuant to Specification 6.9.1 within 30 days and prior to resumption of plant operation. This report shall provide a description of investigations conducted to determine cause of the tube degradation and corrective measures taken to prevent recurrence.

- d. The results of inspections of F* tubes shall be reported to the Commission in a report, prior to the restart of the unit following the inspection. This report shall include:

- 1. Identification of F* tubes, and
- 2. Location and size of the degradation

NRC approval of this report is not required prior to restart.

TABLE 4.4-2A

STEAM GENERATOR TUBE INSPECTION

1ST SAMPLE INSPECTION			2ND SAMPLE INSPECTION		3RD SAMPLE INSPECTION	
Sample Size	Result	Action Required	Result	Action Required	Result	Action Required
A minimum of 5 Tubes per S.G.	C-1	None	N/A	N/A	N/A	N/A
	C-2	Plug defective tubes and inspect additional 25 tubes in this S.G.	C-1	None	N/A	N/A
			C-2	Plug defective tubes and inspect additional 45 tubes in this S.G.	C-1	None
	C-2		C-2		C-2	Plug defective tubes
			C-3		C-3	Perform action for C-3 result of first sample
	C-3		C-3	Perform action for C-3 result of first sample	N/A	N/A
C-3	Inspect all tubes in this S.G., plug defective tubes and inspect 25 tubes in each other S.G. Notification to NRC pursuant to Specification 4.4.5.5.c.	All other S.G.s are C-1	None	N/A	N/A	
		Some S.G.s are C-2 but no additional S.G.s are C-3	Perform action for C-2 result of second sample	N/A	N/A	
		Additional S.G. is C-3	Inspect all tubes in each S.G. and plug defective tubes. Notification to NRC pursuant to Specification 4.4.5.5.c.	N/A	N/A	

$S = \frac{D}{n}$ where n is the number of steam generators inspected during an inspection.

*Defective tubes which fall under the Alternate Tube Plugging Criteria do not have to be plugged.

REACTOR COOLANT SYSTEM

BASES

This plugging limit does not apply to imperfections located below the F* region of any given tube. The F* criterion can be applied only if the tube geometry in the region selected as the F* distance falls within the analytical limits of WCAP-12816.

STEAM GENERATORS (Continued)

The plant is expected to be operated in a manner such that the secondary coolant will be maintained within those chemistry limits found to result in negligible corrosion of the steam generator tubes. If the secondary coolant chemistry is not maintained within these limits, localized corrosion may likely result in stress corrosion cracking. The extent of cracking during plant operation would be limited by the limitation of steam generator tube leakage between the Reactor Coolant System and the Secondary Coolant System (reactor-to-secondary leakage = 500 gallons per day per steam generator). Cracks having a reactor-to-secondary leakage less than this limit during operation will have an adequate margin of safety to withstand the loads imposed during normal operation and by postulated accidents. Operating plants have demonstrated that reactor-to-secondary leakage of 500 gallons per day per steam generator can readily be detected by radiation monitors of steam generator blowdown. Leakage in excess of this limit will require plant shutdown and an unscheduled inspection, during which the leaking tubes will be located and plugged.

Wastage-type defects are unlikely with proper chemistry treatment of the secondary coolant. However, even if a defect should develop in service, it will be found during scheduled inservice steam generator tube examinations. Plugging will be required for all tubes with imperfections exceeding the plugging limit of 40% of the tube nominal wall thickness. Steam generator tube inspections of operating plants have demonstrated the capability to reliably detect degradation that has penetrated 20% of the original tube wall thickness.

Whenever the results of any steam generator tubing inservice inspection fall into Category C-3, these results will be reported to the Commission in a Special Report pursuant to Specification 4.4.5.5.c within 30 days and prior to resumption of plant operation. Such cases will be considered by the Commission on a case-by-case basis and may result in a requirement for analysis, laboratory examinations, tests, additional eddy-current inspection, and revision of the Technical Specifications, if necessary.

3/4.4.6 REACTOR COOLANT SYSTEM LEAKAGE

3/4.4.6.1 LEAKAGE DETECTION SYSTEMS

The RCS Leakage Detection Systems required by this specification are provided to monitor and detect leakage from the reactor coolant pressure boundary. These Detection Systems are consistent with the recommendations of Regulatory Guide 1.45, "Reactor Coolant Pressure Boundary Leakage Detection Systems," May 1973.

3/4.4.6.2 OPERATIONAL LEAKAGE

PRESSURE BOUNDARY LEAKAGE of any magnitude is unacceptable since it may be indicative of an impending gross failure of the pressure boundary. Therefore, the presence of any PRESSURE BOUNDARY LEAKAGE requires the unit to be promptly placed in COLD SHUTDOWN.

REACTOR COOLANT SYSTEM

STEAM GENERATORS

SURVEILLANCE REQUIREMENTS (Continued)

4.4.5.2 (Continued)

3. A tube inspection (pursuant to Specification 4.4.5.4a.8) shall be performed on each selected tube. If any selected tube does not permit the passage of the eddy current probe for a tube inspection, this shall be recorded and an adjacent tube shall be selected and subjected to a tube inspection.
- c. The tubes selected as the second and third samples (if required by Tables 4.4-2 A and B) during each inservice inspection may be subjected to a partial tube inspection provided:
 1. The tubes selected for these samples include the tubes from those areas of the tube sheet array where tubes with imperfections were previously found, and
 2. The inspections include those portions of the tubes where imperfections were previously found.
- d. Each inspection shall include a sample of those tubes expanded in the preheater section of the steam generator. The first sample size, second sample size and subsequent inspection shall follow Table 4.4-2B.
- e. In addition to the 3% sample, all tubes for which the alternate plugging criteria (F*) has been previously applied shall be inspected in the tubesheet region.

The results of each sample inspection shall be classified into one of the following three categories:

<u>Category</u>	<u>Inspection Results</u>
C-1	Less than 5% of the total tubes inspected are degraded tubes and none of the inspected tubes are defective.
C-2	One or more tubes, but not more than 1% of the total tubes inspected are defective, or between 5% and 10% of the total tubes inspected are degraded tubes.
C-3	More than 10% of the total tubes inspected are degraded tubes or more than 1% of the inspected tubes are defective.

Note: In all inspections, previously degraded tubes must exhibit significant (greater than 10%) further wall penetrations to be included in the above percentage calculations.

REACTOR COOLANT SYSTEM

STEAM GENERATORS

SURVEILLANCE REQUIREMENTS (Continued)

4.4.5.4 Acceptance Criteria

a. As used in this specification:

1. Imperfection means an exception to the dimensions, finish, or contour of a tube from that required by fabrication drawings or specifications. Eddy-current testing indications below 20% of the nominal tube wall thickness, if detectable, may be considered as imperfections;
2. Degradation means a service-induced cracking, wastage, wear, or general corrosion occurring on either inside or outside of a tube;
3. Degraded Tube means a tube containing imperfections greater than or equal to 20% of the nominal wall thickness caused by degradation;
4. % Degradation means the percentage of the tube wall thickness affected or removed by degradation;
5. Defect means an imperfection of such severity that it exceeds the plugging limit. A tube containing a defect is defective;
6. Plugging Limit means the imperfection depth at or beyond which the tube shall be removed from service and is equal to 40% of the nominal tube wall thickness. This definition does not apply to the area of the tubesheet region below the F* distance provided the tube is not degraded (i.e., no indications of cracking) within the F* distance.
7. Unserviceable describes the condition of a tube if it leaks or contains a defect large enough to affect its structural integrity in the event of an Operating Basis Earthquake, a loss-of-coolant accident, or a steam line or feedwater line break as specified in Specification 4.4.5.3c., above;
8. Tube Inspection means an inspection of the steam generator tube from the point of entry (hot leg side) completely around the U-bend to the top support of the cold leg; and
9. Preservice Inspection means an inspection of the full length of each tube in each steam generator performed by eddy current techniques prior to service to establish a baseline condition of the tubing. This inspection shall be performed prior to initial POWER OPERATION using the equipment and techniques expected to be used during subsequent inservice inspections.

REACTOR COOLANT SYSTEM

STEAM GENERATORS

SURVEILLANCE REQUIREMENTS (Continued)

10. F* Distance is the distance into the tubesheet from the face of the tubesheet or the top of the last hardroll, whichever is lower (further into the tubesheet), that has been conservatively chosen to be 1.6 inches.
11. Alternate Tube Plugging Criteria does not require the tube to be removed from service or repaired when the tube degradation exceeds the plugging limit so long as the degradation is in that portion of the tube from F* to the bottom of the tubesheet. This definition does not apply to tubes with degradation (i.e., indications of cracking) in the F* distance.

REACTOR COOLANT SYSTEM

STEAM GENERATORS

SURVEILLANCE REQUIREMENTS (Continued)

4.4.5.4 Acceptance Criteria (Continued)

- b. The steam generator shall be determined OPERABLE after completing the corresponding actions (plug all tubes exceeding the plugging limit and all tubes containing through-wall cracks) required by Tables 4.4-2A and B.

4.4.5.5 Reports

- a. Within 15 days following the completion of each inservice inspection of steam generator tubes, the number of tubes plugged in each steam generator shall be reported to the Commission in a Special Report pursuant to Specification 6.9.2;
 - b. The complete results of the steam generator tube inservice inspection shall be submitted to the Commission in a Special Report pursuant to Specification 6.9.2 within 12 months following the completion of the inspection. This Special Report shall include:
 1. Number and extent of tubes inspected,
 2. Location and percent of wall-thickness penetration for each indication of an imperfection, and
 3. Identification of tubes plugged.
 - c. Results of steam generator tube inspections which fall into Category C-3 shall be reported in a Special Report pursuant to Specification 6.9.2 within 30 days and prior to resumption of plant operation. This report shall provide a description of investigations conducted to determine cause of the tube degradation and corrective measures taken to prevent recurrence.
 - d. The results of the inspection of F* tubes shall be reported to the Commission in a report, prior to the restart of the unit following the inspection. This report shall include:
 1. Identification of F* tubes, and
 2. Location and size of the degradation.
- NRC approval of this report is not required prior to restart.

TABLE 4.4-2A
 S.G. GENERATOR TUBE INSPECTION

1ST SAMPLE INSPECTION			2ND SAMPLE INSPECTION		3RD SAMPLE INSPECTION	
Sample Size	Result	Action Required	Result	Action Required	Result	Action Required
A minimum of S Tubes per S.G.	C-1	None	N/A	N/A	N/A	N/A
	C-2	Plug defective tubes* and inspect additional 2S tubes in this S.G.	C-1	None	N/A	N/A
			C-2	Plug defective tubes* and inspect additional 4S tubes in this S.G.	C-1	None
			C-2	Plug defective tubes*	C-3	Perform action for C-3 result of first sample
	C-3	Inspect all tubes in this S.G., plug defective tubes* and inspect 2S tubes in each other S.G. Notification to NRC pursuant to Specification 4.4.5.5.c.	C-3	Perform action for C-3 result of first sample	N/A	N/A
			All other S.G.s are C-1	None	N/A	N/A
Some S.G.s C-2 but no additional S.G.s are C-3			Perform action for C-2 result of second sample	N/A	N/A	
		Additional S.G. is C-3	Inspect all tubes in each S.G. and plug defective tubes.* Notification to NRC pursuant to Specification 4.4.5.5.c.	N/A	N/A	

S = $\frac{S}{n}$ where n is the number of steam generators inspected during an inspection.

* Defective tubes which fall under the Alternate Tube Plugging Criteria do not have to be plugged.

REACTOR COOLANT SYSTEM

BASES

STEAM GENERATORS (Continued)

The plant is expected to be operated in a manner such that the secondary coolant will be maintained within those chemistry limits found to result in negligible corrosion of the steam generator tubes. If the secondary coolant chemistry is not maintained within these limits, localized corrosion may likely result in stress corrosion cracking. The extent of cracking during plant operation would be limited by the limitation of steam generator tube leakage between the Reactor Coolant System and the Secondary Coolant System (reactor-to-secondary leakage = 500 gallons per day per steam generator). Cracks having a reactor-to-secondary leakage less than this limit during operation will have an adequate margin of safety to withstand the loads imposed during normal operation and by postulated accidents. Operating plants have demonstrated that reactor-to-secondary leakage of 500 gallons per day per steam generator can readily be detected by radiation monitors of steam generator blowdown. Leakage in excess of this limit will require plant shutdown and an unscheduled inspection, during which the leaking tubes will be located and plugged.

Wastage-type defects are unlikely with proper chemistry treatment of the secondary coolant. However, even if a defect should develop in service, it will be found during scheduled inservice steam generator tube examinations. Plugging will be required for all tubes with imperfections exceeding the plugging limit of 40% of the tube nominal wall thickness. This plugging limit does not apply to imperfections located below the F* region of any given tube. The F* criterion can be applied only if the tube geometry in the region selected as the F* distance falls within the analytical limits of WCAP-12816. Steam generator tube inspections of operating plants have demonstrated the capability to reliably detect degradation that has penetrated 20% of the original tube wall thickness.

Whenever the results of any steam generator tubing inservice inspection fall into Category C-3, these results will be reported to the Commission in a Special Report pursuant to Specification 4.4.5.5.c within 30 days and prior to resumption of plant operation. Such cases will be considered by the Commission on a case-by-case basis and may result in a requirement for analysis, laboratory examinations, tests, additional eddy-current inspection, and revision of the Technical Specifications, if necessary.

3/4.4.6 REACTOR COOLANT SYSTEM LEAKAGE

3/4.4.6.1 LEAKAGE DETECTION SYSTEMS

The RCS Leakage Detection Systems required by this specification are provided to monitor and detect leakage from the reactor coolant pressure boundary. These Detection Systems are consistent with the recommendations of Regulatory Guide 1.45, "Reactor Coolant Pressure Boundary Leakage Detection Systems," May 1973.

3/4.4.6.2 OPERATIONAL LEAKAGE

PRESSURE BOUNDARY LEAKAGE of any magnitude is unacceptable since it may be indicative of an impending gross failure of the pressure boundary. Therefore, the presence of any PRESSURE BOUNDARY LEAKAGE requires the unit to be promptly placed in COLD SHUTDOWN.

SERIAL: NLS-92-017

ENCLOSURE 5

SHEARON HARRIS NUCLEAR POWER PLANT
NRC DOCKET NO. 50-400/LICENSE NO. NPF-63
REQUEST FOR LICENSE AMENDMENT
STEAM GENERATOR P* TUBE PLUGGING CRITERIA

WCAP-12816

WCAP-12817

Westinghouse Authorization Letter

Affidavit

Proprietary Information Notice

Copyright Notice