

December 1, 1995

NYN- 95099

United States Nuclear Regulatory Commission Washington, DC 20555

Attention:

Document Control Desk

References:

Facility Operating License No. NPF-86, Docket No. 50-443

Subject:

Steam Generator Tubes Plugged During Fourth Inservice Inspection

Gentleman:

Pursuant to Seabrook Station Technical Specification, Surveillance Requirement 4.4.5.5a, North Atlantic Energy Service Corporation (North Atlantic) has enclosed a tabulation of the number of tubes plugged in each of two steam generators during the fourth inservice inspection completed this week.

North Atlantic will submit the complete results of the steam generator tube inservice inspection, as required by Surveillance Requirement 4.4.5.5b prior to November 28, 1996.

Should you have questions regarding this information, please contact Mr. James M. Peschel, Regulatory Compliance Manager, at (603) 474-9521, extension 3772.

Very truly yours,

North Atlantic Energy Service Corporation

(603) 474-9521, Fax (603) 474-2987

The Northeast Utilities System

Ted C. Feigenbaum Senior Vice President &

Chief Nuclear Officer

P.O. Box 300 Seabrook, NH 03874

Ted C. Feigenbaum

TCF/ALL:sm

A0+7.

9512070142 951201 PDR ADOCK 05000443 Q PDR United States Regulatory Commission Attention: Document Control Desk

cc: Mr. Thomas T. Martin
Regional Administrator
U.S. Nuclear Regulatory Commission
Region I
475 Allendale Road
King of Prussia, PA 19406

Mr. Albert W. De Agazio, Sr. Project Manager Project Directorate I-4 Division of Reactor Projects U.S. Nuclear Regulatory Commission Washington, DC 20555

Mr. John B. Macdonald NRC Senior Resident Inspector P.O. Box 1149 Seabrook, NH 03874

ENCLOSURE 1 TO NYN-95099

Seabrook Station

Steam Generator Tubes Plugged During Fourth Inservice Inspection

S/G	Row	Column	%TW	Location	Comment
Α	46	62	40%	AV3	AVB wear
Α	46	64	52%	AV3	AVB wear
			43%	AV4	AVB wear
Α	54	65	47%	AV3	AVB wear
			40%	AV4	AVB wear
Α	46	66	50%	AV2	AVB wear
A	54	67	42%	AV2	AVB wear
			47%	AV3	AVB wear
Α	56	82	55%	AV5	AVB wear
Α	51	92	44%	AV5	AVB wear
Α	49	96	51%	AV5	AVB wear
D	42	53	42%	AV4	AVB wear
D	47	55	41%	AV2	AVB wear
			49%	AV4	AVB wear
D	47	56	45%	AV2	AVB wear
D	49	64	43%	AV4	AVB wear