GENE-T1500013-003 DRF No. T15-00013 March 1996

GIRAFFE TEST

Apparent Test Results Report (ATR)

Helium Series Tests (H)

T-1 & T-2 Tests

Prepared by:

1. Horzog, Senior Engineer

SBWR Test Responsible Engineer

IMPORTANT NOTICE REGARDING CONTENTS OF THIS REPORT PLEASE READ CAREFULLY

The only undertakings of the General Electric Company (GE) respecting information in this document are contained in the contract between the customer and GE, as identified in the purchase order for this report and nothing in this document shall be construed as changing the contract. The use of this information by anyone other than the customer or for any purpose other than that for which it is intended, is not authorized; and with respect to any unauthorized use, GE and Toshiba make no representation or warranty, and assume no liability as to the completeness, accuracy, or usefulness of the information contained in this document.

GENE-T1500013-003

TABLE OF CONTENTS

		Page
1.0	TEST SUMMARY	1
2.0	TEST CONCLUSION	1
3.0	MAJOR TEST RESULTS	1
4.0	TEST ANOMALIES and FAILED INSTRUMENTS	2
5.0	REFERENCES	2

LIST OF FIGURES

FIGURE			
1	TEST T-1	D/W and W/W Pressures	3
2	TEST T-1	Non-condensable Gas Vent and LOCA Vent Water Levels	4
3	TEST T-1	D/W Temperature	5
4	TEST T-1	PCC Tube Bulk Fluid temperature	6
5A	TEST T-1	Suppression Pool Surface Temperature	7
5B	Differenti	al Pressure Measurement Locations in S/C	8
6	TEST T-1	PCC Inlet Flow Rate	9
7	TEST T-2	D/W and W/W Pressures	10
8	TEST T-2	Non-condensable Gas Vent and LOCA Vent Water Levels	11
9	TEST T-2	D/W Temperature	12
10	TEST T-2	PCC Tube Bulk Fluid temperature	13
11	TEST T-2	Suppression Pool Surface Temperature	14
12	TEST T-2	PCC Inlet Flow Rate	15

ABBREVIATIONS AND ACRONYMS

D/W Drywell

GE General Electric

GIRAFFE Gravity-Driven Integral Full-Height Test for Passive Heat Removal

LOCA Loss-of-Coolant Accident

Passive Containment Coc (System)

SBWR Simplified Boiling Water Reactor

S/C Suppression Chamber

TOGE Toshiba/GE

W/W Wetwell

1.0 TEST SUMMARY

The objectives of tests T-1 and T-2 are to demonstrate the operation of a passive containment cooling system with the presence of hig concentrations of a heavier-than-steam non-condensable gas and to provide a tie-back test which includes the appropriate quality assurance procedures.

The T-1 and T-2 test initial conditions are provided in Reference 1. The test procedures and instrument locations are proprietary information.

Test T-1 is a repeat of a previous GIRAFFE main steam line break test. At the start of Test T-1, the drywell contains a mixture of steam and nitrogen at a total pressure of 0.188 MPa. The initial concentration of nitrogen in the drywell is 28 % by volume. Test T-2 has an initial concentration of nitrogen in the drywell that is approximately midway between that for tests H-1 and T-1, and an initial total drywell pressure of 0.266 MPa.

2.0 CONCLUSION

For both tests T-1 and T-2, the D/W peak pressures were confirmed to be well below the design limit. These tests demonstrated the successful operation of the PCCS with the presence of high concentrations of a heavier-than-steam non-condensable gas.

3.0 MAJOR TEST RESULTS

3.1 Test T-1 Results

The test results provided in Figures 1 through 6 are proprietary information.

The figure 1 plots of the measured D/W and W/W pressures are proprietary information.

The figure 2 plots of the measured water levels in the non-condensable gas vent line and the LOCA vent line are proprietary information. The figure 5B locations of the differential pressure measurement locations are proprietary information.

The figure 3 plots of the measured D/W temperatures at the seven thermocouple locations are proprietary information.

The figure 4 plots of the measured PCC tube bulk fluid temperatures are proprietary information.

The figure 5A plot of the measured suppression pool surface temperature is proprietary information.

3.1 Test T-1 Results (Continued)

The figure 6 plot of the preliminary measured PCC inlet flow rate is proprietary information.

3.2 Test T-2 Results

The test results provided in Figures 7 through 12 are proprietary information.

The figure 7 plots of the measured D/W and W/W pressures are proprietary information.

The figure 8 plots of the measured water levels in the non-condensable gas vent line and the LOCA vent line are proprietary information.

The figure 9 plots of the measured D/W temperatures at the seven thermocouple locations are proprietary information.

The figure 10 plots of the measured PCC tube bulk fluid temperatures are proprietary information.

The figure 11 plot of the measured suppression pool surface temperature is proprietary information.

The figure 12 plot of the preliminary measured PCC inlet flow rate is proprietary information.

4.0 TEST ANOMALIES and FAILED INSTRUMENTS

There were no test anomalies or failed instruments

5.0 REFERENCES

 GIRAFFE Helium Test Specification, General Electric Company Specification 25A5677, rev. 1, May 1995 FIGURE 2 TEST T-1 NON-CONDENSABLE GAS VENT and LOCA VENT WATER LEVELS

FIGURE 3 TEST T-1 D/W TEMPERATURE

FIGURE 4 TEST T-1 PCC TUBE BULK FLUID TEMPERATURE

FIGURE 5A TEST T-1 SUPPRESSION POOL SURFACE TEMPERATURE

FIGURE 5B DIFFERENTIAL PRESSURE MEASUREMENT LOCATIONS IN S/C

FIGURE 8 TEST T-2 NON-CONDENSABLE GAS VENT and LOCA VENT WATER LEVELS

FIGURE 9 TEST T-2 D/W TEMPERATURE

FIGURE 10 TEST T-2 PCC TUBE BULK FLUID TEMPERATURE

FIGURE 11 TEST T-2 SUPPRESSION POOL SURFACE TEMPERATURE

FIGURE 12 TEST T-2 PCC INLET FLOW RATE