PRIORITY NORMAL	TRANSMIT	ITAL SPIEN	SIGNATURE U	NE 98-								-											
(1) 0085 G A COPP EC050				DUK	E PC	WER	CON	MPAN	VY.	il.					٠.								
(2) 2665 GEORGE A COOK, MG010	P			DOCUM	ENIT	TRAN	CRAIT	TAL	EAR			0	DATE: _	No. Oak	- 0	3/2	5/96	_					*
(3) 1557 R O SHARPE EC136				DOCOM	-141	ITALY	SIVII	IML	run	IVI	-	0	OCUN	AENT TI	RANSA	MITTAL	•			12,757			
(4) 4409 S A GEWEHR EC050 (5) 3379 D E CALDWELL MG01RC			-	Company and a	-	NST AS	CIALR	345															
(6) 3718 MCG CHEM SHIFT GEN S	UPV MGO	1CH										- 0	A CO	NDITIO	DN					Г	YES THO		
(7) 3133 H E PACEITI MGO1CP					R	EFERE	NCE:	. 1] IES	L	NU
(8) 1896 J S MURANSKY ECORH												0	THER	ACKN	owu	EDGEN	RENT :	REQUI	RED	Г	YES		
(9) 0794 NSRB STAFF ECOSN				MCGUIRE N				ION												REQUI	and a		
10)5194 GARY M BARKER, MGO1C		_		SELECTED		HSEE					1000	+	ACI	KNOW	LEDGE	RECEI	PT BY	RETUR	INING	THIS F	ORM O	R DPC	
11)3744 MCG DIR SIM (LINDSAY) WR030	1		COMMITMEN	TS								FOR	RM 01	183 10								
12)3044 MCG DOC CNTRL MISC M 13)0422 MCG SAFETY REVIEW GR							- 12	213.0	200		gert-R			. 6				Box 1	ar Stati 2700	on			
14)5512 M S KITLAN CNOIRC	טטף מטט.	15K	175700	2835069				85/11			312			- 1		Docur			nent M y Road	G02DM			
15)6593 D E HOLDEN MG03A2					TO SECTION		100		orton Service	100	- SEE THEFT	-				Hunter				28078			
16)2257 R A HARRIS MGO2ME				1,4V68				- 1															
17)3759 U S NUCLEAR REG WASH	nc				185							R	ec'd By							Date			
18)2532 MCG NRC INSP G F MAXL		210		PAI PAI	-		or	1				1											
	QA	T			DE-S	1	OF	4	_	1	-	1	-		-	-	-						5
DOCUMENT NO.	COND	-	Rev. */Doc Contr. Date	Distr. Code D	11	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	TOTAL
SLC 16.11	NA	NA	03/26/96	MADM-03	VI	V1	VI	V1	VI	VI	V1	V1	U1	V1		V1	-	V1	V1	-	V7		
				DETAIN D		1							-	1	1	1	1	V 1	1 1	1	V/	N.I	00
		-			23		-		-	-	1		ļ.,		1								
						1				1													
					1				-		1												
0		1			1						-		1.2										100
60																			1				
8000				force may					-	-					-								To 18
					3											į .							1 3
0					0																		
(3			- 9	54048	12			2.1						1 6									1 %
					13							1											
				answere.	A.								1										
					1																		
9604080252 960229		1			15								1	. 3									1
PDR ADOCK 05000369	7			departie."	27																		
PDR																							
REMARKS		A											-		0		1777	-	-				
															VI	JAL	IIY	CH	LC	KED	F	B	

T C MCMEEKIN VICE PRESIDENT MCGUIRE NUCLEAR STATION

KAY L CRANE MGOIRC KLC/CJB

March 21, 1996

To: All Holders of the Selected Licensee Commitments Manual

Please find attached a revision to the subject manual. Please revise your copy as follows:

Remove these pages:

Insert these pages:

The state of the s	dist of Effective Pages Revision 11
Page 16.11-10 Page 16.11-11 P	Page 16.11-9 Page 16.11-10 Page 16.11-11 Page 16.11-12, 12a

Questions or problems should be directed to Kay Crane, McGuire Regulatory Compliance at extension 4306.

Kay L. Crane,

McGuire Regulatory Compliance

McGuire Nuclear Station Selected Licensee Commitments List of Effective Pages

Page	Revision Date
LOEP Tab	
List of Effective Pages 1 through 7	11
Tab 16.0	
16.0-1	
16.0-2	1/96
Tab 16.1	
16.1-1	
Tab 16.2	
16.2-1	3/91
16.2-2	5/91
16.2-3	
16.2-4	
Tab 16.3	
16.3-1	
Tab 16.4	
Tab 16.5	
16.5-1	01/94
16.5-2	01/94
16.5-3	3/93
16.5-4	3/93
16.5-5	3/93
16.5-6	3/93
16.5-7	3/93
16.5-8	3/93
16.5-9	3/93

Page	Revision Date
16.5-10	3/93
Tab 16.6	
Tab 16.7	
16.7-1	8/95
16.7-2	8/95
16.7-3	8/95
16.7-4	8/95
16.7-5	8/95
16.7-6	8/95
16.7-7	8/95
16.7-8	8/95
16.7-9	8/95
16.7-10	8/95
16.7-11	8/95
16.7-12	8/95
16.7-13	8/95
16.7-14	
	8/95
Tab 16.8	
16.8-1	10/90
Table 16.8-1a 1 of 28	10/94
Table 16.8-1a 2 of 28	10/94
Table 16.8-1a 3 of 28	10/94
Table 16.8-1a 4 of 28	10/94
Table 16.8-1a 5 of 28	10/94
Table 16.8-1a 6 of 28	10/94
Table 16.8-1a 7 of 28	10/94
Table 16.8-1a 8 of 28	10/94

Page		Re	vision Dat
Table	16.8-1a	9 of 28	10/94
Table	16.8-1a	10 of 28	10/94
Table	16.8-1a	11 of 28	10/94
Table	16.8-1a	12 of 28	10/94
Table	16.8-1a	13 of 28	10/94
Table	16.8-1a	14 of 28	10/94
Table	16.8-1a	15 of 28	10/94
Table	16.8-1a	16 of 28	10/94
Table	16.8-1a	17 of 28	10/94
Table	16.8-1a	18 of 28	10/94
Table	16.8-1a	19 of 28	10/94
Table	16.8-1a	20 of 28	10/94
Table	16.8-1a	21 of 28	10/94
Table	16.8-1a	22 of 28	10/94
Table	16.8-1a	23 of 28	10/94
Table	16.8-1a	24 of 28	10/94
Table	16.8-1a	25 of 28	10/94
Table	16.8-la	26 of 28	10/94
Table	16.8-1a	27 of 28	10/94
Table	16.8-1a	28 of 28	10/94
Table	16.8-1b	1 of 30	10/94
Table	16.8-1b	2 of 30	10/94
Table	16.8-1b	3 of 30	10/94
Table	16.8-1b	4 of 30	10/94
Table	16.8-1b	5 of 30	10/94

Table 16.8-1b 6 of 30

Table 16.8-1b 7 of 30

10/94

10/94

Page					Revision	Date
Table	16.8-1b	8	of	30	10)/94
Table	16.8-1b	9	of	30	10)/94
Table	16.8-1b	10	of	30	10	/94
Table	16.8-1b	11	of	30	10)/94
Table	16.8-1b	12	of	30	10	/94
Table	16.8-1b	13	of	30	10	/94
Table	16.8-1b	14	of	30	10	/94
Table	16.8-1b	15	of	30	10	/94
Table	16.8-1b	16	of	30	10	/94
Table	16.8-1b	17	of	30	10	/94
Table	16.8-1b	18	of	30	10	/94
Table	16.8-1b	19	of	30	10	/94
Table	16.8-1b	20	of	30	10	/94
Table	16.8-1b	21	of	30	10	/94
Table	16.8-1b	22	of	30	10	/94
Table	16.8-1b	23	of	30	10	/94
Table	16.8-1b	24	of	30	10	/94
Table	16.8-1b	25	of	30	10	/94
Table	16.8-1b	26	of	30	10	/94
Table	16.8-1b	27	of	30	10	/94
Table	16.8-1b	28	of	30	10	/94
Table	1€.8-1b	29	of	30	10	/94
Table	16.8-1b	30	of	30	10	/94
Tab 16	. 9					
16.9-1					2/	91

16.9-2

16.9-3

Revision 11 Page 4

Page	Revision Dat
16.9-4	
16.9-5	
Table 16.9-1	
16.9-6	1/96
16.9-7	
16.9-8	
16.9-9	
Table 16.9-2	8/90
Table 16.9-2 (cont'd)	
16.9-10	11/95
16.9-11	11/95
16.9-12	12/90
16.9-13	
16.9-14	
Table 16.9-3	12/90
Table 16.9-3 (cont'd)	12/90
Table 16.9-3 / ont'd)	12/90
Table 16.9-3 (cont'd)	2/95
Table 16.9-3 (cont'd)	2/95
Table 16.9-3 (cont'd)	
16.9-15	11/94
16.9-15a	2/91
16.9-16	
16.9-17	6/95

16.9-18

16.9-19

Table 16.9-4

Page	Revision Date
Table 16.9-5	
16.9-20	08/93
16.9-21	2/96
16.9-22	
Tab 16.10	
Tab 16.11	
16.11-1	9/93
16.11-2	
	9/93
16.11-3	9/93
16.11-4	9/94
16.11-5	9/93
16.11-6	9/93
16.11-7	9/93
16.11-8	9/93
16.11-9	2/96
16.11-10	2/96
16.11-11	2/96
16.11-12	2/96
16.11-12a	2/96
16.11-13	9/93
16.11-14	9/93
16.11-15	9/93
16.11-16	
	9/93
16.11-17	9/93
16.11-18	9/93
16.11-19	9/93
16.11-20	9/93

Page	Revision Date
16.11-21	9/93
16.11-22	9/93
16.11-23	9/93
16.11-24	9/93
16.11-25	9/93
16.11-26	9/93
16.11-27	9/93
16.11-28	9/93
16.11-29	9/93
16.11~30	9/93
16.11-31	9/93
16.11-32	9/93
16.11-33	9/93
16.11-34	12/93
16.11-35	12/93
16.11-36	12/93
16.11-37	12/93
16.11-38	9/93
16.11-39	9/93
16.11-40	9/93
16.11-41	9/93
16.11-42	9/93
16.11-43	9/93
16.11-44	9/93
16.11-45	9/93
16.11-46	9/93
16.11- 7	9/93

Page	Revision Date
16.11-48	11/95
16.11-49	9/93
16.11-50	9/93
16.11-51	9/93
16.11-52	11/95
16.11-53	11/95
16.11-54	9/93
16.11-55	11/95
16.11-56	11/95
16.11-57	9/93
16.11-58	9/93
16.11-59	9/93
16.11-60	9/93
16.11-61	9/93
16.11-62	9/93
16.11-63	9/93
16.11-64	9/93
16.11-65	9/93
16.11-66	9/93
16.11-67	9/93
16.11-68	9/93
<u>Tab 16.12</u>	
<u>Tab 16.13</u>	
16.13-1	
16.13-2	1/96
16.13-3	1/96
16.13-4	1/96

Page	Revision Date
16.13-5	1/96
16.13-5	1/96
16.13-6	1/96
16.13-7	1/96
Tab 16.14	
Tab 16.15	

TABLE 16.11-. Page 1 of 3)

RADIOACTIVE LIQUID EFFLUENT MONITORING INSTRUMENTATION

	INSTRUMENT	MINIMUM CHANNELS OPERABLE	ACTION
1.	Radioactivity Monitors Providing Alarm And Automatic Termination of Release		
	a. Waste Liquid Effluent Line (EMF-49)	1 per station	1
	b. Containment Ventilation Unit Condensate Line (EMF-44)	1	3
2.	Radioactivity Monitors Providing Alarm But Not Providing Automatic Termination of Release		
	Conventional Wastewater Treatment Line (EMF-31)	1	2
3.	Continuous Composite Samplers And Sampler Flow Monitor		
	a. Containment Ventilation Unit Condensate Line	1	3
	b. Conventional Wastewater Treatment Line	1 per station	3
4.	Flow Rate Measurement Devices		
	a. Waste Liquid Effluent Line	l per station	4
	b. Containment Ventilation Unit Condensate Line	1	4
	c. Conventional Wastewater Treatment Line	l per station	4
5.	Discharge Canal Minimum Flow Interlock*	l per station	5

^{*}Minimum dilution flow is assured by an interlock terminating waste liquid releases if the number of RC Pumps running falls below the number of pumps required for dilution. The required number of RC Pumps for dilution is determined per station procedures.

TABLE 16.11-2 (Page 2 of 3)

ACTION STATEMENTS

- ACTION 1 With the number of channels OPERABLE less than required by the Minimum Channels OPERABLE requirement, effluent releases may continue for up to 14 days provided that prior to initiating a release:
 - a. At least two independent samples are analyzed in accor-dance with SLC 16.11-1, and
 - b. At least two technically qualified members of the facility staff independently verify the discharge line valving:
 - The manual portion of the computer input for the release rate calculations performed on the computer, or
 - 2) The entire release rate calculations if such calculations are performed manually.

Otherwise, suspend release of radioactive effluents via this pathway.

- ACTION 2 With the number of channels OPERABLE less than required by the Minimum Channels OPERABLE requirement, effluent releases via this pathway may continue provided grab samples are analyzed for radioactivity for up to 30 days at a lower limit of detection of at least 10-microCurie/ml:
 - a. At least once per 12 hours when the specific activity of the secondary coolant is greater than 0.01 microCurie/gram DOSE EQUIVALENT I-131, and
 - b. At least once per 24 hours when the specific activity of the secondary coolant is less than or equal to 0.01 micro-Curie/gram DOSE EQUIVALENT I-131.
- ACTION 3 With the number of channels OPERABLE less than required by the Minimum Channels OPERABLE requirement, effluent releases via this pathway may continue for up to 30 days provided that, at least once per 12 hours, grab samples are collected and ana-lyzed for radioactivity at a lower limit of detection of at least 10- microCurie/ml.

TABLE 16.11-2 (Page 3 of 3)

ACTION STATEMENTS

- ACTION 4 With the number of channels OPERABLE less than required by the Minimum Channels OPERABLE requirement, effluent releases via this pathway may continue for up to 30 days provided the flow rate is estimated at least once per 4 hours during actual releases. Pump performance curves generated in place may be used to estimate flow.
- ACTION 5 With the number of channels OPERABLE less than required by the Minimum Channels OPERABLE requirement, effluent releases may continue for up to 30 days provided that, at least once per 4 hours during actual periods of liquid release, the number of pumps providing dilution is determined to be greater than or equal to the number of pumps required.

TABLE 16.11-3 (Page 1 of 2)

RADIOACTIVE LIQUID EFFLUENT MONITORING INSTRUMENTATION SURVEILLANCE REQUIREMENTS

	INSTRUMENT	CHANNEL	SOURCE CHECK	CHANNEL CALIBRATION	CHANNEL OPERATIONAL. TEST
1	Radioactivity Monitors Providing Alarm And Automatic Termination of Release				
	a. Waste Liquid Effluent Line (EMF-49)	D	P	R(3)	Q(1)
	b. Containment Ventilation Unit Condensate Line (EMF-44)	D	М	R(3)	Q(1)
2.	Radioactivity Monitors Providing Alarm But Not Providing Automatic Termination of Release				
	Conventional Wastewater Treatment Line (EMF-31)	D	М	R(3)	Q(2)
3.	Continuous Composite Samplers and Sampler Flow Monitor				
	a. Containment Ventilation Unit Condensate Line	D(4)	N.A.	R	Q
	b. Conventional Wastewater Treatment Line	D(4)	N.A.	R	Q
4.	Flow Rate Measurement Devices				
	a. Waste Liquid Effluent Line	D(4)	N.A.	R	Q
	b. Containment Ventilation Unit Condensate Line	D(4)	N.A.	R	0 1
	c. Conventional Wastewater Treatment Line	D(4)	N.A.	R	Q
5.	Discharge Canal Minimum Flow Interlock	N.A.	N.A.	N.A.	Q

ANALOG

TABLE 16.11-3 (Page 2 of 2)

TABLE NOTATION

- (1) The ANALOG CHANNEL OPERATIONAL TEST shall also demonstrate that automatic isolation of this pathway and control room alarm annunciation occur if any of the following conditions exists:
 - a. Instrument indicates measured levels above the Alarm/Trip Setpoint;
 - b. Circuit failure (alarm only); and,
 - c. Instrument indicates a downscale failure (alarm only).
- (2) The ANALOG CHANNEL OPERATIONAL TEST shall also demonstrate that control room alarm annunciation occurs if any of the following conditions exists:
 - Instrument indicates measured levels above the Alarm Setpoint;
 - b. Circuit failure;
 - c. Instrument indicates a downscale failure; and,
- (3) The initial CHANNEL CALIBRATION shall be performed using one or more of the reference standards certified by the National Bureau of Standards (NBS) or using standards that have been obtained from suppliers that participate in measurement assurance activities with NBS. These stan-dards shall permit calibrating the system over its intended range of energy and measurement range. For subsequent CHANNEL CALIBRATION, sources that have been related to the initial calibration shall be used.
- (4) CHANNEL CHECK shall consist of verifying indication of flow. CHANNEL CHECK shall be made at least once per 24 hours during periods of release.