### Attachment 1

Millstone Nuclear Power Station, Unit No. 2

Proposed Revision to Technical Specifications Electrical Power Systems - Shutdown

Marked-up Pages

# ELECTRICAL POWER SYSTEMS

### SHUTDOWN .

### LIMITING CONDITION FOR OPERATION

3.8.1.2 As a minimum, the following A.C. electrical power sources shall be OPERABLE:

- One circuit between the offsite transmission network and the switchyard, and
- b. One diesel generator with a fuel oil supply tank containing a minimum of 12,000 gallons of fuel.

APPLICABILITY: MODES 5 and 6.

### ACTION:

With less than the above minimum required A.C. electrical power sources OPERABLE, suspend all operations involving CORE ALTERATIONS or positive reactivity changes with the minimum required A.C. electrical power sources are restended to OPERABLE section.

or movement of irradiated ful

#### SURVEILLANCE REDUIREMENTS

4.8.1.2 The above required A.C. electrical power sources shall be demonstrated OPERABLE per Surveillance Requirements 4.8.1.1.2 Except for TESTING PURSUANT TO SURVEILLANCE PURSUANT P

#### Attachment 2

Millstone Nuclear Power Station, Unit No. 2

Proposed Revision to Technical Specifications Electrical Power Systems - Shutdown

Retyped Pages

# **ELECTRICAL POWER SYSTEMS**

#### SHUTDOWN

### LIMITING CONDITION FOR OPERATION

3.8.1.2 As a minimum, the following A.C. electrical power sources shall be OPERABLE:

- One circuit between the offsite transmission network and the switchyard, and
- One diesel generator with a fuel oil supply tank containing a minimum of 12,000 gallons of fuel.

APPLICABILITY: MODES 5 and 6.

### ACTION:

With less than the above minimum required A.C. electrical power sources OPERABLE, suspend all operations involving CORE ALTERATIONS or positive reactivity changes or movement of irradiated fuel assemblies.

## SURVEILLANCE REQUIREMENTS

4.8.1.2 The above required A.C. electrical power sources shall be demonstrated OPERABLE per Surveillance Requirements 4.8.1.1.1 and 4.3.1.1.2, except for testing pursuant to Surveillance Requirements 4.8.1.1.2.a.3, 4.8.1.1.2.c.2, and 4.8.1.1.2.c.5.