U.S. NUCLEAR REGULATORY COMMISSION NRC Form 966 APPROVED OMB NO. 3150-0104 EXPIRES 8/31/85 LICENSEE EVENT REPORT (LER) DOCKET NUMBER (2) FACILITY NAME (1) EDWIN I. HATCH, UNIT I 1 OF 0 12 0 15 10 10 10 13 12 11 REACTOR SHUTDOWN REQUIRED BY TECH. SPECS. OTHER FACILITIES INVOLVED (8) EVENT DATE (6) LER NUMBER (8) REPORT DATE (7) REQUENTIAL FACILITY NAMES DOCKET NUMBER(S) MONTH DAY MONTH DAY YEAR YEAR 0 | 5 | 0 | 0 | 0 | 8 5 0 2 1 6 8 5 01 3 1 1 8 8 5 0 1 3 0 0 0 | 5 | 0 | 0 | 0 | THIS REPORT IS SUBMITTED PURSUANT TO THE REQUIREMENTS OF 10 CFR §: (Check one or more of the following) (11) OPERATING 50.73(a)(2)(iv) 73.71(6) 20.402(b) 50.73(a)(2)(v) 20.405(a)(1)(i) 50.36(e)(1) OTHER (Specify in Abstract below and in Text, NRC For 0, 1,5 20.408(a)(1)(ii) 50.38(c)(2) 80.73(a)(2)(vii) 50.73(a)(2)(i) 50.73(a)(2)(viii)(A) 50.73(a)(2)(viii)(8) 20 408(a)(1)(iv) 50 73(a)(2)(8) 20.406(a)(1)(v) 50.73(a)(2)(x) 80.73(a)(2)(iii) LICENSEE CONTACT FOR THIS LER (12) TELEPHONE NUMBER NAME AREA CODE T. L. Elton, Acting Superintendent of Regulatory Compliance 9 1 1 12 31617 + 17 18 1511 COMPLETE ONE LINE FOR EACH COMPONENT FAILURE DESCRIBED IN THIS REPORT (13) MANUFAC TO NPROS MANUFAC TO NPROS CAUSE SYSTEM COMPONENT CAUSE SYSTEM COMPONENT

ABSTRACT (Limit to 1400 spaces, i.e., approximately fifteen single-space typewritten lines) [16]

SUPPLEMENTAL REPORT EXPECTED (14)

S|E|A| L|B|5 | 8|0

YES (If yes, complete EXPECTED SUBMISSION DATE)

On 02/16/85 at approximately 1830 CST, with the reactor in steady state operation at 2436 MWt (approximately 100% power), operations personnel determined that drywell floor drain total leakage had risen to 32 gallons per minute, which was in excess of the maximum leakage allowed by Tech. Specs. section 3.6.G.l.c. At 1840 CST, operations personnel began a reactor power reduction in preparation for tripping and isolating the "B" reactor recirculation pump (1B31-C001B), because it had been determined that its shaft seals were leaking.

NO

At approximately 1858 CST, operations personnel initiated an orderly shutdown, tripped and isolated the "B" reactor recirculation pump (1B31-C001B). Drywell floor drain leakage then decreased to approximately 6.0 gallons per minute.

At approximately 2124 CST, operations personnel manually scrammed the reactor as part of an orderly shutdown.

Subsequently, the "B" reactor recirculation pump's (1B31-C001B) shaft seal cartridge was rebuilt and reinstalled. The pump was then satisfactorily functionally tested, and reactor startup commenced on 02/22/85 at approximately 1205 CST.

8503270073 850318 PDR ADDCK 05000321 PDR

X

AID

YEAR

MONTH

EXPECTED

DAY

MRC Form 366A

LICENSEE EVENT REPORT (LER) TEXT CONTINUATION

U.S. NUCLEAR REGULATORY COMMISSION

APPROVED OMB NO. 3150-0104 EXPIRES: 8/31/85

FACILITY NAME (1)	DOCKET NUMBER (2)	LER NUMBER (6) PAGE (3)
		YEAR SEQUENTIAL REVISION NUMBER
EDWIN I. HATCH, UNIT I	0 5 0 0 0 3 2	1 8 5 - 0 1 1 3 - 0 10 0 12 OFO 12

TEXT (If more space is required, use additional NRC Form 366A's) (17)

This 30 day LER is required by 10CFR50.73(a)(2)(i)(A) because this event shows that the reactor was shut down per Tech. Specs. section 3.6.J.2.

On 02/16/85 at approximately 1830 CST, with the reactor in steady state operation at 2436 MWt (approximately 100% power), operations personnel determined that drywell floor drain total leakage had risen to 32 gallons per minute, which was in excess of the 25 gallons per minute maximum leakage allowed by Tech. Specs. section 3.6.G.1.c. At approximately 1840 CST on 02/16/85, operations personnel began reactor power reduction in preparation for tripping the "B" reactor recirculation pump (1B31-C001B), because it had been determined that its shaft seals were leaking to the extent that they were causing the unacceptable quantity of drywell floor drain leakage.

At approximately 1858 CST on 02/16/85, operations personnel initiated an orderly shutdown per the "NORMAL REACTOR SHUTDOWN" procedure (HNP-1-1020), and approximately 1859 CST on 02/16/85, operations personnel isolated and tripped the "B" reactor recirculation pump (1B31-C001B). Drywell floor drain leakage then decreased to approximately 6.0 gallons per minute by 1924 CST; hence, the 4 hour LCO for drywell floor drain leakage limits per Tech. Specs. section 3.6.G.3.a was not exceeded.

After tripping and isolating the "B" reactor recirculation pump (1B31-C001B), operations personnel reduced reactor power level to the limits of Tech. Specs. figure 3.6-5 (reactor operation with one reactor recirculation loop in operation). At approximately 2124 CST on 02/16/85, with the reactor at approximately 375 MWt, operations personnel manually scrammed the reactor. Transients following the scram proceeded as expected, and all group II isolation valves closed.

After further investigation, plant personnel determined that the number one shaft seal on the "B" reactor recirculation pump (1B31-C001B) was leaking excessively, thus causing the unacceptable volume of drywell floor drain leakage. This event is the result of material (pump shaft seal) failure.

The pump's shaft seal cartridge (which contains shaft seals number one and number two) was removed and replaced with a shaft seal cartridge which had been previously rebuilt per the manufacturer's instructions. Subsequent to repair, recirculation pump (1B31-C001B) was satisfactorily functionally tested on 02/22/85. Reactor startup then commenced on 02/22/85 at approximately 1205 CST.

No actual or potential safety consequences or implications resulted from this event; nor did it affect other systems in Unit 1, or Unit 2.

The health and safety of the public were not affected by this non-repetitive event.



Edwin I. Hatch Nuclear Plant

March 18, 1985 GM-85-211

PLANT E. I. HATCH Licensee Event Report Docket No. 50-321

United States Nuclear Regulatory Commission Document Control Desk Washington, D. C. 20555

Attached is Licensee Event Report No. 50-321/1985-013. This report is required by 10CFR 50.73(a)(2)(i).

H. C. Nix

General Manager

HCN/TLE/VIZ

XC:

R. J. Kelly

R. E. Conway

J. T. Beckham, Jr.

P. D. Rice

K. M. Gillespie

Superintendent of Regulatory Compliance

R. D. Baker Control Room Document Control

IE22