

PLANT SYSTEMS

BASES

3/4.7.4 ULTIMATE HEAT SINK

The limitations on the ultimate heat sink level, temperature, and number of fans ensure that sufficient cooling capacity is available to either (1) provide normal cooldown of the facility, or (2) to mitigate the effects of accident conditions within acceptable limits.

The limitations on minimum water level and maximum temperature are based on providing a 30-day cooling water supply to safety-related equipment without exceeding their design basis temperature and is consistent with the recommendations of Regulatory Guide 1.27, "Ultimate Heat Sink for Nuclear Plants," March 1974.

3/4.7.5 FLOOD PROTECTION

The limitation on flood protection ensures that facility protective actions will be taken in the event of flood conditions. The limit of elevation 27.0 ft Mean Sea Level is based on the maximum elevation at which the levee provides protection, the nuclear plant island structure provides protection to safety-related equipment up to elevation +30 ft Mean Sea Level.

3/4.7.6 CONTROL ROOM AIR CONDITIONING SYSTEM

The OPERABILITY of the control room air conditioning system ensures that (1) the ambient air temperature does not exceed the allowable temperature for continuous duty rating for the equipment and instrumentation cooled by this system and (2) the control room will remain habitable for operations personnel during and following all credible accident conditions. The OPERABILITY of this system in conjunction with control room design provisions is based on limiting the radiation exposure to personnel occupying the control room to 5 rem or less whole body, or its equivalent. This limitation is consistent with the requirements of General Design Criterion 19 of Appendix A, 10 CFR Part 50.

Operation of the system with the heaters on for at least 10 hours continuous over a 31-day period is sufficient to reduce the buildup of moisture on the adsorbers and HEPA filters. Obtaining and analyzing charcoal samples after 720 hours of adsorber operation (since the last sample and analysis) ensures that the adsorber maintains the efficiency assumed in the safety analysis and is consistent with Regulatory Guide 1.52.

3/4.7.7 CONTROLLED VENTILATION AREA SYSTEM

The OPERABILITY of the controlled ventilation area system ensures that radioactive materials leaking from the penetration area or the ECCS equipment within the pump room following a LOCA are filtered prior to reaching the environment. The operation of this system and the resultant effect on offsite dosage calculations was assumed in the safety analyses.

ATTACHMENT B

PLANT SYSTEMS

BASES

3/4.7.4 ULTIMATE HEAT SINK

The limitations on the ultimate heat sink level, temperature, and number of fans ensure that sufficient cooling capacity is available to either (1) provide normal cooldown of the facility, or (2) to mitigate the effects of accident conditions within acceptable limits.

The limitations on minimum water level and maximum temperature are based on providing a 30-day cooling water supply to safety-related equipment without exceeding their design basis temperature and is consistent with the recommendations of Regulatory Guide 1.27, "Ultimate Heat Sink for Nuclear Plants," March 1974.

3/4.7.5 FLOOD PROTECTION

The limitation on flood protection ensures that facility protective actions will be taken in the event of flood conditions. The limit of elevation 27.0 ft Mean Sea Level is based on the maximum elevation at which the levee provides protection, the nuclear plant island structure provides protection to safety-related equipment up to elevation +30 ft Mean Sea Level.

3/4.7.6 CONTROL ROOM AIR CONDITIONING SYSTEM

The OPERABILITY of the control room air conditioning system ensures that (1) the ambient air temperature does not exceed the allowable temperature for continuous duty rating for the equipment and instrumentation cooled by this system and (2) the control room will remain habitable for operations personnel during and following all credible accident conditions. The OPERABILITY of this system in conjunction with control room design provisions is based on limiting the radiation exposure to personnel occupying the control room to 5 rem or less whole body, or its equivalent. This limitation is consistent with the requirements of General Design Criterion 19 of Appendix A, 10 CFR Part 50.

Operation of the system with the heaters on for at least 10 hours continuous over a 31-day period is sufficient to reduce the buildup of moisture on the adsorbers and HEPA filters. Obtaining and analyzing charcoal samples after 720 hours of adsorber operation (since the last sample and analysis) ensures that the adsorber maintains the efficiency assumed in the safety analysis and is consistent with Regulatory Guide 1.52.

3/4.7.7 CONTROLLED VENTILATION AREA SYSTEM

The OPERABILITY of the controlled ventilation area system ensures that radioactive materials leaking from the penetration area or the ECCS equipment within the pump room following a LOCA are filtered prior to reaching the environment. The operation of this system and the resultant effect on offsite dosage calculations was assumed in the safety analyses.

ADD

System design is such that a Control Room Air Handling Unit and Emergency Filtration Unit in opposite trains can be credited for system operability. In addition, the function of the heating coils in each Control Room Air Handling train is to provide personnel comfort during normal operation. During emergency conditions low temperatures in the service areas are no concern; therefore, the heaters provide no safety function and are not required for system operability.